MIL-S-24035E
19 May 1988
SUPERSEDING
MIL-S-24035D
16 August 1983

MILITARY SPECIFICATION

SAWS, BAND, CUTOFF, VERTICAL, TRAVELING, TILT-FRAME

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers floor mounted, metalcutting, band type cutoff saws, having a traveling vertical frame with tilting capabilities.

1.2 Classification. Saws covered by this specification shall be of the following types and sizes. Dimensions shown in inches represent the cutoff capacity of the saw with the frame in the vertical position, based on the minimum dimensions of the largest rectangular workpiece cross section that can be accommodated for each size saw listed.

Type I - Nonautomatic - Manual stock feed.
- Size 14 by 21 - 14 inches by 21 inches
- Size 18 by 20 - 18 inches by 20 inches , all mechanical
- Size 18 by 20 - 18 inches by 20 inches
- Size 20 by 20 - 20 inches by 20 inches
- Size 25 by 25 - 25 inches by 25 inches
- Size 25 by 28 - 25 inches by 28 inches

Type II - Automatic - Powered stock feed.
- Size 10 by 10 - 10 inches by 10 inches
- Size 14 by 21 - 14 inches by 21 inches
- Size 18 by 20 - 18 inches by 20 inches
- Size 20 by 20 - 20 inches by 20 inches
- Size 25 by 25 - 25 inches by 25 inches
- Size 25 by 28 - 25 inches by 28 inches

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSM, Memphis, Tennessee 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3405
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specification and standards form a part of this specification to the extent specified herein. The issue of these documents shall be the latest revision of the document on the date of the solicitation and may include title changes.

SPECIFICATIONS

MILITARY

MIL-M-18058 - Machinery, Metal and Woodworking, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Services.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MIL-STD-461 - Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interferences.

MIL-STD-462 - Electromagnetic Interference Characteristics, Measurement of.

2.1.2 Other Government documents. The following Government document forms a part of this specification to the extent specified herein. The issues shall be those in effect on the date of the solicitation and may include title changes.

CODE OF FEDERAL REGULATIONS (CFR)

U. S. DEPARTMENT OF LABOR, OCCUPATIONAL SAFETY AND HEALTH ADMINISTRATION (OSHA)

29 CFR 1910 - Occupational Safety and Health Standards.

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, DC 20402-0001.)

(Copies of specifications, standards, and publications required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:46Z
Check the source to verify that this is the current version before use.

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. The issue of these documents shall be the latest revision of the document on the date of the solicitation and may include title changes.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

ANSI/NEMA MG-1 - Motors and Generators.

ANSI B11.10 - Safety Requirements for the Construction, Care, and Use of Metal Sawing Machines.

(Application for copies should be addressed to the American National Standards Institute, ATTN: Sales Dept., 1430 Broadway, New York, NY 10018-3363.)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 79 - Electrical Standard for Industrial Machinery.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269-9101.)

(Non-Government standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:46Z
Check the source to verify that this is the current version before use.

3.2 Design. The band saw shall be new (not a prototype) and one of the manufacturer's current production models capable of operations in accordance with the requirements herein. The band saw shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Design and construction dimensional systems. Unless otherwise specified (see 6.2.1), either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the band saw. In this specification, all measurements, dimensions, sizes, and capacities are given in US units. These measurements may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.2 Reclaimed materials. The band saw may contain reclaimed materials provided such materials will not jeopardize its intended use, performance, or design life. The materials shall have been reclaimed in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the band saw.

3.2.3 Energy efficiency. The band saw and its components that directly consume energy in normal operation shall be designed and constructed for energy efficiency as governed by the developments available within the industry.

3.2.4 Controls. All operating controls shall be located convenient to the operator's work station(s).

3.2.5 Safety and health requirements. All parts, components, mechanisms, and assemblies furnished on the band saw, whether or not specifically required herein, shall comply with all requirements of 29 CFR 1910 and ANSI B11.10. If a conflict arises between 29 CFR 1910 and B11.10, 29 CFR 1910 shall apply. Additional safety and health requirements (see 6.7) shall be as specified in detail (see 6.2.1)

3.2.6 Environmental protection. Under the operating, service, transportation, and storage conditions described herein, the saw shall not emit materials hazardous to the ecological system as prescribed by Federal, state, or local statutes in effect at the point of installation.

3.2.7 Lubrication. Means shall be provided to ensure adequate lubrication for all moving parts. Recirculating lubrication systems shall include a filter which is cleanable or replaceable. Each lubricant reservoir shall have at least a 24-hour capacity and means for determining fluid level. Means shall be provided to indicate a low oil condition. All oil holes, grease fittings, and filler caps shall be accessible.

Source: https://assist.dla.mil -- Downloaded: 20261O-19T18:46Z
Check the source to verify that this is the current version before use.

3.2.8 Interchangeability. All parts subject to replacement shall be manufactured to definite dimensions and tolerances. Replacement parts (except for hand-fitted parts such as ways and boxed bearings) shall be interchangeable without requiring modification. Replacement parts are those which are subject to wear or failure such as gears, bearings, shafts, feed screws, drive belts, pumps, and seals. Electrical replacement parts shall include, but not be limited to motors, relays, fuses, switches, magnetics, pushbuttons, light bulbs, braking mechanisms, and solid-state devices. Tooling and accessories normally supplied as standard items shall also be considered replacement parts. Foreign-sourced replacement parts shall also be interchangeable with domestically supplied components or be readily available from a domestic source.

3.3 Construction. The saw shall be constructed of parts which are new, without defects, and free of repairs. The structure shall withstand all forces encountered during operation of the saw to its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free of defects, scale, and mismatching. No processes such as welding, peening, plugging, or filling with solder or paste shall be used for reclaiming any defective part.

3.3.2 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed to prevent loosening. Fastening devices subject to removal or adjustment shall not be permanently installed.

3.3.3 Surfaces. All surfaces shall be clean and free of harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.4 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these operations shall be employed as a repair measure for any defective part.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the saw shall be painted in accordance with the manufacturer's commercial practice.

3.3.6 Threads. All threaded parts, either US or SI, used on the saw and its related attachments and accessories shall conform to FED-STD-H28 and the applicable "Detailed Standard" section referenced therein.

3.3.7 Gears. All gears shall be machined from a material suitable for the intended purpose. All gears shall be heat treated by a process that will impart the hardness and roughness that will enable the gear train to transmit full-rated torque of the drive motor without gear damage, failure or premature wear.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

3.3.8 Electromagnetic interference control. When specified (see 6.2.1), equipment furnished under this specification shall comply with MIL-STD-461. The equipment and subsystems class and the emission and susceptibility requirements shall be as specified.

3.4 Components. Each saw shall consist of a carriage, frame assembly, head, drive system, band wheels, band tensioning mechanism, guides and guide arms, tables, vise, and other components as are described herein.

3.4.1 Carriage. The saw shall have a carriage fitted to the base to support the vertical frame assembly and provide forward and reverse traverse motion. The carriage shall maintain alignment of all parts to the degree necessary to meet performance requirements specified herein.

3.4.1.1 Feed system. The carriage shall have a powered feed system to move the supported frame assembly through cutoff cycles. The feed system shall provide an infinitely variable feed force for cutting off both thin wall tubing and solid workpieces. The feed system shall have means of limiting the distance of both forward and return motions of the carriage at any point within the traversing range. The carriage shall be fitted to the base on either anti-friction bearings or sliding type pads that maintain frame alignment to the workpiece support surface of the table.

3.4.2 Frame assembly. The frame assembly shall support the band wheels, guide arms, band guides, band tensioning device, and the saw band. The frame shall enclose the saw band, with the exception of the point of operation area where the band is exposed to workpieces enabling the saw to perform to its capacity. Removable or hinged access doors on the frame shall facilitate installation and removal of saw bands and servicing internal components. The frame shall be capable of tilting to not less than 45 degrees in one or two directions off the vertical position. The frame shall have a scale, graduated in degrees, indicating the angle of column tilt, and shall have a device that securely retains the frame in any position within its range of adjustment. When specified (see 6.2.1), frame tilting shall be powered.

3.4.3 Band drive system. The saw shall have band guides above and below the table to guide and provide rigidity to the band. Guide arms shall support the band guides with one or both of the guide arms being adjustable to accommodate workpieces within the dimensional size specified in table I. Means shall be incorporated to securely lock the guide arms in their adjusted positions. Band guides shall consist of either solid carbide or carbide faced inserts and a carbide backup, block or roller; or hardened and ground side rollers and a back-up roller. Band guides shall be either spring loaded or manually adjustable to maintain band alignment and support.

3.4.4 Table. The table shall have one or more slots for mounting the workholding vise(s) at any point along the entire length of the table. The table shall be constructed with replaceable wear plates or filler strips. The table shall have means for returning coolant to the reservoir. The table shall sustain the weight of the heaviest workpiece which it will be required to support during cutoff operations, without any deformation to the table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

3.4.4.1 Roller conveyor. When specified (see 6.2.1), saws shall have a nonpowered infeed and/or outfeed roller conveyor. The rollers shall sustain the weight of the heaviest workpiece within capacity of the saw without permanent deformation while it is being fed either on or off the conveyor. Conveyor rollers shall be supported by permanently lubricated antifriction bearings.

3.4.4.2 Automatic feeding device. Unless otherwise specified (see 6.2.1), type II saws shall have an automatic stock feeding device, conforming to this paragraph, and shall be fitted to the saw. The automatic feeding device shall have a direct reading digital length readout calibrated in either inches or millimeters, or in combination. The automatic feeding device shall include a manual feature to make a single cut and a feature to accommodate multiple cuts over an incremental range of not less than 0 through 12 inches per single index. The feeding device shall also incorporate a multiple index feature to produce workpieces longer than 12 inches and up to 72 inches in length. The ways of feeding devices shall be either covered, enclosed, or have wipers and be lubricated by either a manual or automatic lubricating system. Automatic feeding devices shall include the number of power operated vises necessary to feed stock material, (forward and reverse), through the automatic cycles to preclude manual push-up of the stock. When specified (see 6.2.1), a discharge table of 5 or 10 feet in length, shall be furnished with the automatic feeding device.

3.4.5. Band tooth cleaning device. All saws shall have a wiper, fixed brush, or powered rotary brush for removing chips from the teeth. The cleaning device shall effectively remove and deposit the chips for their removal from the machine.

3.4.5.1 Swarf/chip removal device. A chip rake or a manually operated conveyor shall be provided for removal of swarf/chips. When specified (see 6.2.1), the conveyor shall be powered.

3.4.6 Coolant system. The saw shall have a coolant system consisting essentially of a reservoir, pump, pipe, tube, hose, and controls for the flow of coolant to both sides of the band. The coolant system shall have a reservoir with a capacity to ensure sustained operating periods. The system shall have a means for draining and cleaning.

3.4.7 Vises. Vise jaws shall be constructed to securely hold workpieces while making both vertical (90 degree) or miter (up to 45 degree) cuts, without cutting the vise jaws. A manual or powered, quick operating vise shall be furnished on nonautomatic saws. Vise jaw openings shall accommodate and securely clamp maximum capacity workpieces. All automatic saws shall have power operated vises. All power operated vises shall have adjustable clamping pressure to accommodate light-weight workpieces without damage or distortion. When specified (see 6.2.1), an additional vise shall be furnished, with jaw height capable of retaining maximum diameter round workpieces. When specified (see 6.2.1), type I, nonautomatic saws shall have powered vises.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

3.4.8 Hydraulic system. Unless otherwise specified (see 6.2.1), the saw shall be hydraulically operated. The hydraulic systems shall be complete and shall include all pumps, valves, pipes, cylinders, and pressure controls. Pressure protection shall be provided in the hydraulic system. The hydraulic system shall have a reservoir with a capacity to prevent overheating of the hydraulic fluid. The hydraulic system reservoir shall have for determining fluid level, and a filter shall ensure clean hydraulic fluid through the hydraulic system. This paragraph does not apply to type I, size 18x20 - all mechanical saws.

3.5 Sizes and capacities. Unless otherwise specified (see 6.2.1), the size and capacity of the saw shall meet or exceed the requirements of the type and size specified in table I.

3.6 Performance and accuracy. The saw shall be capable of sawing SAE 1018 cold finished steel bar at metal removal rates and cutoff accuracies specified in table II.

3.7 Electrical system. The electrical system shall conform to ANSI/NFPA 79. Unless otherwise specified (see 6.2.1), each machine shall draw all of its electrical power from a single 230/460-volt, 3-phase, 60-hertz (Hz) circuit having a fused safety disconnect switch or circuit breaker. The machine shall be initially wired for operation on 460 volts.

3.7.1 Motors. Motors shall be rated for 60-minute duty cycle and shall have ball or roller bearings of the sealed and permanently lubricated type. Alternating-current (AC) motors shall be designed to operate on 60-Hz. Unless otherwise specified (see 6.2.1), each motor enclosure shall meet the requirements for a drip-proof enclosure. All motors shall meet the requirements of ANSI/NEMA MG-1. Each motor shall have an identification plate to identify manufacturer, model, serial number, voltage, amperage, horsepower, phase, and frequency.

3.8 Standard equipment. Unless otherwise specified (see 6.2.1), the following equipment shall be furnished with each saw.

a. Hand tools. One set of hand tools normally furnished by the supplier

b. Work indicator dial or chart. A dial or chart indicating recommended feed rate, band speeds and type of band for general sawing operations on a variety of metals.

c. Saw band. One saw band of the type used in performance testing.

d. Worklight. Each saw shall have a shielded light fixture, operating on 115 volts, providing optimum illumination of the work area.

3.9 Optional equipment. Optional equipment shall be furnished as specified and fully described (see 6.2.1).

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:46Z
Check the source to verify that this is the current version before use.

3.10 Making on plates. All words on plates shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background. All plates shall be corrosion resistant.

3.10.1 Lubrication plate. A lubrication plate shall be permanently and securely attached to each machine. Unless otherwise specified (see 6.2.1), the plate shall contain the following information:

Points of lubricant application
Servicing interval
Type of lubricant
Viscosity

3.10.2 Nameplate. A nameplate shall be securely attached to each machine. Unless otherwise specified (see 6.2.1), the nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model number of the basic standard machine and a suffix identified in the manufacturer's permanent records.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.11 Technical data. When technical data is required, it shall be furnished in accordance with the requirements of DD Form 1423. All technical data furnished shall be written in the English language.

3.12 Workmanship. Workmanship of the machine shall meet all requirements specified herein and shall be of a quality equal to that prevailing among manufacturers producing equipment of the type covered by this specification.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspection set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements (see 6.8).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified (see 6.2.1), all inspections, tests, and examinations shall be performed in an indoor facility with ambient conditions of 55 degree to 100 degree and 10 percent to 95 percent relative humidity.

4.4 First article inspection. When a first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.6 and all tests in 4.7. Failure of the item to pass the first article examination or any test shall be cause for rejection.

4.5 Quality conformance inspection. Quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), quality conformance inspection shall consist of the examination in 4.6, the tests in 4.7, and the inspection in 4.8. Failure of the item to pass the examination, the test, or the inspection shall be cause for rejection.

4.6 Examination. The saw shall be examined to determine compliance with all requirements of this specification.

4.7 Tests.

4.7.1 Operational test. The saw shall be subjected to the following tests to determine compliance with the performance requirements of 3.6. Failure to meet the requirements shall be cause for rejection. A saw band of the width specified in table I shall be used. The pitch and set of the teeth shall be as recommended by the data chart or plate furnished with the saw. Actual cutting time only shall be used to determine the cutting rate.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

4.7.2 Cutoff test. The saw shall make nine cuts in either a 6-, 10- or 12-inch diameter SAE 1018 cold finished steel bar. The type band, speed, and feed rate shall be at the supplier's option, as long as it conforms to the data chart or plate with the saw. Three cuts each shall be made with the frame in the vertical and tilted 45 degrees of the vertical position. The time during which the band is actually sawing the stock shall be established to determine the actual cutting rate. The cutting rate, flatness, squareness, and angular error shall conform to the requirements of table II.

4.7.3 Electromagnetic interference control test. Equipment requiring electromagnetic interference control shall be tested for compliance with 3.3.8 using the procedures given in MIL-STD-462.

4.8 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A preservation, level A or B packing, and marking shall be accomplished in accordance with MIL-M-18058.

6. NOTES

6.1 Intended use. Saws covered by this specification are intended to be used for cutoff and notching operations on solid bars, structural shapes, extrusions, castings, pipe, and tube.

6.2 Ordering data.

6.2.1 Acquisition documents. Acquisition documents should specify the following:

a. Title, number, date and latest revision of this specification.

b. Type and size saw required (see 1.2).

c. First article approval, if required (see 3.1 and 6.3).

d. Measurement system, if different (see 3.2.1).

e. Additional safety and health requirements, if required (see 3.2.5).

f. Painting, if different (see 3.3.5).

g. Electromagnetic interference, if required (see 3.3.8).

h. Powered tilting of saw frame, if required (see 3.4.2).

i. Infeed and/or outfeed roller conveyor 5 feet or 10 feet, 3.4.4.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

j. Automatic feeding device on type II saws, if not required (see 3.4.4.2).

k. A 5 feet to 10 feet discharge, if required (see 3.4.4.2).

l. Powered chip conveyor, if required (see 3.4.5.1).

m. Vises, if different (see 3.4.7).

n. Powered vises on type I saws, if required (see 3.4.7).

o. Hydraulic system, if not required (see 3.4.8).

p. Specify size and capacity of saw if different (see 3.5).

q. Electrical system and voltage for initial wiring, if different (see 3.7).

r. Band motor horsepower and type of enclosure, if different (see 3.7.1).

s. Standard equipment, if different (see 3.8.).

t. Optional equipment, if required (see 3.9).

u. Lubrication chart, if different (see 3.10).

v. Nameplate, if different (see 3.11).

w. First article inspection, if different (see 4.4).

x. Quality conformance inspection, if different (see 4.4).

y. Electromagnetic interference control test, if required (see 4.7.3)

z. If preservation, packing, and marking in accordance with MIL-M-18058 are required, specify level required and specification number (see 5.1).

6.2.2 Consideration of data requirements. The requirements for technical data should be considered when this specification is applied on a contract. The Data Item Descriptions (DIDs), DD Form 1664, for required data should be listed on a Contract Data Requirements List (DD Form 1423). The current issue of DoD 5010.12-L, Acquisition Management Systems and Data Requirements List, (AMSDL) should be researched for the applicable DD Form 1664 and to ensure that only current approved DIDs are cited on the DD Form 1423.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Changes from previous issues. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

6.5 Subject term (keyword) listing.

Automatic
Manual stock feed
Nonautomatic
Power stock feeder
Saws, band cutoff
Tilting
Traveling
Vertical

6.6 Training. Training required by the procuring activity shall be provided as specified in the contract.

6.7 Warranty. Warranty requirements shall be as specified by the procuring activity in the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

Table I - Sizes and capacities.

Characteristics	Type I						
Sizes	10 x 14	14 x 21	18 x 20 (mech)	18 x 20	20 x 20	25 x 25	25 x 28
Workpiece capacity, nominal: Width x height, inches							
at 90° - vertical position	10 x 14	14 x 21	18 x 20	18 x 20	20 x 20	25 x 25	25 x 28
at 45° - angular position (R)	10 x 10	14 x 14	18 x 12½	18 x 13	20 x 14	25 x 17	25 x 16
at 45° - angular position (L)	———	14 x 14	18 x 12½	18 x 11	20 x 14	25 x 17	25 x 16
Band data:							
Band feed force, infinitely variable, pounds	0 - 250	0 - 237	0 - 140	0 -300	0 - 300	0 - 300	0 - 300
Band width x thickness, inches x inches	1 x .035	1 x .035	1 x .035	1¼ x .042	1¼ x 0.042	1½ x 0.50	1½ x .050
Band speed range, feet per minute	60 - 400	75 - 400	50 - 450	60 - 400	40 - 300	50 - 300	60 - 400
Band drive motor, horsepower Optional	3	3	2	7 10	10	10 15	15 10

NOTE: Requirements are "not less than those shown". When a range is shown, the performance shall encompass a range from the stated "minimum or less" to the stated "maximum or greater".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

Table I - Sizes and capacities - Continued.

Characteristics	Type II					
Sizes	10 x 10	14 x 21	18 x 20	20 x 20	25 x 25	25 x 20
Workpiece capacity, nominal: Width x height, inches						
at 90° - vertical position	10 x 10	14 x 21	18 x 20	20 x 20	25 x 25	25 x 28
at 45° - angular position (R)	10 x 7	14 x 14	18 x 13	20 x 14	25 x 17	25 x 16
at 45° - angular position (L)		14 x 14	18 x 11	20 x 14	25 x 17	25 x 16
Band data:						
Band feed force, infinitely variable, pounds	0 - 250	0 - 275	0 - 300	0 - 300	0 - 300	0 - 300
Band width x thickness, inches x inches	1 x .035	1 x .035	1-1/4 x .042	1-1/4 x .042	1-1/2 x 0.50	1-1/2 x .050
Band speed range, feet per minute	60 - 400	75 - 400	60 - 400	40 - 300	50 - 300	60 - 400
Band drive motor, horsepower	3	5	7	10	10	15
Optional			10		15	10

NOTE: Requirements are "not less than those shown". When a range is shown, the performance shall encompass a range from the stated "minimum or less" to the stated "maximum or greater".

Source: https://assist.dla.mil -- Downloaded: 202610-19T18:46Z
Check the source to verify that this is the current version before use.

TABLE II - Performance and accuracies

Material: SAE 1018, cold finished bar	Type I & Type II						
Diameter, inches	6	10	6	10	10	12	12
Blade size, inches	1 x .035	1 x .035	1 x .035	1½ x .042	1½ x .042	1½ x .050	1½ x .050
Machine size	10 x 10 x 10 x 14	14 x 21 x 14 x 20	18 x 20-inch	18 x 20	20 x 20	25 x 25	25 x 28
Minimum cutting rate, inches ^{2}/min.	11	12	11	16	16	20	20
Accuracy:							
a. Maximum error in flatness of cut surface, inches per inch of diameter	±0.002"	±0.002"	±0.002"	±0.002"	±0.002"	±0.003"	±0.003"
b. Maximum error in squareness of cut with axis of workpiece, inch per inch of diameter	±0.002"	±0.002"	±0.002"	±0.002"	±0.002"	±0.003"	±0.003"
c. Maximum angular error of cut surface at 45 degrees	±20 min.	±20 min.	±20 min	±20 min.	±20 min.	±20 min.	±20 min.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.

Custodians:
Navy - SH
Air Force - 99

Review activities:
Navy - SH
Air Force - 84

Preparing activity:
DLA - IP

Project (3405-0083)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T18:46Z
Check the source to verify that this is the current version before use.