MIL-C-81084(OS)
Amendment 3
20 January 1967
Superseding
Amendment 2
30 July 1965

MILITARY SPECIFICATION

CONTAINER, SHIPPING AND STORAGE

MARK 300 MODS 0 AND 1

(For Torpedo Mk 46 Mod 0)

This amendment forms a part of Military Specification MIL-C-81084(OS) of 26 May 1964 and has been approved by the Naval Ordnance Systems Command, Department of the Navy

By this amendment MIL-C-81084(Wep) is changed to MIL-C-81084(OS).

Wherever it appears in specification delete "Bureau of Naval Weapons" and substitute "Naval Ordnance Systems Command".

Page 1: In title, delete "MARK 300 MOD 0" and substitute "MARK 300 MODS 0 AND 1".

Page 1, paragraph 1.1: Delete "Mark 300 Mod 0" and substitute "Mk 300 Mods 0 and 1".

Page 1, paragraph 2.1: Delete "MIL-W-21927" and its title and substitute "WR-11 Design and Test of Packaging, Packing, Shipping, and Handling Equipment for Weapon System Components".

Page 2, under "DRAWINGS": Add "DL 2613831, Container, Shipping and Storage, Mark 300 Mod 1, and all documents listed thereon".

Page 3, paragraph 3.2.1: Delete "BUWEPS LD 541201" and substitute "LD 541201 or DL 2613831".

Page 3, paragraph 3.3.1. Delete and substitute:
"3.3.1 Airtightness. The container shall not leak air at a rate greater then 0.3 psig when pressurized to 0.75 plus 0 minus 0.25 (above ambient) for 30 plus or minus 5 minutes."

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

FSC 1355

Page 3, paragraph 3.4.1, line 2: Delete "one Torpedo Main Assembly or Gas Generator" and substitute "one Torpedo Main Assembly of Gas Generator, or simulated load".

Page 4, paragraph 3.4.2, lines 1 and 2: Delete "with one Torpedo Main Assembly or Gas Generator enclosed" and substitute "with one Torpedo Main Assembly or Gas Generator, or simulated load, enclosed".

Page 4, paragraph 3.4.2.1: Delete "Cornerwise drop" and substitute "Rotational drop" in two places.

Page 4, paragraph 3.4.2.3: Delete "Roll over" and substitute "Tip over".

Page 4, paragraph 3.4.2.4: Delete "Pushing and towing" and substitute "Skid surfaces".

Page 7, paragraph 4.5.2: Delete "Specification MIL-W-21927" and substitute "Weapons Requirement WR-11".

Page 8, paragraph 4.5.3.1, 4.5.3.2, 4.5.3.3, and 4.5.3.4. Delete and substitute:

"4.5.3.1 Rotational drop. Subject the container to the rotational drop test as specified in Weapons Requirement WR-11.

4.5.3.2 Impact. Subject the container to the impact test as specified in Weapons Requirement WR-11.

4.5.3.3 Tip over. Subject the container to the tip over test as specified in Weapons Requirement WR-11.

4.5.3.4 Skid surfaces. Subject the container to the skid surfaces test as specified in Weapons Requirement WR-11."

Page 9, paragraph 4.6.2(b): Delete "Cornerwise drop" and substitute "Rotational drop".

Page 9, paragraph 4.6.2(d): Delete "Roll over" and substitute "Tip over".

Page 9, paragraph 4.6.2(e): Delete "Pushing and towing" and substitute "Skid surfaces".

Page 9, paragraph 4.7.2. Delete and substitute:

"4.7.2 Airtightness. Remove Breather Valve 2452719 and seal opening. Pressurize the container to 0.75 plus 0 minus 0.25 psig and seal inlet. Allow the container to stand for 30 plus or minus 5 minutes. A pressure drop in excess of 0.3 psig constitutes a failure."

Page 9, paragraph 4.7.3: Delete "BUWEPS LD 541201" and substitute "LD 541201 or DL 2613831".

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.