MIL-G81065A(OS)
AMENDMENT 2
8 Jan 1971
Superseding
AMENDMENT 1
9 April 1969

MILITARY SPECIFICATION

GYRO-PENDULUM ASSEMBLY

(For Torpedo Mk 46 Mod O and Mk 46 Mod 1)

This amendment forms a part of Military Specification MIL-G-81065A(OS) of 27 March 1967 and has been approved by the Naval Ordnance Systems Command, Department of the Navy.

Page 5, paragraph 3.3.2.2 (e). Delete and substitute:

"(e) The power factor correction capacitor (Cl O on Drawing 2089913) shall be selected so that with 26 plus or minus 0.1 vrms (4.8 kilocycles (kc) plus or minus 10 cps) the current is 290 plus or minus 30 ma at a power factor of O. 8 to O. 96 leading at room temperature. At O degrees and plus 160 degrees F the current shall be 290 plus or minus 50 ma and the power factor O. 8 to O. 96 leading."

Page 12, paragraph 4.1. Delete and substitute:

"4.1 Responsibility y for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements."

Page 13, paragraphs 4.3.2 and 4.3.2.1. Delete and substitute:

"4.3.2 Periodic production sampling. Periodic production samples shall be selected from units that have passed the acceptance inspections of 4.7 satisfactorily. These samples shall be subjected to the tests of 4.6 at an activity designated by the procuring activity. Periodic production sampling shall be as follows:

Step 1. Upon initiation of production, select at random 1 unit from each group of 30 units. Upon satisfactory compliance of samples selected from 3 consecutive groups, shift to Step 2. Each sample so selected shall

FSC 1355

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:57Z
Check the source to verify that this is the current version before use.

be numbered consecutively, starting with Sample Number 1.

Step 2. Select at random 1 unit from each group of 70 units. Continue with Step 2 for the balance of the contract or until a defective unit is found. Each sample so selected shall be numbered consecutively, starting with a sample number one greater than the highest sample number selected in Step 1.

4.3.2.1 Defective units. When a defective unit is found in any group, acceptance of all units on hand shall be withheld and the contractor shall:

(a) Determine the cause of the defect.

(b) Take the necessary action to correct or eliminate the defect from all units on hand and, if so directed by the procuring activity, eliminate defects from those units previously shipped.

(c) Submit to the procuring activity for approval the proposed corrective action to prevent recurrence of the defect.

(d) Submit to the procuring activity for approval the proposed retest program to verify that the corrective action eliminated the defect.

(e) Return to Step 1 and proceed as indicated when inspection is resumed. ”

Page 17, paragraph 4.5.2.4.2. Delete and substitute:
"4.5.2.4.2 Temperature, operating. The gyro-pendulum shall be stabilized at a temperature of O degrees F and tested to conform to the acceptance test requirements of 4.70 The gyro-pendulum shall then be stabilized at plus 160 degrees F and again tested to conform to the acceptance test requirements of 4.7."

Page 18, paragraphs 4.6 and 4.6.1. Delete and substitute:
“4. 6 Periodic production tests. The periodic production sample, selected in accordance with 4.3.2, shall be subjected to the tests of Table IX in the order specified,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:57Z
Check the source to verify that this is the current version before use.

Table IX

Periodic Production Test Schedule

Test	Sample and Test Sequence		
	1, 4, etc.	2, 5, etc.	3, 6, etc.
Vibration (4.5.2.1)	1*		1*
Acceleration (4.5.2.3)	2*	1*	
Shock (4.5.2.2)	3*	2*	
Temperature, Non-Operating (4.5.2.4.1)	4		3
Temperature, Operating (4.5.2.4.2)	5	3	
Pressure (4.5.2.5)	6		2
Humidity (4.5.2.6)	7	4	
Life (4.5.2.7)	8		
Acceptance (4.7)	9	5	4

*Visual check after testing

4.6.1 Periodic production test equipment. The items of test equipment shall be those specified for conducting all tests of sections 4.5 and 4.7."

Page 18, paragraph 4.6.2: Delete.

Preparing Activity
Navy - OS
Project No. 1355-N

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:57Z
Check the source to verify that this is the current version before use.