MIL-W-81044B
SUPPLEMENT 1A
23 March 1981
SUPERSEDING
SUPPLEMENT 1
31 December 1973

MILITARY SPECIFICATION

WIRE, ELECTRIC, CROSSLINKED POLYALKENE, CROSSLINKED ALKANE-IMIDE POLYMER, OR POLYARYLENE INSULATED, COPPER OR COPPER ALLOY

This supplement forms a part of Military Specification MIL-W-81044B dated 31 December 1973.

SPECIFICATION SHEETS

MIL-W-81044/6	Wire, Electric, Crosslinked Polyalkene Insulated, Tin-Coated Copper, Normal Weight, 600-Volt, 150°C
MIL-W-81044/7	Wire, Electric, Crosslinked Polyalkene Insulated, Silver-Coated High Strength Copper Alloy, Normal Weight, 600-Volt, 150°C
MIL-W-81044/9	Wire, Electric, Crosslinked Polyalkene Insulated, Tin-Coated Copper, Medium Weight, 600-Volt, 150°C
MIL-W-81044/10	Wire, Electric, Crosslinked Polyalkene Insulated, Silver-Coated High Strength Copper Alloy, Medium Weight, 600-Volt, 150°C
MIL-W-81044/12	Wire, Electric, Crosslinked Polyalkene Insulated, Tin-Coated Copper, Light Weight, 600-Volt, 150°C
MIL-W-81044/13	Wire, Electric, Crosslinked Polyalkene Insulated, Silver-Coated High Strength Copper Alloy, Light Weight, 600-Volt, 150°C

Preparing activity:
Navy - AS
(Proj. No. 6145-0738)

☆U.S. GOVERNMENT PRINTING OFFICE: 1981 — 703-023/1729

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:56Z
Check the source to verify that this is the current version before use.