MIL-C-23024A(AS)
10 April 1967
Superseding
MIL-C-23024(Wep)
27 September 1961

MILITARY SPECIFICATION

CARTRIDGE, DELAY, MARK 36 MOD 0

This specification has been approved by the Naval Air Systems Command, Department of the Navy.

1. SCOPE

1.1 This document governs the manufacture, assembly and preparation for delivery of the MARK 36 MOD 0 delay cartridge and the methods of inspection and tests upon which product acceptance will be based.

2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings, and publications, of the issue in effect on date of invitation for bids, form a part of this document to the extent specified herein.

SPECIFICATIONS

Military

MIL-P-20444	Primer, M42
MIL-P-22264	Powders, Ignition, Gasless
MIL-M-21383	Manganese Delay Composition
MIL-D-21625	Design and Evaluation of Cartridges for Cartridge Actuated Devices
MIL-P-116	Preservation, Methods of

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

Bureau of Naval Weapons

OS 9862	Propellant, Double Base (Nitrocellulose-Nitroglycerine)

STANDARDS

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	Marking for Shipment and Storage

DRAWINGS

Bureau of Naval Weapons

ID 419708	Cartridge, Delay, MARK 36 MOD 0
ID 537902	Container, Inner, for Cartridges, Power Source
ID 537903	Container, Outer, for Cartridges, Power Source

Ordnance Corps of the Army

ORD. Dwg. No. 8799925	Primer, M42, Assembly and Details

PUBLICATIONS

BUSANDA Instruction 4030.17	Preservation, Packaging, Packing and Marking; Navy Policy for

Bureau of Naval Weapons

OP 5	Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the Government Inspector for use of the publication.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

WR-43A

Preparation of Quality Assurance Provisions

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following document forms a part of this specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR 71-78 — Transportation, Interstate Commerce Commission, Explosives and Other Dangerous Articles

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402. Orders for the above publication should cite the latest edition and supplements thereto.)

3. REQUIREMENTS

3.1 General.

3.1.1 The MARK 36 MOD delay cartridge covered by this specification shall be manufactured in accordance with LD 419708 and all documents listed thereon.

3.2 Material. All materials used in the manufacture of the cartridges shall conform strictly with the specifications referred to on the respective Bureau of Naval Weapons drawings unless specific approval in writing covering a departure therefrom has been obtained from the Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.2.1 Preproduction sample. Unless otherwise specified by the procuring activity, a preproduction sample of 106 MARK 36 MOD 0 delay cartridges shall be manufactured using the same methods and procedures proposed for the production lot. The sample shall be tested as specified in 4.3.2 to determine that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

3.3 Primary components. For the purposes of this specification the M42 Primer (MIL-P-20444), Powders, Ignition, Gasless (MIL-P-22264), and Manganese Delay Composition (MIL-M-21383) are defined as primary components.

3.4 Primer. The primers shall be furnished from lots manufactured within a year past and shall be in accordance with Ordnance Drawing 8799925 and MIL-P-20444. See 4.7.1.

3.4.1 X-ray. All primers shall be X-rayed and screened for defects as outlined in 4.7.2.

3.5 Gasless ignition powder and loading. The gasless ignition powder, A-1A, shall be manufactured and loaded in accordance with MIL-P-22264 and Bureau of Naval Weapons Drawing 2164484 of LD 419708, respectively.

3.6 Manganese delay composition. The manganese delay composition shall be manufactured and loaded in accordance with MIL-M-21383 and Bureau of Naval Weapons Drawing 2164484 of LD 419708, respectively.

3.7 Base propellant charge. The base propellant charge shall be manufactured and loaded in accordance with Bureau of Naval Weapons OS 9862 and Bureau of Naval Weapons Drawing 2164485 of LD 419708, respectively.

3.7.1 Quantity. The base propellant charge shall be as specified on Bureau of Naval Weapons Drawing 2164485 of LD 419708. Charges shall be determined by weight rather than by volume measurements.

3.7.2 Smokeless powder, handling and loading. Do not subject the smokeless powder to unnecessary handling or exposure to the atmosphere. The handling and loading of smokeless powder exposed to the atmosphere shall be performed only under conditions that do not permit the relative humidity to exceed 75 percent.

3.7.3 Smokeless powder, condition. The smokeless powder utilized shall exhibit no evidence of decomposition. See 4.7.3.

3.8 Cartridge inspection.

3.8.1 Visual inspection. The complete cartridge shall be free of the visible defects noted in 4.7.4.

3.8.2 X-ray. All cartridges shall pass X-ray examination of 4.7.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

3.9 Ballistic requirements. Cartridges from each production lot, selected in accordance with 4.8, shall meet the requirements listed below when subjected to the test prescribed in 4.8.

3.9.1 Delay time. Delay time shall be measured from initial movement of the firing pin to start of pressure rise. The lower and upper limits of delay time shall be T_L = 0.40 second and T_U = 0.75 second, respectively.

3.9.2 Level and duration of pressure.

3.9.2.1 Maximum pressure. The lower limit of the maximum pressure shall be P_L = 1000 psi.

3.9.2.2 Duration of pressure. The lower limit of duration of pressure at or above the minimum pressure of 1000 psi shall be T_L = 0.01 second.

3.9.3 Misfire. There shall be no misfires. See 4.8.2.

3.10 Workmanship. Cartridges shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Sampling. Unless otherwise specified, and when applicable, the sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of MIL-STD-105. Unless otherwise specified in the contract, order, or requisition, all samples for test purposes shall be provided at the expense of the contractor.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

4.3.2 Preproduction sample. Before entering into quantity production, an acceptable preproduction sample of 106 MARK 36 MOD 0 delay cartridges shall be prepared. Ninety-six of these cartridges shall be expended in the tests listed below and 10 shall be retained for investigative purposes. A preproduction sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of paragraphs 3.3 through 3.8 of this specification. The contractor shall deliver the cartridges to the activity designated by the contracting agency for test. Preproduction sample acceptance shall consist of the following tests as prescribed in MIL-D-21625: 40-foot drop (6), 15 "g" shock (12), vibration (12), temperature and humidity cycling (12) (except that the cartridges shall be subjected to 14 days of temperature and humidity cycling in lieu of 28 days as stated in MIL-D-21625), high temperature storage (18), +70°F (12), -65°F (12), and +160°F (12). No cartridge shall produce results outside the limits set forth in paragraph 3.9. Firings shall be conducted in the test fixture of 4.8.1. Any quantity production prior to notification by the contracting agency of preproduction sample acceptability shall be at the contractor's risk. The preproduction cartridges will not be applied as a part of the quantity specified for delivery by the contract.

4.3.3 Production lot. The suggested production lot size is 111 minimum and 500 maximum cartridges. Cartridges required for all test purposes are selected from the production lot and will not be applied as a part of the quantity specified for delivery by the contract. Only primary components from a single lot shall be used in a production lot of cartridges. One primary component production lot may be used in more than one cartridge production lot. Cartridges selected for the ballistic test shall be delivered to the activity designated by the contracting agency.

4.4 Gages. The contractor shall provide and utilize gages as necessary to insure that the material covered by this specification will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as Critical, Major or Minor in accordance with WR-43A. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of the test or examination. Tests and examinations not annotated with a classification code are classified minor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

4.6 Production and acceptance inspection. Production and acceptance inspection shall consist of verification of the characteristics classified on the drawings of LD 419708 and the following tests and examinations.

Item	Nature of Test	Requirement	Test	Classification (WR-43A)
Primary Component	Single Lot Verification	3.3	4.3.3	(M101)
Primer	Age and Acceptance Verification	3.4	4.7.1	(C1)
Primer	X-ray	3.4.1	4.7.2	(C2)
Ignition Powder	Manufacture Verification	3.5	---	(C3)
Ignition Powder	Loading Verification	3.5	---	(M102)
Delay Composition	Manufacture Verification	3.6	---	(C4)
Delay Composition	Loading Verification	3.6	---	(M103)
Propellant Charge	Manufacture and Loading Verification	3.7	---	(C5)
Propellant Charge	Weight Verification	3.7.1	---	(C6)
Smokeless Powder	Condition	3.7.3	4.7.3	(C7)
Cartridge	Visual Inspection	3.8.1	4.7.4	(M104)
Cartridge	X-ray	3.8.2	4.7.5	(C8)
Cartridge	Ballistics	3.9	4.8	(C9)

4.6.1 Packing, packaging and marking. (M105) The inspector shall ascertain that the packing and packaging of the cartridges and the container markings conform to Section 5 of this specification.

4.7 Tests.

4.7.1 Primer, verification. Verification shall be obtained that the primers to be used were manufactured within a year past and were furnished from lots certified by the supplier to have been accepted in accordance with the provisions of MIL-P-20444.

4.7.2 Primer X-ray. Primers should be mounted in suitable grooved racks. For the most revealing exposure, the primers are laid on their side with the anvil cutouts vertical. Pressure sensitive tape may be used as an aid in positioning the primers. Reject any that are questionable from any standpoint, especially for: missing

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

or abnormally thin charge; charge broken, cracked, or deformed; misplaced or cracked anvil; or other misplaced or cracked inert parts.

4.7.3 Smokeless powder, condition. Smokeless powder shall be inspected in accordance with the applicable portions of paragraphs 1308-1318 and 1322 of OP 5. Evidence of decomposition shall be cause for rejection.

4.7.4 Visual inspection. Examine each cartridge produced under a contract and reject for dents, deep scratches, split or cracked lip in the crimped area, perforated closure discs, sharp edges, burrs, or other defects which may prevent entry into the device of intended application or affect stability or resistance to moisture.

4.7.5 X-ray examination. Examine all cartridges by X-ray and any observable imperfections in assembly shall be cause for rejection. X-ray plates may be destroyed after ballistic acceptance of cartridges.

4.8 Ballistic tests.

4.8.1 The number of cartridges selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table I of MIL-STD-105, Inspection Level III. The sample of cartridges shall be divided into three equal lots. One lot each shall be conditioned for 24 hours at -65°F ± 5°F, +70°F ± 5°F and +160°F ± 5°F. The cartridges shall be fired within 3 minutes after removal from the conditioning box in a MARK 11 MOD 0 initiator or equivalent. The initiator shall fire into a closed chamber of 0.3 cubic inch volume. The chamber shall be adapted for a pressure transducer, and a record of pressure versus time shall be recorded by suitable instrumentation on each firing. In addition to the sample of cartridges for the above test, 10 additional cartridges shall be furnished from the production lot for investigative purposes.

4.8.1.1 Criteria of acceptability. The delay time, lower limit of maximum pressure and duration of maximum pressure shall meet the requirements of 3.9. Any cartridge that produces results outside the limits set forth in 3.9 shall be cause for rejection of the lot represented.

4.8.2 Misfire. The failure of any cartridge to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.8.3 Retest. There shall be no retests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

4.8.4 Test failure. If test failure is attributable to an assignable cause, excluding the test cartridges, original test results should be discarded and the complete test reconducted.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging. For definitions of packaging levels, see 6.4.

5.1.1 Level A. Level A packaging shall be used for packaging of all production lots for service use. Four cartridges shall be packaged in an inner container in accordance with LD 537902.

5.1.2 Level B. Not applicable.

5.1.3 Level C. When directed by the procuring activity, cartridges intended for expenditure in preproduction sample testing and for production lot acceptance tests shall be packaged in accordance with Method III of MIL-P-116 and with the Code of Federal Regulations 49 CFR 71-78.

5.2 Packing. For definitions of packing levels, see 6.4.

5.2.1 Level A. Level A packing shall be used for packing of all production lots for service use. Six inner containers as described in 5.1.1 shall be packed in accordance with Bureau of Naval Weapons LD 537903.

5.2.2 Level B. Not applicable.

5.2.3 Level C. When directed by the procuring activity, those cartridges intended for expenditure in preproduction sample testing and for production lot acceptance tests and are packaged in accordance with 5.1.3 shall be packed to afford protection against damage during direct shipment from the supply source to the first receiving activity for immediate use. The shipping container shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3 Markings.

5.3.1 Special markings. Marking of exterior containers shall be in accordance with the Code of Federal Regulations 49 CFR 71-78.

5.3.2 Normal markings. In addition to the markings required by contract or order and as specified on Bureau of Naval Weapons LD 537902 and LD 537903, unit packages and shipping containers shall be marked in accordance with the requirements of MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The primary use of the MARK 36 MOD 0 delay cartridge is to provide a ballistic delay in aircraft personnel escape systems.

6.2 Ordering information. Procurement documents should specify the following:

a. title, number and date of this specification;

b. whether preproduction inspection is required and if so, specify the test activity;

c. production lot size and test activity (see 4.3.3);

d. items of data required for each preproduction and production lot (see 6.3).

6.3 Data. For the information of Contractors and Contracting Officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in Section 2 of this specification or (c) referenced lower-tier documents, need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order. The data to be furnished shall be listed on DD Form 1423 (Contractor Data Requirements List) which shall be attached to and made a part of the contract or order. NAVWEPS Form 4200/15 (Drawings, Lists, and Specifications Required) shall be attached where applicable.

6.3.1 Test report. Results of ballistic tests shall be forwarded to the Naval Air Systems Command and the procuring activiry.

6.3.2 Data cards. The contract or order should state the format, quantity and destination of data cards.

6.4 Definitions. The definitions of Levels A and C packaging and packing given below were extracted from BUSANDA Instruction 4030.17.

6.4.1 Level A packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during handling, shipment, indeterminate storage and world-wide redistribution.

6.4.1.1 Level C packaging. The degree of preservation and packaging which will afford adequate protection against corrosion, deterioration and physical damage during shipment from supply source

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

to the first receiving activity for immediate use. This level may conform to supplier's commercial practice when such meets the requirements of this level.

6.4.2 Level A packing. The degree of packing which will afford adequate protection during shipment, handling, indeterminate storage and world-wide redistribution.

6.4.2.1 Level C packing. The degree of packing which will afford protection against damage during direct domestic shipment from the supply source to the first receiving activity for immediate use. This level in general will conform to applicable carrier rules and regulations and may be the supplier's commercial practice when such meets the requirements of this level.

6.5 Explosives safety precautions.

6.5.1 Applicability. The loading, assembly and handling of the explosives, subassemblies and the finished items covered by this specification, involve hazardous operations and therefore require suitable explosives safety precautions. At plants of the Naval Air Systems Command, Department of the Navy, and other Government plants where the Government is responsible for safety, the precautions listed below are mandatory. These same minimum provisions listed below are recommended for observance by a contractor or manufacturer that explosively loads the item covered in this specification in order to fulfill his own safety responsibility. Other warnings and precautions, pertaining to the operational effectiveness or safety of the specified item during its use (for example, during its handling, launching or firing) are included in the detailed technical requirements of the specification. Use of this specification shall not be construed to replace other safety regulations of governmental agencies or to relieve the contractor or manufacturer of responsibility for the safety of his operations.

6.5.2 Personnel and equipment. Proper care must be exercised at all times to protect personnel from accidents, fires or explosions, and to limit damage to equipment and loading areas. In connection with the above, the precautionary measures in the following paragraphs should be observed. (See also paragraph 6.5.4, Static and electrical and other applicable parts of these safety precautions.)

6.5.2.1 Explosives operations shall be kept under strict supervision. Periodic inspections shall be employed to assure compliance with established safety regulations.

6.5.2.2 Safe equipment and methods should be utilized for handling and transporting explosives and loaded parts.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

6.5.2.3 Where required, remote control barricaded handling equipment shall be used for explosives operations such as mixing, pouring, weighing, charging, sifting, drying, pressing, casting, cripming, etc.

6.5.2.4 Employ properly proportioned and properly located protective barricades, screens or shields at all required points.

6.5.2.5 Maintain equipment such as presses, dies, crimpers, blenders, mixers, sifters, conveyors, and the like, in safe operating condition.

6.5.2.6 Enforce, where necessary, the wearing of suitable safety footwear, gloves, goggles, respirators, and impregnated garments to protect personnel against burns, poisoning and associated industrial hazards.

6.5.2.7 During static tests, propulsion units such as rocket motors shall be restrained against full thrust to prevent flight if ignited, for example, during test of igniter circuit. Also, means to vent flames and exhaust gases harmlessly shall be provided.

6.5.3 Operating procedures. All loading operations shall be conducted in full accordance with a formalized operating procedure which shall include the following:

6.5.3.1 Keep only minimum limited quantities of explosives and completed or partially loaded parts present at each stage of operations.

6.5.3.2 Allow no fires or exposed electrical or other sparking equipment, and little or no flammable material to be present in loading, handling and storage spaces. Enforce proper "Match" and "No Smoking" rules where necessary.

6.5.3.3 Appropriate safety instructions for specific operations shall be posted and personnel instructed as to the hazards present and precautions involved.

6.5.3.4 The number of working personnel and transients permitted in each work space shall be established and posted in such areas. The numbers shall be the minimum number required to accomplish necessary operations.

6.5.3.5 All loading operations should be conducted in a neat and orderly manner.

6.5.3.6 Enforce good housekeeping and maintain effective policing, inspection and supervisory methods throughout the loading area and surroundings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

6.5.3.7 Employ effective cleaning methods periodically to minimize the accumulation of explosives or explosive dust and other contamination upon, and assure its removal from, floors, walls, ceiling, ledges, tables, benches, piping, and equipment or the items loaded. Clean up any spilled material immediately.

6.5.3.8 The exposure of explosive materials and related parts should be so controlled as to minimize the absorption of moisture from the atmosphere or other sources during loading and handling operations.

6.5.3.9 Personnel handling detonators, primers, delay elements, lead-ins, boosters, and related parts which affect functioning should, insofar as practicable, avoid using bare fingers or improper equipment, in order to prevent damage, corrosion, or deterioration from perspiration or other contaminating deposits.

6.5.3.10 Keep explosives and explosive parts in approved covered receptacles with covers in place when material is not being taken out of or put into the receptacles. Where necessary, receptacles should be conductive to ground electrostatic charges. (See paragraph 6.5.4).

6.5.4 Static and electrical.

6.5.4.1 Protect operations from electrostatic charges by effectively grounding all machinery, equipment, and fixtures; and, where necessary, employ suitable grounded conductive coverings for floors, work benches and tables, and workers' conductive shoes. Workers' clothing of a type to minimize the accumulation of static charges shall be employed. Fabrics such as silk and nylon, which promote static generation shall be avoided. Additional grounding devices such as grounded bracelets for workers should be employed where operations are conducted with items which are unusually sensitive to initiation by static electricity. Such items include initiating explosives, tracer mixtures, and low energy type electric primers, detonators and squibs. The latter types of items shall have the free ends of lead wires bared and twisted together, and be packed in relatively small groups wrapped in bare non-insulated aluminum foil or other uncoated metal foil. During assembly and processing operations such sensitive electric items should be short circuited by clips or other devices until installed with safety shunt in the final device. Additional precautions for these items should include mechanical shielding to contain or deflect fragments and blast, also electrical shielding from induced electric currents originated by sources such as lightning, static, electromagnetic radiations, etc. Where necessary for safety, humidity of work rooms should be appropriately increased, as required to lessen electrostatic effects but without inducing excessive moisture absorption by any of the components of the item being processed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

6.5.4.2 Protect all explosive operations from effects of electric current originating in equipment such as soldering irons or guns, heaters, switches, wiring, motors, lights, test instruments, etc., by suitable insulation, grounding, separation or shielding. Such electric sources may initiate explosives by heat, sparks, arcs, or due to completing an electric circuit through an electric primer, detonator or squib. For example, circuits may be inadvertently completed from a defective electric soldering iron through a grounded contact. All electric type primers, detonators or squibs provided with wire leads shall have the free ends of the wires bared and twisted together to short circuit each unit, except when in process of assembly into a finished item. Removable short circuiting clips, or other devices should be employed during manufacturing operations involving items such as electric primers, detonators or squibs.

6.5.4.3 Where necessary, protect personnel and operations from electromagnetic energy. In certain work with very sensitive explosives or items, a shielded environment free from significant electromagnetic energy should be provided.

6.5.5 Operating facility and storage regulations.

6.5.5.1 All explosives and completely or partially loaded items should be stored in suitable storage magazines located in accordance, at a minimum, with the American Table of Distances (ATD); and, while in process, in safety lockers and chests if in loading rooms, or in adequate ready or service magazines located in accordance with Intraplant Distances set forth in the ATD when outside of loading rooms. For Navy managed or contractor managed Navy owned explosives loading plants, the Armed Services Explosives Safety Board standards approved by the Department of Defense, the Secretary of the Navy and the Naval Air Systems Command, covering quantity-distance relations for explosives, apply.

*U.S. GOVERNMENT PRINTING OFFICE: 1967-251-519/6071

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-23024A(AS) CARTRIDGE, DELAY, MARK 36 MOD 0

ORGANIZATION *(Of submitter)*	CITY AND STATE

CONTRACT NO.	QUANTITY OF ITEMS PROCURED	DOLLAR AMOUNT
		$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*	DATE

DD FORM 1 APR 63 1426

C-8378

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.