MILITARY SPECIFICATION

CARTRIDGE, DELAY, MARK 36 MOD 0

This amendment forms a part of Military Specification MIL-C-23024A, dated 10 April 1967.

PAGE 2

* Above STANDARDS: Delete "Bureau of Naval Weapons" and the document listed thereunder.

* Under DRAWINGS: Delete "Bureau of Naval Weapons" and substitute "Naval Air Systems Command (Code Ident 30003)". Add,

"LD 2838183	Test Set, for Cartridge Delay, Assembly (.38 CAL Size)
2838190	Sleeve
838AS100	Propellant, Double Base"

Under PUBLICATIONS: Delete "BUSANDA Instruction 4030.17" and title.

* Delete "Bureau of Naval Weapons" and substitute "Naval Sea Systems Command".

PAGE 3

2.2, under CODE OF FEDERAL REGULATIONS, delete "49 CFR 71-78" and title, and substitute:

"49 CFR 171-178	Transportation, Explosives and other Dangerous Articles"

* 3.2, line 3: Delete "Bureau of Naval Weapons".

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

PAGE 4

* 3.5, 3.6, 3.7, 3.7.1: Delete "Bureau of Naval Weapons".

* 3.7, line 3: Delete "OS 9862" and substitute "Drawing 838AS100".

PAGE 5

* 3.9.2: Delete "Level and duration of pressure" and substitute "Pressure".

* 3.9.2.1, line 2: Delete "1000" and substitute "2330".

* 3.9.2.2: Delete in its entirety and substitute

"3.9.2.2 Time to 1600 psi. Time to 1600 psi shall not exceed 4.1 ms T_u."

* Add the following:

"3.9.2.3 Time to maximum pressure. The upper limit to maximum pressure shall be T_u 8.4 ms."

PAGE 6

4.3.3, line 1: Delete "111" and substitute "91".

PAGE 7

4.6.1, delete and substitute:

"4.6.1 Packaging, packing and marking. (M105) Quality conformance inspection shall be conducted in accordance with the inspection criteria on the applicable drawings referenced in Section 5."

PAGE 8

* 4.8.1, delete and substitute:

"4.8.1 The number of cartridges selected from each production lot for the ballistic tests shall be in accordance with the requirements of Table I of MIL-STD-105, Inspection Level III. The sample of cartridges shall be divided, as nearly as possible, into three equal groups; if the sample of cartridges is not equally divisible by 3, the excess cartridges shall be placed in the group

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

that is to be fired at -65° F. Samples in group 1 inserted in sleeve (Drawing 2838190) of test set (Drawing DL 2838183) shall be conditioned at -65° ± 5° F for a minimum of 24 hours and fired in the test set within three minutes after removal from conditioning. Samples in group 2 inserted in sleeve (Drawing 2838190) of test set (Drawing DL 2838183) shall be conditioned at 160° ± 5° F for a minimum of 24 hours and fired in the test set within three minutes after removal from conditioning. Samples in group 3 inserted in sleeve (Drawing 2838190) of test set (Drawing DL 2838183) shall be conditioned at 70° ± 5° F for a minimum of 24 hours and fired in the test set within three minutes after removal from conditioning. In addition to the sample of cartridges for the above test, 10 additional cartridges shall be furnished from the production lot for investigative purposes."

* 4.8.1.1, delete first sentence and substitute: "The delay time, time to 1600 psi, time to maximum pressure, and lower limit of maximum pressure shall meet the requirements of 3.9."

PAGE 9

5.1.3, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.2.3, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.3.1, last line, delete "49 CFR 71-78" and substitute "49 CFR 171-178".

5.3.2, delete and substitute:

"5.3.2 Normal markings. Unless otherwise specified in the contract or order, the marking information on unit packages and shipping containers shall be as specified on the drawings listed on LD 537902 and LD 537903, respectively. The specified marking information shall be applied to the containers in accordance with the applicable provisions of MIL-STD-129."

PAGE 10

6.3.1, delete and substitute:

"6.3.1 Test report. The contract or order should specify that results of ballistic tests are to be forwarded to the Naval Air Systems Command (AIR-5323G) and the procuring activity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.

6.4, delete and substitute:

"6.4 Definitions. For the purposes of this specification, the following definitions apply."

PAGES 11, 12, 13 and 14

6.5 and subparagraphs, delete and substitute:

"6.5 Explosives safety precautions. Safety precautions for explosive-loaded items are contained in DOD 4145.26M, "DOD Contractors' Safety Manual for Ammunition, Explosives and Related Dangerous Material"."

NOTE: The margins of this amendment are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Preparing Activity
NAVY - AS
Project No. 1377-N647

☆U.S. GOVERNMENT PRINTING OFFICE: 1978—703-122/3041

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T15:16Z
Check the source to verify that this is the current version before use.