MIL-B-36538A
26 September 1974
SUPERSEDING
MIL-B-36538
31 May 1967

MILITARY SPECIFICATION

BAG, BUCKSHOT

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers bags for holding buckshot to serve as weight when used with frames, for extension of fractures.

1.2 Classification.

1.2.1 Types and sizes.

Type I. Open end with handle, Round.
Type II. Closed end with small opening, Rectangular.

Size A. 3 inch
Size B. 5 inch

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of the specification to the extent specified herein.

SPECIFICATIONS

Federal

CCC-C-419	Cloth, Cotton Duck, Unbleached, Plied Yarns, Army and Numbered.
PPP-B-585	Box, Wood, Wirebound.
PPP-B-601	Box, Wood, Cleated-Plywood.
PPP-B-621	Box, Wood, Nailed and Lock-Corner.
PPP-B-636	Box, Fiberboard.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

Military

MIL-L-10547	Liners, Case and Sheet, Overwrap; Water-Vaporproof or Waterproof, Flexible.
MIL-W-530	Webbing, Textile, Cotton, General Purpose, Natural or In Colors.

STANDARDS

Federal

FED-STD-191	Textile Test Methods
FED-STD-751	Stitch, Seam, and Stitching

Military

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	Marking for Shipment and Storage.

(Copies of specification, standards, and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Material. Material shall be as specified herein; of the highest quality throughout, and suitable in all respects for the purpose intended.

3.2 Design and construction. Design and construction of buckshot bags, in the types and sizes indicated shall be as follows.

3.2.1 Type I. Type I bag shall be cylindrical, 9 inches in height and 8 inches in diameter with open end and handle. Tolerance shall be -0, +1 inch.

* 3.2.1.1 Bag. Bag shall be of unbleached cotton duck in accordance with the requirements of CCC-T-419 for type III-Army Duck, 9.85 ounces per square yard, minimum. Side wall of bag shall be constructed of one piece, with one side seam type LSc-2, in accordance with FED-STD-751. Bottom shall be one piece; bottom seam shall be type SS-F-3, using a type I, 5/8-inch wide cotton hem, (with edge turned up). Stitching for upper edge shall conform to type EFb-1 of FED-STD-751.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

3.2.1.2 Handle. The handle shall be in accordance with the requirements of MIL-W-530, for unbleached, type I, light weight webbing, one-inch width. The length of the handle shall be a minimum of 10 inches, excluding the sewed ends. The ends of the handle shall be secured to the upper hem of the bag, each end secured to a diametrically opposite side of the bag. In securing each handle end, a minimum of 3/8 inch of the handle end shall be turned under the upper hem of the bag, and this portion shall be sewed to the bag during the sewing of the hem. Each handle end shall be further secured to the hem of the bag by stitching around the periphery of the portion of the handle end in contact with the upper hem and by cross stitching within the peripheral stitching (diagonally from corner to corner of the peripherally stitched area). Two copper rivets (1/4 inch rivet heads) shall be placed through each handle end and the upper hem of the bag near the top edge of the bag. A 1/4 inch copper washer shall be placed under each rivet head and under the peened portion of each rivet on the inside of the bag.

3.2.2 Type II.

3.2.2.1 Size A. Bag shall be made of unbleached cotton duck in accordance with the requirements of CCC-C-419 for type III, Army Duck, 8.25 ounces per square yard, minimum. The bag shall be 3 inches by 4-1/2 inches minimum, and shall be made of two pieces of material joined on all four sides by seam type SS-C-1. A one-inch opening shall be left on one corner for insertion of buckshot. Seams shall have not less than 16 stitches to the inch.

3.2.2.2 Size B. Bag shall be 5 inches square, minimum; and similar in construction to size A bag. Bag shall be made of unbleached cotton duck in accordance with the requirements of CCC-C-419 for type III, Army duck, 8.25 ounces per square yard, minimum.

* 3.3 Shrinkage in laundering. Material shall not show more than one percent of shrinkage after being tested in accordance with method 5550 of FED-STD-191.

* 3.4 Identification marking. Each bag shall be permanently and legibly marked with the following information:

Name or registered trademark of the manufacturer.
National Stock Number.
Contract or purchase order number.

Marking secured by adhesives shall not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

3.5 Workmanship. Workmanship shall be first class throughout. The bags shall be free from defects which detract from their appearance or may impair their serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

* 4.1.1 Records. Records of examinations and tests performed by or for the contractor shall be maintained by the contractor and made available to the Government, upon the Government's request, at any time, or from time to time, during the performance of the contract and for a period of 3 years after delivery of the supplies to which such records relate.

4.1.2 Inspection. Inspection, as used in this specification, is defined as both examination (such as visual or auditory, investigation without the use of special laboratory appliances or procedures) and testing (determination by technical means of physical and chemical properties) of the item.

4.1.3 Certificates of quality. When available, certificates of quality, supplied by the manufacturer of the component or material, listing the specified test method and test results obtained, may be furnished in lieu of actual performance of such testing by the contractor.

4.2 Sampling.

4.2.1 For examination. Sampling for examination shall be conducted in accordance with MIL-STD-105 and Table I.

Table I

	Inspection level	AQL (defects per hundred units)
For visual examination		
Major defects	II	2.5
Minor defects	II	6.5
For dimensional examination	S-3	2.5

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

4.2.2 Raw materials. Sufficient number of samples of each lot of cloth, tape, thread, and webbing use in the manufacture of the bag shall be selected for the applicable tests and examinations.

4.3 Examination. The bags shall be examined to determine compliance with all requirements contained in this specification.

4.3.1 Classification of defects. Examination shall be conducted in accordance with the classification of defects listed in Table II.

Table II. Categories and defects*

Major	
101	Handle not secured to the bag as specified.
102	Bag not free of holes and tears.
103	Stitching not free of breaks.
Minor	
201	Bag not free of spots, discolorations
202	Identification marking not present, complete, correct, legible, nor permanent.

* Examination shall not be restricted to the classified possible defects listed above.

4.3.2 Dimensionsal examination. The bags shall be examined for defects in dimensions. Any dimension not within the tolerance specified herein shall be classified as a defect.

5. PREPARATION FOR DELIVERY

5.1 Packaging.

5.1.1 Unit of issue. One bag, as specified, constitutes one unit of issue.

5.1.2 Packaging quantities. The number of units of issue indicated in Table III shall be packaged in each unit, intermediate, and exterior container, as applicable, for the required level of protection specified in the procurement document.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

Table III

Type	Unit package	Intermediate package	Exterior container
II			
Size A	Not required	144 units	3456 units
Size B	Not required	48 units	2304 units
I	Not required	24 units	432 units

5.1.2.1 Packing variation permitted. If the required number of units in the entire shipment is less than the number of units specified to be overpacked in an exterior container, such units shall be packed in an exterior container of suitable size and design, acceptable to a common carrier, which shall insure safe delivery to destination.

5.1.3 Level A.

* 5.1.3.1 Unit package. No unit package required.

* 5.1.3.2 Intermediate package. Intermedaite package shall be a box of appropriate size and design constructed in accordance with PPP-B-636, type CF, class domestic.

5.1.4 Level C. Units shall be packaged in standard commercial containers of the size and kind commonly used, which will afford the degree of protection required for shipment and use of the product for its intended purpose.

5.2 Packing.

5.2.1 Level A.

* 5.2.1.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 3, style 3; PPP-B-601, overseas type; PPP-B-621, class 2; or PPP-B-636, class weather-resistant, grade V3c. Closure and strapping shall be as specified in the appendix of the applicable box specification. Special requirements of applicable table shall apply for PPP-B-636 box.

* 5.2.1.2 Case liner. Each Level A wood box shall be lined with a waterproof case liner conforming to MIL-L-10547. Closure and sealing shall conform to applicable paragraphs of appendix thereto. Case liner shall not be required for fiberboard boxes. Fiberboard box shall be waterproof in accordance with paragraph 30.4 of PPP-B-636.

5.2.2 Level B.

* 5.2.2.1 Exterior container. Exterior container shall be designed for a type 2 load and constructed in accordance with PPP-B-585, class 1, style 3; PPP-B-601, domestic type; PPP-B-621, class 1; or PPP-B-636, class domestic. Closure shall be as specified in the appendix of the applicable box specification. Fiberboard box shall be closed by method II of PPP-B-636. Special requirements of applicable table shall apply for PPP-B-636 box.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. The subject commodity shall be packed in substantial commercial containers of the type, size, and kind commonly used for the purpose, so constructed as to insure acceptance and safe delivery by common or other carriers, at the lowest rate, to point of delivery called for in the contract or purchase order.

5.3 Marking.

* 5.3.1 Unit package. Each unit shall be marked with National Stock Number, item description, quantity (1 EA), date packed, contract or purchase number, and name of contractor.

5.3.2 Intermediate packages. Each intermediate package shall be marked in accordance with MIL-STD-129. When labels are utilized, waterproofing shall be required only when applicable carton is fabricated of water-resistant material. Contract or purchase order number and name of contractor shall be shown.

5.3.3 Exterior container. Exterior container shall be marked in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. Shall be suitable for use in military medical facilities to contain buckshot during fracture traction techniques.

* 6.2 Ordering data. Procurement documents should specify the following:

(a) Number and date of this specification.
(b) Selection of applicable levels of packing (see 5.1 and 5.2).
(c) Type and size of bag.

6.3 This specification covers the following items appearing in the Federal Supply Catalog:

Stock No.	Item Identification	Specification Designation	
		Type	Size
6530-00-308-4100	Bag, Buckshot, 3 inch	II	A
6530-00-308-4200	Bag, Buckshot, 5 inch	II	B
6530-00-308-4400	Bag, Buckshot, 8 inch	I	

6.4 This specification does not cover all types, classes, grades, or sizes of the commodity indicated by the title of this specification, or those which are commercially available, but is intended to cover the types which are normally procured to meet requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

6.5 The margins of this specification are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodians:
Army - MD
Navy - MS
Air Force - 03

Review activities:
Army - MD
Navy - MS
Air Force - 03

Preparing activity:
Defense Supply Agency - DSA-DM

Project No. 6530-1315

Review information is current as of the date of this document. For future coordination of changes to this document, draft circulation should be based on the information in the current DODISS.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB Approval
No. 22-R255

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help achieve procurement of suitable products at reasonable cost and minimum delay, or will otherwise enhance use of the document. DoD contractors, government activities, or manufacturers/ vendors who are prospective suppliers of the product are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE: MIL-B- 36538A

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426 REPLACES EDITION OF 1 JAN 66 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T08:46Z
Check the source to verify that this is the current version before use.