NOTE: The document identifier and heading have been changed on this page to reflect that this is a performance specification. There are no other changes to this document. The document identifier on subsequent pages has not been changed, but will be changed the next time this document is revised.


MIL-PRF-27/240A
8 April 1980
SUPERSEDING
MIL-T-27/240
11 September 1978

PERFORMANCE SPECIFICATION SHEET

TRANSFORMERS AND INDUCTORS
(AUDIO, POWER AND HIGH-POWER PULSE)
INDUCTORS, AUDIO FREQUENCY, HIGH Q, TF5R20ZZ

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the inductors described herein shall consist of this document and the latest issue of Specification MIL-T-27.



WV-175 V
ALTITUDE-75,000 FT MAX
(SEE TABLE I FOR VALUE OF "X")

CIRCUIT DIAGRAM AND MARKING

INCHES	MM
.016	0.41
.025	0.64
.125	3.18
.281	7.14
.328	8.33
.468	11.89
1.250	31.75

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Marking shall be on the side of the case.
4. Electrical values shall be marked as specified in table I, as applicable.

FIGURE 1. Dimensions and configurations.

(A) Denotes changes

FSC 5950

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:56Z
Check the source to verify that this is the current version before use.

REQUIREMENTS. (When numbers in parentheses, i e , (1-2) are used, they indicate the winding and the extreme terminals of the winding)

Electrical ratings See table I

TABLE I Electrical ratings. 1/

Dash No	Inductors 2/ mH (1-2) ±2%	DC 3/ current mA (1-2) max.	DC resistance ohms (max) (1-2)	Quality factor (min)	Temperature stability (-55° to +105°C)	Working voltage (peak) volts	Voltage (1-2)
01	3.0	50	4.8	40 at 50 kHz	±2%	175	0.1 volt at 1 kHz
02	5 0	40	8 0	40 at 50 kHz	±2%	175	0.1 volt at 1 kHz
03	8 0	30	13.0	40 at 50 kHz	±2%	175	0.1 volt at 1 kHz
04	12 5	25	19.0	40 at 50 kHz	±2%	175	0.1 volt at 1 kHz
05	20.0	20	31.0	45 at 25 kHz	±2%	175	0 1 volt at 1 kHz
06	30.0	16	47 0	45 at 25 kHz	±2%	175	0 1 volt at 1 kHz
07	60 0	11	94 0	45 at 25 kHz	±2%	175	0 1 volt at 1 kHz
08	120 0	8	186.0	40 at 25 kHz	±2%	175	0.1 volt at 1 kHz

1/ Qualification testing and approval to M27/240-8 shall be sufficient to grant qualification approval to M27/240-1 through M27/240-7.
2/ The inductance is measured with 0 Adc applied to (1-2) and at the specified voltage across (1-2).
3/ The amount of DC current that will reduce the inductance a maximum of 7%

Design and construction·
Dimensions and configuration See figure 1.
Duty cycle Continuous.
Case Diallyl phthalate.
Ⓐ Terminals· 0 025 tin-lead plated type D4 in accordance with MIL-STD-1276
Weight 0.08 ounce maximum
Altitude 75,000 feet maximum.
Operating temperature range -55° to +105°C.

Terminal strength MIL-STD-202, method 211, test condition A, 2 pounds

Dielectric withstanding voltage
At sea level 500 volts rms
At reduced barometric pressure 300 volts rms

Vibration (high frequency) MIL-STD-202, method 204

Marking location See figure 1

Part number M27/240- (dash number from table I)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:56Z
Check the source to verify that this is the current version before use.

Custodians
Army - ER
Navy - EC
Air Force - 85

Review activities
Army - MI
Navy - SH, OS
Air Force - 11, 17, 99
DLA - ES

User activities
Army - AR, WC
Navy - MC, AS
Air Force - 19

Preparing activity
Army - ER

Agent
DLA - ES

(Project 5950-0569-14)

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:56Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document If there are additional papers, attach to form and place both in an envelope addressed to preparing activity A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-T-27/240A TRANSFORMERS AND INDUCTORS (AUDIO, POWER AND HIGH-POWER PULSE) INDUCTORS, AUDIO FREQUENCY, HIGH Q, TF5R20ZZ

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW

A GIVE PARAGRAPH NUMBER AND WORDING

B RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO

DATE

DD FORM 1 OCT 76 1426

EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:56Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID



OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

Cdr, US Army ERADCOM
ATTN: DELET-R-S
Fort Monmouth, NJ 07703

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T03:56Z
Check the source to verify that this is the current version before use.