MILITARY SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING

TYPE 6360

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

DESCRIPTION: Double tetrode, rf amplifier, F1 = 200 MHz

Outline	---	6-4 (EIA)
Base	---	E9-1
Envelope	---	T6-1/2
Cathode	---	Coated unipotential

Base connections:

Pin No.	---	1	2	3	4	5	6	7	8	9
Element	---	1g1	k, int sd	2g1	h	h	1a	1g2, 2g2	2a	hct

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ef	Eb	Ec1	Ec2	Ⓒ Ehk	Ik	Ib
Unit:	V	Vdc	Vdc	Vdc	v	mAdc	mAdc
Maximum:							
Class C, Telep (continuous duty)	6.9 or 13.9	240	-150	200	100	2x40	2x37.5
Class C, Teleg (continuous duty)	6.9 or 13.9	300	-150	200	100	2x50	2x45
Minimum:	5.7 or 11.3	---	---	---	---	---	---
TEST CONDITIONS:	6.3 or 12.6	200	Adj	200	---	---	2x30

ABSOLUTE-MAXIMUM RATINGS:

Parameter:	Ic1	Pg1	Pg2	Pp	Pi	TE	Ⓒ Alt
Unit:	mAdc	W	W	W	W	°C	ft
Maximum:							
Class C, Telep (continuous duty)	2x3	2x0.2	2x0.65	2x3.3	2x7.5	225	Note 1
Class C, Teleg (continuous duty)	2x3	2x0.2	2x1.0	2x5.0	2x11.25	225	Note 1
Minimum:	---	---	---	---	---	---	---
TEST CONDITIONS:	---	---	---	---	---	---	---

GENERAL:

Qualification - Required

Ⓒ denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1							
1301	Heater current	Ef = 6.3 V	0.65	II	If	770	880	mAdc
1256	Electrode current (1) (anode)	Ec1 = -15 Vdc (see note 2)	0.65	II	Ib	10	65	mAdc
1266	Total grid current	Eb = Ec2 - 150 Vdc; Ib = 2 x 40 mAdc; t = 180 sec (see note 3)	0.65	II	Ic1	---	-6.0	µAdc
1231	Peak emission	eb = ec2 = 200 V; Ec1 = +60 V (see note 4)	0.65	II	is	800	---	mA
1201	Short and discontinuity detection		0.4	II	---	---	---	---
	Quality conformance inspection, part 2							
1316	Amplification factor (screen)	See notes 2 and 6	---	---	Mu	5.6	9.3	---
1331	Direct-interelectrode capacitance	See note 5	---	---	Cgp	---	0.1	pF
					Cin	5.6	6.8	pF
					Cout	2.2	3.0	pF
1031	Low-frequency vibration	Eb = 250 Vdc; Ec1/Ib = 10 mAdc; Rp = 2,000 ohms (see note 2)	---	---	Ep	---	800	mVac
(C) 1236	Power output	Class C amplifier; F = 150 MHz; Eb = 300 Vdc; Ic1 = 2 mAdc (max); Ec2 = 175 Vdc; Ib = 75 mAdc (max); Ic2 = 5 mAdc (max); Rg2 = 100 ohms; Ec1 = -40 Vdc (see note 7)	---	---	Po	10	---	W
1121	Base strain		---	---	---	---	---	---
2126	Glass strain		2.5	I	---	---	---	---
(C) 1211	Insulation of electrodes		4.0	S3	---	---	---	---
(C) 1105	Permanence of marking		---	---	---	---	---	---
	Quality conformance inspection, part 3							
---	Life-test provisions	Group C; Class "C" amplifier	---	---	---	---	---	---
---	Life-test end points (500 hours)	Power output	---	---	Po	8	---	W
		Peak emission	---	---	is	600	---	mA
		Total grid current	---	---	Ic1	---	-10.0	µAdc

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

NOTES:

1. See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.
2. Each unit shall be read separately. Control grid of unit not under test shall be connected to -100 Vdc.
3. This test to be performed at the conclusion of the holding period.
4. Test both units in parallel. Ec1 is a rectangular pulse voltage with a pulse width of 800 µs; this pulse voltage is superimposed on Ec1 -100 Vdc (total pulse voltage = 160 V. Duty cycle = 0.04.
5. Each unit shall be tested separately; ground unit not under test.
6. Screen grid Mu is determined by measuring grid voltage required to adjust anode current for grid 2 voltages of 210 and 190 volts. Mu = 20/Δ Ec1 at Eb = 200 Vdc; Ib = 30 mAdc.
7. Power output is total power at drive frequency delivered to load output circuit adjusted so that Pp does not exceed 2 x 5 watts.

Custodians:
Army - EL
Navy - EC
Air Force - 80

Review activities:
Army - EL, MU
Navy -
Air Force - 11, 80
DSA - ES

User activities:
Army - WC
Navy - AS, OS, MC, CG, SH
Air Force - 19

Preparing activity: Navy - EC

Agent: DSA - ES

(Project 5960-2425-81)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

3256 | Anode delay time grid | 11 | Anode delay

FOLD

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)*

CITY AND STATE

CONTRACT NO.

QUANTITY OF ITEMS PROCURED

DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)*

DATE

DD FORM 1 APR 63 1426

REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.