INCH-POUND

MIL-PRF-1/1308D
19 July 1999
SUPERSEDING
MIL-E-1/1308C
17 August 1970

PERFORMANCE SPECIFICATION SHEET

ELECTRON TUBE, RECEIVING
TYPE 6360

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the electron tube described herein shall consist of this document and the latest issue of MIL-PRF-1.

DESCRIPTION: Double tetrode, rf amplifier, F1 = 200 MHz.
Outline: 6-4 (EIA).
Base: E9-1.
Envelope: T6-1/2.
Cathode: Coated unipotential.
Base connections:

| Pin No. | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 |
|---|---|---|---|---|---|---|---|---|---|
| Element | 1g1 | k, int sd | 2g1 | h | h | 1a | 1g2, 2g2 | 2a | hct |

ABSOLUTE MAXIMUM RATINGS:

| Parameter: | Ef | Eb | Ec1 | Ec2 | Ehk | Ik | Ib |
|---|---|---|---|---|---|---|---|
| Unit: | V | V dc | V dc | V dc | v | mA dc | mA dc |
| Maximum: | | | | | | | |
| Class C, Telep (continuous duty) | 6.9 or 13.9 | 240 | -150 | 200 | 100 | 2 x 40 | 2 x 37.5 |
| Class C, Teleg (continuous duty) | 6.9 or 13.9 | 300 | -150 | 200 | 100 | 2 x 50 | 2 x 45 |
| Minimum: | 5.7 or 11.3 | --- | --- | --- | --- | --- | --- |
| Test conditions: | 6.3 or 12.6 | 200 | Adj | 200 | --- | --- | 2 x 30 |

ABSOLUTE MAXIMUM RATINGS:

| Parameter: | Ic1 | Pg1 | Pg2 | Pp | Pi | TE | Alt |
|---|---|---|---|---|---|---|---|
| Unit: | mA dc | W | W | W | W | °C | ft |
| Maximum: | | | | | | | |
| Class C, Telep (continuous duty) | 2 x 3 | 2 x 0.2 | 2 x 0.65 | 2 x 3.3 | 2 x 7.5 | 225 | 1/ |
| Class C, Teleg (continuous duty) | 2 x 3 | 2 x 0.2 | 2 x 1.0 | 2 x 5.0 | 2 x 11.25 | 225 | 1/ |
| Minimum: | --- | --- | --- | --- | --- | --- | --- |
| Test conditions: | --- | --- | --- | --- | --- | --- | --- |

See footnotes at end of table I.

GENERAL:

Qualification: Required.


DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection.

| Inspection | Method | Conditions | Acceptance level | Inspection level or code | Symbol | Limits | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | | | | Min | Max | |
| Conformance inspection, part 1 | | | | | | | | |
| Heater current | 1301 | Ef = 6.3 V | 0.65 | II | If | 770 | 880 | mA dc |
| Electrode current (1) (anode) | 1256 | Ec1 = -15 V dc 2/ | 0.65 | II | Ib | 10 | 65 | mA dc |
| Total grid current | 1266 | Eb = Ec2 = 150 V dc; Ib = 2 x 40 mA dc; t = 180 sec 3/ | 0.65 | II | Ic1 | --- | -6.0 | µA dc |
| Peak emission | 1231 | eb = ec2 = 200 V; Ec1 = +60 V 4/ | 0.65 | II | is | 800 | --- | mA |
| Short and discontinuity detection | 1201 | | 0.4 | II | --- | --- | --- | --- |
| Conformance inspection, part 2 | | | | | | | | |
| Amplification factor (screen) | 1316 | 2/ 6/ | --- | --- | Mu | 5.6 | 9.3 | --- |
| Direct-interelectrode capacitance | 1331 | 5/ | --- | --- | Cgp | --- | 0.1 | pF |
| | | | | | Cin | 5.6 | 6.8 | pF |
| | | | | | Cout | 2.2 | 3.0 | pF |
| Low-frequency vibration | 1031 | Eb = 250 V dc; Ec/Ib = 10 mA dc; Rp = 2,000 ohms 2/ | --- | --- | Ep | --- | 800 | mV ac |
| Power output | 1236 | Class C amplifier; F = 150 MHz; Eb = 300 V dc; Ic1 = 2 mA dc (max); Ec2 = 175 V dc; Ib = 75 mA dc (max); Ic2 = 5 mA dc (max); Rg2 = 100 ohms; Ec1 = -40 V dc 7/ | --- | --- | Po | 10 | --- | W |
| Base strain | 1121 | | --- | --- | --- | --- | --- | --- |
| Glass strain | 2126 | | 2.5 | I | --- | --- | --- | --- |
| Insulation of electrodes | 1211 | | 4.0 | S3 | --- | --- | --- | --- |
| Permanence of marking | 1105 | | --- | --- | --- | --- | --- | --- |

See footnotes at end of table.



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

TABLE I. Testing and inspection - Continued.

| Inspection | Method | Conditions | Acceptance level | Inspection level or code | Symbol | Limits | | Unit |
|---|---|---|---|---|---|---|---|---|
| | | | | | | Min | Max | |
| Conformance inspection, part 3 | | | | | | | | |
| Life-test provisions | --- | Group C;<br>Class "C" amplifier | --- | --- | --- | --- | --- | --- |
| Life-test end points<br>(500 hours) | --- | Power output<br>Peak emission<br>Total grid current | ---<br>---<br>--- | ---<br>---<br>--- | Po<br>is<br>Ic1 | 8<br>600<br>--- | ---<br>---<br>-10.0 | W<br>mA<br>µA dc |

1/ See "Reduced pressure (altitude) rating", and altitude, maximum peak voltage.

2/ Each unit shall be read separately. Control grid of unit not under test shall be connected to -100 V dc.

3/ This test to be performed at the conclusion of the holding period.

4/ Test both units in parallel. Ec1 is a rectangular pulse voltage with a pulse width of 800 µs; this pulse voltage is superimposed on Ec1 = -100 V dc (total pulse voltage = 160 V.) Duty cycle = 0.04.

5/ Each unit shall be tested separately; ground unit not under test.

6/ Screen grid Mu is determined by measuring grid voltage required to adjust anode current for grid 2 voltages of 210 and 190 volts. Mu = 20/ΔEc1 at Eb = 200 V dc; Ib = 30 mA dc.

7/ Power output is total power at drive frequency delivered to load output circuit adjusted so that Pp does not exceed 2 x 5 watts.



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.

Custodian:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AR
Navy - AS, CG, MC, OS
Air Force - 19, 99

Preparing activity:
DLA - CC

(Project 5960-3546-03)



Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:26Z
Check the source to verify that this is the current version before use.