MILITARY SPECIFICATION SHEET

ELECTRON TUBE, NEGATIVE GRID (MICROWAVE)

TYPE 7554

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for procuring the electron tube described herein shall consist of this document and the latest issue of Specification MIL-E-1.

DESCRIPTION: Triode, pencil, ceramic-metal

See figure 1

Mounting position: Any

Weight: 0.3 ounce (8.5 grams) nominal

ABSOLUTE RATINGS: Class C amplifier

Parameter:	Ef	Eb	Ec	Ehk	Rk	Rg	Ik	Ic	Pp	TE	Barometric pressure, reduced
Unit:	V	Vdc	Vdc	V	Ohms	Meg	mAdc	mAdc	W	°C	mmHg
Maximum:	6.9	250	0	+50	---	0.25	25	6	2.5	225	8
Minimum:	5.7	---	-50	-50	---	---	---	---	---	---	---
TEST CONDITIONS:	6.3	125	---	---	50	---	---	---	---	---	---

GENERAL:

Qualification - Required

(D) denotes changes

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS MIN	LIMITS MAX	UNIT
	Quality conformance inspection, part 1								
1266	Total grid current	3	Eb = 200 Vdc; Ec = -2 Vdc; Rg = 0.5 Meg	0.65	II	Ic	0	-0.3	µAdc
1256	Electrode current (1) (anode)	-	Ck = 1,000 µF	0.65	II	Ib	9	19	mAdc
1256	Electrode current (2) (anode)	-	Ec = -5 Vdc; Rk = 0	0.65	II	Ib	—	50	µAdc
1306	Transconductance (1)	-	Ck = 1,000 µF	0.65	II	Sm	12,500	19,500	µmhos
(D) 4250	Output power (1)	4	Eb = 250 Vdc	0.65	II	Po	1.7	—	W
	Quality conformance inspection, part 2								
(D) 1301	Heater current	-	Ef = 6.3 V	---	---	If	205	245	mA
1336	Heater-cathode leakage	-	Ehk = +60 Vdc Ehk = -60 Vdc	--- ---	--- ---	Ihk Ihk	--- ---	30 30	µAdc µAdc
1306	Transconductance (2)	5	Ef = 5.7 V	---	---	ΔSm Ef	---	15	%
(D) 1331	Direct-interelectrode capacitance	1		---	---	Cgp Cgk Cpk	1.5 3.6 ---	2.7 5.00 0.040	pF pF pF
1256	Electrode current (3) (anode)	-	Ec = -2.5 Vdc; Rk = 0	---	---	Ib	100	---	µAdc
1316	Amplification factor	-	Ck = 1,000 µF	---	---	Mu	65	85	---
1211	Insulation of electrodes	-	E(g-all) = -100 Vdc E(p-all) = -300 Vdc	---	---	R	100	---	Meg
(D) 4250	Output power (2)	4	Ef = 5.7 V; Eb = 250 Vdc; do not retune cavity	---	---	ΔPo Ef	---	0.2	W
	Quality conformance inspection, part 3								
1031	Sweep frequency vibration	2, 18	Ebb = 125 Vdc; Rl = 10,000 ohms; Rk = 50 ohms	---	---	Ep	---	180	mVac
1031	Variable-frequency vibration	2, 18	Ebb = 125 Vdc; Rl = 10,000 ohms; Rk = 50 ohms	---	---	Ep	---	180	mVac
1041	Shock	16, 18	Hammer angle = 30°	---	---	---	---	---	---
1031	Vibration fatigue	17, 18	2.5 G; fixed frequency; F = 25 Hz (min), 60 Hz (max)	---	---	---	---	---	---
---	Shock and vibration-fatigue test end points:								
1031	Sweep and variable-frequency vibration	-		---	---	Ep	---	200	mVac
1336	Heater-cathode leakage	-		---	---	Ihk	---	60	µAdc
---	Seal fracture	6, 7, 18		---	---	---	30	---	Lbs

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.

METHOD	REQUIREMENT OR TEST	NOTES	CONDITIONS	AQL (PERCENT DEFECTIVE)	INSPECTION LEVEL OR CODE	SYMBOL	LIMITS		UNIT
							MIN	MAX	
	Quality conformance inspection, part 3 -Continued								
---	Seal strain	7, 18, 19		---	---	---	---	---	---
				---	---	---	---	---	---
1806	Heater-cycling life	9, 14, 18	Group D; Ef = 6.3 V; Ehk = 0; Eb = 0; Rk = 0	---	---	---	---	---	---
---	Heater-cycling life-test end points:								
---	Shorts or open heaters	-		---	---	---	---	---	---
1336	Heater-cathode leakage	-	Ehk = +90 Vdc	---	---	Ihk	---	30	μAdc
			Ehk = -90 Vdc	---	---	Ihk	---	30	μAdc
1211	Insulation of electrodes	-	E(g-all) = -100 Vdc	---	---	R	90	---	Meg
1516	Stability life test (2 hours)	11, 20	Group D; Eb = 215 Vdc; Rk = 150 ohms; TA = room, 25° ±5°C; g1 grounded	---	---	---	---	---	---
---	Stability life-test end point:								
1306	Transconductance (1)	-		---	---	Δ Sm t	---	15	%
1521	Survival-rate life test	13, 15	Stability life test, or equivalent conditions; TA = room, 25° ±5°C; t = 100 hours	---	---	---	---	---	---
---	Survival-rate life test end points:								
1256	Electrode current (2) (anode)	-		---	---	Ib	---	50	μAdc
1306	Transconductance (1)	-		---	---	Sm	9,000	---	umhos
1801	Intermittent life	10, 12, 14	Group C; Ef = 6.3 V; Ebb = 280 Vdc	---	---	t	2,000	---	cycles
---	Intermittent life-test end points:								
4250	Output power (1)	-		---	---	Po	8.90	---	W
1266	Total grid current	-		---	---	Ic	---	-1.0	μAdc
1211	Insulation of electrodes	-		---	---	R	90	---	Meg
(B) 1002	Barometric pressure, reduced	8	Pressure = 8 ±2 mmHg; voltage = 300 Vac	---	---	---	---	---	---

NOTES:

1. Test in capacitance jig RCA Capacity Adapter Model H-1786E, or equivalent.

2. The tube shall be vibrated perpendicular to the major tube axis through a frequency range from 5 to 500 Hz and back. From 5 to 50 Hz, the tube shall be vibrated at a constant displacement of 0.060 ±0.0025 inch (1.02 ±0.06 mm). From 50 to 500 Hz, the tube shall be vibrated at a constant acceleration of 10 ±2G. Total time to complete a sweep cycle shall be 10 ±5 minutes.

   (a) Each tube shall be vibrated for 60 seconds at the frequency which gives maximum vibrational output. If at the end of 60 seconds the vibrational output is still increasing, the vibration shall continue until there is no further increase.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

2. -Continued

   (b) The tube shall be rejected for vibrational output voltage exceeding the limit specified herein or failure to pass the continuity and shorts test.

3. This test is to be the first test performed at the conclusion of the holding period.

4. This test shall be performed in amplifier cavity Amerac Model No. 1244-1, or equivalent. Test frequency shall be 550 ±10 MHz. Input = 0.2 W. When the amplifier has been tuned, adjust Ec for Ib = 20 mAdc.

5. Transconductance (2) is the percent change in transconductance (1) of an individual tube resulting from a change in Ef.

6. Tube supported at cathode and anode terminals with the grid disk centered. The supports shall be placed 0.938 ±0.016 inch (23.83 ±0.41 mm) apart. Apply force to the grid disk without shock, perpendicular to the axis of the tube. Inspect for defects described in MIL-E-1, appendix D, paragraph Vacuum seal (metal-to-glass) defect classification.

7. Electrical rejects may be used.

8. This test shall be conducted on the initial lot and thereafter on a lot approximately every 90 days. In the event of lot failure, the lot shall be rejected and the succeeding lots shall be subjected to this test until a lot passes. Once a lot has passed, the 90 day rule shall apply.

9. The no-load to steady-state full load of the heater voltage supply shall be not more than 3 percent. A failure or defect shall consist of an open heater, open cathode circuit, heater cathode short, or heater cathode leakage in excess of the specified heater cycling life-test end-point limit.

10. Test shall be performed in amplifier cavity Amerac Model No. 1244-1, or equivalent. Test frequency shall be 550 ±10 MHz. Adjust Rk for Ik = 25 mAdc and Rg for Ig = 6 mAdc.

11. Cycle Ef only, 110 minutes "on", 10 minutes "off".

12. The sample shall consist of 10 tubes per lot. Should a sample fail, a second sample of 20 tubes shall be selected from the lot and life tested. Acceptance then shall be based on the combined first and second sample.

13. Test shall be performed in accordance with method 1521 and MIL-E-1 every 90 days. Failure of any tube shall revert back to MIL-E-1 monthly lot sampling. After three consecutive successful submissions have been completed, the test shall revert to the quarterly basis.

14. A complete cycle is made in a 6 minute period as follows: 3 minutes on, 3 minutes off. This is a destructive test. Mechanical or electrical rejects may be used.

15. Tubes meeting the initial test requirements after stability and survival-rate life tests shall be accepted under this specification.

16. Subject tubes to shock in positions X, Y, and Z for a total of 15 blows, five blows in each position.

17. Vibrate in positions X and Y only for a total of 64 hours, 32 hours in each position.

(D) 18. This test shall be performed during the initial production and once each succeeding 12-calendar months in which there is production. A regular double sampling plan shall be used, with the first sample of three tubes with an acceptance number of zero, and a second sample of three tubes with a combined acceptance number of two. In the event of failure, the test will be made as a part of quality conformance inspection, part 2, code level B, with an AQL of 6.5. The regular "12-calendar month" double sampling plan shall be reinstated after three consecutive samples have been accepted.

19. Use basic test method 2126 (for receiving tubes) for seal strain test of this ceramic tube type.

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.

NOTES: -Continued

20. Test shall be performed on a group D basis every 90 days with the lot consisting of the current month and two subsequent months. Failure of any tube shall revert back to group D monthly lot sampling. After three consecutive successful lot submissions have been completed, the test may revert to the quarterly basis.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 11, 17, 80
DSA - ES

User activities:
Army - MU, MC
Navy - AS, OS, MC, CG, SH

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-2896)

Source: https://assist.dla.mil -- Downloaded: 202640-15T14:29Z
Check the source to verify that this is the current version before use.




FIGURE 1. Outline drawing of electron tube type 7554.

Source: https://assist.dla.mil -- Downloaded: 202640-15T14:29Z
Check the source to verify that this is the currentversion before use.

Ltr	Dimensions in inches with metric equivalents (mm) in parentheses		Notes
	Minimum	Maximum	
Quality conformance inspection, part 1			
C	.602 (15.29)	.652 (16.56)	
G	.590 (14.99)	.630 (16.00)	
H	.320 (8.13)		
Y	.740 (18.80)	.780 (19.81)	
Quality conformance inspection, part 2			
A		.230 (5.84)	
B		.180 (4.57)	
D	.213 (5.41)	.253 (6.43)	
E	.049 (1.24)	.055 (1.40)	
F	.166 (4.22)	.196 (4.98)	
J	.245 (6.22)	.252 (6.40)	b & d
K		.115 (2.92)	
L	.400 (10.16)	.420 (10.67)	
M	.048 (1.22)	.068 (1.73)	
N	.547 (13.89)	.557 (14.15)	c
P	.035 (.89)		
Q		.010 (.25)	
R	.130 (3.30)	.160 (4.06)	
S		1.460 (37.08)	
U	.095 (2.41)	.135 (3.43)	
V	.019 (.48)	.022 (.56)	
W	.110 (2.79)	.120 (3.05)	
Reference			
AA	.015 (.38) Rad.		
AB	.030 (.76) Rad.		
AC	.060 (1.52)		

NOTES:

a. Reference plane "A" is defined as that plane against which annular surface "B" of the grid flange abuts.

b. The axis of the anode terminal shall be coincident with the axis of the cathode terminal within .010 inch (.25 mm).

c. The axis of the cathode terminal shall pass through the exact center of the grid flange (dimension N) within .005 inch (.13 mm).

d. With annular surface "B" resting on reference plane "A", the axis of the cathode terminal (dimensions H and J) shall be within 2 degrees of a line perpendicular to reference plane "A".

FIGURE 1. Outline drawing of electron tube type 7554 - Continued.

Source: https://assist.dla.mil -- Downloaded: 202640-15T14:29Z
Check the source to verify that this is the currentversion before use.

POLS

DEPARTMENT OF THE NAVY
NAVAL ELECTRONIC SYSTEMS COMMAND
WASHINGTON, D. C. 20360

POSTAGE AND FE
NAVY DEPART
300 316

OFFICIAL BUSINESS

COMMANDER
NAVAL ELECTRONIC SYSTEMS COMMAND
DEFENSE STANDARDIZATION PROGRAM BRANCH
DEPARTMENT OF THE NAVY
WASHINGTON, D. C. 20360

POLS

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:29Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

OMB No.

INSTRUCTIONS: The purpose of this form is to solicit beneficial comments which will help ment of suitable products at reasonable cost and minimum delay, or will otherwise enhance u DoD contractors, government activities, or manufacturers/vendors who are prospective suppli are invited to submit comments to the government. Fold on lines on reverse side, staple in c preparing activity. Comments submitted on this form do not constitute or imply authorization portion of the referenced document(s) or to amend contractual requirements. Attach any perti may be of use in improving this document. If there are additional papers, attach to form and envelope addressed to preparing activity.

DOCUMENT IDENTIFIER AND TITLE

NAME OF ORGANIZATION AND ADDRESS

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT

1. HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY DOCUMENT REQUIREMENT CONSIDERED TOO RIGID

3. IS THE DOCUMENT RESTRICTIVE?

☐ YES ☐ NO *(If "Yes", in what way?)*

4. REMARKS

SUBMITTED BY *(Printed or typed name and address - Optional)*

TELEPHONE NO.

DATE

DD FORM 1 JAN 72 1426

REPLACES EDITION OF 1 JAN 68 WHICH MAY BE USED

Source: https://assist.dla.mil -- Downloaded: 202610-15T14:29Z
Check the source to verify that this is the current version before use.