MILITARY SPECIFICATION SHEET

ELECTRON TUBE, NEGATIVE GRID (MICROWAVE)

~~TYPE 7554~~

This amendment forms a part of Military Specification Sheet MIL-E-1/1325D, dated 1 May 1975, and is approved for use by all ~~Departments and Agencies~~ of the Department of Defense.

PAGE 1

TEST CONDITIONS, under Ec column: Add "(Note 8)".

PAGE 2

Quality conformance inspection, part 1, Method 1266, Total grid current, under Conditions column: Add "Rk = 0".

Quality conformance inspection, part 2, Method 1336, Heater-cathode leakage, under Max limits column: Delete "$^{30}_{30}$" and substitute "$^{+30}_{-30}$".

Quality conformance inspection, part 3, Method 1041, Shock, under Conditions column: Add "no voltages applied".

Quality conformance inspection, part 3, Shock and vibration-fatigue test end points, Method 1336, Heater-cathode leakage, under MAX limits column: Delete "60" and substitute "±60".

PAGE 3

Quality conformance inspection, part 3, Method 1506, Heater-cycling life, under NOTES column: Delete "18"; under Conditions column, add "Ec = 0".

Quality conformance inspection, part 3, Heater-cycling life-test end points, Method 1336, Heater-cathode leakage, under MAX limits column: Delete "$^{30}_{30}$" and substitute "$^{+30}_{-30}$".

Quality conformance inspection, part 3, Method 1516, Stability life test (2 hours), under NOTES column: Delete "20" and substitute "12".

Quality conformance inspection, part 3, Method 1501, Intermittent life, under NOTES column: Delete "12".

Quality conformance inspection, part 3, Method 1002, Barometric pressure, reduced, under NOTES column: Delete "8" and substitute "18".

NOTE 1, add the following sentence: "A capacitance bridge operating frequency of 1.0 to 2.0 kHz may be used."

PAGE 4

NOTE 2(b), add the following sentence: "For sweep-frequency vibration record the Ep measured over the vibration-frequency range from 50 to 500 Hz and for variable-frequency vibration record the Ep measured over the vibration-frequency range from 5 to 50 Hz."

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.

NOTE 8, delete and substitute new note as follows:

"8. Whenever Ec is not specified on any test, the grid shall be grounded directly or through a grid resistor (if specified) except where related MIL-STD-1311 test methods imply grid variance to accomplish the test."

NOTE 12: Delete and substitute note 20.

Custodians:
Army - EL
Navy - EC
Air Force - 85

Review activities:
Air Force - 17, 99
DSA - ES

User activities:
Army - MU, WC
Navy - AS, OS, MC, CG
Air Force - 11

Preparing activity:
Navy - EC

Agent:
DSA - ES

(Project 5960-3132)

Source: https://assist.dla.mil -- Downloaded: 2026-10-15T14:29Z
Check the source to verify that this is the current version before use.