INCH-POUND

MS75084E
W/AMENDMENT 1
7 October 2022
SUPERSEDING
MS75084E
31 August 2007


MILITARY SPECIFICATION SHEET

COILS, RADIO FREQUENCY, MOLDED, FIXED, (IRON CORE), TYPES LT10K061 TO LT10K077, INCLUSIVE

Inactive for new design, after 4 September 1985.
For new design, use MIL-PRF-39010/9.

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the products described herein shall consist of this specification and MIL-PRF-15305.



LTR	Minimum	Maximum
A	.085 (2.16)	.105 (2.67)
B	.240 (6.10)	.260 (6.60)
C	1.250 (31.75)	1.625 (41.28)
D	.0185 (0.470)	.0215 (0.546)

NOTES:
1. Dimensions are in inches with metric equivalents (mm) in parentheses.
2. Metric equivalents are given for general information only.
3. These coils are intended to be supported by their leads.
4. Solderable/weldable lead wire, number 24 AWG.

FIGURE 1. Dimensions and configuration.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:28Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Design, construction, and physical dimensions: See figure 1.

Weight: 0.0106 ounce, maximum.

Operating temperature range: -55° to +105°C.

Ambient temperature: + 90°C maximum.

Terminal pull: 5 pounds, minimum

Altitude: 70,000 feet with a test voltage of 300 V rms.

Dielectric withstanding voltage:

At sea level: MIL-STD-202-301, test voltage 1,000 V rms.

At reduced barometric pressure: MIL-STD-202-105, test condition C.

Electrical characteristics: See tables I and II.

Inductance: See table I.

Q values: See table I.

Self-resonant frequency (SRF): See table I.

DC resistance (DCR): See table I.

Part or Identifying Number (PIN): MS75084 - (dash number from table I).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:28Z
Check the source to verify that this is the current version before use.

TABLE 1. Electrical characteristics (initial).

Dash Number MS75084	Type Designa-tion	Inductance (μH) ±10%	Q Min.	Test Frequency (L and Q) (MHz)	SRF Minimum (MHz)	DC resistance (25°C) maximum (Ohms)	Rated DC current, (mA) 1/
-1	LT10K061	1.2	25	7.9	150	.18	590
-2	LT10K062	1.5	28	7.9	140	.22	535
-3	LT10K063	1.8	30	7.9	125	.30	455
-4	LT10K064	2.2	30	7.9	115	.40	395
-5	LT10K065	2.7	37	7.9	100	.55	355
-6	LT10K066	3.3	45	7.9	90	.85	270
-7	LT10K067	3.9	45	7.9	80	1.00	250
-8	LT10K068	4.7	45	7.9	75	1.20	230
-9	LT10K069	5.6	50	7.9	65	1.80	185
-10	LT10K070	6.8	50	7.9	60	2.00	175
-11	LT10K071	8.2	55	7.9	55	2.70	155
-12	LT10K072	10	55	7.9	50	3.70	130
-13	LT10K073	12	45	2.5	40	2.70	155
-14	LT10K074	15	40	2.5	35	2.80	150
-15	LT10K075	18	50	2.5	30	3.10	145
-16	LT10K076	22	50	2.5	25	3.30	140
-17	LT10K077	27	50	2.5	20	3.50	135

1/ For the overload test, direct current shall be used. The value of this current shall be 1.5 times the rated dc current.

TABLE II. Electrical characteristics (final). 1/

Inspection group	Allowable variation from Initial measurement	Allowable variation from Initial measurement	Allowable percent from specified minimum value in electrical characteristics (initial) table	Allowable percent from specified minimum value in electrical characteristics (initial) table
	Inductance (percent)	DC resistance	Self-resonant frequency	Q
Qualification inspection				
Group II	±2	---	---	-10
Group III	±5	±(3% +.001 ohm)	-8	-10
Group IV	±5	±(2% +.001 ohm)	-10	-15
Conformance inspection group C				
Subgroup I	±2	---	---	-10
Subgroup II	±5	±(2% +.001 ohm)	-10	-15
Subgroup III	±5	±(3% +.001 ohm)	-8	-10

1/ Test fixture allowance of +.01μH shall be added to all change in inductance limits ±(_ percent +.01 μH).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:28Z
Check the source to verify that this is the current version before use.

Application notes:

1. The polarization voltage during moisture the moisture resistance tests is applied with the positive lead Connected to the coil terminals tied together, and the negative lead connected to the metal strap.
2. The temperature rise, terminal twist test are applicable.

Amendment notations. The margins of this specification are marked with vertical lines to indicate modifications generated by this amendment. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-PRF-15305, this document references the following:

MIL-STD-202-105 MIL-STD-202-301

Custodians:
Army – CR
Navy - EC
Air Force - 85
DLA – CC

Preparing activity:
DLA – CC

Project 5950-2022-064

Review activities:
Army – AR, CR4, MI
Navy – AS, CG, MC, OS, SH
Air Force – 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T20:28Z
Check the source to verify that this is the current version before use.