FED SUP CLASS
5340




TABLE I. DASH NUMBERS AND DIMENSIONS

B LENGTH	A-LENGTH .438	.500	.562	.625	.688	.750
	DASH NUMBERS					
.438	-005 1/					
.500	-006 1/	-046 1/				
.562	-007 1/	-047 1/	-087 1/			
.625	-008 1/	-048 1/	-088 1/	-128 1/		
.688	-009 1/	-049 1/	-089 1/	-129 1/	-169 1/	
.750	-010 1/	-050 1/	-090 1/	-130 1/	-170 1/	-210 1/
.812	-011	-051	-091	-131	-171	-211
.875	-012 1/	-052 1/	-092 1/	-132 1/	-172 1/	-212 1/
.938	-013	-053	-093	-133	-173	-213
1.000	-014 1/	-054 1/	-094 1/	-134 1/	-174 1/	-214 1/
1.062	-015	-055	-095	-135	-175	-215
1.125	-016 1/	-056 1/	-096 1/	-136 1/	-176 1/	-216 1/
1.188	-017	-057	-097	-137	-177	-217
1.250	-018 1/	-058 1/	-098 1/	-138 1/	-178 1/	-218 1/
1.312	-019	-059	-099	-139	-179	-219
1.375	-020 1/	-060 1/	-100 1/	-140 1/	-180 1/	-220 1/
1.438	-021	-061	-101	-141	-181	-221
1.500	-022 1/	-062 1/	-102 1/	-142 1/	-182 1/	-222 1/
1.562	-023	-063	-103	-143	-183	-223
1.625	-024 1/	-064 1/	-104 1/	-144 1/	-184 1/	-224 1/
1.688	-025	-065	-105	-145	-185	-225
1.750	-026 1/	-066 1/	-106 1/	-146 1/	-186 1/	-226 1/
1.875	-027 1/	-067 1/	-107 1/	-147 1/	-187 1/	-227 1/

1/ PREFERRED SIZES

(8) ENTIRE STANDARD REVISED

PA	INTERNATIONAL INTEREST	TITLE	MILITARY STANDARD
NAVY-AS Other Cust AIR FORCE-11		BRACKET,ANGLE,90°,CRES, .190 BOLT	MS9600
PROCUREMENT SPECIFICATION: NONE	SUPERSEDES: MS9228		PAGE 1 OF 2

DD FORM 672-1 (COORDINATED) PREVIOUS EDITIONS OF THIS FORM ARE OBSOLETE 5340-1825

APPROVED 22 NOV 66 REVISED (8) 5 JUN 87

USER ACTIVITIES

REVIEWER ACTIVITIES
DLA-IS

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited

This military standard is approved for use by all Departments and Agencies of the Department of Defense. Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

AMSC N/A

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:21Z
Check the source to verify that this is the current version before use.

TABLE I. DASH NUMBERS AND DIMENSIONS - CONTINUED

B LENGTH	A-LENGTH .812	.875	938	1.000
	DASH NUMBERS			
.812	-251			
.875	-252	-292 1/		
.938	-253	-293	-333	
1.000	-254	-294 1/	-334	-374 1/
1.062	-255	-295	-335	-375
1 125	-256	-296 1/	-336	-376 1/
1.188	-257	-297	-337	-277
1.250	-258	-298 1/	-338	-278 1/
1.312	-259	-299	-339	-379
1.375	-260	-300 1/	-340	-380 1/
1.438	-261	-301	-341	-381
1.500	-262	-302 1/	-342	-382 1/
1.562	-263	-303	-343	-383
1.625	-264	-304 1/	-344	-384 1/
1.688	-265	-305	-345	-385
1.750	-266	-306 1/	-346	-386 1/
1.875	-267	-307 1/	-347	-387 1/

1/ PREFERRED SIZES

REQUIREMENTS

1. MATERIAL : CORROSION RESISTANT STEEL IN ACCORDANCE WITH AMS 5504.
2. FINISH : HEAT TREATMENT AND CLEANING IN ACCORDANCE WITH AMS 2550.
3. HARDNESS : ROCKWELL C 30-38
4. DIMENSIONING AND TOLERANCING. DIMENSIONING AND TOLERANCING SHALL BE IN ACCORDANCE WITH ANSI Y14.5M.
5. TOLERANCES. UNLESS OTHERWISE SPECIFIED, TOLERANCES SHALL BE FOR LINEAR DIMENSION ± 010 ANGULAR DIMENSIONS ± 5° .
6. EDGES : BREAK SHARP EDGES .003-.015 UNLESS OTHERWISE SPECIFIED.
7. PART NUMBER. THE PART NUMBER SHALL CONSIST OF THE BASIC MS NUMBER FOLLOWED BY A DASH NUMBER FROM TABLE I.

EXAMPLE: MS9600-005
(005 — DASH NUMBER; MS9600 — BASIC MS NUMBER)

MS9600-005 INDICATES - BRACKET, ANGLE, 90°, CRES , 190 BOLT, 438 X .438 LONG

NOTES:

1. ALL DIMENSIONS ARE IN INCHES.
2. DO NOT USE UNASSIGNED PART NUMBER.
3. IN THE EVENT OF A CONLICT BETWEEN THE TEXT OF THIS STANDARD AND THE REFERENCES CITED HEREIN, THE TEXT OF THIS STANDARD SHALL TAKE PRECEDENCE.
4. REFERENCED GOVERNMENT (OR NON-GOVERNMENT) DOCUMENTS OF THE ISSUE LISTED IN THAT ISSUE OF THE DEPARTMENT OF DEFENSE INDEX OF SPECIFICATIONS AND STANDARDS (DODISS) SPECIFIED IN THE SOLICITATION FORM A PART OF THIS STANDARD TO THE EXTENT SPECIFIED HEREIN.
5. THIS STANDARD WAS DEVELOPED COOPERATIVELY WITH THE ENGINE AND PROPELLER UTILITY PARTS COMMITTEE OF THE SAE.
6. AS AND AMS ARE SOCIETY OF AUTOMOTIVE ENGINEERS, INC PUBLICATIONS
7. APPROXIMATE WEIGHT LB/100 = .877 (A+B) + .157.

APPROVED 22 NOV 66 REVISED (B) FOR CHANGES SEE PAGES 1 AND 2

USER ACTIVITIES
REVIEWER ACTIVITIES
DLA-IS
This military standard is approved for use by all Departments and Agencies of the Department of Defense
Selection for all new engineering and design applications and for repetitive use shall be made from this document when applicable

PA NAVY-AS / Other Cust AIR FORCE-11	INTERNATIONAL INTEREST	TITLE BRACKET, ANGLE, 90°, CRES, .190 BOLT	MILITARY STANDARD MS9600
PROCUREMENT SPECIFICATION NONE	SUPERSEDES MS9228		PAGE 2 OF 2

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T13:21Z
Check the source to verify that this is the current version before use.