MILITARY SPECIFICATION

SONAR SET AN/BQC-1 ( )

This amendment forms a part of Military Specification MIL-S-15232B(SHIPS), 25 January 1966.

Pages 1 and 2, paragraph 2.1: Delete "MIL-B-18/19" and substitute "MIL-B-18/9."

Pages 1 and 2, paragraph 2.1: Delete "RF51F128" and substitute "RE51F128."

Page 6, paragraph 3.3.2.2.1.1: Delete and substitute:

"3.3.2.2.1.1 Input.- A sound input with a pressure level of 75 dynes/cm^2 at the microphone shall produce at least the full output of the transmitter as required by 3.3.2.2."

Page 6, paragraphs 3.3.2.3 and 3.3.2.3.1: Delete and substitute:

"3.3.2.3 Receiver.- The receiver shall be capable of delivering at least 7.0 volts to the handset speaker. Limiting shall be employed to limit receiver output to the handset speaker to a maximum of 10 volts. An input signal at 9kc. of-117 db referred to one volt shall produce an output signal of 1.0 volt across the handset speaker. Input signal level shall be measured across a one ohm resistor connected between the ground side of the input circuit and the low side of the transducer or an equivalent load substituted for the transducer."

"3.3.2.3.1 Signal-to-noise ratio.- At the gain setting required to produce an output of one volt across the handset speaker for an input signal at 9kc. of -117 db referred to one volt, the self-noise level shall be 25 db below one volt or less. At minimum gain and a resistive load equivalent to the transducer, the self-noise level measured across the handset receiver shall be 50 db below one volt or less."

Page 7, paragraph 3.3.2.3.3:

"3.3.2.3.3 Linearity.- Receiver output, when measured across the handset receiver, shall be linear from 10 db above self-noise to 7 volts for input signals up to 40 db below one volt, measured across a one ohm resistor between the low side of the transducer or equivalent resistor and the ground side of the input circuit."

FSC 5845

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T05:54Z
Check the source to verify that this is the current version before use.

Page 7, paragraph 3.3.2.6: In line 5, delete "and d.c. supplies" and substitute "supply"; and sixth sentence, delete.

Page 8, paragraph 3.3.3: Delete "Transudcer" and substitute "Transducer "

Page 10, paragraph 3.3.3.15.2: Delete and substitute:

"3.3.3.15.2 Transmitting frequency.- The transducer shall have resonant frequencies at 9.6 kc. ± 300 cycles and 24.3 kc. ± 500 cycles as determined from the peaks of the transmitting power response with an input of one watt."

Page 10, paragraph 3.3.3.15.4 Delete.

Page 10, paragraph 3.3.3.15.7, line 3: Delete "2.9 k.c." and substitute "2.0 kc.".

Page 11, paragraph 3.3.3.15.7.1: Delete and substitute:

"3.3.3.15.7.1 Receiving.- The frequency band for receiving shall be 8.1 kc. to 11.0 kc."

Page 11, paragraph 3.3.3.15.8: Add "Resistance from shield to water ground shall be at least one megohm."

Page 11: Add as paragraph 4.1.1 and 4.1.2:

"4.1.1 Contractor's quality assurance system.- The contractor shall provide and maintain an effective inspection and quality assurance system acceptable to the Government covering the supplies under the contract. A current written description of the system shall be submitted to the cognizant government inspector for system approval prior to preproduction inspection. Any changes to the approved quality assurance system which might affect the degree of assurance required by this specification or other applicable documents shall be submitted to the cognizant inspector and approved in writing prior to use.

Source: https://assist.dla.mil -- Downloaded: 202640-18T05:54Z
Check the source to verify that this is the current version before use.

"4.1.2 Government verification.- All quality assurance operations performed by the contractor will be subject to Government verification at any time. Verification will consist of (a) surveillance of the operations to determine that practices, methods, and procedures of the written system description are being properly applied, and (b) Government product inspection to measure quality of product to be offered for acceptance. Failure of the contractor to promptly correct deficiencies discovered by him or of which he is notified shall be cause for suspension of acceptance until corrective action has been made or until conformance of product to prescribed criteria has been demonstrated."

Preparing activity:
Navy - Sh
(Project 5845-N422SH)

Source: https://assist.dla.mil -- Downloaded: 202610-18T05:54Z
Check the source to verify that this is the currentversion before use.