MILITARY SPECIFICATION

ADAPTER & FUZE, ASSEMBLY: M624, PARTS FOR

This Specification is approved for use within the U. S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the parts for Adapter & Fuze Assembly: M624.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-2550 - General Specification for Ammunition Except Small Arms Ammunition.
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification for.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament Research, Development and Engineering Center, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes. (ABC-STD-105)
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-1169- Packaging, Packing and Marking for Shipment of Inert Ammunition Components.
MIL-STD-1235- Continuous Sampling Procedures and Table for Inspection by Attributes.

(Copies of specifications, standards, drawings, publications, and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

US ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

12546032 - Adapter & Fuze Assembly- M624

2.2 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Parts. All parts shall comply with drawings, specifications and standards.

3.3 Metal parts assembly. The metal parts assembly shall comply with all requirements specified on Drawing (Dwg.) 12546032, all associated drawings, and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

3.4 X-ray of delay assembly. Delay assemblies shall be x-rayed in accordance with 4.5.1 to confirm proper loading.

3.5 Delay time. The delay assemblies shall comply with the delay time requirement of Drawing (Dwg.) 12554910 when tested in accordance with 4.5.2.

3.6 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.7 Workmanship. All parts and assemblies shall be fabricated and assembled in thorough, workmanlike manner. They shall be free of burrs, chips, weld spatter, sharp edges, chipped edges, gouges, cracks, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. All required markings shall be neat and sharply defined. External threads shall be full, complete and undamaged for their entire length. Exterior surface coatings shall be continuous except for a few light scratches not exposing base material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection.

b. Quality conformance inspection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table I.

Part Description	Drawings	Quantities
Element, Locking	12554905	50
Cap	12554906	50
Cap Assembly	12554908	50
Rod, Forward	12546028	50
Rod, Middle	12546029	50
Rod, End	12546030	50
Rod, Extension Assembly	12546027	50
Spring, Compression	12554909	50
Gasket	12546026	50
Holder, Delay	12546039	50
Delay Assembly	12554910	50
Adapter	12546031	50
Adapter Assembly	12546025	50

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

4.3.3 Rejection. See MIL-A-48078. If any items fail to comply with any of the applicable requirements, the first article sample shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Adapter & Fuze, Assembly: M624				See below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Element, Locking (Dwg. 12554905) Examination for Defects	50		3.2	4.4.2.1
	Cap (Dwg. 12554906) Examination for Defects	50		3.2	4.4.2.2
	Cap, Assembly (Dwg. 12554908) Examination for Defects	50		3.3	4.4.2.3

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE: Adapter & Fuze, Assembly,: M624		SHEET 2 OF 3		DRAWING NUMBER: See Below NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Rod, Forward (Dwg. 12546028) Examination for Defects	50		3.2	4.4.2.4
	Rod, Middle (Dwg. 12546029) Examination for Defects	50		3.2	4.4.2.5
	Rod, End (Dwg. 12546030) Examination for Defects	50		3.2	4.4.2.6
	Rod, Extension Assembly (Dwg. 1246027) Examination for defects	50		3.3	4.4.2.7
	Spring Compression (Dwg. 12554909) Examination for Defects	50		3.2	4.4.2.8
	Gasket (Dwg. 12546026) Examination for Defects	50		3.2	4.4.2.9

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-A-70609(AR)

PARAGRAPH	TITLE: Adapter & Fuze, Assembly: M624		SHEET 3 OF 3		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY: --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Holder Delay (Dwg. 12546039) Examination for Defects	50		3.2	4.4.2.10
	Delay Assembly (Dwg. 12554910) Examination for Defects	50		3.2	4.4.2.11
	Adapter (Dwg. 12546031) Examination for Defects	50		3.2	4.4.2.12
	Adapter Assembly (Dwg. 12546025) Examination for Defects	50		3.3	4.4.2.13

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II. Continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the procuring activity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Element, Locking				12554905
					NEXT HIGHER ASSEMBLY 12554908
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Minor diameter of thread		0.40%	3.2	Gage
103	Overall length		0.40%	3.2	Gage
Minor					
201	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cap		12554906
			NEXT HIGHER ASSEMBLY 12554908

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch of diameter of inside thread		0.40%	3.2	Gage
102	Minor diameter of inside thread		0.40%	3.2	Gage
103	True position of internal undercut		0.40%	3.2	Gage
104	True position of spacer hole		0.40%	3.2	Gage
105	Height of undercut		0.40%	3.2	Gage
106	Pitch diameter of locking element hole		0.40%	3.2	Gage
107	Minor diameter of locking element hole		0.40%	3.2	Gage
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Overall height		0.65%	3.2	Gage
203	Workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Cap Assembly				12554908
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Presence of locking element		0.40%	3.2	Visual
102	Presence of spacer		0.40%	3.2	Visual
Minor					
201	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Rod, Forward				12546028
					NEXT HIGHER ASSEMBLY 12546027
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	Diameter of thread pilot, max.		0.40%	3.2	Gage
104	Length of thread pilot, max.		0.40%	3.2	Gage
105	Distance from base to top of thread min.		0.40%	3.2	Gage
106	Threads not rolled		0.40%	3.2	Visual
107	Deep cuts or grooves		0.40%	3.2	Visual
108	True position of pilot hole		0.40%	3.2	Gage
109	Perpendicularity of base		0.40%	3.2	Gage
Minor					
201	Length, total		0.65%	3.2	Gage
202	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Rod, Middle				12546029
					NEXT HIGHER ASSEMBLY
					12546027
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	Diameter of thread pilot, max.		0.40%	3.2	Gage
104	Length of thread pilot, max.		0.40%	3.2	Gage
105	Distance from base to top of thread min.		0.40%	3.2	Gage
106	Threads not rolled		0.40%	3.2	Visual
107	Deep cuts or grooves		0.40%	3.2	Visual
108	True position of pilot hole		0.40%	3.2	Gage
109	Perpendicularity of base		0.40%	3.2	Gage
110	Perpendicularity of undercut below external threads		0.40%	3.2	Gage
Minor					
201	Length, total		0.65%	3.2	Gage
202	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Rod, End	1 OF 1	12546030
			NEXT HIGHER ASSEMBLY 12546027

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread		0.40%	3.2	Gage
103	True position of base		0.40%	3.2	Gage
104	Perpendicularity of undercut below external threads		0.40%	3.2	Gage
Minor					
201	Length, total		0.65%	3.2	Gage
202	Protective coating inadequate, damaged, or improper		0.65%	3.2	Visual
203	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Rod, Extension Assembly				12546027
					NEXT HIGHER ASSEMBLY
					12546034
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Overall length, max		0.40%	3.2	Gage
Minor					
201	Workmanship		0.65%	3.7	Gage

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.8	Spring, Compression		12554909
			NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Free length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
Minor					
201	Diameter of wire		0.65%	3.2	Gage
202	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Gasket				12546026
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major	None defined				
Minor					
201	Outside diameter		0.65%	3.2	Gage
202	Inside diameter		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.10	Holder, Delay				12546039
					NEXT HIGHER ASSEMBLY 12554910
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Pitch diameter of threads		0.40%	3.2	Gage
102	Major diameter of threads		0.40%	3.2	Gage
103	Length of thread		0.40%	3.2	Gage
104	Distance from bottom to start of thread		0.40%	3.2	Gage
Minor					
201	Diameter of blast exit		0.65%	3.2	Gage
202	True position of blast exit hole		0.65%	3.2	Gage
203	Depth of blast exit hole		0.65%	3.2	Gage
204	Diameter of relay assembly hole		0.65%	3.2	Gage
205	True position of relay assembly hole		0.65%	3.2	Gage
206	Diameter of top counterbore		0.65%	3.2	Gage
207	True position of counterbore		0.65%	3.2	Gage
208	Depth of top counterbore		0.65%	3.2	Gage
209	Outside diameter		0.65%	3.2	Gage
210	True position of outside diameter		0.65%	3.2	Gage
211	Step diameter		0.65%	3.2	Gage
212	True position of step diameter		0.65%	3.2	Gage
213	Depth of step		0.65%	3.2	Gage
214	Overall length		0.65%	3.2	Gage
215	Workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.11	Delay Assembly		12554910
			NEXT HIGHER ASSEMBLY 12546025

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Presence of M42 percussion primer		0.40%	3.2	Visual
102	Evidence of crimping		0.40%	3.2	Visual
103	Presence of proper loading		0.40%	3.2	4.5.1
104	Delay time		0.40%	3.5	4.5.2
Minor					
201	Overall height		0.65%	3.2	Gage
202	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
4.4.2.12	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None define				
Major					
101	Large outside diameter before knurling		0.40%	3.2	Gage
102	Major diameter of Ref. A		0.40%	3.2	Gage
103	Pitch diameter of Ref. A		0.40%	3.2	Gage
104	Minor diameter of Ref. A		0.40%	3.2	Gage
105	Major diameter of capped end		0.40%	3.2	Gage
106	Pitch diameter of capped end		0.40%	3.2	Gage
107	True position of large counterbore on fuze end		0.40%	3.2	Gage
108	Diameter of large counterbore on fuze end		0.40%	3.2	Gage
109	True position of small counterbore on fuze end		0.40%	3.2	Gage
110	Diameter of small counterbore on fuze end		0.40%	3.2	Gage
111	Depth of large counterbore on fuze end		0.40%	3.2	Gage
112	Full depth of counterbore on fuze end		0.40%	3.2	Gage
113	Major diameter of internal thread on fuze end		0.40%	3.2	Gage
114	True position of internal thread on fuze end		0.40%	3.2	Gage
115	Diameter of undercut on fuze end		0.40%	3.2	Gage
116	Depth of undercut on fuze end		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE		SHEET 2 OF 3		DRAWING NUMBER
4.4.2.12	Adapter				12546031
					NEXT HIGHER ASSEMBLY 12546025
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
117	Distance from face of fuze end to bottom of internal threads		0.40%	3.2	Gage
118	Diameter of thru hole for delay assembly		0.40%	3.2	Gage
119	True position of through hole for delay assembly		0.40%	3.2	Gage
120	Diameter of counterbore on discharge end		0.40%	3.2	Gage
121	True position of internal thread on discharge end		0.40%	3.2	Gage
122	Major diameter of internal thread on discharge end		0.40%	3.2	Gage
123	Pitch diameter of internal thread on discharge end		0.40%	3.2	Gage
124	Depth of internal thread on discharge end		0.40%	3.2	Gage
125	Depth of counterbore on discharge end		0.40%	3.2	Gage
126	True position of external thread on discharge end		0.40%	3.2	Gage
127	Major diameter of external thread on discharge end		0.40%	3.2	Gage
128	Pitch diameter of external thread on discharge end		0.40%	3.2	Gage
129	Depth of full thread		0.40%	3.2	Gage
130	Distance from face of discharge end to beginning of largest O.D. external threads		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.12	Adapter	3	3	12546031
				NEXT HIGHER ASSEMBLY: 12546025

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
131	Distance from face of discharge end to bottom of largest O.D. external threads		0.40%	3.2	Gage
132	Distance from face discharge end to underside of knurled diameter		0.40%	3.2	Gage
133	Overall height		0.40%	3.2	Gage
Minor					
201	Diameter of (4) four counterbores on knurled face		0.65%	3.2	Gage
202	Depth of (4) four counterbores on knurled face		0.65%	3.2	Gage
203	Protective finish		0.65%	3.2	Visual
204	Workmanship		0.65%	3.7	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-70609(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.13	Adapter Assembly		12546025
			NEXT HIGHER ASSEMBLY 12546032

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of gasket		0.40%	3.2	Visual
102	Presence of cap assembly		0.40%	3.2	Visual
103	Presence of delay assembly		0.40%	3.2	Visual
Minor					
201	Overall length		0.65%	3.2	Gage
202	Workmanship		0.65%	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

4.4.3 Inspections to be performed. Each part shall be inspected for all dimensions, except those dimensions that have been machined, and characteristics specified on the applicable detail drawing.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and tests prescribed in this specification is identified in the "Paragraph Reference/Inspection Method" column in Classification of Defects and Tests forms beginning with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. All test procedures shall be submitted a minimum of 30 days prior to test to AMSMC-QAT-M(D), Dover, NJ.

4.5 Methods of inspection.

4.5.1 X-ray. The delay assembly shall be x-rayed, in accordance with 4.4.4, for the presence of the delay composition and the relay assembly. The x-ray shall not show the presence of cracks, voids, etc.

4.5.2 Delay time. This test is to be performed by the contractor with the government's technical agency's concurrence as per 4.4.4.

5. PACKAGING

5.1 Preservation and packaging.

5.1.1 Level C. The parts and assemblies for Adapter & Fuze Assembly M624 shall be packed in accordance with MIL-STD-1169 in such a manner that no damage will occur during shipment.

5.2 Packing.

5.2.1 Level C. The parts and assemblies for Adapter & Fuze Assembly M624 shall be packed in accordance with MIL-STD-1169. Separately designated items shall not be packed together.

5.3 Data cards. Data card information shall be as specified in Specification MIL-A-2550.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

5.5 Marking and labeling. Marking of the cartons shall be in accordance with Standard MIL-STD-129 and Specification MIL-P-10025.

6. NOTES

6.1 Ordering data. See MIL-A-48078.

6.2 Data cards. (See MIL-A-48078). Distribution of data cards shall include the following: Commander, U S ARDEC, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U S ARDEC, ATTN: AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

6.4 Drawings. Drawings listed in section 2 of this specification under the heading US Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, US Army Armament Research and Development Command (ARRADCOM), Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARDEC.

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue, due to the extensiveness of the changes.

6.6 Subject term (key word) listing.
Adapter
Fuze
Parts
Extension Rod Assembly
Compression spring
Adapter Assembly
Delay time

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A369)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-A-70609	ADAPTER & FUZE, ASSEMBLY: M624, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:47Z
Check the source to verify that this is the current version before use.