MILITARY SPECIFICATION

DESK-FILING CABINET, WRITING-TYPING, FIELD OFFICE MXU-619/E82; LIGHTWEIGHT, BARE BASE

1. SCOPE

1.1 This specification covers one type of lightweight, field office, writing and typing desk and filing cabinet, designated MXU-619/E82.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

Federal

QQ-S-634	Steel, Bar, Carbon, Cold Finished (Standard Quality)
QQ-S-698	Steel, Sheet and Strip, Low Carbon
QQ-T-830	Tube, Steel (Carbon, Mechanical, Seamless and Welded)

STANDARDS

Federal

595	Colors

Military

MIL-STD-100	Engineering Drawing Practices
MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-130	Identification Marking for U S Military Property
MIL-STD-143	Standards and Specifications, Order of Precedence for the Selection of
MIL-STD-808	Finishes, Protective, and Codes, for Finishing Schemes for Ground and Ground Support Equipment
MIL-STD-831	Test Reports, Preparation of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

DRAWING

Vineland Corporation

6902 Furniture, Modular Type, Steel, Field Office

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

National Bureau of Standards

Handbook H28 Screw-Thread Standards for Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington, D. C. 20402.)

National Electrical Manufacturers Association

LPT-1964 Laminated, Thermosetting Decorative Sheets

(Application for copies should be addressed to the National Electrical Manufacturers Association, 155 East 44th Street, New York, New York 10017.)

3. REQUIREMENTS

3.1 Preproduction. This specification makes provisions for preproduction testing.

3.2 Components. The desk-filing cabinet shall consist of the following major components:

a. One two-drawer file cabinet, including correspondence tray

b. Table top section with provisions for attaching to file cabinet as intermediate top or as end table top with two adjustable, folding legs.

3.3 General requirements. The requirements of Drawing 6902 and details thereto (see 6.2) apply as requirements of this specification with the exceptions and additions specified herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

3.4 Selection of specifications and standards. Specifications and standards for necessary commodities and services not specified herein shall be selected in accordance with MIL-STD-143.

3.5 Materials. Materials not definitely specified shall conform to the quality normally used for the purpose in commercial practice.

3.5.1 Steel, sheet and strip, low carbon. The steel, sheet and strip shall conform to any quality, temper, hot or cold rolled, 1008-1020 of QQ-S-698. The cold rolled and stretcher or roller leveled steel shall be used for all exposed surfaces of the components. Hot rolled pickled and oiled steel shall be used for interior structural parts of the components. Hot rolled annealed steel shall be used for drawer body, back, interior drawer front, and follower block.

3.5.2 Steel, bar, carbon, cold finished. The steel, bar, carbon, cold finished shall conform to QQ-S-634.

3.5.3 Tube, steel. The steel tube shall be either seamless, hot rolled or electric resistance welded, round, conforming to QQ-T-830.

3.5.4 Laminated, thermosetting, decorative sheets. The laminated, thermosetting, decorative sheets shall be general purpose type with a minimal thickness of 1/16 inch and shall conform to the applicable requirements of NEMA LPI-1964.

3.5.5 Hardware

3.5.5.1 Face hardware. The hardware for the face of the cabinet shall be fabricated from satin-finished anodized aluminum; corrosion-resisting steel, type 302, 304 or 430; or brushed chromium on steel or on die-cast zinc, brass, or bronze.

3.5.5.2 Miscellaneous hardware. The studs, nuts, screws and washers shall be commercial items, of steel, and shall be zinc or cadmium plated. Threaded parts shall be made with screwthreads in accordance with Handbook H28.

3.6 Construction. The components of the desk-filing cabinet shall conform to the design, details, steel gage numbers and dimensions specified on Drawing 6902 and to the requirements specified herein. Each component shall be constructed to permit field assembly without the use of tools.

3.7 File cabinet. The file cabinet shall show no damage nor shall the contents of the drawers be displaced or damaged when the cabinet is subjected to the test specified in 4.7.5.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

3.7.1 Case. The case for the file cabinet shall be fabricated from the steel specified in 3.5.1. One hinged-carrying handle shall be built into each side of the exterior case. The handles shall be commercial items, and shall be heavy wrought steel, hinged type fitted into a recess. In the noncarrying position, the handles shall be flush with the sides of the case. The free gripping part of the handle shall be not less than 2-3/4 inches long, and not less than 3/8 inch in diameter. In a lifting position, the handles shall be secured in a horizontal position. The handles shall be of sufficient strength to withstand lifting the cabinet with 70 pounds in each drawer. Four keyhole slots required for attaching table top sections to cabinets shall be located in each side of the case exterior as shown on Drawing 6902. Dustproof covers and reinforcements shall be fabricated from steel as specified in 3.5.1. Lifting handles and keyhole slots shall have recessed dust covers. All reinforcements shall be spot-welded to the case. The case shall be rigidly formed, braced, reinforced, and welded. Case shall show no warping, twisting, or distortion in the locks, locking mechanism, latches, operation of drawers or misalignment of top sections when tested as specified in 4.7.3. The keyhole slots shall show no visible defects as a result of the load test. Each case shall have a lock in accordance with 3.7.4.

3.7.2 Drawers. Drawers shall be constructed from the material specified in 3 5.1. The drawers shall be box type, double-head design of rigid construction with the outer and inner heads made of the steel gages specified on the drawing. All exposed edges of the drawer body shall be box formed, rolled or beaded. Stops shall be provided to prevent the drawer from hitting the back of the cabinet and to deaden noise in operation. A sufficient number of stops shall be provided to prevent the drawers from falling out when loaded and fully opened. The drawers shall mount into the case and the drawer suspension shall operate smoothly without bending. Each drawer shall have a drawer latch as specified in 3.7.2.3. The backs of the drawers shall be flush with the face of the cabinet when the drawers are fully extended.

3.7.2.1 Follower block. The drawers shall have a sliding follower block constructed of material specified in 3.5.1. The follower block shall be positive or friction locking types, removable without special tools, and adjustable for the full depth of the drawers. The rearward movement of the follower block shall not exceed 1/2 inch between the two marks when tested as specified in 4.7.5.

3.7.2.2 Drawer pulls. The pulls shall be commercial items and shall be fabricated of one of the materials specified in 3.5.5, and shall conform to the configuration shown on the drawing with no rough or sharp edges. Pulls shall be attached to the drawers in accordance with commercial practice. The dimensions of the handhole blank shall be as shown on the drawing.

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:48Z
Check the source to verify that this is the current version before use.

3.7.2.3 Drawer latch. The drawer latch shall be commercial items and shall be fabricated of one of the materials specified in 3.5.5. The drawer latch shall be sufficiently strong to hold the loaded drawer in a closed position against a normal rebound, a tilt, or an uneven floor. The latching mechanism shall be guarded or concealed and located as shown on the drawing.

3.7.3 Drawer suspension. The drawer suspension shall be a commercial item and shall be the full progressive type with side-arm journaled rollers. Each drawer suspension shall have at least six ball bearing rollers and two plain rollers. Rollers shall be 1/4 inch thick and not less than 1-inch in diameter and shall be turned from cold rolled steel, case hardened. Case and intermediate channels and drawer slides shall be fabricated from steel as specified in 3.5.1. Intermediate channels shall be cadmium, zinc, or chromium plated in accordance with commercial practice. Sufficient number of stops shall be provided to prevent accidental removal of drawers. The drawer and stop for closing position shall be so located that the drawer does not stop against the rear of the case. The suspension shall travel easily, quietly, and smoothly with the drawer loaded as specified in 4.7.3; the drawer operating force shall not exceed 3-3/4 pounds to complete the forward stroke before or after 50,000 cycles when tested as specified in 4.7.3.

3.7.4 Lock. The lock shall be a commercial item and shall be fabricated of one of the materials specified in 3.5.5. The locking mechanism shall consist of a guided vertically moving lock-bar and a cam attached to a plunger-type lock (paracentric key) in the left hand top corner of the case frame to control vertical movement of the lock-bar. When the lock is pressed in, the bar shall move into locked position, locking both drawers. The locking mechanism shall be so constructed that the drawers left open may be closed and locked after the cabinet is locked, without distorting the locking mechanism. The paracentric key lock shall have not less than four pin-tumblers and all locks shall use the same key. Two keys shall be supplied with each lock. The locking mechanism shall work smoothly, easily and quietly, without binding.

3.7.5 Correspondence tray. Correspondence tray shall be fabricated from the steel specified in 3.5.1 and in accordance with Drawing 6902.

3.8 Table top sections. The table top sections, identical in design, details and dimensions shall be used interchangeably as an intermediate top section or as an end table top with two folding legs. The tops, folding legs, folding braces, leg mounts, spreaders, trim, and the adjustable ends shall be fabricated from the steel specified in 3.5.1. The rod shall be fabricated from the steel specified in 3.5.2 or 3.5.3. The studs and springs shall be commercial items and shall be of commercial steel. The legs shall have a height adjustment mechanism. Each leg shall have double braces that will enable the legs to be positioned under the top section when not in use. The tops shall be edged

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

with the molding as shown on the drawing. The height adjustment mechanism shall not deform, bend or break down when tested as specified in 4.7.2. The tops of the table top sections shall show no permanent indentation, no deflection greater than 1/8 inch, or damage when tested as specified in 4.7.2.

3.8.1 Top materials. The top material shall be as specified in 3.5.4. The top material shall be securely bonded to the steel table tops with an adhesive recommended by top material manufacturer. Pressure, pressing time, assembly periods and curing temperature shall conform to the recommendations of the manufacturer. The color of the top shall allow for the least possible eye strain during use.

3.9 Part numbering of interchangeable parts. All parts having the same manufacturer's part number shall be functionally and dimensionally interchangeable. The item identification and part number requirements of MIL-STD-100 shall govern the manufacturer's part numbers and changes thereto.

3.10 Finishes and protective coatings. Cleaning, painting, and finishing shall be in accordance with MIL-STD-808. The exterior color shall be green, color 24064 or 24087, conforming to Federal Standard 595.

3.11 Assembly instructions. An illustration or one set of comprehensive assembly instructions describing method of assembling individual units into groups shall be furnished with each desk-filing cabinet.

3.12 Identification of product. Equipment, assemblies, and parts shall be marked for identification in accordance with MIL-STD-130.

3.13 Workmanship. The desk-filing cabinet, including all parts and accessories, shall be constructed and finished in a thoroughly workmanlike manner. Particular attention shall be given to freedom from blemishes, defects, burrs, and sharp edges; accuracy of dimensions, radii of fillets, and marking of parts and assemblies; thoroughness of welding, brazing, painting, and riveting; alignment of parts and tightness of assembly.

3.13.1 Dimensional tolerances. Dimensions and tolerances not specified shall be as close as is consistent with the best shop practices. Where dimensions and tolerances may affect the interchangeability, operation, or performance of the desk-filing cabinet they shall be held or limited accordingly.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 Classification of tests. The inspection and testing of the desk-filing cabinet shall be classified as follows:

a. Preproduction testing . . . . . See 4.4

b. Acceptance tests. . . . . See 4.5.

4.3 Test conditions. Unless otherwise specified, all tests shall be conducted under prevailing room conditions.

4.4 Preproduction testing (see 6.2)

4.4.1 Test samples. Two desk-filing cabinets shall be subjected to the examinations and tests specified in 4.4.3.

4.4.2 Test report. After completion of the preproduction examinations and tests, a test report shall be prepared in accordance with MIL-STD-831 and three complete copies of the report furnished the procuring activity.

4.4.3 Preproduction tests. The preproduction tests shall consist of:

a. Examination for defects in accordance with 4.6.1

b. Dimensional examination in accordance with the drawings. Any dimension not within the specified tolerance shall be classified as a defect

c. All tests described under 4.7.

4.5 Acceptance tests. The acceptance tests shall consist of:

a. Individual test

b. Sampling tests.

4.5.1 Individual test. Each desk-filing cabinet shall be subjected to the assembly test described under 4.7.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

4.5.2 Sampling tests. The sampling tests shall consist of:

a. Examinations (4.6.1 and 4.6.2)

b. Periodic tests (4.6.3).

4.5.2.1 Sampling for examinations. Sampling for examinations shall be performed in accordance with the provisions of MIL-STD-105. The lot shall consist of all complete desk-filing cabinets offered for examination at one time. The sample unit shall be one complete desk-filing cabinet.

4.5.2.2 Sampling for periodic tests. Desk-filing cabinets shall be selected at random in accordance with the following and subjected to the periodic tests of those described in 4.6.3.

Sampling Schedule

Consecutively Produced Items	Quantity of Items to be tested
1-50	2
51-150	1
Each additional 200	1.

4.6 Examinations and periodic tests

4.6.1 Visual examination. Samples selected in accordance with 4.5.2.1 shall be examined for defects as specified in table I. The inspection level shall be II with an acceptable quality level (AQL) of 2.5 for major defects and 6.5 for total defects expressed in terms of defects per hundred units.

4.6.2 Dimensional examination. Samples selected in accordance with 4.5.2.1 shall be examined for defects in dimensions. Any dimension not within the specified tolerance shall be classified as a defect. The inspection level shall be S-2 with an AQL of 4.0 expressed in terms of defects per hundred units.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of Defects

Examine	Defect	Classification Major	Classification Minor
Finish	Color not as specified		X
	Area of no film	X	
	Not continuous or is not smooth		X
	Contains runs, drops, or streaks		X
	Foreign matter embedded		X
	Evidence of peeling, flaking, or blistering	X	
Construction and workmanship	Any component missing	X	
File cabinet	Any component not attached as specified	X	
	Latching mechanism does not function	X	
	Lock not as specified	X	
	Handles not secured in horizontal position when lifted	X	
File cabinet	Handles not flush	X	
	One keyhole slot missing	X	
	One dustproof cover missing		X
	More than one dustproof cover missing	X	
	One reinforcement missing	X	
Drawers	Exposed edges of body not box formed rolled or beaded	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of Defects (Contd)

Examine	Defect	Classification Major	Minor
	Rough or sharp edges on corners	X	
	Back of drawer not flush with face of cabinet when fully extended	X	
	Number of stops not sufficient to prevent pull out	X	
	Drawer suspension does not operate smoothly	X	
	Drawer block (compressor) not easily adjustable	X	
	Rough or sharp edges on drawer pull	X	
	Drawer latch not sufficiently strong to hold loaded drawer against rebound	X	
Follower	Does not adjust the full depth of drawer		X
	Cannot be removed without special tools		X
Welding	More than one spot weld missing, broken, or not fused where specified	X	
	One spot weld missing, broken, or not as specified		X
	Not sound and free from porosity		X
	Contains flashes or burn through		X
Assembly instructions	Missing, illegible, or not comprehensive	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

TABLE I. Classification of Defects (Contd)

Examine	Defect	Classification Major	Minor
Marking	Missing, illegible, incomplete, misspelled, or not as specified		X

4.6.3 Periodic tests. Samples selected in accordance with 4.5.2.2 shall be subjected to the tests listed under 4.7 as follows:

a. Load test (4.7.2) - Complete test

b. Rack test (4.7.3) - Time shall be for 30 minutes only

c. Service test (4.7.4) - Except only 100 cycles are required

d. Moving test (4.7.5) - Time shall be 10 minutes only

e. Follower block test (4.7.6) - Except only 50 cycles are required.

4.7 Test methods

4.7.1 Assembly test. The desk top section shall be assembled as an intermediate section between two file cabinets at both heights and shall be checked for ease of assembly and accuracy of fit of the bolts in the desk top and the key holes in the cabinet. The top section then shall be attached to one file cabinet section as an end table and shall be checked at both heights as before.

4.7.2 Load test. The components shall be assembled into a unit, two file cabinets, one top section attached between the two file cabinets (intermediate top); another top section attached as an end table. One 400-pound weight shall be placed on the intermediate section and also on the end table sections, on an area not to exceed 12 inches in diameter for not less than 5 minutes. The weight shall be placed at the front center and then at the back center of the intermediate top and end table sections for a period of not less than 5 minutes at each position. The intermediate top and the end table top shall not deflect more than 1/8 inch and shall not take on any permanent set. The bolts in the intermediate top and end table top shall work freely and have no visible defects. The key holes in the file cabinets shall show no visible defects. In addition, the leg mechanism on the end table shall be inspected for defects. Any defect shall be cause for rejection of the unit on which defect is noted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

4.7.3 Rack test. The desk-file cabinet shall be examined and tested to determine the impairment, if any, of the ease of operation of drawers, locks, locking mechanism, latches, or other movable devices under conditions of loaded level uniform support and after uneven support. A load of 70-pounds consisting of bond paper, guide cards, and folders or similar material shall be evenly distributed from front to back in each drawer of file cabinet. The cabinet shall then be raised not less than 1 inch and not more than 6 inches and supported on two diagonally opposite corners and allowed to remain in this position for 24 hours. Repeat test by lifting with handles only. The cabinet then shall be returned to a level position, re-examined for failures or defects, and the drawer pull test (4.7.4) conducted. The drawer operating force shall not exceed 3-3/4 pounds to complete the forward stroke.

4.7.4 Service test. The desk-filing cabinet with one drawer loaded as specified in 4.7.3 shall be bolted or otherwise secured in a level position and connected to a test machine which will operate the loaded drawer on its suspension. There shall be a means for adjusting the length of its stroke so that the drawer will travel the full distance beginning 1/2 inch from back to 1/4 inch from front stop and a method to drive the drawer at a rate not to exceed 20 cpm but shall not in any way contribute to the support of the drawer. The suspension shall be cleaned and lubricated at the start and at each 10,000 cycles and shall have no further attention until the test is completed. At the beginning of the test and at each 10,000 cycles, a test shall be conducted to determine the force required to start the loaded drawer forward and to move it to its full outward limit. This part of the test shall be conducted by attaching a limp cord to the center of the drawer pull, over a sheave, with weight applied to its free end or by a gage. The drawer suspension shall be considered as having failed the service test if the drawer operating force exceeds 3-3/4 pounds to complete the forward stroke before or at 50,000 cycles. Should failure be perceptible during the increments of 10,000 cycles, the apparatus shall be stopped and the pull test conducted at that point.

4.7.5 Moving test. With all drawers of the desk-filing cabinet loaded as specified in 4.7.3, and the follower drawn up tight, the cabinet shall be tipped over on its back on a furniture moving dolly, and shall remain in that position for not less than 3 hours, then set up. The unit shall then be examined for damage to the cabinet, the drawers, latches, follower drawer suspensions, and locks, and for any displacement or damage to the filing contents.

4.7.6 Follower block test. A drawer shall be loaded to not less than two-thirds the capacity specified in 4.7.4 and the filing material shall be held against the front of the drawer by the follower block. The location of the follower block shall be marked on the drawer. The apparatus, or its

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:48Z
Check the source to verify that this is the current version before use.

equivalent, specified in 4.7.4 shall be set in motion and made to operate 500 cycles. Upon completion, the position of the follower block shall be indicated by a similar mark. The rearward movement of the follower block, as a result of this test, shall not exceed 1/2 inch as indicated by the distance between the two marks.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with the instructions of the procuring activity.

6. NOTES

6.1 Intended use. The MXU-619/E82 desk-filing cabinet is for use in Bare Base operations. It is designed as a lightweight, field office, desk-filing cabinet, adjustable in height for typing or writing. The desk-filing cabinets may be quickly interconnected with each other for a variety of purposes.

6.2 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification

b. In the event it becomes necessary to change the drawing (see 3.3) in order to achieve the performance requirements of this specification, the contractor will immediately notify the contracting officer with recommendations for drawing changes to obtain the required performance. To the extent approved, such changes will be processed in accordance with the provisions of the changes clause of this contract

c. Location and conditions for preproduction testing (see 4.4).

Custodian:
Air Force - 11

Reviewer:
Air Force - 84

Preparing activity:
Air Force - 11

Project No. 7110-F109

Source: https://assist.dla.mil -- Downloaded: 202610-23T07:48Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

AFLC–WPAFB–OCT 67 2M

Source: https://assist.dla.mil -- Downloaded: 202640-23T07:48Z
Check the source to verify that this is the current version before use.

4950/TZSM
Wright-Patterson AFB, O 45433

POSTAGE AND FEES PAID

UNITED STATED AIR FORCE
OFFICIAL BUSINESS

4950/TZSM
Wright-Patterson AFB, O 45433

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T07:48Z
Check the source to verify that this is the current version before use.