MILITARY SPECIFICATION

FUZE, DEMOLITION KIT, M1134A2 WITH DETONATORS, PARTS FOR

This Specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings and provides quality assurance provisions for the fabrication of parts, assembly and packing for one type of fuze designated as Fuze, Demolition Kit, M1134A2.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-I-13857	-	Impregnation of Metal Castings.
MIL-D-46253		Detonator,Electric T20E1, Parts for Loading, Assembling, and Packing.
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament,Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1375
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-454	-	Standard General Requirements for Electronic Equipment
MIL-STD-1169	-	Packaging, Packing, and Marking for Shipment of Inert Ammunition Components.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

8799682	-	Carton, Packing, Ammunition for Fuze, Demolition Kit, M1134A2.
8799683	-	Container, Fiberboard, Ammunition for Fuze, Demolition Kit, M1134A2.
9370065	-	Fuze, Demolition Kit, M1134A2.

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

3.2 Fuze assembly. The fuze assembly shall comply with all requirements specified on drawing (dwg.) 9370065, all associated drawings and with all requirements specified in applicable specifications and standards.

3.3 Electrical resistance (continuity).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

3.3.1 Unarmed position. The electrical resistance, between the external connector pins and the arming pin assembly, (fully inserted into the complete fuze) shall be an open circuit when measured as specified in 4.5.2.

3.3.2 Armed position. To indicate acceptable continuity, the electrical resistance between the pins of the external connector shall be no less than one (1) ohm nor greater than two and one half (2.5) ohms when the arming pin assembly is sufficiently withdrawn to arm the fuze. The test shall be performed as specified in 4.5.2.

3.4 Non-arming and arming test. The testing shall be performed prior to insertion of the shear pin, as specified in 4.5.3.

3.5 Salt spray. The nut, arming pin assembly, container assembly, and disconnect arming pin shall be subjected to and pass the salt spray test when performed as specified in 4.5.4.

3.6 Torque test. The rotor spring shall meet the requirements on the applicable drawing when tested in accordance with 4.5.1.

3.7 First article. This specification makes provisions for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

3.8 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, distortion, unblended radii, surface defects, chips, dirt, grease, rust, weld splatter, corrosion products, and other foreign material. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coatings shall be continuous except for a few slight scratches not exposing base metal. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspecitions set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:58Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor or the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspection. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provision of 4.3.2. The first article sample shall be in accordance with Table I.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 5		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Nut (Dwg. 9370100)				
	Examination for defects	5		3.2	4.4.2.1
	Salt spray	5-0-1		3.5	4.5.4
	Cover, lead cup (Dwg. 9370097)				
	Examination for defects	5		3.2	4.4.2.2
	Spacer, rotor (Dwg. 9370102)				
	Examination for defects	5		3.2	4.4.2.3
	Cup, rotor, lead (Dwg. 9370099)				
	Examination for defects	5		3.2	4.4.2.4
	Rotor (Dwg. 9370094))				
	Examination for defects	5		3.2	4.4.2.5
	Cup, booster, lead (Dwg. 9370114)				
	Examination for defects	5		3.2	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-F-70758 (AR)

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH CATEGORY	TITLE EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	SHEET 2 OF 5 DRAWING NUMBER See Below NEXT HIGHER ASSEMBLY -- PARAGRAPH REFERENCE /INSPECTION METHOD
	Retainer rotor				
	(Dwg. 9370092)				
	Examination for defects	5		3.2	4.4.2.7
	Container				
	(Dwg. 9370088)				
	Examination for defects	5		3.2	4.4.2.8
	Container assembly				
	(Dwg. 9370087)				
	Examination for defects	5		3.2	4.4.2.9
	Salt spray	5-0-1		3.5	4.5.4
	Tube center				
	(Dwg. 9370078)				
	Examination for defects	5		3.2	4.4.2.10
	Guide, arming				
	(Dwg. 9370084)				
	Examination for defects	5		3.2	4.4.2.11
	Disconnect, arming pin				
	(Dwg. 9370091)				
	Examination for defects	5		3.2	4.4.2.12
	Salt spray	5-0-1		3.5	4.5.4

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 3 OF 5		DRAWING NUMBER See Below
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	NEXT HIGHER ASSEMBLY -- / PARAGRAPH REFERENCE /INSPECTION METHOD
	Guide and terminal assembly (Dwg. 9370083)				
	Examination for defects	5		3.2	4.4.2.13
	Salt spray	5-0-1		3.5	4.5.4
	Center tube assembly (Dwg. 9370067)				
	Examination for defects	5		3.2	4.4.2.14
	Assembly, prior to assembly of container and nut (Dwg. 9370066)				
	Examination for defects	5		3.2	4.4.2.15
	Electrical continuity	5		3.3	4.5.2
	Assembly (Dwg. 9370066)				
	Examination for defects	5		3.2	4.4.2.16
	Arming/Non-arming	5		3.4	4.5.3
	Ground plate (Dwg. 9370081)				
	Examination for defects	5		3.2	4.4.2.17

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS MIL-F-70758 (AR)

PARAGRAPH	TITLE			SHEET 4 OF 5	DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Connector (Dwg. 9370080) Examination for defects	5		3.2	4.4.2.18
	Spacer (Dwg. 9370075) Examination for defects	5		3.2	4.4.2.19
	Plate end (Dwg. 9370089) Examination for defects	5		3.2	4.4.2.20
	Terminal, arming pin (Dwg. 9370086) Examination for defects	5		3.2	4.4.2.21
	Pin, arming (Dwg. 9370075) Examination for defects	5		3.2	4.4.2.22
	Spring rotor (Dwg. 9370103)				
	Examination for defects	5		3.2	4.4.2.23
	Torque test	5		3.6	4.4.2.23
NOTES:					

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 5 OF 5		DRAWING NUMBER See Below
					NEXT HIGHER ASSEMBLY --
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Bushing, insulating (Dwg. 9370105) Examination for defects	5		3.2	4.4.2.24
	Bar, stop (Dwg. 9370104) Examination for defects	5		3.2	4.4.2.25
	Connector filtered (Dwg. 9370079) Examination for defects	5		3.2	4.4.2.26
NOTES:					

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lot shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Parts of only one lot number from one supplier.

b. T20E1 detonators from only one lot number from one supplier.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:58Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9370100
4.4.2.1	Nut				NEXT HIGHER ASSEMBLY 9370066
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Perpendicularity of either face with pitch diameter of thread		0.40%	3.2	Gage
102	Pitch diameter		0.40%	3.2	Gage
103	Minor diameter, min.		0.40%	3.2	Gage
104	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	Location of wrench holes		0.65%	3.2	Gage
202	Thickness, min.		0.65%	3.2	Gage
203	Protective coating incomplete or inadequate		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.2	Cover, Lead Cup		9370097
			NEXT HIGHER ASSEMBLY 9370096

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness		0.40%	3.2	Gage
102	Diameter, max.		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370102
4.4.2.3	Spacer, rotor				NEXT HIGHER ASSEMBLY 9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length, min.		0.40%	3.2	Gage
Minor					
201	O.D.		0.65%	3.2	Gage
202	I.D.		0.65%	3.2	Gage
203	Protective finish incomplete or inadequate		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Cup, rotor, lead		9370099
			NEXT HIGHER ASSEMBLY 9370098

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE / INSPECTION METHOD
Critical	none defined				
Major					
101	Thickness through bottom		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Length, max.		0.40%	3.2	Gage
Minor					
201	Diameter of flange		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Rotor				9370094
					NEXT HIGHER ASSEMBLY 9370093
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Contour		0.40%	3.2	Gage
102	Location of all holes		0.40%	3.2	Gage
103	Diameter of lead assembly holes, min. (2 places)		0.40%	3.2	Gage
104	Diameter of lead assembly counterbores, min. (2 places)		0.40%	3.2	Gage
105	Depth of lead assembly counterbore, min. (2 places)		0.40%	3.2	Gage
106	Diameter of pivot hole, min.		0.40%	3.2	Gage
107	Diameter of arming pin hole, min.		0.40%	3.2	Gage
108	Angle of arming pin hole		0.40%	3.2	Gage
109	Depth clip assembly holes (3 places)		0.40%	3.2	Gage
110	Diameter stop holes (2 places)		0.40%	3.2	Gage
111	Depth stop holes (2 places)		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Cup, booster, lead		9370114
			NEXT HIGHER ASSEMBLY 9370113

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Thickness through bottom		0.40%	3.2	Gage
102	Outside diameter, max.		0.40%	3.2	Gage
103	Length, max.		0.40%	3.2	Gage
Minor					
201	Diameter of flange		0.65%	3.2	Gage
202	Protective finish incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Retainer, rotor		9370092
			NEXT HIGHER ASSEMBLY 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Concentricity of "O" ring shoulder with inside diameter		0.40%	3.2	Gage
102	Concentricity of outside diameter with inside diameter		0.40%	3.2	Gage
103	Thickness		0.40%	3.2	Gage
104	Outside diameter, max.		0.40%	3.2	Gage
105	Location of holes		0.40%	3.2	Gage
106	Inside diameter, min.		0.40%	3.2	Gage
107	Diameter of lead cup holes (2 places)		0.40%	3.2	Gage
108	Diameter of lead cup holes counterbores, min. (2 places)		0.40%	3.2	Gage
109	Depth of lead cup holes counterbores (2 places)		0.40%	3.2	Gage
110	Diameter of "O" ring shoulder		0.40%	3.2	Gage
111	Arming pin hole diameter		0.40%	3.2	Gage
112	Arming pin hole location		0.40%	3.2	Gage
Minor					
201	Protective coating incomplete or inadequate		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Container	1 OF 1	9370088
			NEXT HIGHER ASSEMBLY: 9370087

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Inside diameter		0.40%	3.2	Gage
104	Location of inside diameter		0.40%	3.2	Gage
105	Location of side wall hole		0.40%	3.2	Gage
Minor					
201	Counterbore diameter		0.65%	3.2	Gage
202	Counterbore location		0.65%	3.2	Gage
203	Sidewall hole diameter		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.9	Container Assembly				9370087
					NEXT HIGHER ASSEMBLY
					9370066
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Width of weld, max.		0.40%	3.2	Gage
102	End plate distorted		0.40%	3.2	Gage
103	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	Weld protrudes beyond edge of container		0.65%	3.2	Gage
202	Protective coating incomplete or inadequate		0.65%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Tube, center		9370078
			NEXT HIGHER ASSEMBLY 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of center cavity		0.40%	3.2	Gage
102	Distance from (aft) shoulder of base to forward face of front flange		0.40%	3.2	Gage
103	Outer diameter of front flange		0.40%	3.2	Gage
104	Diameter of rotor contacting surface		0.40%	3.2	Gage
105	Diameter of shoulder, forward of flange		0.40%	3.2	Gage
106	Length of undercut forward of flange		0.40%	3.2	Gage
107	Location of detonator holes		0.40%	3.2	Gage
108	Location of hole in rear surface of base		0.40%	3.2	Gage
109	Location of fuze positioning slot in relation to detonator holes		0.40%	3.2	Gage
110	Pitch diameter of male thread		0.40%	3.2	Gage
111	Major diameter of male thread, max.		0.40%	3.2	Gage
112	Impregnation test	1/			1/
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

1/ Sampling, testing, and rejecting shall be in accordance with MIL-I-13857.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.11	Guide, arming				9370084
					NEXT HIGHER ASSEMBLY 9370083
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
102	Diameter		0.40%	3.2	Gage
103	Pitch diameter of thread		0.40%	3.2	Gage
104	Minor diameter of thread, min.		0.40%	3.2	Gage
105	Distance from arming pin surface to front of scarf groove, max.		0.40%	3.2	Gage
106	Distance from rear surface to rear of scarf groove, max.		0.40%	3.2	Gage
107	Radial distance from outside surface to top of scarf lip		0.40%	3.2	Gage
108	Concentricity of "O" ring groove with outside diameter		0.40%	3.2	Gage
109	Diameter of terminal, arming pin holes (2 places)		0.40%	3.2	Gage
110	True position of terminal, arming pin holes (2 places)		0.40%	3.2	Gage
111	Depth of groove on side		0.40%	3.2	Gage
112	Distance from arming pin surface to forward end of slot on outside surface		0.40%	3.2	Gage
113	Distance from arming pin surface to rear end of slot on outside surface		0.40%	3.2	Gage

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.11 (Cont'd)	Guide, arming		9370084
			NEXT HIGHER ASSEMBLY 9370083

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
114	Radial distance from outside surface to bottom of scarf groove		0.40%	3.2	Gage
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Width of "O" ring groove		0.65%	3.2	Gage
203	Diameter of "O" ring groove		0.65%	3.2	Gage
204	Protective coating incomplete or inadequate		0.65%	3.2	Visual
205	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.12	Disconnect, arming pin				9370091
					NEXT HIGHER ASSEMBLY 9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread, max.		0.40%	3.2	Gage
103	Diameter of shear pin hole, min.		0.40%	3.2	Gage
104	Diameter of non threaded length, max.		0.40%	3.2	Gage
105	Distance from threaded end to front of scarf groove, max.		0.40%	3.2	Gage
106	Total length		0.40%	3.2	Gage
107	Width of scarf groove, min.		0.40%	3.2	Gage
108	Radial distance from outside surface to top of scarf lip		0.40%	3.2	Gage
109	Concentricity of "O" ring groove with unthreaded diameter		0.40%	3.2	Gage
110	Distance from threaded end of scarf groove to shear pin hole		0.40%	3.2	Gage
111	Radial distance from outside surface to bottom of scarf groove		0.40%	3.2	Gage
112	Salt spray	5-0-1		3.5	4.5.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 2 OF 2	DRAWING NUMBER
4.4.2.12 (Cont'd.)	Disconnect, arming pin		9370091
			NEXT HIGHER ASSEMBLY 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Distance from threaded end to front of "O" ring groove		0.65%	3.2	Gage
203	Distance from rear surface to rear of "O" ring groove		0.65%	3.2	Gage
204	Diameter of "O" ring groove		0.65%	3.2	Gage
205	Protective finish improper or inadequate		0.65%	3.2	Visual
206	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Guide and terminal assembly				9370083
					NEXT HIGHER ASSEMBLY 9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length of exposed terminal arming pins		0.40%	3.2	Gage
102	Brazing, terminal, arming pin, missing or improper		0.65%	3.2	Visual
103	Protective finish incomplete or inadequate		0.40%	3.2	Visual
104	Salt spray	5-0-1		3.5	4.5.4
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.14	Center tube assembly	1	1	9370067
				NEXT HIGHER ASSEMBLY: 9370066

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Rotor not in full safe position		100%	3.2	Visual
Major					
101	Any component missing or loose		0.40%	3.2	Visual/Manual
102	RTV sealant missing or improperly applied		0.40%	3.2	Visual
103	Thread sealing compound missing or improperly applied		0.40%	3.2	Visual
104	Locktite missing or improperly applied		0.40%	3.2	Visual
105	Set screw, guide & terminal assy. improperly positioned		0.40%	3.2	Visual
106	Detonator missing or improperly assembled		0.40%	3.2	Visual
107	Bushing, insulating, missing		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.15	Assembly, prior to assembly of container and nut		9370066
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Rotor action not free		0.40%	3.2	Manual
102	Any component missing or improperly assembled		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.16	Assembly				9370066
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Red warning stencil or decal missing or illegible		100%	3.2	Visual
2	Green safing indicator not visible		100%	3.3	Visual
Major					
101	Any part missing, improperly assembled, or damaged		0.40%	3.2	Visual
102	Nut more than hand tight		0.40%	3.2	Manual
Minor					
201	Protective finish incomplete or inadequate		0.65%	3.2	Visual
202	Dust cap(s) missing		0.40%	3.2	Visual
203	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.17	Ground plate				9370081
					NEXT HIGHER ASSEMBLY 9370079
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Location of holes		0.40%	3.2	Gage
102	Diameter of small end		0.40%	3.2	Gage
103	Plating missing or inadequate		0.40%	3.2	Visual
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.18	Connector				9370080
					NEXT HIGHER ASSEMBLY
					9370079
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of large thread		0.40%	3.2	Gage
102	Major diameter of large thread, max.		0.40%	3.2	Gage
103	Pitch diameter of small thread		0.40%	3.2	Gage
104	Major diameter of small thread, max.		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.19	Spacer				9370075
					NEXT HIGHER ASSEMBLY
					9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Length		0.65%	3.2	Gage
202	Diameter		0.65%	3.2	Gage
203	Wall thickness		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370089
4.4.2.20	Plate, end				NEXT HIGHER ASSEMBLY 9370087
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter, max.		0.40%	3.2	Gage
102	Diameter of hole, min.		0.40%	3.2	Gage
103	Concentricity of hole with outside diameter		0.40%	3.2	Gage
Minor					
201	Thickness		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370086
4.4.2.21	Terminal, arming pin				NEXT HIGHER ASSEMBLY 9370083
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter		0.40%	3.2	Gage
Minor					
201	Length		.65%	3.2	Gage
202	Poor workmanship		1.00%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.22	Pin, arming		9370085
			NEXT HIGHER ASSEMBLY 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Pitch diameter of thread		0.40%	3.2	Gage
102	Major diameter of thread, max.		0.40%	3.2	Gage
103	Large O.D.		0.40%	3.2	Gage
104	Surface finish, large O.D.		0.40%	3.2	Gage
105	Angle of taper, large O.D.		0.40%	3.2	Gage
106	Surface finish, taper, large O.D.		0.40%	3.2	Gage
107	Angle of taper of tip		0.40%	3.2	Gage
108	Length, tip				
Minor					
201	Length of thread		0.65%	3.2	Gage
202	Total length		0.65%	3.2	Gage
203	Protective finish incomplete or inadequate		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9370103
4.4.2.23	Spring, rotor				NEXT HIGHER ASSEMBLY 9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Torque test	30-0-1		3.6	4.5.1
102	Inside diameter of coil, min.		0.40%	3.2	Gage
103	Outside diameter of coil, max.		0.40%	3.2	Gage
104	Length of legs		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.8	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.24	Bushing, insulating		9370105
			NEXT HIGHER ASSEMBLY 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter of flange, max.		0.40%	3.2	Gage
102	Outside diameter of body, max.		0.40%	3.2	Gage
103	Diameter of hole		0.40%	3.2	Gage
Minor					
201	Thickness of flange, min.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.25	Bar, stop		9370104
			NEXT HIGHER ASSEMBLY: 9370067

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major	None defined				
Minor					
201	Overall length		0.65%	3.2	Gage
202	Height of ends		0.65%	3.2	Gage
203	Protective finish missing, improper or inadequate		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-70758 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.26	Connector, filtered				9370079
					NEXT HIGHER ASSEMBLY 9370067
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical 1	Filters not present		100%	3.2	Visual
Major 101	Soldering not in compliance with MIL-STD-454	each lot		3.2	Certificate of compliance
102	Potting missing or incomplete		0.40%	3.2	Visual
Minor 201	Length of exposed filters, max.		0.65%	3.2	Gage
202	Poor workmanship		1.0%	3.8	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article Inspection Table I, the Quality Conformance Inspection Tables herein, as well as in the following paragraph.

4.4.3.1 Check test for deterioration of detonators (see MIL-D-46253). If the total time between original acceptance of any detonator lot and the assembly of that lot into the fuzes exceeds two years, or if the detonators have been subjected to adverse conditions, however brief, at any time since previous tests, the detonator lot shall be subjected to and must satisfactorily pass the check test for deterioration specified in MIL-D-46253 immediately before the detonator lot is assembled into the fuzes. This test shall be performed by the contractor on detonators selected by the Government inspector at the facility assembling the detonators into the fuzes (see 6.4).

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in Table I starting with 4.4.2.1. The contractor shall submit inspection equipment designs, for approval, in accordance with the terms of the contract. See section 6 of MIL-A-48078, and 6.3 and 6.4 herein.

4.5 Methods of inspection.

4.5.1 Rotor spring torque test. The springs shall be assembled to the applicable test fixture and the torque required to rotate the legs of the spring parallel to each other shall be recorded. Any spring which fails to comply with the specified drawing requirement shall be classified defective.

4.5.2 Electrical continuity test. The assembly shall be connected to the approved test fixture and the electrical resistance of the lead circuit shall be measured with the fuze first in the unarmed position and then with the fuze in the armed position. Any assembly which fails to comply with the specified requirement shall be classified defective and removed from the lot. This test shall be performed behind a suitable barricade.

4.5.3 Non-arming and arming test. The fuze less shear pin shall be assembled to the approved test fixture and a force between 20 and 30 pounds shall be applied to the arming pin disconnect in a direction so as to withdraw the pin from the assembly. If the arming pin disconnect does not withdraw sufficiently enough to allow the rotor to move to the armed position, the assembly shall be classified defective and removed from the lot.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:58Z
Check the source to verify that this is the currentversion before use.

After arming, the pin disconnect shall be re-inserted into the assembly. If the rotor fails to return to the fully unarmed position, the assembly shall be classified defective and removed from the lot. After the arming test, the shear pin shall be assembled to the fuze.

Warning: This test may be dangerous and should be performed behind a suitable barricade.

4.5.4 Salt spray test. After application of the protective coating specified on the applicable drawing, the samples shall be subjected to the salt spray test for the period specified on the applicable drawing. If one or more units of the sample show evidence of corrosion after testing, the lot of components represented by the sample shall be rejected.

5. PACKAGING

5.1 Packaging.

5.1.1 Assembled fuze. The assembled fuze shall be packaged in accordance with Dwg. 8799682.

5.2 Packing.

5.2.1 Assembled fuze. The packaged outer cartons shall be packed in accordance with Dwg. 8799683.

5.3 Marking. All marking shall be done in accordance with MIL-STD-1169.

5.4 Shipping. When component parts from more than one lot are shipped as a carload, each lot shall be kept separate and the division between lots clearly indicated.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:58Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. The parts covered by this specification are intended for use on a Demolition Fuze with other demolition items.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, ARDEC, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Cost of check test. The contracting officer will arrange for the contractor to be reimbursed for the expense incurred in the performance of the check test for deterioration of the assemblies. The test shall be conducted at Government expense without cost to the contractor who loaded the detonator assemblies or to the contractor assembling the detonator assemblies into the fuzes, and shall not constitute a basis for rejection against either contractor except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the detonator assembly lot was under the jurisdiction of either contractor.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading U.S. Army Armament Research, Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

6.6 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

6.7 Subject term (key word) listing.

Fuze
Demolition kit

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1375-A392)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an *acknowledgement* will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-70758 (AR)	FUZE, DEMOLITION KIT, M1134A2 WITH DETONATORS, PARTS FOR

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:58Z
Check the source to verify that this is the current version before use.