MILITARY SPECIFICATION

GRENADE AND TUBE ASSEMBLY
METAL PARTS ASSEMBLY

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of two component grenade and stem assembly used to generate a kill mechanism used in the M692/M731 munition. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-B-117	-	Bags and Sleeves, Interior Packaging.
MIL-H-6875	-	Heat Treatment of Steels (Aircraft Practice, Process for)
MIL-A-48078	-	Ammunition, Standard Quality Assurance Provisions, General Specification For.
DOD-P-16232	-	Phosphate Coating, Heavy Manganese or Zinc Base (for ferrous metals)

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn. AMSMC-QA, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1320
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-171	-	Finish of Metal and Wood Surfaces
MIL-STD-1169	-	Packaging, Packing and Marking for Shipment of Inert Ammunition Components.

DRAWINGS

U.S. ARMY ARMAMENT, RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8865569	-	Shell, Lower
8865570	-	Shell-Tube Assembly

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on the date of invitation for bids or request for proposal shall apply.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM B 117	-	Standard Method of Salt Spray (Fog) Testing
ATSM-E-18	-	Standard Methods for test for Rockwell Hardness and Rockwell Superficial Hardness of Metallic Materials.

(Application for copies should be addressed to: American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103).

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

3.2 Parts and assemblies. The parts and assemblies shall comply with all requirements specified on assembly drawings and associated drawings and with all requirements specified in applicable specification.

3.3 First article testing. This specification makes provisions for first article testing. Submission of first article quantity by the contractor shall be as specified in the contract.

3.4 Heat Treatment Process. Parts shall be heat treated by the same overall process (including the normalizing and stress relief phase, when part of the contractor's overall heat treat process) using the same quench bath and in the same furnace for each phase of the overall heat treatment process. Parts from each furnace shall be kept segregated until all heat treat tests in this specification has been completed. Beyond this point in the process, acceptable parts may be combined for further processing and lot formation.

3.5 Workmanship. All parts and assemblies shall be fabricated and finished in a thorough, workmanlike manner. They shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to any parts, nor shall the parts be contaminated by the cleaning agents.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

4.1.1. Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classed as follows:

a. First article inspection (See 4.3).

b. Quality conformance inspection (See 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated in Table I.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I as specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE Grenade and Tube Assembly Metal Parts Assembly		SHEET 1 OF 2		DRAWING NUMBER --- NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Sleeve, Detonator Tube (Dwg. 8864980)				
	Examination for defects	25		3.2	4.4.2.1
	Tube, Detonator (Dwg. 8865558)				
	Examination for defects	25		3.2	4.4.2.2
	Shell, Lower (Dwg. 8865569)				
	Examination for defects	25		3.2	4.4.2.3
	Stock Control	5		3.2	4.4.3.1
	Salt Spray	25		3.2	4.4.3.2/ASTM Standard Method B 117
	Minimum Inside Volume	25		3.2	4.4.3.3/Gage
	Shell, Upper (Dwg. 8865568)				
	Examination for defects	25		3.2	4.4.2.4
	Stock Control	5		3.2	4.4.3.1
	Salt Spary	25		3.2	4.4.3.2/ASTM Standard Method B 117
	Minimum Inside Volume	25		3.2	4.4.3.3/Gage

NOTES:

5

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE Grenade and Tube Assembly Metal Parts Assembly		SHEET 2 OF 2		DRAWING NUMBER ---
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Shell Tube Assembly (Dwg. 8865570)				
	Examination for defects	25		3.2	4.4.2.5
	Torque Test	25		3.2	Gage
	Push Through Test	25		3.2	Gage
	Tube, Detonator (Dwg. 8865558)				
	Examination for defects	25		3.2	4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot provisions of MIL-A-48078. Inspection lots shall contain.

a. Fastener spring grip from only one manufacturer of not more than one grade of material.

b. Steel from only one manufacturer of not more than one grade.

4.4.2 Examination. See MIL-A-48078. Unless otherwise specified in the classification of defects, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.1	Sleeve, Detonator Tube	1	1	8864980
				NEXT HIGHER ASSEMBLY 8865570

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Diameter of body		0.40%	3.2	Gage
102	Burr(s)		0.40%	3.2	Visual
103	Crack or perforation		0.40%	3.2	Visual
104	Inside diameter		0.40%	3.2	Gage
105	Finish			3.2	Certification
106	Shoulder length		0.40%	3.2	Gage
107	Shoulder diameter		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Tube, Detonator				8865558
					NEXT HIGHER ASSEMBLY 8865570
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	True position of flash hole		0.40%	3.2	Gage
102	Diameter of flash hole		0.40%	3.2	Gage
103	Pitch diameter of thread		0.40%	3.2	Gage
104	Diameter of cavity above thread, minimum		0.40%	3.2	Gage
105	True position of diameter of cavity above thread with outside diameter		0.40%	3.2	Gage
106	True position of smaller (sleeve) cavity with outside diameter		0.40%	3.2	Gage
107	Length of effective thread, min.		0.40%	3.2	Gage
108	Angle missing from flash hole		0.40%	3.2	Visual
109	Flash hole missing		0.40%	3.2	Visual
Minor					
201	Minor diameter of thread, max.		0.65%	3.2	Gage
202	Diameter of thread counterbore		0.65%	3.2	Gage
203	Depth of thread counterbore		0.65%	3.2	Gage
204	Poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-29T03:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.3	Shell, Lower	1	1	8865569
				NEXT HIGHER ASSEMBLY: ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Largest outside diameter		0.40%	3.2	Gage
102	Thickness, min.		0.40%	3.2	Gage
103	Contour improper		0.40%	3.2	Gage
104	Diameter of hole		0.40%	3.2	Gage
105	Concentricity of hole with largest outside diameter to mating surface perpendicularity		0.40%	3.2	Gage
106	Angle incorrect on lip end		0.40%	3.2	Visual
107	Stock control		----	3.2	4.4.3.1
108	Salt spray	15/0/1	----	3.2	4.4.3.2/ASTM Standard Method B 117
109	Minimum inside volume	10/0/1	----	3.2	4.4.3.3/Gage
110	Hardness	30/0/1	----	3.4	4.5.2
Minor					
201	Small lip radius missing		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil - Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE	SHEET	OF	DRAWING NUMBER
4.4.2.4	Shell, Upper	1	1	8865568
				NEXT HIGHER ASSEMBLY ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Distance from hole to flat end including chamfer		0.40%	3.2	Gage
102	Outside diameter		0.40%	3.2	Gage
103	Diameter of hole, min.		0.40%	3.2	Gage
104	Depth to hole face, min.		0.40%	3.2	Gage
105	True position of hole with outside diameter		0.40%	3.2	Gage
106	True position of second largest outside diameter with largest outside diameter		0.40%	3.2	Gage
107	Thickness, min.		0.40%	3.2	Gage
108	Contour improper		0.40%	3.2	Gage
109	Angle of outside diameter incorrect		0.40%	3.2	Gage
110	Stock control		----	3.2	4.4.3.1
111	Salt spray	15/0/1	----	3.2	4.4.3.2/ASTM Standard Method B 117
112	Minimum inside volume	10/0/1	----	3.2	4.4.3.3/Gage
113	Hardness	30/0/1	---	3.4	4.5.2
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Shell Tube Assembly				8865570
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Torque test		0.40%	3.2	Gage (See Note)
102	Protrusion of tube assembly		0.40%	3.2	Gage
103	True position of diameter of tube assembly with outside diameter of upper shell including perpendicularity with shell face		0.40%	3.2	Gage
104	Inside diameter of spring grip fastener, max.		0.40%	3.2	Gage
105	Inside diameter of detonator tube sleeve, min.		0.40%	3.2	Gage
106	Distance between shell hemisphere face and tube face		0.40%	3.2	Gage
107	Component or operation missing		0.40%	3.2	Visual
109	Push through test	125/1/2	----	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:
1. Alternate method shown in 4.3.3.5.

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-G-70721 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Sleeve, Outer				9298356
					NEXT HIGHER ASSEMBLY 9298357
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%	3.2	Gage
102	Finish		100%	3.2	Certification
103	Hardness	30-0-1	1/	3.2	Test Equipment
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:
1. Test should be performed on each heat treat batch.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Dimensional inspection of stock specimen. Two (2) stock specimens shall be taken from each coil of finished stock just prior to forming the upper and lower shells. The width of each specimen shall be the width of the stock, and the length shall be as necessary to obtain the total surface area of the tool to be used in production. One (1) specimen shall be taken from the beginning of the coil and the other specimen shall be taken from the end of the coil. An additional specimen shall be taken whenever a new, repaired, or altered tool is entered into production. Each specimen shall be identified with an index position of the tool and for the direction of travel of the stock with respect to the tool. The specimens shall also be identified as being from the beginning or end of the coil. If, for any specimen, the average value of fifteen (15) measurements for the total thickness dimension and the depth dimension fails to comply, or if the direction of tool travel does not comply with the applicable drawing requirements, the coil, or portion thereof, from which the specimen was taken, shall be rejected. In addition, the tool which produced the rejected specimen shall be removed from production. All shells produced from the rejected coil shall be rejected. The dimensional inspection shall be performed using equipement in accordance with 4.4.4.

The specimen from a new, repaired, or adjusted tool entering production shall be subjected to dimensional inspection of all stock dimensions specified in the applicable drawings. Fifteen (15) readings shall be taken for each dimension. The tool shall not be used in production until dimensional compliance with the drawing requirements has been determined from the specimen produced by the tool.

4.4.3.2 Salt spray test of upper shell and lower shell.

4.4.3.2.1 Phosphate - coated (batch-type process). Fifteen (15) each of upper shell and lower shell shall be selected from each batch and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the batch represented by the failing part shall be rejected.

4.4.3.2.2 Phosphate - coated shells (continuous-type process). Fifteen (15) each of upper shell and lower shell shall be selected from each four (4) hours of production, or portion thereof, and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specification requirement, the quantity represented by the failing part shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

4.4.3.2.3 Phosphate - coated shells (lot plan). Twenty-five (25) each of upper shell and lower shell shall be selected from each lot and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the lot shall be rejected.

4.4.3.2.4 Plated shells (when applicable). Twenty-five (25) each of upper shell and lower shell shall be selected from each lot and subjected to the salt spray test as specified on the applicable drawing. If any part fails to comply with the specified requirement, the lot shall be rejected.

4.4.3.3 Minimum inside volume of hemispheres (prior to phosphating). A sample of ten (10) each upper shells and lower shells shall be selected for determination of minimum volume requirement to qualify the production process. In addition, five (5) parts shall be selected from the last portion of each four (4) hours production or fraction thereof, for determination of minimum volume requirement as a control of the production process. This determination shall be performed using equipment in accordance with 4.4.4. If any defective parts are found during qualification of the production process, the process producing the defective part shall be removed from production. Further, that portion of production since the last production process control check shall be returned to the contractor for corrective action.

All production processes removed from production because of some fault may, after corrective action, be returned to production, providing they pass the qualification test above. The contractor may request a change of inspection frequency, providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.4.3.4 Dimensional control of stamped parts. In place of the normal sampling associated with the classification of defects, and with the approval of the Contracting Officer, a sample of at least ten (10) parts may be dimensionally inspected to qualify the tool used in the stamping process for use in production. In addition, a random sample of five (5) parts shall be selected from the last portion of each hour's production for dimensional inspection as a control of the tool during production.

If any defective parts are found during qualification of the tool, the tool producing the defective part shall not be used in production.

If any defective parts are found when inspection is performed for control of the tool, the tool producing the defective part shall be removed from production. Further, that portion of production since the last tool control check shall be returned to the contractor for corrective action.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

All tools removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

4.4.3.5 Minimum torque of tube assembly. In place of the normal sampling procedure associated with the classification of defects, and with the approval of the Contracting Officer, the following inspection procedures may be used: at the start of each day, and whenever a new piece of equipment is put into operation, five (5) tube assemblies shall be selected from each piece of equipment for determination of minimum assembly torque of the tube assembly for qualifying the equipment. In addition, five (5) assemblies per machine shall be selected from each hour's production, or fraction thereof, for the determination of the minimum tube assembly torque as a control of the equipment. If any defective assemblies are found during qualification of the equipment, the equipment producing the defective assemblies shall not be used in production. If any defective assembly is found when inspection is performed for control of the equipment, the equipment having produced the defective assembly shall be removed from production.

Further, that portion of production since the last equipment check shall be returned to the contractor for corrective action. All equipment removed from production because of some fault may, after corrective action, be returned to production providing it passes the qualification test above.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the tables beginning with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See 6.4 herein and MIL-A-48078, Section 6.

4.5 Methods of inspection.

4.5.1 Dimensional inspection of stock specimens. Fifteen (15) measurements shall be taken on each sample specimen for the total thickness dimension and the depth dimension. There shall be three (3) points of measurement across the width of the specimen at five (5) places along the length. The spacing of the readings shall be approximately uniform. One measurement for each characteristic shall be performed at each of the fifteen (15) measuring points on the specimen. An average value for each characteristic shall be computed for each specimen for which these measurements were obtained. In addition to the above, stock specimens from a new, repaired, or adjusted tool entering production shall have the following characteristics measured; groove radius, spherical radius, and the .0965 dimension.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

4.5.2 Hardness Test of Shell Lower, prior to Application of Protective Finish. Each sleeve outer shall be identified to the furnace from which it came. The test shall be performed using the methods and procedures specified in ASTM-E-18 (part 10) and as follows:

Three readings shall be taken on the outside diameter approximately 120° apart and approximately 3/8 inch from the end. A minimum reported data shall specify a serial number, the three hardness readings, their average and the results of the test.

5. PACKAGING

5.1 Preservation (Level C).

5.1.1 Lower shell (Dwg. D-8865569). The lower shell shall be packed in accordance with MIL-STD-1169, except that a Type 1, Class E, Spec MIL-B-117 barrier bag and an outer fiber box shall be used in addition to the inner fiber box. The inner fiber box corners shall be blunted before placing in bag. Prior to sealing bag, exhaust all excess air. Maximum moisture content of inner fiber box and any other packaging material used within the inner box shall be 9%.

5.1.2 Shell-tube assembly (Dwg. D-8865570). Packaging shall be in accordance with 5.1.1.

5.2 Packing (Level C).

5.2.1 Lower shell (Dwg. D-8865569). Packing shall be in accordance with 5.1.1.

5.2.2 Shell-tube assembly (Dwg. D-8865570). Packing shall be in accordance with 5.1.1.

5.3 Marking. Marking shall be in accordance with MIL-STD-1169.

5.4 Shipping. When components from more than one lot are shipped as a carload, each lot shall be kept separate, and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The shell and shell assemblies covered by this specification is intended for use in the munition for projectiles, H.E., 155MM, M692 and M731.

6.2 Ordering data. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-I (D), Picatinny Arsenal, New Jersey 07806-5000. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and tests paragraph number. This address will be specified on the Contract Data Requirements List, DD Form 1423 in the contract. Unless otherwise specified, data item DI-R-1714 will apply.

6.4 Submission of test data and data card. In addition to the normal distribution of records, when the projectiles are procured by the U.S. Amry Armament Material Readiness Command, one (1) copy of all ballistic data and ammunition data cards shall be forwarded to: Commander, U.S. Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M (D), Picatinny Arsenal, New Jersey 07806-5000.

6.6 Key word listing.
Tube, Detonator
Shell and Tube Assembly
Salt Spray
Hardness Test

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1320 - AB21)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

COMMANDER
US ARMY ARDEC
ATTN: AMSMC-QA
PICATINNY ARSENAL, NJ 07806-5000

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-G-70721	GRENADE AND TUBE ASSEMBLY METAL PARTS ASSEMBLY

3a. NAME OF SUBMITTING ORGANIZATION

b. ADDRESS *(Street, City, State, ZIP Code)*

4. TYPE OF ORGANIZATION *(Mark one)*

- ☐ VENDOR
- ☐ USER
- ☐ MANUFACTURER
- ☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:54Z
Check the source to verify that this is the current version before use.