MILITARY SPECIFICATION

WARHEAD, 2.75 INCH ROCKET, M261 AND M267, PARTS FOR

This specification is approved for use by the U.S. Army Armament Research and. Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers the quality assurance provisions and special requirements not covered by the drawings for metal parts and assemblies of the M261 and M267 Multipurpose Submunition (MPSM) Warheads.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2) , the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification for

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by attributes
MIL-STD-1167	Ammunition Data Cards
MIL-STD-1169	Packaging, Packing, and Marking for Shipment of Inert Ammunition Components

FSC 1340

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Center, Attn. DRSMC-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the currentversion before use.

2.7.2 Other Government documents drawings and publications. The following other Government documents, drawings and publications form a part of this specification to the extent specified herein.

DRAWINGS

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

PRODUCT DRAWINGS

933411.9	Cone, Nose Assembly
9334127	Plug, Base Assembly
9334128	Cover, Expulsion Charge
9334129	Support, Fuze
9334131	Warhead Case and Nose Cone Base Assembly
9334137	Plate, Pusher
9334141	Spring, Conical

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials. Materials shall be in accordance with the applicable drawings and specifications.

3.2 Components and assemblies. The components and assemblies shall comply with all requirements specified on Drawings 9334119, 9334127, 9334128, 9334129, 9334131, 9334135, and 9334141 and associated drawings and with all requirements specified in applicable specifications and standards.

3.3 First article inspection. This specification makes provision for first article inspection. Requirements for submission of first article samples by the contractor shall be as specified in the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

3.3.1 Process specification - molded or cast parts. When a multiple cavity mold is used in the fabrication of plastic or die cast components , a minimum of five (5) components from each mold cavity shall be included in the first article sample. The components shall bear a mark which identifies the component with the individual cavity.

3.4 Workmanship

3.4.1 Mechanical. Unless otherwise specified on the drawing, all parts and assemblies shall be free f ran burrs , chips , sharp edges , cracks , unblended radii , surface defects, dirt, grease, rust , porosity , warpage , burn marks, checks , blisters , excess flash, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agents. Surface coating shall be continuous except for a few slight scratches not exposing base material . The loading and assembly operations shall be performed in a thorough, workmanlike manner consistent with the best practices of the industry. All required markings shall be neat and legible .

3. 4,2 Electrical. Cable assemblies and wires shall be dressed in such manner as to prevent pinching or chafing of the wire insulation. Ends of wires shall be free from flux, chips, dirt, grease, rust or foreign material.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract , the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification when such inspections are deemed necessary to assure supplies and services conform to prescribed requirements . Unless otherwise specified herein or in the contract , the provisions of MIL-A-48078 Shall apply and are made a part of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. Unless otherwise specified herein, or in the contract, the following types of inspection shall be conducted on this item:

a. First Article Inspection

b. Quality Conformance Inspection

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated:

Part Description	Drawing	Quantity
Spring, Conical	9334141	15
Support, Fuze	9334129	15 or 5/cavity whichever is greater
Plate, Pusher	9334135	15 or 5/cavity whichever is greater
Bushing, Cable Sealing	9334125	10
Base, Plug	9334138	15
Cover, Expulsion Charge	9334128	10
Cone, Nose	9334120	15 or 5/cavity whichever is greater
Base, Nose Cone	9334113	15 or 5/cavity whichever is greater
Base, Nose Cone Assy	9334110	25
Cone, Nose Assy	9334119	15
Plug, Base Assy	9334127	15
War head Case	9334133	25
Warhead Case and Nose Cone Base, Assy	9334131	20

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specified herein.

4. 3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

TABLE I. First Article Inspection.

CLASSIFICATION OF DEFECTS & TESTS MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 3		DRAWING NUMBER
	Warhead, 2.75 Inch Practice: M267				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Spring, Conical (Dwg. 9334141)				
	Examination for defects	15		3.2	4.4.2.1
	Load test	15		3.2	4.5.1
	Support, Fuze (Dwg. 9334129)				
	Examination for defects	15(a)		3.2/ 3.3.1	4.4.2.2
	Plate, Pusher (Dwg. 9334135)				
	Examination for defects	15(a)		3.2/ 3.3.1	4.4.2.3
	Bushing, Cable Sealing (Dwg. 9334125)				
	Examination for defects	10		3.2	4.4.2.4

NOTES: (a) Minimum of 5/cavity for multiple mold with at least 15 total.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE: Warhead, 2.75 Inch Practice: M267		SHEET 2 OF 3		DRAWING NUMBER: See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Base Plug (Dwg. 9334138)				
	Examination for defects	15		3.2	4.4.2.5
	Cover, Expulsion Charge (Dwg. 9334128)				
	Examination for defects	10		3.2	4.4.2.6
	Cone, Nose (Dwg. 9334120)				
	Examination for defects	15(a)		3.2/ 3.3.1	4.4.2.7
	Base, Nose Cone (Dwg. 9334113)				
	Examination for defects	15(a)		3.2/ 3.3.1	4.4.2.8
	Base, Nose Cone Assy (Dwg. 9334110)				
	Examination for defects	25		3.2	4.4.2.9
	Cone, Nose Assy. (Dwg. 9334119)				
	Examination for defects	15		3.2	4.4.2.10
	Umbilical Lead Pull Test	10		3.2	4.5.3

NOTES:
(a) Minimum of 5/cavity for multiple mold with at least 15 total.

DRDAP Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER / NEXT HIGHER ASSEMBLY
	Warhead, 2.75 Inch Practice: M267				See Below
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Plug, Base Assy. (Dwg. 9334127)				
	Examination for defects	15		3.2	4.4.2.11
	Warhead Case. (Dwg. 9334133)				
	Examination for defects.	25		3.2	4.4.2.12
	Warhead Case and Nose Cone Base Assy. (dwg. 9334131)				
	Examination for defects	20		3.2	4.4.2.13

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall amply with the lot formation provisions of MIL-A-48078. In addition , inspection lots of warhead metal parts assemblies shall contain Metal and molded and cast parts from no more than two lots bearing the same inter fix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling Plans. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Spring, Conical				9334141
					NEXT HIGHER ASSEMBLY 9334122
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Load test		0.40%	3.2	4.5.1
MINOR	None defined				

NOTES:

DSCC-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Support, fuze				9334129
					NEXT HIGHER ASSEMBLY 9334126
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Largest outside diameter		0.40%	3.2	Gage
102	Inside diameter of fuze cavity		0.40%	3.2	Gage
103	Thickness of center web		0.40%	3.2	Gage
104	Mold inspection	5/ cavity		3.2	4.5.2
MINOR					
201	Outside diameter of case intrusion		0.65%	3.2	Gage
202	Diameter of charge expulsion cover hole		0.65%	3.2	Gage
203	Depth of charge expulsion cover hole		0.65%	3.2	Gage
204	Total height		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DEDiR-04 Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Plate, pusher				9334135
					NEXT HIGHER ASSEMBLY 9334097
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Mold inspection	5/ cavity		3.2	4.5.2
202	Flange thickness		0.65%	3.2	Gage
203	Chamfer, flange		0.65%	3.2	Gage
204	Largest diameter		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DSDLAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Bushing, Cable Sealing				9334125
					NEXT HIGHER ASSEMBLY 9334119
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Hole diameter		0.65%	3.2	Gage
202	Radius		0.65%	3.2	Gage
203	Thickness		0.65%	3.2	Gage
204	Outside diameter		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DSCP-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the currentversion before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.5	Base, plug		9334138
			NEXT HIGHER ASSEMBLY 9334127

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter threads		0.40%	3.2	Gage
102	Seal diameter		0.40%	3.2	Gage
MINOR					
201	Spanner hole diameter		0.65%	3.2	Gage
202	Distance between spanner holes		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.6	Cover, expulsion charge				9334128
					NEXT HIGHER ASSEMBLY 9334126
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Diameter		0.65%	3.2	Gage
202	Thickness		0.65%	3.2	Gage
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DESC-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.7	Cone, nose		9334120
			NEXT HIGHER ASSEMBLY 9334119

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Length of shoulder		0.40%	3.2	Gage
102	Mold inspection	5/ cavity		3.2	4.5.2
MINOR					
201	Outside diameter of shoulder		0.65%	3.2	Gage
202	Wall thickness of shoulder		0.65%	3.2	Gage
203	Largest outside diameter		0.65%	3.2	Gage
204	Diameter of umbilical cable hole		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DSDLR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.8	Base, nose cone				9334113
					NEXT HIGHER ASSEMBLY 9334110
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Largest diameter		0.40%	3.2	Gage
102	O-ring groove diameter		0.40%	3.2	Gage
103	O-ring groove surface finish		0.40%	3.4	Visual/Comparison Gage
104	Mold inspection	5/ cavity		3.2	4.5.2
MINOR					
201	O-ring groove width		0.65%	3.2	Gage
202	Length of inside flange min.		0.65%	3.2	Gage
* 203	Hole diameter, 2 places		0.65%	3.2	Gage
204	Total length		0.65%	3.2	Gage
205	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.9	Base, nose cone assy.		9334110
			NEXT HIGHER ASSEMBLY 9334131

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Contact resistance between ground lead and nose cone base		100%	3.2	Milliohmmeter
102	Insulation resistance between charge lead and nose cone base		100%	3.2	Megohmmeter
MINOR					
201	Poor solder connection (charge lead)		0.65%	3.2	Visual
202	Poor solder connection (ground lead)		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES

DESC-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:12Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.10	Cone, nose assy.		9334119
			NEXT HIGHER ASSEMBLY 9334097/9334148

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Bushing missing or improperly installed		0.40%	3.2	Visual
102	Umbilical lead pull test		0.40%	3.2	4.5.3
MINOR					
201	Length of umbilical cable after seating and crimping		0.65%	3.2	Gage
202	Poor solder connections		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

18

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.11	Plug, base assy.				9334127
					NEXT HIGHER ASSEMBLY 9334097/9334148
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR	None defined				
MINOR					
201	Felt pad missing, loose, or improperly applied		0.65%	3.2	Visual
202	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

DLA-IR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.12	Warhead Case				9334133
					NEXT HIGHER ASSEMBLY 9334131
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Pitch diameter of outside threads		0.40%	3.2	Gage
102	Bourrelet diameter max		0.40%	3.2	Gage
103	Wall thickness in expanded area min		0.40%	3.2	Gage
104	Base nose, core hole diameter		0.40%	3.2	Gage
105	Inside cargo diameter		0.40%	3.2	Gage
106	Straightness		0.40%	3.2	Gage
107	Pitch diameter of inside threads		0.40%	3.2	Gage
108	O-ring groove diameter		0.40%	3.2	Gage
109	O-ring groove surface finish		0.40%	3.4	Gage/Visual
* 110	Chamfer missing		0.40%	3.2	Visual
MINOR					
201	Bourrelet diameter min.		0.65%	3.2	Gage
202	Overall length		0.65%	3.2	Gage
203	Base to shoulder length		0.65%	3.2	Gage
204	Rib height		0.65%	3.2	Gage
205	Fuze support hole diameter		0.65%	3.2	Gage
206	Width of O-ring groove		0.65%	3.2	Gage
207	Front to shoulder length		0.65%	3.2	Gage
208	Rib width		0.65%	3.2	Gage
209	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:12Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-W-64044(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.13	Warhead Case and Nose Cone Base Assy.				9334131
					NEXT HIGHER ASSEMBLY 9334122/9334123
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
CRITICAL	None defined				
MAJOR					
101	Nose cone base skirt protrudes beyond end of warhead case		0.40%	3.2	Visual
MINOR					
201	Shrink on missing or improperly installed		0.65%	3.2	Visual
202	Poor solder connections		0.65%	3.2	Visual
203	Evidence of poor workmanship		0.65%	3.4	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the Quality Conformance inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with paragraph 4.4.2.1. The Contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein. The Contractor shall submit all inspection equipment designs to the Government for evaluation and approval prior to fabrication of such equipment.

4.5 Test methods and procedures.

4.5.1 Load test. Apply loads to the spring until the compressed length meets the drawing requirement. Any spring that requires a load that does not meet the drawing requirement shall be classed as defective.

4. 5.2 Dimensional control of molded or cast parts. In place of normal sampling and inspection associated with the Classification of Defects sample of five (5) parts as molded from each cavity shall be fully inspected dimensionally to qualify a new or reworked cavity f or use in production. The molded parts shall carry the individual cavity identification. As a control of each cavity during production, the above quantity of parts from each cavity shall be inspected for at least the defects listed in paragraphs 4.4.2.2, 4.4.2.3, 4.4.2.7 and 4.4.2.8, after the continuous production of each 5,000 parts or at the end of each week, whichever occurs first. Of the sample, one (1) part shall be the last produced. If any defective parts are found during qualification of the cavity, the cavity producing the defective part will not be used in production. If any defective parts are found when inspection is performed for the control of the cavity, the cavity producing the defective part shall be removed from production. Further , that portion of production since the last control check shall be returned to the contractor for inspection for each type of defect according to MIL-STD-105, using the AQL's detailed in the classification of defects. All cavities removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test above. The contractor may request a change of inspection frequency providing he presents objective evidence to the Contracting Officer to substantiate the request.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the currentversion before use.

4.5.3 Umbilical lead pull test. Apply the required pull at the connector. The umbilical lead shall withstand a pull of 5.0 lbs. minimum without displacing the cable stop eyelet. Any nose cone assembly that does not comply with the drawing requirement shall be classed defective.

5. PACKAGING

5.1 Packaging and marking. The warhead parts and assemblies shall be packaged and marked in accordance with MIL-STD-1169.

5.2 Packing and marking. The packaged parts and assemblies shall be packed and marked in accordance with MIL-STD-1169.

5.3 Ammunition data cards. Data card information shall be as specified in MIL-STD-1167.

6. NOTES

6.1 Intended use. The assemblies and components covered by this specification are intended for use as part of the 2.75 Inch Folding Fin Aerial Rocket System.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment for design approvals. See 6.2 of MIL-A-48078. Submit designs as required to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAF-I, Dover, NJ 07801.

6.4 First article. When a first article is required for inspection and approval, see 3.3 and 4.3.

6.5 Source control and specification control drawings. Certificates of conformance from the supplier certifying that the item complies with the drawing requirements shall be provided to the Government representative.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1340-A646)

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:12Z
Check the source to verify that this is the current version before use.