NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/145B
1 May 1997
SUPERSEDING
MIL-D-3943/145A
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS CIVILIAN SERVICE AWARD, DEFENSE INFORMATION SYSTEMS AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

MATERIAL: Red brass

FINISH: Nickel Plated, Silver Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip number 13.

DIMENSIONS:
HEIGHT (Including Lug): 1-1/2 inches (3.81 cm) REF
DIAMETER: 1-3/8 inch (3.49 cm) (REF)
THICKNESS: 0.125 inch ± 0.010 inch (0.313 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:04Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The reverse shall be suitable for engraving.

3. Decoration set shall consist of a regular size medal packaged in a presentation case conforming to MIL-DTL-14633, Type XVI with a Type XVI, Class 1 or 3 pad.

4. The lapel button shall conform to MIL-DTL-11484/369.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH
DISA - DC

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:04Z
Check the source to verify that this is the current version before use.