NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/146B
1 May 1997
SUPERSEDING
MIL-D-3943/146A
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, DISTINGUISHED SERVICE MEDAL, DEPARTMENT OF TRANSPORTATION

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Gilding Metal

FINISH:
BASE: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
DEVICE: Hard Enameled, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER:
-1: 1-7/16 inches (3.65 cm) (REF)
-2: 3/4 inch (1.91 cm) (REF)

HEIGHT (To Wing Tip):
-1: 1-13/16 inches (4.60 cm) (REF)
-2: 7/8 inch (2.22 cm) (REF)

THICKNESS:

BASE:
-1: 0.090 inch ± 0.005 inch (0.229 cm ± 0.012 cm)
-2: 0.065 inch ± 0.005 inch (0.165 cm ± 0.012 cm)

DEVICE:
-1: 0.045 inch ± 0.005 inch (0.114 cm ± 0.012 cm)
-2: 0.040 inch ± 0.005 inch (0.102 cm ± 0.012 cm)

THICKNESS (Overall at Thickest Point):
-1: 0.135 inch ± 0.010 inch (0.343 cm ± 0.025 cm)
-2: 0.105 inch ± 0.010 inch (0.267 cm ± 0.025 cm)

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The color shall conform to the TIOH chip numbers listed below or the standard sample.

COLOR	CHIP NUMBER
Green (Wreath)	12
Blue (Device)	18

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. Epoxy resin shall be smooth and flush with the dikes.

4. The suspension device is part of the base. The reverse side of the suspension device shall be flat.

5. The inscription bar on the reverse of the medal shall be suitable for engraving.

6. Decoration set shall consist of a regular size medal, miniature size medal, service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type V, Style 5 with a Class 1 or 1a pad.

7. The ribbon for the pendant drape shall conform to MIL-DTL-11589/372.

8. The lapel button shall conform to MIL-DTL-11484/192.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:

(Project No. 8455-0887)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.

DLA - CT

Civil Agency Coordinating Activities:
DOT

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.