INCH-POUND


MIL-DTL-3943/146E
1 March 2007
SUPERSEDING
MIL-DTL-3943/146D
23 January 2007

DETAIL SPECIFICATION SHEET

DECORATION, DISTINGUISHED SERVICE MEDAL, DEPARTMENT OF HOMELAND SECURITY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



MATERIAL: Gilding Metal

DASH NO.
-1: Regular Size
-2: Miniature Size

FINISH:

BASE: Hard Enameled, Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
DEVICE: Hard Enameled, Nickel Plated, Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.

DIMENSIONS:

DIAMETER:
-1: 1-7/16 inches (REF)
-2: 3/4 inch (REF)
HEIGHT (To Wing Tip):
-1: 1-13/16 inches (REF)
-2: 1 inch (REF)

THICKNESS:
BASE:
-1: 0.130 inch ± 0.005 inch
-2: 0.090 inch ± 0.005 inch
DEVICE:
-1: 0.070 inch ± 0.005 inch
-2: 0.060 inch ± 0.005 inch

THICKNESS (overall at thickest point):
-1: 0.200 inch ± 0.010 inch
-2: 0.150 inch ± 0.010 inch

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Enameled areas shall be as indicated. The colors shall conform to the TIOH Hard Enamel Color Chip Numbers listed below.

COLOR	CHIP NUMBER
Green	12
Blue	18
Blue	33

3. Epoxy resin (stoning epoxy) may be used in lieu of hard enamel at the option of manufacturer. When epoxy resin is used in lieu of hard enamel, the material requirement shall be gilding metal or red brass.

4. The suspension device is part of the base. The reverse side of the suspension device shall be flat.

5. The inscription bar on the reverse of the medal shall be suitable for engraving.

6. Decoration set shall consist of a regular size medal, miniature size medal, service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type V, Style 5 with a Class 1 or 1a pad.

7. The ribbon for the pendant drape shall conform to MIL-DTL-11589/372.

8. The lapel button shall conform to MIL-DTL-11484/192.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-2007-026)

Civil Agency Coordinating Activities:
DOT

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:05Z
Check the source to verify that this is the current version before use.