NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/149B
1 May 1997
SUPERSEDING
MIL-D-3943/149
13 May 1996

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS SERVICE MEDAL, FEDERAL BUREAU OF PRISONS, DEPARTMENT OF JUSTICE

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.

OBVERSE

REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass

FINISH: Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Including lug):
-1: 1-1/2 inches (3.81 cm) (REF)
-2: 27/32 inch (2.14 cm) (REF)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:06Z
Check the source to verify that this is the current version before use.

WIDTH (Overall):
-1: 1-3/8 inches (3.49 cm) (REF)
-2: 11/16 inch (1.75 cm) (REF)

THICKNESS (At Edge):
-1: 0.150 inch ± .010 inch (0.381 cm ± 0.025 cm)
-2: 0.100 inch ± .010 inch (0.254 cm ± 0.025 cm)

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant drape for Dash -1 large size civilian medals shall be a neck ribbon fabricated as shown on Figure 4 of MIL-DTL-3943. The pendant shall be attached to the neck ribbon using two jump rings. A jump ring fabricated from 0.050 inch (0.127 cm)diameter wire having an outside diameter of 3/8 inch (0.95 cm) shall be attached to the pendant. A neck ribbon ring fabricated from 0.050 inch (0.127 cm)diameter wire having an outside diameter of 1/2 inch (1.27 cm) shall be attached to the pendant jump ring though which the neck ribbon shall be placed. The ends of the jump rings shall be square cut, in line and together.

3. Decoration set for military personnel shall consist of a regular size medal, a miniature size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XVI with a Type XVI, Class 2 or 4 pad.

4. Decoration set for civilians shall consist of a regular size medal with a neck ribbon, a miniature size medal and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type XVI with a Type XVI, Class 2 or 4 pad.

5. The ribbon for the pendant drape shall conform to MIL-DTL-11589/376.

6. The lapel button for military personnel shall conform to MIL-DTL-11484/195.

7. The lapel button for civilians shall conform to MIL-DTL-11484/198.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Preparing activity:
Army - IH

Review activities:
DLA - CT

(Project No. 8455-0887)

Civil Agency Coordinating Activities:
DOJ-FPI

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:06Z
Check the source to verify that this is the current version before use.