NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/149G(IH)
24 July 2024
SUPERSEDING
MIL-DTL-3943/149F(IH)
24 September 2019

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS SERVICE MEDAL, FEDERAL BUREAU OF PRISONS, DEPARTMENT OF JUSTICE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.

OBVERSE

REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: Silver Plated, Oxidized, Buffed Relieved, Matte Finished and shall match The Institute of Heraldry Metal Finish Chip Number 14.

DIMENSIONS:
HEIGHT (Including lug):
-1: 1-1/2 inches (REF)
-2: 27/32 inch (REF)
WIDTH (Overall):
-1: 1-3/8 inches (REF)
-2: 11/16 inch (REF)
THICKNESS (At edge):
-1: 0.150 inch ± 0.010 inch
-2: 0.100 inch ± 0.010 inch

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:06Z
Check the source to verify that this is the current version before use.

DECORATION SETS:

1: Decoration set for military personnel shall consist of a regular size medal, a miniature size medal, a service ribbon, and a lapel button, all packaged in a presentation case conforming to MIL-DTL-14633, Type VI, Class 2 or 2A pad.

2: Decoration set for civilians shall consist of a regular size medal with a neck ribbon, a miniature size medal, and a lapel button, all packaged in a presentation case conforming to MIL-DTL-14633, Type I with a Class 2 pad.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The pendant drape for the regular size (-1) civilian medal shall be a neck ribbon fabricated as illustrated by the figure in MIL-DTL-3943 titled "Neck ribbon, Legion of Merit, Commander." The pendant shall be attached to the neck ribbon using two jump rings. A jump ring fabricated from 0.050 inch diameter wire having an outside diameter of 3/8 inch shall be attached to the pendant. A neck ribbon ring fabricated from 0.050 inch diameter wire having an outside diameter of 1/2 inch shall be attached to the pendant jump ring. The neck ribbon shall be placed through the neck ribbon ring. The ends of the jump rings shall be square cut, in line, and together.

3. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/376.

4. The specification slash sheet for the lapel button for military personnel is MIL-DTL-11484/195

5. The specification slash sheet for the lapel button for civilians is MIL-DTL-11484/198.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-222)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:06Z
Check the source to verify that this is the current version before use.