MIL-A-50093A(MU)
29 April 1964
SUPERSEDING
MIL-A-50093(CmlC)
9 February 1960

MILITARY SPECIFICATION

ADAPTER, COMPRESSED AIR BREATHING APPARATUS, M4

1. SCOPE

1.1 This specification covers a compressed air hose adapter.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-566 - Boxes, Folding, Paperboard.
PPP-B-636 - Box, Fiberboard.
PPP-B-676 - Boxes, Set-up, Paperboard.

MILITARY

MIL-P-116 - Preservation, Methods of.

FSC 4240

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

DRAWINGS

EDGEWOOD ARSENAL

DL5-82-8 - Adapter, Compressed Air Breathing Apparatus, M4. (All drawings referenced in this specification are listed on Drawing DL5-82-8.)

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

UNIFORM CLASSIFICATION COMMITTEE

Uniform Freight Classification Ratings, Rules and Regulations.

(Application for copies of these freight classification rules should be addressed to the Uniform Classification Committee, 202 Union Station, Chicago 6, Illinois.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL5-82-8, or on the subsidiary drawings, shall conform to the specifications listed thereon or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the adapter shall conform to the specifications and drawings listed on Drawing DL5-82-8 and the subsidiary drawings.

3.2 Manufacture and assembly. The adapter shall be manufactured and assembled as specified on Drawing C5-82-8.

3.3 Workmanship. The adapter shall be free from damage (dents, bends, burrs, cracks, or deformations) and foreign matter (dirt, grease, oil, or viscous material).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Supplier's responsibility will be as specified in the contract or order.

4.2 Special provisions.

4.2.1 Alternative inspection. The supplier may utilize any alternative inspection procedure which will provide equal or better assurance of quality by submitting a written proposal with justification and obtaining written approval from the Government prior to instituting the procedure. In case of dispute, the procedures of this specification will govern.

4.2.2 Objective evidence. The supplier shall provide objective evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

4.2.3 Substation inspection. If the supplier elects to establish substations for the purpose of conducting inspection for certain listed defects, the Acceptable Quality Levels (AQL's) for each inspection substation shall be equal to the AQL which is the next numerically lower value than the AQL specified for the total listed defects. The requirements of Standard MIL-STD-105 are applicable to each substation and to the end item.

4.3 Lotting. A lot shall consist of the adapters produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions.

4.4 Sampling. Sampling shall be conducted in accordance with Standard MIL-STD-105.

4.5 Inspection provisions.

4.5.1 For examination. Sample adapters shall be examined in accordance with the classification of defects and Standard MIL-STD-105.

4.5.2 Classification of defects.

4.5.2.1 Adapter, compressed air breathing apparatus, M4, assembly and detail (Dwg C5-82-8).

Categories		Defects
Critical:		None defined
Major:		AQL 1.0 percent defective
	101	Component missing or incorrectly assembled
	102	Valve control nonfunctioning
	103	Air passage obstructed
	104	Thread incorrect (Dwg B5-82-5)
	105	Diameter (0.550-0.010) incorrect (Dwg B5-82-6)
	106	Next assembly threads incorrect (Dwg AN 816-4-4)
	107	Workmanship (see 3.3)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

4.5.2.1 Adapter, compressed air breathing apparatus, M4, assembly and detail (Dwg C5-82-8). Continued.

Categories	Defects
Minor:	AQL 2.5 percent defective
201	Machine finish or radius (5/32) incorrect (Dwg 85-82-6)
202	Thread lute missing
203	Protective finish missing or incorrect

5. PREPARATION FOR DELIVERY

5.1 Cleaning and drying. The adapter shall be cleaned and dried in accordance with Specification MIL-P-116. Cleaning method C-1 and any of the drying methods listed therein shall be used.

5.2 Preservation and packaging. Level shall be as specified (see 6.2).

5.2.1 Level A. No preservative shall be applied to the adapter. The adapter, cleaned and dried as specified in 5.1, shall be packaged in accordance with method IA-15 of Specification MIL-P-116. The inner container shall be a box conforming to Specification PPP-B-676 or PPP-B-566.

5.2.2 Level C. The adapter, cleaned and dried as specified in 5.1, shall be packaged to afford adequate protection from the supply source to the first receiving activity for immediate use.

5.3 Packing. Level shall be as specified (see 6.2).

5.3.1 Level A. Fifty adapters, packaged as specified in 5.2, shall be packed in a box conforming to V3c, style RSC-SL, of Specification PPP-B-636. The box shall be closed in accordance with the requirements for exterior boxes, and all seams, including the manufacturer's joint, shall be taped.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

5.3.2 Level C. Adapters, packaged as specified in 5.2, shall be packed in a manner to insure carrier accpetance and safe delivery at first domestic destination. Containers shall conform to the Uniform Freight Classification rules or regulations of other carriers applicable to the mode of transportation.

5.4 Marking. In addition to any special marking required by the contract or order, unit packages and shipping containers shall be marked in accordance with Standard MIL-STD-129.

6. NOTES

6.1 Intended use. The adapter covered by this specification is used to connect the compressor air hose to the port of the M15 breathing apparatus and to permit sampling of compressed air for determining carbon monoxide content.

6.2 Ordering data. Procurement documents should specify the following:

(a) The title, number, and date of this specification.
(b) The level of packaging and packing required.

6.3 International interest. Certain provisions of this specification are the subject of an ABC international standardization agreement. When amendment, revision, or cancellation of this specification is proposed, the departmental custodians will inform their respective Departmental Standardization Offices so that appropriate action may be taken respecting the international agreement concerned.

Custodian:

Army - MU

Preparing activity:

Army - MU

International interest (see section 6)

Project No. 4240-A188

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.

SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(see indicated on reverse hereof)*.

SPECIFICATION

ORGANIZATION *(Of submitter)* | CITY AND STATE

CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT
$

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity)* | DATE

DD, FORM 1426, APR 63 REPLACES NAVSHIPS FORM 4863, WHICH IS OBSOLETE PLATE NO. 15419

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:16Z
Check the source to verify that this is the current version before use.