MILITARY SPECIFICATION

COVERALLS, FIREMEN'S, ALUMINIZED, PROXIMITY

This amendment forms a part of Military Specification MIL-C-82284C, dated 1 February 1984, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 6

3.5.1, add "(bellows)" after "Back inverted pleat facing"

PAGE 11

Following operation 11 add the following:

"TABLE I - CONSTRUCTION OF COVERALLS

No.	Operation	Stch Type	Seam/ Stch type	Stch/ in	Thread (3.3.4)
12.	Prepare fronts (liner).				
	a. Stitch the darts according to the marks on the pattern.	301 or 401	OSf-1	6-8	
	b. Stitch from the base of the front opening to the crotch, face to face, 1/2 inch gauge. Spread open and topstitch seam 1/4 inch gauge.	301 or 401	SSz-3	6-8	
13.	Join center back seam and form pleat (liner).				
	a. Stitch center back seam 1/2 inch gauge.	301 or 401	SSa-1	6-8	
	b. At base of pleat, notch right seam allowance to stitching, turn seam to left and topstitch 1/4 inch gauge to crotch.	301 or 401	LSq-2(b)	6-8	
	c. Form pleat at neckline by folding at notch on left side of center back and matching notch on right side. Tack across pleat about 1/4 inch from the edge.	301	--	6-8	

FSC 8415

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.

TABLE I - CONSTRUCTION OF COVERALLS

No.	Operation	Stch Type	Seam/ Stch type	Stch/ in	Thread (3.3.4)
14.	Join shoulder, armhole and underarm seams, outseams and inseams of liner.				
	Stitch seams with a 1/4 to 3/8 inch bight 4-thread overedge, or 1/4 to 3/8 inch gauge safety stitch, face to face.		SSa-1 or SSa-2	10-12 (overedge) 6-8 (safety stitch)	
15.	Attach knitted wristlets.				
	a. Double the knitted wristlets with edges even and safety stitch edges together.	515, 516 or 519	SSa-2	6-8	
	b. Sew the wristlets to the inside of the liner with two rows of stitching about 1/4 inch apart in accordance with the pattern marks.	301	SSbd-2	6-8	
16.	Attach anchor strips				
	Fold anchor strips (inside armhole hanging tabs) in half widthwise. Attach strips at each shoulder/armhole seam and at each armhole/underarm seam in both the liner and the outer shell by stitching and backstitching across the strips about 1/4 inch from the ends. Strips shall finish between the liner and the outer shell in the assembled garment.	301	--	12-16	
17.	Make neck facing, join to liner and attach zipper.				
	a. Center and stitch, 1/16 inch from edges, the four sides of the identification label to the back neck facing. The bottom edge of the label shall be parallel to and approximately 1/2 inch above the bottom edge of the neck facing.	301	LSbj-1	6-8	
	b. Join front facings to back facing face to face 3/8 inch gauge. Spread open and topstitch 1/4 inch from seams.	301 or 401	SSz-3	6-8	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.

TABLE I - CONSTRUCTION OF COVERALLS

No.	Operation	Stch Type	Seam/ Stch type	Stch/ in	Thread (3.3.4)
	c. Stitch, face to face, 3/8 inch gauge, the bottom edge of the facing to the liner neckline, catching darts folded away from center front. The raw front edge of the facing shall align with the raw front edge of the liner. Turn liner to finished position and topstitch close to seam.	301 or 401	LSq-2	6-8	
	d. Attach zipper to liner with the back of the tape against the face of the liner on the right and left sides. Stitch 3/8 inch from the aligned edges of the tape and liner. The top edge of the zipper tape shall finish even with the top raw facing edge."	301	SSa-1	6-8	

PAGES 15 and 16

Delete in their entirety.

PAGE 17

Following para 4.1.1, add the following:

"4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

1. First article inspection (see 4.3).
2. Quality conformance inspection (see 4.4).

4.3 First article inspection. The first article submitted in accordance with 3.2 shall be inspected as specified in 4.4.2 for compliance with design, construction, workmanship and dimensional requirements.

4.4 Quality conformance inspection. Inspection shall be performed in accordance with MIL-STD-1666, except when otherwise indicated.

4.4.1 Component and material inspection. In accordance with 4.1 above, components and materials shall be inspected and tested in accordance with all the requirements of referenced specifications, drawings and standards unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Testing of components. In addition to the quality assurance provisions of the referenced specifications, components listed in Table III shall be tested for characteristics shown therein. The methods of testing as specified herein shall be followed. All test reports shall contain the individual values utilized in expressing the final result. The lot shall be unacceptable if one or more sample units fail to meet any requirement specified. The sample size shall be in accordance with the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.

Lot Size	Sample Size
800 or less	2
801 thru 22,000	3
22,001 and over	5

The lot size expression and sample units for testing shall be as follows:

Component	Lot size expressed as	Sample unit
Snaps and dee-rings	gross	6 each

Table III - Testing of components

Component	Characteristic	Requirement Paragraph	Test Method
Treated Leather	Water Absorption	3.3.3.1	1/, 2/
	Identification of Silicone Treatment	3.3.3.1	1/
Snaps and Dee-Rings	Material Identification	3.3.8.1	1/
	Style	3.3.8.1	Visual
	Dimensions	3.3.8.1	Visual"

PAGE 18

Following para 5.2.1, add:

"*5.2.2 Level B. Five coveralls, of one size only, packaged as specified in 5.1.1, shall be packed in a fiberboard shipping container assembled and closed conforming to type CF, class domestic, grade 275, variety DW, size 3A of MIL-B-17757. The fiberboard for the liner shall conform to type CF, class domestic of MIL-B-17757. Level A packages shall be packed flat within the shipping container with every other coverall reversed end to end and the length of the coverall parallel to the side panels of the container. Each container shall have the contents completely covered on the top and bottom with a sheet of commercial grade kraft paper. Toward the end of the contract, or when there are less than the required amount per container of the same size, mixed sizes may be packed within the same shipping container.

5.2.3 Level C (Commercial packing). Coveralls, packaged as specified in 5.1, shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the contractor for retail distribution. Containers shall comply with the US Postal Service Manual, Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.3 Marking. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance wtih MIL-STD-129.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.

5.3.1 Polyethylene bagged packages. The polyethylene bags specified in 5.1.1 shall have the required information legibly printed or stamped in black bold letters, 1/4 inch in height, directly on the bag across the center face or on a white paper label inserted within the bag so as to permit ready identification. The bag or label shall indicate the following information:

STOCK NUMBER
NOMENCLATURE
SIZE
QUANTITY

5.3.2 Labels, mixed sizes. Each shipping container, packed with mixed sizes, shall have securely attached to the end and side, directly under the printing or stenciling, a white paper label 5 by 4 inches with the words "MIXED SIZES" plainly stamped or printed thereon and under these words shall be legibly stamped or printed the correct quantity and sizes contained therein.

6. NOTES

6.1 Intended use. The coveralls are intended to be used in conjunction with the Hood and Gloves, Firemen's, Aluminized, Proximity. The coveralls are intended for use by personnel engaged in aircraft crash rescue fires and damage control work."

PAGE 19

Delete in its entirety.

ADDITIONAL PAGE

Add the following DD Form 1426 at the end of the document:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.

Custodian:
Navy - NU

Review Activity:
Navy - SH
DLA - CT

User Activity:
Navy - AS, CG, MC

Preparing Activity:
Navy - NU

Project No. 8415-N406

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T06:59Z
Check the source to verify that this is the current version before use.