MIL-K-50889(MU)
1 April 1971

MILITARY SPECIFICATION

KNOB, SETTING

This specification is mandatory for use by the activities of the Army Munition Command.

1. SCOPE

1.1 Scope. This specification covers special requirements, quality assurance provisions, and the preparation for delivery criteria for one type of setting knob used to set XM28 Timer on the Training Atomic Demolition Charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition

MIL-STD-1169(MU) - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8852323 - Knob, Setting
8883538 - Bag, Packing for Repair Parts
EL - 8852323 - Equipment List

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

FSC 1195

(Copies of specifications, standards, drawings, and publications required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The knob shall comply with all requirements specified on the drawing (dwg 8852323), with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection.

4.3 Product acceptance inspection.

4.3.1 Lot formation. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.1 Inspection lot. An inspection lot shall be the quantity of parts, subassemblies, or assemblies from the same lot, which are submitted to inspection for Government acceptance.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Knob, setting (see dwg 8852323).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major		
101.	Material (see 3.1)	Visual
102.	Pin hole diameter	Gage
103.	Shaft hole diameter	Gage
104.	Depth of shaft hole	Gage
Minor		
201.	Large outside diameter	*Measure
202.	Small outside diameter	*Measure
203.	Chamfer present	Visual
204.	Total length	*Measure
205.	Length of flange	*Measure
206.	Location of pin hole	*Measure
207.	Knurl present	Visual
208.	Marking	Visual
209.	Workmanship (see 3.3)	Visual

*Measure with suitable scale.

4.3.2.1.2 Bag, Packing, for Repair Parts (see dwg 8883538 covering dwg. part number 8883538-2 and section 5).

Categories	Characteristics	Method of Inspection
Critical: None defined		
Major:		
101.	Material (see 3.1)	Visual
102.	Length before packing, min	*Measure
103.	Width before packing, min	*Measure
104.	Objective evidence (see 6.2) available for heat seal test in accordance with MIL-P-116	Visual
105.	Properly packed	Visual
106.	No tear, split, or crack in bag	Visual

*Measure with suitable scale.

Minor		
201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual-Manual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Packing and Marking for Storage and Shipments (see dwg. 8808362 and section 5).

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major		
101.	Gross load weight, max	*Measure
102.	Contents tight in package	Visual
103.	Correctly packed	Visual-Manual
104.	Package material (see 3.1)	Visual
*Determine weight with a suitable scale.		
Minor		
201.	Marking	Visual
202.	Workmanship (see 3.3)	Visual-manual

4.3.3 Testing. Not applicable.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL) (See EL-8852323). When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment. The contractor shall obtain approval of such designs, operating instructions, and special calibration instructions as specified in 6.3 prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired.
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL.

4.3.4.2 Minor Characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Not Applicable.

5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.

5.1.1.1 Level A. The knob shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The knob shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The knob shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The knob shall be packaged in accordance with dwgs 8883538 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The knob shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The knob shall be packed in accordance with dwgs 8883538 and 8808362.

5.2.3 Marking. Marking shall be as specified in accordance with dwgs 8883538 and 8808362.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment. The contractor shall obtain approval of equipment designs, operating instructions, and calibration instructions from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-NR4.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 1195-A096

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:42Z
Check the source to verify that this is the current version before use.