21 May 1973

# MILITARY SPECIFICATION

## METER, MODULATION ME-57( )/U

This amendment forms a part of Military Specification MIL-M-55638(EL) dated 20 November 1970 and is approved for use by all Departments and agencies of Department of Defense.

Page 1

2.1 Add: NN-P-71 Pallets, Material Handling, Wood, Double Faced, Stringer Construction

Page 2

2.1 Add: MIL-B-43014 Boxes, Water Resistant Paperboard; Folding, Set-Up and Metal-Stayed

Page 19

5. PREPARATION FOR DELIVERY delete and substitute:

5. PREPARATION FOR DELIVERY.

5.1 Preservation and packaging. Preservation and packaging shall be level A or C, as specified (see 6.2(b)).

5.1.1 Level A.

5.1.1.1 Cleaning. Meter, Modulation ME-57( )/U shall be cleaned in accordance with process C-1 of MIL-P-116.

5.1.1.2 Drying. Meter, Modulation ME-57( )/U shall be dried in accordance with the applicable procedure of MIL-P-116.

5.1.1.3 Preservation application. None required.

FSC 6625



Source: https://assist.dla.mil -- Downloaded: 202610-22T23:46Z
Check the source to verify that this is the current version before use.

5.1.1.4 Unit packaging. Unit packaging shall be in accordance with the methods prescribed in MIL-P-116 as specified herein.

5.1.1.4.1 Technical literature. Each technical literature shall be packaged method 1C-1.

5.1.1.4.2 Electron tubes. All tubes not securely clamped in place shall be removed and, with spare tubes, packaged individually in accordance with MIL-E-75.

Page 20

5.1.1.4.3 Spare fuses. Spare fuses shall be packaged method III as follows: Cushion the fuses by wrapping together in paperboard conforming to PPP-P-291, type 1 and secure the wrap with gummed paper tape conforming to PPP-T-45, type III, grade A.

5.1.1.4.4 Spare lamps. Each spare lamp shall be individually packaged method III as follows: Cushion each lamp by wrapping in paperboard conforming to PPP-P-291, type 1, secure wrap with gummed paper tape conforming to PPP-T-45, grade A, type III.

5.1.1.4.5 Consolidated package. Consolidate the items, packaged as specified in 5.1.1.4.2 thru 5.1.1.4.4 within a close-fitting box conforming to MIL-B-43014, Form 1, Style II, fill all voids with paperboard conforming to PPP-P-291, type 1, to prevent movement. Closure shall be in accordance with appendix of the box specification.

5.1.1.4.6 Meter, Modulation ME-57( )/U. Each Meter, Modulation shall be individually packaged method III as follows: Place the unit within the transit case. Close the cover and secure with fasteners provided. Cushion the transit case on all surfaces with cells or pads or both fabricated of fiberboard conforming to PPP-F-320, type CF, class weather-resistance, variety SW, grade W5c, designed to protect all projections and absorb the shock of impact in handling and transit. Place the cushioned unit and spare parts, packaged as specified in 5.1.1.4.2 thru 5.1.1.4.5, within a close-fitting fiberboard box conforming to PPP-B-636, W5c. Place the technical literature, packaged as specified in 5.1.1.4.1, on top of the contents, directly under the lid of the box. Close the box in accordance with the appendix of the box specification.

5.1.2 Level C. Meter, Modulation shall be preserved and packaged in a manner that will afford adequate protection against physical and environmental damage during shipment, handling and limited intransit storage.

5.2 Packing. Packing shall be level A, B or C, as specified. Shipping containers for all levels shall be capable of stacking and supporting superimposed loads during shipment and storage without damaging the container(s) or its contents. (see 6.2(b)).

5.2.1 Level A.



Source: https://assist.dla.mil -- Downloaded: 202640-22T23:46Z
Check the source to verify that this is the current version before use.

5.2.1.1 Palletized load. A quantity of Meter, Modulation, packaged as specified in 5.1, shall be placed on a pallet, load type 1, conforming to MIL-STD-147 except that the pallet shall be softwood conforming to NN-P-71, type IV, size 2. A fiberboard cap shall be employed over the load having two sides extending down the stacked load at least 12 inches to accommodate marking requirements. The cap shall be fabricated of fiberboard conforming to PPP-F-320, class weather-resistant, W5s or V3c. The load shall be "bonded" to the pallet by strapping.

5.2.1.2 Less than palletized load. When quantities per destination are less than a pallet load, the item, packaged as specified in 5.1, shall be waterproofed, with tape conforming to PPP-T-76, in accordance with the taping requirements of the appendix of the box specification. A quantity of the waterproofed containers shall be packed within a close-fitting box conforming to PPP-B-601, overseas type; PPP-B-621, style 4, class 2; or PPP-B-585, style 2 or 3, class 3. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, 3 x 4 inch skids, laid flat, shall be applied in accordance with the requirements of the container specification, or if not specified in the specification, in a manner which will adequately support the item and facilitate the use of material handling equipment. Closure and strapping shall be in accordance with the applicable container specification or appendix thereto except that metal strapping shall conform to QQ-S-781, type I, class B.

5.2.2 Level B.

5.2.2.1 Palletized load. A quantity of Meter, Modulation, packaged as specified in 5.1, shall be palletized as specified in 5.2.1.1.

5.2.2.2 Less than palletized load. When quantities per destination are less than a pallet load, a quantity of Meter, Modulation packaged as specified in 5.1, shall be packed within a close-fitting fiberboard box conforming to PPP-B-640, class 2, style E, or PPP-B-636, type CF, class weather-resistant, variety DW. The gross weight of boxes conforming to PPP-B-640, shall not exceed 250 pounds. When the gross weight exceeds 200 pounds, or the container length and width is 48 x 24 inches or more and the weight exceeds 100 pounds, containers will be palle t-mounted on pallets conforming to NN-P-71, type IV. Closure shall be in accordance with the appendix of the applicable box specification. Reinforcing shall be by pressure-sensitive filament tape banding or nonmetallic strapping conforming to PPP-T-97, type IV and PPP-S-760, type II, respectively; selection of the material and application shall be in accordance with the appendix of the applicable box specification.

5.2.3 Level C.



Source: https://assist.dla.mil -- Downloaded: 202610-22T23:46Z
Check the source to verify that this is the current version before use.

(page 21 contd)

5.2.3.1 Palletized load. A quantity of Meter, Modulation packaged as specified in 5.1, shall be palletized as specified in 5.2.1.1 except that fiberboard caps shall be class domestic.

5.2.3.2 Less than palletized load. When quantities per destination are less than a pallet load, a quantity of Meter, Modulation packaged as specified in 5.1 shall be packed as specified in 5.2.2.2 except that the fiberboard boxes shall conform to PPP-B-640 and PPP-B-636, class 1 and class domestic, respectively and reinforcing shall not be required for boxes conforming to PPP-B-636.

Page 22

5.3 Marking. In addition to any special marking required by the contract or order, interior packages and exterior shipping containers shall be marked in accordance with MIL-STD-129.

Custodian:
Army - EL

Preparing activity
Army - EL

Project Number 6625-A590



Source: https://assist.dla.mil -- Downloaded: 202610-22T23:46Z
Check the source to verify that this is the current version before use.