MIL-R-50776(MU)
5 April 1972
SUPERSEDING
FA-PD-MI-2419, Rev. 1
16 March 1962

MILITARY SPECIFICATION

REMOVER, AIRCRAFT CANOPY: M8A2 ASSEMBLY

1. SCOPE

1.1 This specification covers Remover, Aircraft Canopy: M8A2 Assembly, loaded with Cartridge, Aircraft Canopy, Remover, M150, for use in conjunction with other propellant actuated devices in aircrew emergency escape system.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

Military
MIL-A-2550 - Ammunition and Special Weapons General Specification for

STANDARDS

Military
MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-109 - Quality Assurance Terms and Definitions

DRAWINGS

Munitions Command
F10522144 - Remover, Aircraft Canopy, M8A2 Assembly
C8837890 - Carton, Packing, Ammunition for Remover, Aircraft Canopy, M8A1 with Cartridge M150

FSC 1377

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

DRAWINGS (Cont'd)

| | |
|---|---|
| C9230161 | - Box, Packing, Ammunition for (1) Remover, Aircraft Canopy, M8A1 with Cartridge M150 |
| IEL-10522144 | - Inspection Equipment List for Remover, Aircraft Canopy, M8A2 Assembly |

(Copies of specifications, standards and drawings required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 General.-Materials, parts and assemblies shall comply with the requirements specified on the applicable drawings and referenced specifications and the following:

3.2 Torque.

3.2.1 Assembly.-An assembly torque of 500 plus 50 inch pounds (running plus bottoming torques) shall be applied between the head and adapter housing after insertion of cartridge.

3.2.2 Breakaway.-The head and adapter housing of the assembled remover shall withstand a breakaway torque application of 400 inch pounds without loosening or deformation.

3.3 Functional.

3.3.1 Ballistics.-Removers loaded with accepted M150 Cartridge shall propel a 350 pound mass vertically and shall comply with the requirements listed in Table I.

TABLE I

| Temperature | *Velocity, min. (fps) | Peak Thrust, Pounds Min. | Peak Thrust, Pounds Max. | Ignition Delay Max. (see 6.3) |
|---|---|---|---|---|
| -65° to -70°F | 10.7 | 3500 | 7000 | 25 milliseconds |
| 65° to 75°F | 10.7 | 3500 | 7000 | 25 milliseconds |
| 200° to 205°F | 10.7 | 3500 | 9000 | 25 milliseconds |

* Velocity taken at tube separation.



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

3.3.2 Locked shut.-Removers loaded with accepted M150 Cartridges and temperature conditioned at minus 65 degrees F to minus 70 degrees F, and plus 200 degrees F to plus 205 degrees F, shall withstand the generated gas pressures with no evidence of leakage or mechanical failure (See 6.2) of exterior components when fired "locked shut" (See 6.4). The peak thrust shall not exceed 10,200 pounds over the temperature range.

3.3.3 The removers shall not fail to fire.

3.3.4 The removers shall function without mechanical failure (see 6.2).

3.4 Workmanship.-The requirements for workmanship are as specified on the applicable drawing, referenced specification and the following:

3.4.1 Metal defects.-All components shall be free from cracks, splits, cold shuts, inclusions, porosity or any similar defect.

3.4.2 Burr.-No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.4.3 Foreign matter.-No part or assembly shall contain chips, dirt, grease, rust, corrosion or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Quality assurance terms and definitions.-Reference shall be made to MIL-STD-109 to define quality assurance terms used.

4.1.2 Inspection.-Inspection shall be in accordance with MIL-A-2550 except as specified herein.

4.2 Inspection provisions.

4.2.1 Lot.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.

4.2.1.1 Submittal of product.-The product shall be submitted in accordance with MIL-STD-105.

4.2.1.2 Size of lot.-A lot shall consist of an identifiable group of assembled units containing metal parts assemblies produced by a homogeneous process and loaded with a single lot of accepted cartridges.

4.2.2 Examination.-One hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects, using the sampling plan and associated criteria in Table II. The total number of allowable defects per class for either the major or minor classification shall not exceed the acceptance number of Table II. All non-conforming material shall be rejected. Four power(4X) magnification may be used in performing visual examination for such defects as burr and foreign matter.

TABLE II

| Lot Size | Sample Size | Major | | Minor | |
|---|---|---|---|---|---|
| | | Accept | Reject | Accept | Reject |
| 1 - 300 | 100% Examination | - | - | - | - |
| 301 - 800 | 50 | 0 | 1 | 1 | 2 |
| 801 -1800 | 90 | 1 | 2 | 2 | 3 |
| 1801 -10000 | 200 | 2 | 3 | 3 | 4 |

4.2.2.1 Cartridge, Aircraft Canopy, M150, Drawing D10521960 covering a detail of Drawing F10522144.

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| 1. Mixed cartridges | Visual |
| 2. Metal defective | Visual |
| 3. Sealing disc, missing, damaged or improperly secured | Visual |
| 4. Marking, missing, incorrect or illegible | Visual |
| MAJOR | |
| 101. Foreign matter | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:37Z
Check the source to verify that this is the current version before use.

4.2.2.1 (Cont'd)

| Defect | Method of Inspection |
|---|---|
| **MINOR** | |
| 201. Case scratch, wrinkled, bulged or dented | Visual |
| 202. Varnish, missing or inadequate | Visual |

4.2.2.2 Assembly Dwg. F10522144 (before assembly of head).

| | |
|---|---|
| **CRITICAL** | |
| 1. Gas port hole obstructed | Visual |
| 2. Cartridge missing | Visual |
| 3. Firing pin missing | Visual |
| **MAJOR** | |
| 101. Thread damaged | Visual |
| 102. Burr | Visual |
| 103. Foreign matter | Visual |
| **MINOR** | |
| None defined | |

4.2.2.3 Assembly, Drawing F10522144.

| | |
|---|---|
| **CRITICAL** | |
| 1. Mixed removers | Visual |
| 2. Marking, missing, incorrect or illegible | Visual |
| **MAJOR** | |
| 101. Protective finish, inadequate or defective | Visual |
| 102. Burr | Visual |
| 103. Foreign matter | Visual |
| **MINOR** | |
| 201. Shipping plug missing | Visual |
| 202. Location of labels | Visual |



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

4.2.2.4 Packing in Inner Box, Drawing C8837890.

| Defect | Method of Inspection |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| None defined | |
| MINOR | |
| 201. Contents loose | Manual |
| 202. Top of box, loose | Manual |
| 203. Strapping, missing, loose or improperly assembled | Manual & Visual |
| 204. Supports or fillers, missing from box | Visual |
| 205. Box damaged | Visual |
| 206. Seal, missing or improperly positioned | Visual |
| 207. Motor wire loose | Visual |
| 208. Marking, missing, incorrect or illegible | Visual |

4.2.2.5 Packing in Outer Box, Drawing C9230161.

| | |
|---|---|
| CRITICAL | |
| None defined | |
| MAJOR | |
| None defined | |
| MINOR | |
| 201. Contents loose | Manual |
| 202. Liner, fillers, cushions or spacers, missing | Visual |
| 203. Strapping, missing, loose or improperly assembled | Visual |
| 204. Hardware, missing, loose or improperly engaged | Visual |
| 205. Box damaged | Visual |
| 206. Contents of box exposed | Visual |
| 207. Car seal, missing or improperly sealed | Visual |
| 208. Marking, missing, incorrect or illegible | Visual |



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

4.2.3 Inspection testing.-The following tests shall be performed in accordance with 4.3.

4.2.3.1 Breakaway torque.-Each head and adapter housing of the assembled remover shall be subjected to the breakaway torque application. Failure of any remover to comply with the requirement of 3.2.2 shall be cause for rejection of the remover.

4.2.3.2 Functional tests.-The following tests shall be performed by the Government.

4.2.3.2.1 Ballistics.-Eighteen units shall be tested as specified in 4.3.2 to determine compliance with the requirements of 3.3.1, 3.3.3, 3.3.4 and Table I. The units shall be temperature conditioned as provided in Table III and 4.3.2.3. Failure of any unit to comply with the requirements shall be cause for rejection of the lot.

TABLE III

| Temperature | Sample Size |
|---|---|
| -65° to -70°F | 6 |
| 65° to 75°F | 6 |
| 200° to 205°F | 6 |

4.2.3.2.2 Locked shut.-One remover temperature conditioned at minus 65 degrees F. to minus 70 degrees F. and 2 removers at 200 degrees F. to 205 degrees F. shall be fired "locked shut" (See 6.4). The units shall be temperature conditioned as specified herein and 4.3.2.3. Failure of any unit to comply with 3.3.2 and 3.3.3 shall be cause for rejection of the lot.

4.2.4 Inspection equipment.-The examination and tests shall be made using equipment listed on IEL-10522144.

4.3 Test methods and procedures.

4.3.1 Breakaway torque.-A torque wrench set at the torque requirement specified in 3.2.2 for the head and adapter housing shall be used to determine the adequacy of the joint. The assembly shall be secured in a fixture and the breakaway torque applied to each head and adapter housing.

4.3.2 Functional tests.



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

4.3.2.1 Ballistics.-The remover samples shall be rigidly supported in the fixture by the mounting points. The remover tube shall be secured to a carriage and allowed to move freely while propelling the weight specified in 3.3.1 when test fired. The remover shall be initiated by means of an M3A1 Initiator or simulated pressure with sufficient force to activate the firing pin. The remover shall be tested within 10 minutes after removal from the conditioning chamber. Samples shall be reconditioned at the original temperature if this time is exceeded.

4.3.2.2 Locked shut.-The remover samples shall be rigidly supported in a fixture and initiated by means of an M3A1 or simulated pressure with sufficient force to activate the firing pin. The remover shall be tested within 10 minutes after removal from the conditioning chamber. Samples shall be reconditioned at the original temperature if this time is exceeded.

4.3.2.3 Temperature conditioning.-Prior to conducting the ballistic test and locked shut test specified in 4.3.2.1 and 4.3.2.2 respectively, the assembly samples shall be subjected to the temperature conditions specified in Table III and 4.2.3.2.2. A simulated assembly loaded with a dummy cartridge containing a temperature sensitive element shall be placed in the temperature conditioning chamber at the same time as the remover samples. The conditioning time shall be a minimum of one hour longer than the time necessary to bring the element contained in the dummy cartridge to the required temperature. Upon completion of the required temperature conditioning, each remover shall be tested as specified herein.

## 5. PREPARATION FOR DELIVERY

5.1 Packing and marking.-(Level A) - Packing and marking shall be in accordance with Drawings C8837890 and C9230161. Marking shall be changed to specify Remover, Aircraft Canopy, M8A2.

## 6. NOTES

6.1 Ordering data.-Procurement documents should specify the title, number and date of this specification.

6.2 A "mechanical failure" is defined as any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3 "Ignition Delay" is defined as the time that elapses between the firing of the cartridge primer and the beginning of the continuous rise in the thrust time record.



Source: https://assist.dla.mil -- Downloaded: 202640-22T20:37Z
Check the source to verify that this is the currentversion before use.

6.4 "Locked shut" is defined as a condition in which the inside tube is restrained from moving upon firing the remover.

6.5 Supersession data.-This specification includes the requirements of Purchase Description FA-PD-MI-2419 dated 16 March 1962.

Custodian:

Army - MU

Preparing activity:

Army - MU(FA)

Project No. 1377-A500



Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

FOLD

POSTAGE AND FEES PAID
Department of the Army

OFFICIAL BUSINESS

Commanding Officer
Frankford Arsenal
ATTN: SMUFA-J4000
Philadelphia, Pa. 19137

FOLD

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 22-R255

INSTRUCTIONS: This sheet is to be filled out by personnel, either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity. Comments and suggestions submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or serve to amend contractual requirements.

SPECIFICATION

ORGANIZATION

CITY AND STATE

CONTRACT NUMBER

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

| | YES | | | NO *(If "yes", in what way?)*

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

SUBMITTED BY *(Printed or typed name and activity - Optional)*

DATE

DD FORM 1 JAN 66 1426

REPLACES EDITION OF 1 OCT 64 WHICH MAY BE USED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:37Z
Check the source to verify that this is the current version before use.