MILITARY SPECIFICATION

CARTRIDGE, IMPULSE, MARK 67 MOD 0

This amendment forms a part of Military Specification MIL-C-81563A(AS), dated 27 August 1970.

PAGE 4

Add new paragraph as follows:

"3.3.3 Leakage. Cartridge leaking rate shall not exceed 10^{-5} cubic centimeters of air per second when tested in accordance with 4.7.6."

PAGE 8

Add new paragraph as follows:

"4.7.6 Leakage. Each cartridge in the preproduction sample and each cartridge of the production lot ballistic and cartridge integrity samples shall be leak tested in a dry gas leak tester. Cartridges which exhibit a leak rate in excess of 10^{-5} cubic centimeters per second air at a pressure differential of 1.0 ± 0.1 atmosphere shall be considered defective. Cartridges of the preproduction sample which exhibit a leakage defect shall be rejected. If the number of cartridges of the ballistic sample or cartridge integrity sample exhibiting leak defects exceeds an AQL of 2.5 (percent defective) from table II of MIL-STD-105, then a 100 percent leak test of the lot being tested shall be required at no additional expense to the government. Cartridges which exhibit a leak rate in excess of that specified above shall be rejected. (See 6.6)".

PAGE 12

Delete 6.5 and 6.5.1 and substitute "6.5 Explosive safety precautions. Safety precautions for explosive-loaded items are contained in DOD 4145.26M, 'DOD Contractors' Safety Manual for Ammunition, Explosives and Related Dangerous Material'."

Add new paragraph as follows:

"6.6 Advisory leak test. Indian Head leak tests cartridges in accordance with 'Cartridge Leak Test Procedures at the Naval Ordnance Station, Indian Head, Md.'."

Custodian:
Navy-AS

Preparing activity:
Navy-AS
(Project 1377-N628)

☆U.S. GOVERNMENT PRINTING OFFICE: 1978–703-122/662

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.