INCH-POUND

MIL-DTL-81577B(OS)
20 April 2000
SUPERSEDING
MIL-I-81577A(AS)
24 September 1974

MILITARY SPECIFICATION

IGNITION ELEMENT, ELECTRIC, MARK 17 MOD 0

This specification is approved for use by the Naval Sea Systems Command, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements documents specified in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications and standards. The following specifications and standards handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-I-23659 Initiators, Electric, Design and Evaluation of

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Team (Code 840M), 101 Strauss Avenue, Indian Head, MD 20640-5035, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

STANDARDS

DEPARTMENT OF DEFENSE

DOD-STD-2101	Classifications of Characteristics

(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

Naval Air Systems Command (CAGE Code 30003)

DL 613468	Ignition Element, Electric, Mark 17 MOD 0
2302224	Ignition Element, Electric, Mark 17 MOD 0, Assembly
2519610	Primer Assembly

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Documentation Branch (Code 8410), Indian Head, MD 20640-5035.)

PUBLICATIONS

Naval Sea Systems Command (CAGE Code 53711)

OP 5	Ammunition Ashore (This publication is not furnished to bidders and contractors by the procuring activity. Contractors should contact the program sponsor or contracting officer for use of the publication.)

(Copies may be procured from Defense Distribution Depot Susquehanna Pennsylvania, 05 E Street, Mechanicsburg, PA 17055-5003. Requisitions should be submitted in accordance with NAVSUP Publication 600.)

2.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

AMERICAN SOCIETY FOR QUALITY CONTROL

ANSI/ASQC Z1.4	Sampling Procedures and Tables for Inspection by Attributes (DoD adopted)
ANSI/ASQC Z1.9	Sampling Procedures and Tables for Inspection by Variables for Percent Nonconforming (DoD adopted)

(DoD activities may obtain copies from the Standardization Documents Oder Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094. The private sector and Government agencies may purchase from the American Society for Quality Control, PO Box 3005, 611 E. Wisconsin Ave., Milwaukee, WI 53201-4606.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2) by the procuring activity, a sample of 137 ignition elements shall be subjected to first article inspection (see 6.3) in accordance with 4.3.2. The sample shall be manufactured using the same methods and procedures proposed for the production lot and is for the purpose of determining that the contractor, prior to starting production, is capable of producing items which comply with the technical requirements of the contract.

3.2 Conformance to documents. The Ignition Element, Electric, Mark 17 Mod 0, covered by this specification shall be manufactured in accordance with the drawings listed on DL 613468.

3.3 Materials. All materials used in the manufacture of the ignition elements shall conform strictly with the specifications referred to on the respective drawings, unless specific approval in writing covering a departure therefrom has been obtained from the Navy cognizant field activity for cartridges prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal.

3.4 Primary components. For the purposes of this specification the ignition compositions, primer composition, and main propellant charge are defined as primary components.(See 4.3.3.).

3.5 Cleanliness and condition of parts. All parts shall be free of chips, dirt, grease, rust and all other foreign materials. There shall be no burrs nor other imperfections of manufacture which would harmfully affect either the assembly or the functioning of the product. The cleaning methods which are used shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents which are used.

3.6 Explosive components volatiles. The ignition compositions and the primer compositions shall have a maximum moisture content of 0.5 percent at the time of loading, as determined in accordance with

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

4.7.1. After consolidation of the primer composition, the subassembly shall be dried in accordance with Drawing 2302224.

3.7 Insulation resistance. The insulation resistance between shorted electrodes (connector pins) and receptacle of each completely assembled ignition element shall be a minimum of 20 megohms when tested in accordance with 4.7.3 at a relative humidity of 80 percent or less.

3.8 Ignition and primer compositions, compounding and loading. The ignition compositions and the primer composition shall be compounded in accordance with the applicable drawings, and shall be loaded in accordance with Drawings 2519610 and 2302224, respectively.

3.9 Propellant charges.

3.9.1 Quantity. All propellant charges shall be as specified on Drawing 2302224. Charges shall be determined by weight rather than by volume measurements.

3.9.2 Smokeless powder, handling and loading. Do not subject the smokeless powder to unnecessary handling or exposure to the atmosphere. The handling and loading of smokeless powder exposed to the atmosphere shall be performed only under conditions that do not permit the relative humidity to exceed 75 percent.

3.9.2.1 Smokeless powder, condition. The smokeless powder utilized shall exhibit no evidence of decomposition. (See 4.7.2.)

3.10 Ignition element inspection.

3.10.1 Visual inspection. Ignition elements shall be free of the following visible defects: chips, burrs rough edges, incomplete threads, improper crimp, perforated closure disc, or any other imperfections which could, harmfully affect either assembly or functioning. (See 4.7.6.)

3.10.2 Bridge circuit resistance. The resistance of the bridge circuit in each completely assembled ignition element, when measured electrically as specified in 4.7.5, shall be not less than 1.0 ohm nor more than 1.2 ohms.

3.10.3 Leakage. Ignition element leakage rate shall not exceed 10^{-5} cc of air or gas per second, when tested in accordance with 4.7.7.

3.10.4 X-ray. Ignition elements shall be free, of the following defects when examined by X-ray in accordance with 4.7.4: improper assembly of components, charges or inert components missing, or any other imperfections which could adversely affect performance.

3.11 Tests.

3.11.1 Electric sensitivity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

3.11.1.1 No-fire. The ignition element shall not fire when an electric current of 1.0 +0.10, −0.00 ampere (A) is applied in accordance with 4.7.8.1.

3.11.1.2 All-fire. The ignition element shall fire within 0.025 second when an electric current of 4.0 +0.10, −0.00 A is applied in accordance with 4.7.8.2.

3.11.2 Ballistic requirements. Ignition elements from each production lot, selected in accordance with 4.7.9, shall meet the requirements listed below when subjected to the tests prescribed in 4.7.9.

3.11.2.1 Chamber pressure. The upper (U) and lower (L) limits of maximum chamber pressure, in pounds per square inch (psi), shall be 1800 psi and 1200 psi, respectively.

3.11.2.2 Response time. The time from application of firing current to start of pressure rise shall not exceed 0.025 second. The time from start of pressure rise to maximum pressure shall not exceed 0.015 second.

3.11.2.3 Misfire. There shall be no misfires. (See 4.7.9.2.3.)

3.12 Workmanship. Ignition elements shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention should be directed to dimensions, finishes and coatings.

4. VERIFICATION

4.1 Classification of inspections.

a. First article inspection (see 4.3.2).

b. Conformance inspection (see 4.6).

4.2 Sampling. Unless otherwise specified, and when applicable, the, sampling plans and procedures used in the determination of the acceptability of products submitted by a supplier shall be in accordance with the provisions of ANSI/ASQC Z1.4 or Z1.9, whichever applies.

4.3 Lots.

4.3.1 Inspection lots. Inspection lot definition, formation, and size shall be in accordance with ANSI/ASQC Z1.4 or Z1.9, whichever applies.

4.3.2 First article. When specified by the procuring activity and before entering into quantity production, an acceptable first article sample of 137 ignition elements shall be prepared. Of these ignition elements, 127 shall be expended in the tests listed below and ten shall be retained for investigative purposes. A first article sample acceptable for environmental and functional testing shall be defined as a sample which has met the requirements of 3.4 through 3.10.4 of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

4.3.2.1 First article tests. First article sample acceptance shall consist of the following tests, which, except as otherwise specified herein, shall be conducted in accordance with MIL-I-23659:

a. 40-foot drop (6) (nonfiring test); temperature and humidity cycling (THC) (36); vibration (12); high temperature (12); low temperature (12); untreated (12). The numbers in parentheses denote the, allocation of ignition elements for the tests.

b. After exposure to the specified environmental treatment, the units from THC and the vibration tests, together with the 12 untreated units, shall be conditioned for a minimum of 6 hours at 70° ±5°F and fired in the test set as specified in 4.7.9.1. All of these units shall fire and produce results within the limits set forth in 3.11.2.1 and 3.11.2.2.

c. The units allocated for the high temperature and low temperature tests shall be conditioned at 225° ±5°F and −80° ±5°F, respectively, for not less than 6 nor more than 24 hours and fired in the test set as specified in 4.7.9.1. All of these, units shall fire and produce results within the limits set forth in 3.11.2.1 and 3.11.2.2 except that the upper and lower limits of maximum pressure for these units shall be 1900 psi and 1000 psi, respectively.

d. In addition, 25 ignition elements shall be subjected to the no-fire and all-fire tests. None of these 25 units shall fire, when temperature conditioned and tested in accordance with 4.7.8.1, and all of these same 25 units shall fire within 0.025 second when temperature conditioned and tested in accordance with 4.7.8.2.

e. Additionally, 12 ignition elements shall be subjected to an electrostatic sensitivity test. Each of these 12 units shall withstand the stimulus from an electrically charged capacitor without firing when tested as specified in the applicable paragraph under the electrical tests of MIL-I-23659.

All of the specified firings and tests shall be, conducted within 3 minutes after removal of the units from the specified temperature conditioning. The failure of any ignition element to meet the requirements as stated above shall cause rejection of the first article sample.

4.3.3 Production lot. The suggested ignition element production lot size is 1301 minimum and 3200 maximum. Only primary components from a single lot or batch shall be used in a production lot of ignition elements; however, one primary component production lot may be used in more than one ignition element production lot.

4.4 Gages. The contractor shall provide gages as necessary to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings.

4.5 Classification of characteristics. The characteristics verified by the tests and examinations herein are classified as critical, major or minor in accordance with DOD-STD-2101. Tests and examinations that verify critical characteristics are identified by the symbol (C) and major characteristics by the symbol (M). The number following the classification symbol indicates the serial number of test or examination. Tests and examinations which are not annotated with a classification code are classified minor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

4.6 Quality conformance inspection. Quality conformance inspection shall consist of verification of the characteristics classified on the drawings of DL 613468 and verification of the following requirements and tests:

Classified Characteristics List

Item	Nature of Requirement Verification	Applicable Paragraphs	Classification (DOD-STD-2101)
Primary Component	Single lot or batch	3.4, 4.3.3	(M101)
Ignition and Primer Compositions	Moisture content	3.6, 4.7.1	(M102)
Ignition and Primer Compositions (loaded)	Drying	3.6	(M103)
Ignition Element	Insulation resistance	3.7, 4.7.3	(M104)
Ignition and Primer Compositions	Compounding and loading	3.8	(M105)
Propellant charge	Type and weight	3.9.1	(M106)
Smokeless Powder	Condition	3.9.2.1, 4.7.2	(M107)
Ignition Element	Visual inspection	3.10.1, 4.7.6	(M108)
Ignition Element	Bridge circuit resistance	3.10.2, 4.7.5	(C1)
Ignition Element	Leakage	3.10.3, 4.7.7	(C2)
Ignition Element	X-ray	3.10.4, 4.7.4	(C3)
Ignition Element	Electric sensitivity	3,11.1, 4.7.8	(C4)
Ignition Element	Ballistic requirements	3.11.2, 4.7.9	(M109)

4.7 Tests.

4.7.1 Determining moisture content. Transfer approximately 2 grams of the ignition composition to be used in loading to a tarred weighing dish, weigh to the nearest 0.1 milligram, calculate the weight of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

the sample, transfer weighing dish and sample to a vacuum drying oven, dry at 160° ±5°F and 28 ±2 inches of mercury vacuum until constant weight is obtained. The loss of weight represents the percentage of moisture in the original sample. Use the same procedure for the primer composition.

4.7.2 Smokeless powder, condition. Smokeless powder shall be inspected in accordance with the applicable paragraphs of OP 5. Evidence of decomposition shall be cause for rejection.

4.7.3 Insulation resistance. The insulation resistance of each completely assembled ignition element shall be checked with an applied voltage, of 350 ±10 volts D.C. This measurement shall be made between shorted electrodes (connector pins) and receptacle. Units which fail to meet the requirements of 3.7 shall be rejected.

4.7.4 X-ray of ignition element. Examine all ignition elements by X-ray and reject those, having any of the defects of 3.10.4. Ignition elements shall be mounted in suitable racks or frames and laid on their side so that the most revealing exposure can be obtained. Pressure-sensitive tape may be used as an aid in positioning the ignition elements.

4.7.5 Bridge circuit resistance. Conformance, with the bridge circuit resistance of 3.10.2 shall be ascertained by means of a test circuit which limits the bridge current to 25 milliamperes, maximum. The test circuit shall be connected to the ignition element through a number PTO6E-8-2S Bendix connector, or equivalent. A new connector shall be used after a maximum of 500 connections. A safety chamber with an interlock switch shall be used to protect the operator during the application of current. A suitable bridge which is known to be accurate within 1 percent in the range of resistance specified shall be used to determine whether or not the requirement is being met. Units which fail to meet the requirements of 3.10.2 or fail to assemble completely, by hand, with the specified connector, with ignition element lugs locked in connector detents, shall be rejected. The results of bridge circuit resistance measurements shall not be affected by resistance of the test circuit or connector.

4.7.6 Visual inspection. Examine all ignition elements visually and reject those having any of the defects of 3.10.1.

4.7.7 Leakage. Each ignition element in the first article sample or production lot sample shall be leak tested in a dry gas or dry air leak tester. Ignition elements which exhibit a leak rate in excess of 10^{-5} cc/sec gas or air at a pressure differential of 1.0 ±0.1 atmosphere shall be considered defective. Ignition elements of the first article sample which exhibit a leakage defect shall be rejected. If one or more ignition elements of the production lot sample exhibit a leakage defect, then a 100 percent leak test of the lot being tested shall be required at no additional expense to the government. Ignition elements which exhibit a leak rate in excess of that specified above shall be rejected.

4.7.8 Electric sensitivity tests.

4.7.8.1 No-fire test. The number of ignition elements selected from each production lot for the no-fire test shall be in accordance with the requirements of table I of ANSI/ASQC Z1.4, General Inspection Level I. Each ignition element shall be conditioned at 70° ±5° F for a minimum of 6 hours and then tested. During this test insure that the ignition element is sufficiently shielded to prevent personnel

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

injury or material damage in the event an ignition element fires. The firing circuit shall contain a resistor in series sufficient to regulate the current to 1.0 +0.10, −0.00 ampere measured to within an accuracy of 1 percent. This current shall be applied to the ignition element for a period of not less than 5 nor more than 5.1 minutes. An ignition element which fires shall be considered defective and shall cause rejection of the lot represented. If the ignition elements pass this test they shall then be subjected to the test of 4.7.8.2.

4.7.8.2 All-fire test. The ignition elements shall be conditioned at 70° ±5° F for a minimum of 6 hours and then tested. During this test insure that the ignition element is sufficiently shielded to prevent personnel injury or material damage. The firing circuit shall contain a resistor in series sufficient to regulate the current to 4 +0.10, −0.00 amperes measured to within an accuracy of 1 percent. Any ignition element which tails to fire within 0.025 second after current application shall be considered defective and shall cause rejection of the lot represented. As a precaution against obtaining an apparent defective element due to high internal circuit resistance, it is recommended that the resistance of each element be measured prior to conducting the test.

4.7.9 Ballistic tests.

4.7.9.1 Number of ignition elements. The number of ignition elements selected from each production lot for the ballistic tests shall be in accordance with the requirements of table A-2 of ANSI/ASQC Z1.9, General Inspection Level II, but shall never be less than 15 (see 6.2 and 6.6). The ignition elements shall be conditioned for a minimum of 6 hours at 70° ±5°F and fired in a closed chamber having an internal volume, exclusive of ignition element volume, of ten cubic centimeters and adapted for measurement of time from application of current to start of pressure rise and maximum pressure. The ratio of length to diameter of the closed chamber shall be approximately 1:1. The firing current shall be 5 ±0.10 amperes. In addition to the sample of ignition elements for the above test, ten additional ignition elements shall be furnished from the production lot for investigative purposes.

4.7.9.2 Criteria of acceptability.

4.7.9.2.1 Chamber pressure. The chamber pressure shall meet the requirements of 3.11.2.1. Lot acceptability shall be determined in accordance with the applicable provisions of ANSI/ASQC Z1.9 (see 6.2 and 6.6).

4.7.9.2.2 Response time. The failure of any ignition element to meet the response time requirements of 3.11.2.2 shall cause rejection of the lot represented.

4.7.9.2.3 Misfire. The failure of any ignition element to fire shall result in rejection of the lot represented, unless such failure is plainly attributable to faulty test equipment or procedure.

4.8 Retest. There shall be no retests.

4.9 Test failure. If test failure is attributable to an assignable cause, excluding the test ignition element, original test results should be discarded and that part of the test reconducted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order, (See 6.2). When actual packaging of material is to be performed by DOD personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department of Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory)

6.1 Intended use. The Mark 17 Mod 0 ignition element is intended for use as (1) an igniter for power source cartridges, and (2) the power source for the operation of an aircraft store jettison mechanism. This ignition element is military unique and there is no equivalent commercial application for this design.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number and date of this specification.

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.2.1 and 2.2.2).

c. Whether first article inspection is required and, if so, specify the test activity.

d. Whether first article inspection is required and, if so, specify the test activity (see 3.1 and 4.3.2).

e. Production lot size and test activity (see 4.3.3).

f. Items of data required for each first article and production lot (see 6.7).

g. Selections for quality conformance inspection (see 4.7.9.1, 4.7.9.2 and 6.6).

h. Level of packaging and packing desired (see 5.1).

i. Safety requirements (see 6.4 and 6.5).

6.3 First article. When first article inspection is required, the contracting officer should provide specific guidance to offerors whether the item(s) should be a preproduction sample, a first article sample,

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

a first production item, a sample selected from the first production items, or a standard production item from the contractor's current inventory (see 3.1), and the number of items to be tested (see 4.2.2). The contracting officer should also include specific instructions in acquisition documents regarding arrangements for examinations, approval of first article test results, and disposition of first articles.

6.3.1 Bids. Invitations for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Ammunition and explosive safety.

6.4.1 Contractor's responsibility. The safety requirements of the "Contractor's Safety Manual for Ammunition, Explosives and Related Dangerous Material" (DOD 4145.26M) are applicable when this specification is used for acquisition.

6.4.2 Government activity's responsibility. The safety precaution requirements of "Ammunition and Explosives Ashore", OP5 are applicable when this specification is used as part of a description of work to be accomplished by a government activity.

6.5 Hazard notice. The ignition element described herein and certain of its components are flammable or explosive and present hazards in manufacturing, handling, storing and shipping. The contractor should recognize these properties and take appropriate measures to guard and protect against fire, explosion, adverse environment, corrosive atmosphere, rough handling and electrically induced incidents.

6.6 Quality conformance inspection criteria. The Acceptable quality level of 0.10 for each production lot and chamber pressure has been used successfully for quality conformance inspection of the ignition element lots (see 4.7.9.1 and 4.7.9.2). The contracting activity is cautioned that any deviation from this ANSI/ASQC Z1.9 selection should be warranted and verified statistically.

6.7 Consideration of data requirements. The following data requirements should be considered when this specification is applied on a contract. The applicable Data Item Descriptions (DIDs) should be reviewed in conjunction with the specific acquisition to ensure that only essential data are requested/provided and that the DIDs are tailored to reflect the requirements of the specific acquisition. To ensure correct contractual application of data requirements, a Contract Data Requirements List (DD Form 1423) must be prepared to obtain the data, except where DOD FAR Supplement 227.405-70 exempts the requirement for a DD Form 1423.

Reference paragraph	DID Number	DID Title
6.7.1.1	DI-NDTI-80809	Test/Inspection Reports
6.7.1.2	DI-MISC-80043	Ammunition Data Card

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

(The above DID's were cleared as of the date of this specification. The Current issue of DOD 5010.12-L, Acquisition Management Systems and Data Requirements Control List (AMSDL), must be researched to ensure that only current, cleared DID's are cited on the DD Form 1423.)

6.7.1 Data. For the information of Contractors and contracting officers, any of the data specified in (a) subparagraphs below, (b) applicable documents listed in section 2 of this specification or (c) referenced lower-tier documents need not be prepared for the Government and shall not be furnished to the Government unless specified in the contract or order.

6.7.1.1 Test report. The contract or order should specify that results of ballistic tests are to be forwarded to the Commander, Indian Head Division, Naval Surface Warfare Center, CAD/PAD Division (Code 5220), Indian Head, Maryland and the procuring activity.

6.7.1.2 Data cards. The contract or order should specify the format, quantity in destination of data cards.

6.8 Subject term (keyword) listing.

Explosive components
Ignition compositions
Primer composition
Smokeless powder condition

6.9 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

+ +

Custodian:
Navy – OS

Preparing activity
Navy – OS
(Project No. 1377-0114)

..

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	**1. DOCUMENT NUMBER** MIL-DTL-81577B	**2. DOCUMENT DATE (YYYYMMDD)** 20000420

3. DOCUMENT TITLE **IGNITION ELEMENT, ELECTRIC, MARK 17 MOD 0**

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include Zip Code)*	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON *(if applicable)*	**7.DATE SUBMITTED** (YYYYMMDD)

8. PREPARING ACTIVITY

a. NAME COMMANDER, INDIAN HEAD DIVISION NAVAL SURFACE WARFARE CENTER	b. TELEPHONE *Include Area Code)* (1) Commercial (2) AUTOVON
c. ADDRESS *(Include Zip Code)* STANDARDIZATION TEAM (CODE 840M) 101 STRAUSS AVENUE INDIAN HEAD, MD 20640-5035	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman road, Suite 2533 Ft. Belvoir, VA 22060-2533 Telephone (703) 767-6888 AUTOVON 427-6888

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T05:43Z
Check the source to verify that this is the current version before use.