INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

WRENCH, IMPACT, ELECTRIC

This interim amendment was developed by the Federal Supply Service, General Services Administration, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification W-W-650C, dated June 22, 1970.

PAGE 3

Paragraph 3.8.2: Delete and substitute:

"3.8.2 Impacting mechanism. The impacting mechanism and its related parts shall be an alloy steel of sufficient strength and hardness to withstand continuous use. The ability of the wrench to withstand the rigors of 4.5.5 shall define continuous use. The impacting mechanism shall deliver the rotary impact movement of force to the spindle. Impacts per second and ultimate torque after 5 minutes of impacting shall conform to table I for the size wrench specified."

PAGE 5

Add new paragraph as follows:

"3.8.4.3.1 Switch. Each wrench shall be provided with an AC/DC rated constant pressure switch, safely and conveniently located, that will interrupt input current when the pressure is released. Current rating shall not be less than the rated load current of the tool."

Paragraph 3.9: Delete and substitute:

"3.9 Performance. The wrenches shall conform to table I for the wrench size and capacity specified when tested in accordance with 4.5.4 and shall comply with the applicable tests for impact wrenches specified in UL 45."

PAGE 8

Add new paragraphs as follows:

"4.5.6 Mechanical abuse test. Each sample impact wrench shall be dropped three times from a height of 3 feet onto a hard wood surface. The manner of dropping shall be such that a different part of the impact wrench will strike the hard wood surface on each successive drop. After the drop test, the impact wrench shall be examined. Any evidence of cracking or breakage of the housing or handle shall be considered a failure.

6.5 The wrenches covered by this specification are in compliance with the requirements of the Occupational Safety and Health Administration (OSHA) standards published prior to the date of this document."

FSC 5130

GSA DC 74-10314

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:33Z
Check the source to verify that this is the current version before use.