MILITARY SPECIFICATION

TEST SET, RADIO AN/URM-101(*)

This amendment forms a part of Military Specification MIL-T-21050(Aer) of 15 August 1957, and has been approved by the Bureau of Aeronautics, Department of the Navy

Page 6 paragraph 3.5.1.2.2 Delete and substitute:

"3.5.1.2.2 Power Output - Under standard conditions and without 15 and 135 cycle amplitude modulation, the peak power output from the transmitter shall be -30 ±2 dbm on each of the two transmitted frequencies. The transmitter peak power output shall not vary more than an additional ±1 db over the range of the environmental conditions specified in Specification MIL-T-945: the POWER SET adjustment shall be used to keep the POWER OUTPUT meter indication on the reference mark indicating proper power output level."

Page 6 paragraph 3.5.1.2.3 Delete and substitute:

"3.5.1.2.3 Sensitivity - Under standard conditions, the receiver shall have a sensitivity of +3 ±2 dbm and shall not vary more than an additional ±4 db over the range of environmental conditions specified in Specification MIL-T-945.

Page 6 paragraph 3.5.1.2.5 Delete and substitute:

"3.5.1.2.5 Traffic Handling Capacity - The test set shall be capable of receiving standard TACAN interrogations from 4 aircraft simultaneously (each of which is at least 100 feet distant from the test set) and replying at least 70% of all interrogations from each aircraft for distance replies of 5 miles."

Page 7 paragraph 3.5.1.2.9 Delete "or 18" and substitute "and/or 118"
Delete "or 1205" and substitute "and 1205"

Page 7 paragraph 3.5.1.2.10.1 Delete and substitute:

"3.5.1.2.10.1 Pulse Groups

(1) Main Reference Pulse Group - The 15 cycle reference bearing signal, called the Main Reference Group, shall consist of a group of 12 ± 2 pairs of pulses. The spacing between pairs shall be 30 ± 1.0 microseconds. The repetition rate of the group shall be 15 cycles per second ± 2%.

(2) Auxiliary Reference Pulse Group - The 135 cycle reference bearing signal, called the Auxitiary Reference Group, shall consist of a group of 6 ± 1 pairs of pulses. The spacing between pairs shall be 24 ± 0.8 microseconds. The repetition rate shall be 135 cps and shall be precisely synchronized with the Main Reference Group; however, the Auxiliary Group which would otherwise coincide in time with the Main Reference Group, shall be removed so that only the Main Reference Group appears in this position in the final output signal."

Source: https://assist.dla.mil -- Downloaded: 202610-19T08:36Z
Check the source to verify that this is the current version before use.

Page 9 paragraph 3.5.1.3.1

(a) Delete: "Controls - The following controls, labelled as capitalized shall be provided on the front panel of the test set:" and substitute:

"Controls and Indicators - The following controls and indicators, labelled as capitalized shall be provided on the front panel of the test set: "

(b) Add subparagraph (4):

"(4) POWER OUTPUT - A meter mounted on the front panel which indicates the transmitter power output level. A distinctive reference mark shall be provided at a point corresponding to 60% of the full-scale reading. This mark shall be identified with the words "POWER SET"."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:36Z
Check the source to verify that this is the current version before use.