MILITARY SPECIFICATION

POWER CONTROL C: 10526593

This amendment forms a part of Military Specification MIL-P-60213(MU), dated 4 March 1965.

Paragraph 3.4.3.1, line 3: Delete "(Part No. 10525850)" and substitute "(Part Nos. 9144277 and 10525850)".

Paragraph 3.4.3.2, line 3: Delete "(Part No. 10525850)" and substitute "(Part Nos. 10525850 and 10525855)".

Paragraph 3.4.4.1: Delete first sentence in its entirety.

After paragraph 4.1.1: Add new paragraph 4.1.2.

"4.1.2 First article (initial production) submission.- When required by the contract, an initial production sample shall be submitted in accordance with the contract schedule to a Government approved facility for test and evaluation. The sample shall consist of three power controls. The sample shall be manufactured in the same manner, using the same materials, equipment, processes and procedures as used in regular production. All parts and materials, including packaging and packing, shall be the same as used for regular production and shall be obtained from the same source of supply. After inspection and provisional acceptance at source, the initial production sample shall be inspected at a Government approved facility for all requirements of the drawings, and specifications. The Government reserves the right to require new initial production samples until such time as an acceptable sample is submitted."

Paragraph 4.4.1.1, item 4, Description Column: Delete "reverse current" and substitute "current rating".

Paragraph 4.5.1.3.2: Delete in its entirety and substitute:

"4.5.1.3.2 Operating.- This test shall be conducted in accordance with the humidity test defined in Procedure III of MIL-F-13926, except that the humidity shall be maintained at 92 to 97 percent for the 24 hour period, and the test shall cease at the end of that period (Method 106 of MIL-STD-202 shall be excluded). Throughout the test period, the board shall be capable of performing the tests of 4.5.13 through 4.5.15 to determine compliance with 3.3.4.1. In order to demonstrate this

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.

capability, the tests of 4.5.13 and 4.5.15 shall be performed a minimum of once each 6 hours of the 24 hour period. The final test shall be conducted during the final portion of the 24 hour period."

Paragraph 4.5.1.4: Delete in its entirety and substitute:

"4.5.1.4 Salt spray.- This test shall be conducted in accordance with the salt spray test defined in Method 101, Condition B of MIL-STD-202 using a 5 percent salt solution. At the end of the exposure period, salt deposits shall be removed from the board by a gentle wash, not exceeding 30 minutes, in running water not warmer than 100°F, using a soft hair brush or plastic bristle brush. The board shall then be air dried in a controlled environment at 72°F ± 5°F and a relative humidity of 30 to 50 percent for a period of 24 hours. The board shall be inspected visually for any physical damage, then tested in accordance with 4.5.3 through 4.5.15, excluding 4.5.10, to determine compliance with 3.3.6."

Paragraph 4.5.1.5: Delete "3.4.3" and substitute "3.4.7"; delete "4.5.2.2 inclusive" and substitute "4.5.15 inclusive, excluding 4.5.10".

Paragraph 4.5.5.1, Table IX, Column C, line 14: Delete "plus 1.2" and substitute "plus 1.6"; Line 16: Delete "plus 0.6" and substitute "plus 0.8".

Table XII: Add to the columns:

"Column A	Column B	Column C
Pin	Pin	VDC
11B	28B	minus 1.29 ± 0.10

Paragraph 4.5.12(a), Table XXIII, Column C, line 2: Delete "plus 2.0 Vdc minimum" and substitute "plus 0.5 Vdc minimum".

Paragraph 4.5.12(a), Table XXV, Column C, line 2: Delete "plus 2.0 Vdc minimum" and substitute "plus 0.5 Vdc minimum".

Custodian:

Army - MU

Preparing activity:

Army - MU

Project No. 1220-A063

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:18Z
Check the source to verify that this is the current version before use.