INCH-POUND

MIL-T-60694B
30 April 1993
SUPERSEDING
MIL-T-60694A(MU)
14 January 1975

MILITARY SPECIFICATION

THRUSTER, CARTRIDGE ACTUATED, M15 REMANUFACTURED METAL PARTS ASSEMBLY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the requirements for the M15 Cartridge Actuated Thruster Remanufactured Metal Parts Assembly (see 6.1).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplements thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

MILITARY

MIL-A-2550	Ammunition, General Specification For

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures And Tables For Inspection By Attributes
MIL-STD-109	Quality Assurance Terms And Definitions
MIL-STD-413	Visual Inspection Guide for Elastomeric O-rings

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Standardization Branch (Code 8420), 101 Strauss Avenue, Indian Head, MD 20640-5000, by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by sending a letter.

AMSC N/A FSC 1377

DISTRIBUTION STATEMENT A: Approved for public release; distribution is unlimited.
(Unless otherwise indicated, copies of federal and military specifications and standards are available from Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

2.1.2 Other Government documents, drawings, and publications. The following Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation (see 6.2).

DRAWINGS

Naval Surface Warfare Center, Indian Head (CAGE Codes 19200 and 19203)

10520876	Thruster, Cartridge Actuated, M15, Metal Parts Assembly
8858440	Box, Packing, Ammunition, For Thruster, Cartridge Actuated, M15
8858441	Box, Fiberboard (Inner), Packing, Ammunition, For Thruster, Cartridge Actuated, M15
9217560	Box, Fiberboard (Outer), Alternative, Packing Ammunition, for Thruster, Cartridge Actuated, M15

U.S. Air Force

TPO 00-607-0314	Thruster, Cartridge Actuated, M15

(Application for copies should be addressed to: Commander, Indian Head Division, Naval Surface Warfare Center, Attn: Data Control Branch (Code 8410), Indian Head, MD 20640-5035.)

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Materials. All materials used in the manufacture of the thrusters shall conform to the specifications referred to on the respective drawings unless specific approval in writing covering a departure therefrom has been obtained from the cognizant Navy design activity prior to manufacture. When alternate materials or methods of manufacture are specified on the drawings, the bidder's selections shall be clearly stated in the proposal. The remanufactured thruster metal parts assembly shall contain the following new parts or items: shear pins, gasket, silicone fluid, O-rings, leather backup rings, and retainer rings.

3.2 Hydrostatic pressure. The body shall withstand a hydrostatic pressure of 11,000 pounds per square inch (psi) for 15 seconds, minimum, without leaking, deformation, or mechanical failure (see 6.3.1).

3.3 Protective finish. Protective finish shall be in accordance with the applicable specifications and drawings and shall apply to all surfaces of the component regardless of configuration. Remanufactured exterior components (see 6.3.2) shall have the existing protective finish stripped and the specified protective finish reapplied. When there are only small surface areas of exposed base metal on the aluminum exterior

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

components (reservoir assembly, body, and firing pin housing) it may be permissible to treat the surfaces with chemical film Class 1A as specified in MIL-C-5541.

3.4 Residual magnetism. The metal parts assembly shall not deflect the indicator of the compass more than five degrees in either direction using the procedures of 4.5.5.

3.5 Shear pin strength.

3.5.1 Shear pin. The shear pin, after application of protective finish, shall shear when a load of 55 ± 5 pounds is applied at the steady rate of 0.125 inch per minute.

3.5.2 Unlock shear pin. The unlock shear pin, after application of protective finish, shall shear when a load of 1150 ± 150 pounds is applied at the steady rate of 0.125 inch per minute.

3.6 Metal parts assembly. Parts shall be combined to produce an assembly which conforms to the requirements of the metal parts assembly drawing. All threaded joints shall be assembled with sufficient torque to lightly bottom components, except as noted.

3.6.1 Torque.

3.6.1.1 Hollow lock screw. A torque of 5 ± 1 inch pounds shall be applied to seat hollow lock screw on the gasket.

3.6.1.2 Ring nut and pellet assembly. Torque requirements shall be as specified in table I. No movement or deformation shall occur upon application of the breakaway torque.

TABLE I. Torque requirements.

Component	A	B	C
	Run-On, Min (inch pounds)	Seating or Bottoming (inch pounds)	Breakaway, Min (inch pounds)
Ring nut and pellet assembly with body	40	600 ± 30	400

3.6.2 Piston rod retraction. The piston rod shall not retract into the body upon application of a static compression load of 25 ± 5 pounds between mounting points.

3.6.3 Fluid leakage. The thruster shall not show evidence of fluid leakage when tested in positions I and II (see 3.6.3.1 and 3.6.3.2) for a minimum of 12 hours each prior to the installation of the reservoir assembly.

3.6.3.1 Position I. Thruster positioned horizontally with the orifice hole facing down.

3.6.3.2 Position II. Thruster positioned vertically with the piston facing down.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

3.6.4 Integrated plant products. When remanufacturing and loading of the assembly is performed in an integrated plant, the metal parts assembly requirement may be waived and the residual magnetism requirement performed on the loaded assembly only.

3.6.5 Threaded component parts. Class 2A or 2B thread gage shall be used on remanufactured component parts inspection versus class 3A or 3B thread gage required on new hardware for thrusters.

3.6.6 Remanufactured components. Remanufactured components which require modification shall be modified in accordance with instructions noted in 6.5.

3.7 Workmanship. Thrusters shall be free of cracks, splits, or other defects which might prevent proper mating with connecting parts or proper functioning of the device.

3.7.1 Metal defects. All components shall be free from cracks, splits, cold shuts, inclusions, porosity, or any similar defect.

3.7.2 Burr. No part shall have a burr which might interfere with the assembly or function of the item or which might be injurious to personnel handling the item.

3.7.3 Foreign matter. No part or assembly shall contain chips, dirt, grease, rust, corrosion, or other foreign matter.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements (see 6.2).

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements; however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Quality assurance terms and definitions. Reference shall be made to MIL-STD-109 to define the quality assurance terms used.

4.1.3 Inspections. Inspections shall be in accordance with MIL-A-2550.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.2 Inspection conditions. Unless otherwise specified (see 6.2), all inspections shall be performed under the following conditions:

a. Temperature: room ambient (68 to 77•F)
b. Altitude: sea level
c. Humidity: 50 percent relative, maximum
d. Atmospheric pressure: 14.7 psi

4.3 Quality conformance inspection.

4.3.1 Lot.

4.3.1.1 Submission of product. Unless otherwise specified by the contracting activity, formation and identification of lots shall be in accordance with MIL-STD-105.

4.3.1.2 Size of lot. For the purpose of identification and shipment, the shipping lots of metal parts assemblies shall consist of 1200 assemblies, maximum, provided the homogeneity requirements of inspection lots have been retained.

4.3.2 Examination. On reprocessed parts, one hundred percent examination shall be performed for all critical defects. Examination for major and minor defects shall be performed on a defect basis in accordance with the classification of defects. Four power (4x) magnification may be used in performing visual examination for such defects as burr and foreign matter. Inspection for rubber O-rings shall be in accordance with MIL-STD-413. When compliance with the applicable requirement is in doubt as a result of visual examination, the characteristic shall be measured or gaged to determine acceptability. All nonconforming material shall be rejected.

4.3.2.1 Examination of reclaimed parts. Examination of reusable parts, which require no reprocessing, shall be limited to inspection of defects that require visual type inspection. One hundred percent examination shall be performed for all such defects. All nonconforming parts shall be reprocessed or rejected.

4.3.2.2 Pin, Firing, Drawing 8593878, covering a detail of Drawing 10520876.

Characteristics	Defect	Method of Inspection
Critical		
None defined		
Major		
101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual
Minor		

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

None defined

4.3.2.3 Plug, Drawing 10520879, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Crease or dent in membrane	Visual
104	Burr or sharp corner	Visual
105	Foreign matter	Visual

Minor
None defined

4.3.2.4 Rod, End, Drawing 10520884, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Pitch diameter of thread, max	Gage
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Burr	Visual
105	Foreign matter	Visual

Minor
None defined

4.3.2.5 Spacer, Reservoir, Drawing 10520886, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual

Minor
None defined

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.3.2.6 Piston, Gas, Drawing 10520887, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corner	Visual
104	Foreign matter	Visual

Minor
None defined

4.3.2.7 Spacer, Piston, Drawing 10520888, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Metal defective	Visual
102	Protective finish inadequate or defective	Visual
103	Burr or sharp corners	Visual
104	Foreign matter	Visual

Minor
None defined

4.3.2.8 Body, Drawing 10520889, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Pitch diameter of thread, large cavity, max	Gage
102	Pitch diameter of thread, small cavity, max	Gage
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Obstruction in orifice	Visual
106	Burr or sharp corners	Visual
107	Foreign matter	Visual

Minor
None defined

4.3.2.9 Rod, Piston, Drawing 10520885, covering a detail of Drawing 10520876.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Critical
None defined

Major

101	Pitch diameter of thread, min	Gage
102	Thread damaged or not full	Visual
103	Sharp corner on body, missing	Visual
104	Metal defective	Visual
105	Protective finish inadequate or defective	Visual
106	Burr	Visual
107	Foreign matter	Visual
108	Pellet missing, loose, or improperly inserted	Manual/Visual

Minor
None defined

4.3.2.10 Housing, Firing Pin, and Pellet Assembly, Drawing 10520880, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Pitch diameter of external thread, min	Gage
102	Pitch diameter of internal thread, max	Gage
103	Thread damaged or not full	Visual
104	Metal defective	Visual
105	Protective finish inadequate or defective	Visual
106	Burr or sharp edge	Visual
107	Foreign matter	Visual
108	Pellet missing, loose, or improperly inserted	Manual/Visual

Minor
None defined

4.3.2.11 Nut, Ring, and Pellet Assembly, Drawing 10520881, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Pitch diameter of thread, min	Gage
102	Thread damaged or not full	Visual
103	Metal defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

104	Protective finish inadequate or defective	Visual
105	Burr	Visual
106	Foreign matter	Visual
107	Pellet missing, loose, or improperly inserted	Manual/Visual

Minor
None defined

4.3.2.12 Reservoir Assembly, Drawing 10520890, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Liquid in tube	Manual/Visual
102	Inlet hole, obstructed	Visual
103	Improper assembly	Visual
104	Metal defective	Visual
105	Protective finish inadequate or defective	Visual
106	Burr	Visual
107	Foreign matter	Visual

Minor
None defined

4.3.2.13 Spacer, Piston, prior to installation on Rod, consisting of components 10520888, AN6227-B13, AN6227-B20, and MS35803-115, covering a detail of Drawing 10520876.

Critical
None defined

Major

101	Improper assembly	Visual
102	Rings missing	Visual
103	Packing missing	Visual
104	Material defective	Visual
105	Burr	Visual
106	Foreign matter	Visual

Minor
None defined

4.3.2.14 Piston, Gas, prior to installation on Rod, consisting of components 10520887, MS20513-122, MS35803-115, and AN6227-B13, covering a detail of Drawing 10520876.

Critical

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

None defined

Major		
101	Improper assembly	Visual
102	Rings missing	Visual
103	Packing missing	Visual
104	Material defective	Visual
105	Burr	Visual
106	Foreign matter	Visual

Minor
None defined

4.3.2.15 Piston Rod, Gas Piston and Piston Spacer Subassembly, consisting of components 10520885, 10520887, 10520888, 10520882, 10520883, AN6227-B13, AN6227-B20, MS29513-122, and MS35803-115, covering a detail of Drawing 10520876.

Critical
None defined

Major		
101	Improper assembly	Visual
102	Any part missing	Visual
103	Material defective	Visual
104	Burr	Visual
105	Foreign matter	Visual

Minor
None defined

4.3.2.16 Metal Parts Assembly, Drawing 10520876, prior to installation of Hollow Lock Screw and Reservoir Assembly, Drawing 10520890.

Critical		
1	Gasket missing or incorrectly installed	Manual/Visual
2	Plug (frangible) missing or incorrectly installed	Manual/Visual
3	Oil hole obstructed	Visual
Major		
101	Any part missing, not otherwise classified	Visual
102	Improper assembly, not otherwise classified	Visual
103	Thread damaged	Visual
104	Foreign matter	Visual
Minor		
201	Protective finish inadequate or defective	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.3.2.17 Metal Parts Assembly, Drawing 10520876.

Critical		
1	Evidence of oil leakage	Visual
Major		
101	Crack in weld on reservoir	Visual
102	Excessive distortion of the reservoir	Visual
103	Any part missing	Visual
104	Improper assembly	Visual
105	Marking missing, incorrect, or illegible	Visual
Minor		
201	Protective finish inadequate or defective	Visual
202	Foreign matter	Visual

4.3.2.18 Pin, Shear, Drawing 8593876, covering a detail of Drawing 10520876.

Critical		
None defined		
Major		
101	Diameter, max	Gage
102	Total length, min	Gage
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Burr	Visual
106	Foreign matter	Visual
Minor		
201	Total length, max	Gage
202	Profile of ends	Visual
203	Surface finish improper	Visual

4.3.2.19 Gasket, Drawing 10520878, covering a detail of Drawing 10520876.

Critical		
None defined		
Major		
101	Outside diameter	Gage
102	Inside diameter	Gage
103	Thickness	Gage
104	Material defects, flow line or splits	Visual
105	Foreign matter	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

Minor
None defined

4.3.2.20 Pin, Unlock Shear, Drawing 10520882, covering a detail of Drawing 10520876.

Critical
None defined

Major		
101	Diameter, max	Gage
102	Metal defective	Visual
103	Protective finish inadequate or defective	Visual
104	Foreign matter	Visual

Minor		
201	Total length	Gage
202	Profile of ends	Gage
203	Surface finish improper	Visual

4.3.2.21 Ring, Retaining, Drawing 10520883, covering a detail of Drawing 10520876.

Critical
None defined

Major		
101	Inside diameter	Gage
102	Thickness	Gage
103	Metal defective	Visual
104	Protective finish inadequate or defective	Visual
105	Burr	Visual

Minor		
201	Opening between ends	Gage
202	Radius or chamfer incorrect	Gage
203	Foreign matter	Visual

4.3.2.22 Box, Fiberboard (Inner), Packing, Ammunition, Drawing 8858441.

Critical
None defined

Major
None defined

Minor		
201	Contents loose	Manual
202	Box damaged	Visual
203	Marking missing, incorrect, or illegible	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

204	Cut, damaged, or improperly sealed bag	Visual

4.3.2.23 Box, Packing, Ammunition, Drawing 8858440.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Visual/Manual
202	Strapping missing, loose, broken, or improperly assembled	Visual/Manual
203	Contents of box exposed	Visual
204	Box damaged	Visual
205	Marking missing, incorrect, or illegible	Visual
206	Number of units incorrect	Visual

4.3.2.24 Box, Fiberboard (Outer), Alternative, Packing, Ammunition, Drawing 9217560.

Critical
None defined

Major
None defined

Minor

201	Contents loose	Manual/Visual
202	Hardware missing, loose, broken, or improperly engaged	Visual
203	Strapping missing, loosed, broken, or improperly engaged	Visual
204	Contents of box exposed	Visual
205	Box damaged	Visual
206	Marking missing, incorrect, or illegible	Visual

4.4 Inspection testing. The following tests shall be performed in accordance with 4.5.

4.4.1 Hydrostatic pressure. Each body shall be subjected to the hydrostatic pressure test. Failure of any body to comply with 3.2 shall be cause for rejection of the unit.

4.4.2 Breakaway torque. Each body and ring nut subassembly shall be subjected to a breakaway torque application. Failure to comply with the requirements of column C, table II shall be cause for rejection of the subassembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

4.4.3 Piston rod retraction. Each piston rod and body subassembly shall be subjected to a static compression load application. Failure to comply with the requirement of 3.4.3 shall be cause for rejection of the subassembly.

4.4.4 Fluid leakage. Each thruster shall be subjected to a leakage test. Failure of any thruster to comply with the requirement of 3.4.4 shall be cause for rejection of the thruster.

4.4.5 Protective finish. The number of units for protective finish tests shall be in accordance with the applicable specification. Failure of any unit in the inspection sample to comply with the requirements of the applicable specification shall be cause for rejection of the lot.

4.4.6 Residual magnetism. Each assembly shall be subjected to the test for excessive residual magnetism as specified in 4.5.5. Failure of any unit in the inspection sample to comply with 3.4 shall be cause for rejection of the assembly.

4.4.7 Shear pin strength. Fifty pins of each type from each lot of shear pins shall be tested for shear strength. Failure of any shear pin to comply with 3.5 shall be cause for rejection of the lot.

4.5 Test methods and procedures.

4.5.1 Hydrostatic pressure. Prior to application of protective finish the body shall be mounted in the device, using a fixture for properly sealing all openings, and subjected to the internal hydrostatic pressure to determine compliance with 3.2.

4.5.2 Breakaway torque. A torque wrench set at the requirement as specified in 3.6.1.2 shall be used in conjunction with a fixture to determine the adequacy of the joint. The thruster body shall be secured in an air vise or other holding fixture. The torque shall be applied to the ring nut.

4.5.3 Piston rod retraction. After assembly of the piston rod into the body and the torque has been applied to the ring nut, the static compression load as specified in 3.6.2 shall be applied between the mounting points of the thruster.

4.5.4 Fluid leakage. The thruster shall be placed on paper or any material that will show oil fluid markings. The thruster shall be tested as specified in 3.6.3.1 and 3.6.3.2. The test shall be performed after the piston rod and ring nut have been assembled into the thruster, but prior to installation of the reservoir assembly.

4.5.5 Protective finish. Test procedures for protective finish shall be in accordance with the applicable specification referenced on the applicable drawing.

4.5.6 Residual magnetism. The assembly shall be tested for excessive residual magnetism using an approved compass in an area free of local magnetic effects by placing the assembly 5 inches from the end and at the same height as the compass, in a north-south horizontal position (cap end at south) with the compass set in an east-west heading. The assembly shall be moved at a speed no greater than 10 feet per minute past the compass for its entire length, rotated 90 degrees in the horizontal position about its longitudinal axis and

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

moved slowly back past the compass. This procedure shall be repeated for each 90 degree rotation of the assembly for four full passes.

4.5.7 Shear pin strength. After application of protective finish, the pin shall be subjected to the shear pin strength test to determine compliance with 3.5. The test shall be performed in a fixture in conjunction with a tensile testing machine.

4.6 Inspection of packaging. The sampling and inspection of the packaging, packing, and container marking shall be in accordance with the requirements of section 5.

5. PACKAGING

5.1 Packing and marking. Packing and marking shall be Level A or B, as specified by the contracting activity (see 6.2). Level A shall be in accordance with Drawings 8858440 and 8858441. Level B shall be in accordance with Drawings 8858441 and 9217560.

5.2 Air Force packaging. Air Force packaging shall be in accordance with TPO 00-607-0314.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The thruster assembly is used in conjunction with other propellant actuated devices in Aircrew Emergency Escape Systems.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification

b. Issue of DODISS to be cited in the solicitation and, if required, the specific issue of individual documents referenced (see 2.1.1 and 2.1.2)

c. The responsible inspection activity (see 4.1)

d. Any special instruction requirements (see 4.2)

e. Level of packing and marking (see 5.1)

6.3 Definitions.

6.3.1 Mechanical failure. Mechanical failure is any deformation or breakage of a part, the occurrence of which is other than a design function.

6.3.2 Exterior components. Remanufactured exterior components are: firing pin housing, reservoir assembly, body, ring nut, rod end, and piston rod.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.

6.4 Old engraved or stamped lot and serial numbers. Old serial numbers and lot numbers engraved or stamped on metal parts shall be over-stamped by x's to obliterate those markings before applications of final protective finish.

6.5 Nylon pellets. Components which contain nylon pellets and are to be replated or anodized shall have the pellets removed and new pellets installed after new application of protective finish. Pellets shall be installed in accordance with the applicable drawing.

6.6 Subject term (keyword) listing.

Ejection systems, aircrew
Emergency escape systems, aircrew
Escape systems, aircrew
Life-saving systems, aircrew

6.7 Changes from previous issue. Marginal notations are not used to identify changes with respect to the previous issue because of the extensiveness of the changes.

Custodian:

Preparing activity
Navy - OS

Navy - OS

Air Force - 99

(Project 1377-0E27)

Review activity:
Air Force - 70

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T00:56Z
Check the source to verify that this is the current version before use.