INCH-POUND
MIL-PRF-8805/27G
8 April 2026
SUPERSEDING
MIL-PRF-8805/27F
17 March 2021

PERFORMANCE SPECIFICATION SHEET

SWITCHES, SENSITIVE, 10 AMPERES AND LOW LEVEL, UNSEALED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The complete requirements for acquiring the switch described herein shall consist of this specification and the latest issue of MIL-PRF-8805.




FIGURE 1. Dimensions and configurations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

NOTES:
1. Dimensions are in inches.
2. DELETED.
3. Exact shape of switch optional provided dimensions specified are not exceeded.
4. Mark, stamp or mold NO, NC and COM terminal designations and arrows on either side of switch.
5. Metric equivalents are given for general information only and are based upon 1.00 inch = 25.4 mm.
6. Military Standard Drawing MS25253 is canceled and superseded by MIL-PRF-8805/27. However, MS25253-X is still used as part of the PIN

FIGURE 1. Dimensions and configurations - Continued

REQUIREMENTS:

Dimensions and configurations: See figure 1.

Enclosure design: 1 (Unsealed).

Temperature characteristic: 1 (-55° to +85°C).

Shock type: test condition A, MIL-STD-202-213 (50 G).

Vibration grade: 1 (10 to 500 Hz).

Weight: .35 ounce maximum.

Operating characteristics:

Actuating force:

MS25253-1, -2, -3, and –5 through –7: 14 ounces maximum.
MS25253-8, through –13: 135 grams maximum.

Movement differential:

MS25253-1, -2, -3, and –5 through –7: .020 inch maximum.
MS25253-8, through –13: .010 inch maximum.

Pretravel: .047 inch maximum.

Overtravel:

MS25253-1, -2, -3, and –5 through –7: .031 inch minimum.
MS25253-8, through –13: .050 inch minimum.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

Strength of actuating means: 25 pounds.

Material:

Plunger: May be glass filled nylon.

Contact resistance:

MS25253-1, -2, -3, and –5 through –7: Not applicable.
MS25253-8, through –13: : 0.05 ohm maximum initially.
0.10 ohm maximum after mechanical life.

Contact bounce:

MS25253-1, -2, -3, and –5 through –7: Not applicable.
MS25253-8, through –13: : 5 milliseconds maximum.

Dielectric withstanding voltage:
Sea level: 1,000 Vrms.
Altitude: 50,000 feet – 400 Vrms.
In qualification inspection table after electrical endurance the dielectric withstanding voltage points of application between all unconnected terminals of the same pole is not applicable.

Mechanical endurance:

MS25253-1, -2, -3, and –5 through –7: 25,000 cycles..
MS25253-8, through –13: 500,000 cycles.

Electrical endurance (power circuits): 25,000 cycles.

Low level circuits:

MS25253-1, -2, -3, and –5 through –7: Not applicable.
MS25253-8, through –13: : 50,000 cycles.

Electronic logic circuits (5.0 V dc, .010 ampere):

MS25253-1, -2, -3, and –5 through –7: Not applicable.
MS25253-8, through –13: : 50,000 cycles when tested in accordance with ECA-RS-448-4, method 17. Rate of action shall be 120 cycles per minute maximum. No “stick” or “misses” allowed.

Operating temperature:

a. 25 percent of the test cycle at the minimum temperature specified.
b. 25 percent of the test cycle at room ambient conditions.
c. 50 percent of the test cycle at the maximum temperature specified.

Electrical ratings: See table I and II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

Quality assurance:

Qualification inspection: See table III
Inspection of product for delivery: See table IV.

Part or Identifying Number (PIN): See table V

TABLE I. Electrical ratings silver contacts (MS25253-1, -2, -3, and –5 through –7).

Load	Sea level		50,000 feet	
	28 V dc	115 V ac, 60 Hz	28 V dc	115 V ac, 60 Hz
	Amperes	Amperes	Amperes	Amperes
Resistive	10	10	10	10
Inductive	10	10	6	10
Motor	6	3	----	----

TABLE II. Electrical ratings gold contacts (MS25253-8 through –13).

Load	Sea level and 50,000 feet		Sea level
	Power circuit 28 V dc	Electronic logic circuit 5 V dc	Low level 1/ 30 millivolts
	Amperes	Amperes	Amperes
Resistive	1.0	0.01	0.01
Inductive	0.5	----	----

1/ 30 millivolts max dc or peak ac.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

TABLE III. Qualification inspection (group submission).

Inspection	Sample	Extent of approval
Group I Visual and mechanical 1/ Solderability (when applicable) 2/ Dielectric withstanding voltage Insulation resistance Operating characteristics	MS25253-1 (all samples) MS25253-2, -3, (2 samples each) Visual and mechanical MS25253-11 (all samples)	All
Group II Terminal strength 3/ Strength of actuating means 3/ Thermal shock Vibration Shock Moisture resistance Marking visibility Dielectric withstanding voltage Operating characteristics	MS25253-1, -11 (4 sample each)	
Group IV Salt spray Marking visibility	MS25253-1 (2 samples)	
Group V Explosion Operating characteristics	MS25253-1 (2 samples)	
Group VI Contact resistance (when applicable) Contact bounce (when specified) Low temperature operation Mechanical endurance at low temperature Mechanical endurance at high temperature Contact resistance (when applicable) Short circuit 4/ Dielectric withstanding voltage Operating characteristics	MS25253-1, -11 (4 samples)	
Group VII Overload cycling Electrical endurance Contact resistance (when applicable) Dielectric withstanding voltage Operating characteristics	MS25253-1, (20 samples) MS25253-11 (8 samples)	
Group X Low level circuit Operating characteristics	MS25253-11 (2 samples)	
Electronic logic circuit Operating characteristics	MS25253-11 (2 samples)	

1/ Two samples for physical dimensions.
2/ Four samples of each applicable terminal type..
3/ Two samples of each PIN.
4/ Short circuit test shall be conducted at the 28 V dc electrical rating.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

TABLE IV. Inspection of product for delivery.

Inspection
Visual and mechanical 1/ Operating characteristics 2/ Contact bounce (when specified) 2/ Dielectric withstanding voltage Contact resistance (when applicable) 2/

1/ In-process inspection may be used to satisfy the dimensional requirements.
2/ Do not exceed 6 V dc, or peak ac, 10 milliamperes during inspection of MS25253-8 through –13..

TABLE V. PIN's.

PIN 1/ MS25253-	Description					Sugested application 2/		
	Contacts	Circuit	Rating maximum	Terminals		Power Circuit	Electronic logic	Low level
				Type	Strength (lbs.)			
1	Silver	SPDT	Table I (10 AMPS)	Screw	20	X		
2	"	SPNO	"	"	"	X		
3	"	SPNC	"	"	"	X		
5	"	SPDT	"	Solder	"	X		
6	"	SPNO	"	"	"	X		
7	"	SPNC	"	"	"	X		
8 3/	Gold	SPDT	Table II (1 AMP)	Screw	"	X	X	X
9 3/	"	SPNO	"	"	"	X	X	X
10 3/	"	SPNC	"	"	"	X	X	X
11 3/	"	SPDT	"	Solder	"	X	X	X
12 3/	"	SPNO	"	"	"	X	X	X
13 3/	"	SPNC	"	"	"	X	X	X

1/ MS25253-4 is canceled, use MS25253-1.
2/ Application information

Power circuits – Those electrical loads where the voltage and current exceed the minimum arcing conditions of the contact material. As a general rule, application loads in excess of 8 volts, 0.5 amperes are considered power circuits.

Electronic logic circuits – Those electrical loads in which the applied voltage is less than the arcing voltage and greater than the non-arcing application loads in excess of 0.5 volts are considered logic level circuits.

Low level circuits - Those electrical loads in which the applied voltage is less than the softening voltage of the contact material. As a general rule, application loads less than .08 volts are considered low level circuits.

3/ MS25253-8 through –13 have two levels of capabilities. However, switches previously tested or used above 10 milliamperes resistive at 6 V dc max or peak ac are not recommended for use in electronic logic or low level application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.

Referenced documents. In addition to MIL-PRF-8805, this document references the following:
MIL-STD-202-213
AN508
ECA-RS-448-4

The margins of this specification are marked with vertical lines to indicate where modifications from this revision were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

(Project 5930-2026-034)

Review activities:
Army – AR, MI
Navy - AS, MC
Air Force - 19

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil/

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T11:04Z
Check the source to verify that this is the current version before use.