INCH-POUND

MIL-F-51525A(EA)
AMENDMENT 7
10 July 1992

SUPERSEDING
AMENDMENT 6
23 April 1992

MILITARY SPECIFICATION

FILTER, GAS, 200 CFM

This amendment forms a part of MIL-51525A(EA), dated 3 February 1988, and is approved for use by the U.S. Army Chemical Research, Development and Engineering Center, Department of the Army and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

1.1: Delete in its entirety and substitute the following:

"1.1 Scope. This specification covers two types of cylindrical gas filters with airflow ratings of 200 cubic feet per minute (cfm).

1.2 Classification. Falters covered by this specification shall be of the following types as specified (see 6.2):

Type I - Part Number 5-19-6368
Type II - Part Number 5-19-6368-10"

PAGE 2

2.1.2: Above DRAWINGS add the following:

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for *public release;* distribution *is* unlimitcd.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

"PURCHASE DESCRIPTIONS

EA-C-1704 - Carbon, Activated, Impregnated, Copper-Silver-Zinc-Molybdenum-Triethylenediamine (ASZM-TEDA)

(Copiis are available from Commander, U.S. Army Chemical Research, Development and Engineering Center, ATTN: SMCCR-PET-O Aberdeen Proving Ground, MD 21010-5423.)"

PAGE 3

3.3.2: Change "Airstream-relative humidity (RH)" from "less than or equal to 30 percent" to "less than or equal to 50 percent".

PAGE 4

3.3.3:

Line 2: Delete "5-19-6368" and substitute "5-19-6368 or 5-19-6368-10".

Change filter preheat test parameter requirement from "110° ± 5°F" to "120 ± 10°F".

3.3.4: Delete the paragraph in its entirety and substitute the following:

"3.3.4 Cyanogen chloride (CK) gas-life. After completion of all manufacturing steps, the gas filter's carbon shall have a minimum unaged CK life of 30 for Type I and 50 for Type II when tested in accordance with 4.4.4.5.

3.3.5, line 2: Delete "weight" and substitute 'weight for Type I and 3.0 percent by weight for Type II".

PAGE 6

4.3.3.2(c): Delete (c) in its entirety and substitute "(c) CK gas-life. CK gas-life shall be performed in accordance with 4.4.4.5. Any failure of a sample constitutes failure of the preproduction lot."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

PAGE 7

4.3.3.3.1: Add the following sentence to the end of the paragraph: “The preproduction lot of filters shall be rejected if any filter fails to meet the requirements of 3.3.3.”

PAGE 9

4.4.4.1: Add the following sentence to the end of the paragraph: ‘Purge the filter by passing fresh air in the reverse direction through the filter at its rated airflow for 1 minute.”

4.4.4.2, line 1: Delete “5-19-6368” and substitute “5-19-6368 or 5-19-6368-10”.

4.4.4.3(a) - (i): Delete subparagraphs in their entirety and substitute the following:

“(a) Preheat sample filter to 120 ± 10°F for a minimum of 30 minutes.

(b) While in the bypass mode adjust the controls until rated airflow is reached and the temperature is 110 ± 5 °F. Generate DMMP vapor until the influent concentration detection (see 6.6) indicates 5.0 ± 0.01 milligrams DMMP per liter air.

(c) Insert preheated sampled filter using the applicable test fixture if necessary.

(d) Switch to test mode and start timer. Make final adjustments to airflow, temperature, and DMMP concentration.

(e) Stop the test and record when the effluent concentration detector indicates that the break concentration has been reached. Record the airflow resistance (iwg) of the filter. ”

PAGE 10

4.4.4.4(a), line 5: Delete “ASTM D 2867” and substitute “ASTM D 2867 for Type I and ASTM D 2867, Oven-Drying Test Method, except that the oven temperature shall be 103°- 107°C and the drying time shall be 3 hours, for Type II,”.

4.4.4.5, line 3: Delete “MIL-C-13724” and substitute “MIL-C-13724 for Type I and EA-C-1704 for Type II”.

6.1, line 1: Delete “a 200 cfm gas filter” and substitute “two types of 200 cfm gas filters”.

6.2: Add the following new subparagraph:

“(e) Type of filter (see 1.2)”

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.

Custodian

Army - EA

Preparing activity:

Army - EA

Project No. 4240-A043

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:03Z
Check the source to verify that this is the current version before use.