MILITARY SPECIFICATION

ADAPTER, CONNECTOR, COAXIAL, RADIOFREQUENCY, BETWEEN SERIES, TYPE UG–586B/U

This specification has been approved by the Department of Defense and is mandatory for use by the Departments of the Army, the Navy, and the Air Force.

1. SCOPE

1.1 This specification covers the detail requirements for type UG–586B/U, between series (series LC to series LT), radiofrequency, coaxial connector adapter.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids, form a part of this specification to the extent specified herein:

SPECIFICATION

MILITARY

MIL–A–27434 — Adapters, Connector, Coaxial, Radiofrequency, Between Series, General Specification for.

DRAWINGS

BUREAU OF SHIPS

REA10002 — Bushing.

REB10008 — Contact.

REB10076 — Body.

REB101200 — Insulator.

REB101201 — Insulator.

(Copies of specifications and drawings required by contractors in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Requirements. Requirements shall be in accordance with Specification MIL–A–27434, and as specified herein.

3.2 Design and construction. The connector adapter shall be of the design, construction, and physical dimensions specified on figure 1.

3.2.1 *Gage tests for contacts.* The contact shall meet the gage tests for contacts specified in 4.2 to 4.2.1, inclusive.

4. QUALITY ASSURANCE PROVISIONS

4.1 Sampling and inspection. Sampling and inspection shall be in accordance with Specification MIL–A–27434, and as specified herein.

4.1.1 *Group B inspection.* Group B inspection shall be in accordance with Specification MIL–A–27434. Mating dimensions shall be as specified in figure 2.

4.2 Gage tests for contacts (applicable only to series LT termination) (see 3.2.1). The

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:55Z
Check the source to verify that this is the current version before use.





FIGURE 1. *Type UG-586/U connector adapter.*



All dimensions in inches

FIGURE 2. *Dimensional requirements for group B inspection.*

center contact shall be subjected to the gage tests specified in 4.2.1 prior to assembly into the connector adapter. The pins used in the performance of these tests may be tapered at their ends to facilitate insertion, but the tapered portions shall not be included in the specified dimensions. All tests shall be performed in the order shown.

4.2.1 After insertion and removal of a pin 0.200 inch minimum in diameter to a depth of 0.187 inch minimum, all contact members shall make contact, within 0.031 inch of their tip ends, with a pin 0.176 inch diameter inserted to a depth of 0.187 inch minimum. The contact shall then be tested as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:55Z
Check the source to verify that this is the current version before use.

(a) A pin 0.168 inch minimum in diameter inserted to a depth of 0.187 inch minimum shall not deflect the contact members.

(b) When a pin 0.196 inch minimum in diameter is inserted to a depth of 0.187 inch minimum, all contact members shall make contact with said pin 0.031 inch maximum from their tip ends. The contact shall then pass through a cylindrical hole 0.230 inch maximum in diameter and 0.500 inch long when a pressure of not more than 2 pounds is applied.

4.3 Dielectric withstanding voltage. The test voltage shall be 10,000 volts root mean square, applied at a rate of 500 volts per second, until the rated test voltage is reached.

5. PREPARATION FOR DELIVERY

5.1 Preparation for delivery shall be in accordance with Specification MIL-A-27434.

6. NOTES

6.1 Notes. In addition to the notes specified herein, the notes specified in Specification MIL-A-27434 are applicable to this specification.

6.2 This specification covers the design of type UG-586B/U connector adapter which was previously covered by Bureau of Ships Drawing REB49164.

Notice. When Government drawings, specifications, or other data are used for any purpose other than in connection with a definitely related Government procurement operation, the United States Government thereby incurs no responsibility nor any obligation whatsoever; and the fact that the Government may have formulated, furnished, or in any way supplied the said drawings, specifications, or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture, use, or sell any patented invention that may in any way be related thereto.

Custodians:

Army—Signal Corps
Navy—Bureau of Ships
Air Force

Preparing activity:

Army—Signal Corps

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T11:55Z
Check the source to verify that this is the current version before use.