NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/136C
1 May 1997
SUPERSEDING
MIL-D-3943/136B
24 June 1994

DETAIL SPECIFICATION SHEET

DECORATION, MERITORIOUS CIVILIAN SERVICE AWARD, ON-SITE INSPECTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of MIL-DTL-3943 listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation.




OBVERSE




REVERSE

MATERIAL: Red Brass

FINISH: Nickel Plated, Silver Plated, Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip number 14.

DIMENSIONS:
HEIGHT (Including Lug): 1-9/16 inches (3.97 cm) (REF)
WIDTH (Overall): 1-3/8 inches (3.49 cm) (REF)
THICKNESS (At Thickest Point): 0.155 inch ± 0.010 inch (0.393 cm ± 0.025 cm)

AMSC N/A FSC 8455
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:01Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type VIII, Style 6 with a Class 1, 1A or 3 pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-DTL-11589/345.

4. The lapel button shall conform to MIL-DTL-11484/210.

CHANGES FROM PREVIOUS ISSUE: Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0887)



Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:01Z
Check the source to verify that this is the current version before use.