NOT MEASUREMENT SENSITIVE

MIL-D-3943/137A
12 November 1992
SUPERSEDING
MIL-D-3943/137
9 July 1990

MILITARY SPECIFICATION SHEET

DECORATION, EXCEPTIONAL CIVILIAN SERVICE AWARD, ON-SITE INSPECTION AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass

FINISH: Gold Plated, Rose Gold Plated, Lightly Relieved, Matte Finish

DIMENSIONS:

HEIGHT (Overall): 1-9/16 inch ± 1/64 inch (3.97 cm ± 0.04 cm) (REF)
WIDTH (Overall): 1-3/8 inch ± 1/64 inch (3.49 cm ± 0.04 cm) (REF)
THICKNESS (At Thickest Point): 0.155 inch ± 0.010 inch (0.393 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:01Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal, a service ribbon and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type VIII, Style 6 with a Class 1 or 1A pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/346.

4. The lapel button shall conform to MIL-L-11484/172.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0689)

Source: https://assist.dla.mil -- Downloaded: 202610-17T01:01Z
Check the source to verify that this is the current version before use.