NOT MEASUREMENT SENSITIVE

MIL-D-3943/139A
24 June 1994
SUPERSEDING
MIL-D-3943/139
30 March 1991

MILITARY SPECIFICATION SHEET

DECORATION, NATIONAL COMMUNICATIONS SYSTEM MEDAL

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

MATERIAL: Red Brass

FINISH: Oxidized, Relieved, Matte Finish and shall match TIOH Metal Finish Chip Number 4.

DIMENSIONS:

HEIGHT (Including Lug): 1-3/8 inch (3.49 cm) (REF)
DIAMETER: 1-1/4 inch (3.18 cm) (REF)
THICKNESS (At Thickest Point): 0.125 inch ± 0.010 inch (0.317 cm ± 0.025 cm)

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:02Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. Decoration set shall consist of a regular size medal and a service ribbon all packaged in a presentation case conforming to MIL-C-14633, Type XVI with a Type XVI, Class 1 pad.

3. The ribbon for the pendant drape and service ribbon shall conform to MIL-R-11589/358.

Custodians:
Army - IH

Review activities:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-0764)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:02Z
Check the source to verify that this is the current version before use.