NOT MEASUREMENT SENSITIVE

MIL-D-3943/144
21 December 1992

MILITARY SPECIFICATION SHEET

DECORATION, EXCEPTIONAL CIVILIAN SERVICE AWARD, DEFENSE INFORMATION SYSTEMS AGENCY

This specification is approved for use by all Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the issue of the following specification listed in that issue of the Department of Defense Index of Specifications and Standards (DODISS) specified in the solicitation: MIL-D-3943.



OBVERSE



REVERSE

MATERIAL: Red brass

DIMENSIONS:

DIAMETER: 1-3/8 inch (3.49 cm) (REF)

HEIGHT (Including Lug): 1-1/2 inches (3.81 cm) REF

THICKNESS: 0.125 inch ± 0.010 inch (0.313 cm ± 0.025 cm)

FINISH: Gold Plated, Matte Finish, Polished Highlights

AMSC N/A FSC 8455

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil - Downloaded: 2026-10-17T01:04Z
Check the source to verify that this is the current version before use.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The reverse shall be suitable for engraving.

3. Decoration set shall consist of a regular size medal and a lapel button all packaged in a presentation case conforming to MIL-C-14633, Type XVI with a Class 1 pad.

4. The ribbon for the pendant drape shall conform to MIL-R-11589/370.

5. The lapel button shall conform to MIL-L-11484/190.

Custodians:
Army - IH

Review activities:
DLA - CT

User activities:
Other - DISA

Preparing activity:
Army - IH

(Project No. 8455-0698)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T01:04Z
Check the source to verify that this is the current version before use.