MILITARY STANDARD

TRUCKLOADING

HARPOON Missile RGM-84A-1 (ASROC)
in Container Mk 608 Mod 0

TO ALL HOLDERS OF MIL-STD-1320-169 (NAVY)

Page 2.

1. After Note 3 of General Notes delete the Note after WARNING and substitute

   When loading/unloading trailers with unitized containers, extra caution should be taken to prevent toppling. Special attention should be given to appropriate backup of outboard containers. Containers shall be deunitized after unloading the vehicle.

2. Delete General Notes 5 and 6 and substitute

   5. Chains, Fittings and Loadbinders shall meet the requirements of the basic Truckloading Document MIL-STD-1320 (NAVY) and applied as shown on Page 5 of this document.

   6. Steel strap used as tiedowns shall be 2 X .050 and shall conform to and be applied as specified in the basic truckloading document MIL-STD-1320 (NAVY) as shown on Page 3 of this document.

3. In Note 11 delete "Class A" and substitute "Heavy Duty, Finish A, B, or C."

Page 5.

1. In List of Materials, add "or 5/16" to Size of Piece No. 10.

Page 6.

1. Delete "Load Strapping" and all material under that heading.

Preparing Activity:

NAVY - OS
(Project No. 8140-N436)

Review Activity:

NAVY - OS

☆ U.S. GOVERNMENT PRINTING OFFICE: 1979-603-022/2392

FSC 8140

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:45Z
Check the source to verify that this is the current version before use.