MILITARY STANDARD
TRUCKLOADING
STANDARD MISSILE (MR)

RIM-66A, TYPE 1; RIM-66C; RGM-66D-1, 2 or
ROCKET MOTOR MK 56 & MODS (DTRM)
IN CONTAINER MK 372 MODS 2, 3, or 5

To All Holders of MIL-STD-1320-209 (NAVY)

Page 6

a. Container Unitizing Procedure. Add the following. Step 5 change "Double Crimp" to "Double Notch the seals".

b. Container Handling Procedures. Add the following. Step 2 "When loading the middle stack (three wide load) with a 6000 lb. cap. forklift truck, tine extensions must be used and only one container can be placed at a time on the trailer. All unitization (for middle stack only) will be done on the trailer. A crane or a 10,000 lb. capacity forklift (with tine extensions) can load a middle stack of three high containers."

c. Also add the following to the WARNING "To avoid toppling of the farside stack when loading the nearside stack (of 3), a forklift shall be positioned at the far side stack with its tines inserted in the forklift pockets of the containers while the nearside stack is loaded onto the trailer".

Activity:
Review Activities
NAVY-OS

Preparing Activity
Navy - OS
(Project #8140-N622)
FSC 8140

☆U.S. GOVERNMENT PRINTING OFFICE: 1984 — 505-038/A4625

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T23:47Z
Check the source to verify that this is the current version before use.