MIL-F-13549F
22 March 1968
SUPERSEDING
MIL-F-13549E
16 April 1963

MILITARY SPECIFICATION

FILE DESTROYER, INCENDIARY, ABC-M4

This specification is mandatory for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers one type of file destroyer.

2. APPLICABLE DOCUMENTS

2.1 Government documents. The following documents, of the issue in effect on date of invitation for bids or request for proposal, form a part of this specification to the extent specified herein:

SPECIFICATIONS

FEDERAL

PPP-B-621 - Boxes, Wood, Nailed and Lock-corner.
PPP-F-320 - Fiberboard; Corrugated and Solid, Sheet Stock (Container Grade), and Cut Shapes.
PPP-B-636 - Box, Fiberboard.

MILITARY

MIL-L-10547 - Liners, Case, and Sheet, Overwrap, Water-Vaporproof or Waterproof, Flexible.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

DRAWINGS

US ARMY MUNITIONS COMMAND

DL4-11-103 - File Destroyer, Incendiary, ABC-M4.

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. All materials cited on Drawing DL4-11-103 or on the subsidiary drawings shall conform to the specifications listed thereon, or to the specific characteristics set forth on the drawings.

3.1.2 Components. All components of the file destroyer shall conform to the specifications and drawings listed on Drawing DL4-11-103 and subsidiary drawings.

3.2 Igniter box. The igniter box shall contain 330 ± 9 grams (g) of igniter mixture box charge conforming to Drawing B143-8-3. The box shall be ignited and the combustible components completely burned when tested as specified in 4.3.4.

3.3 Oxidizer box. The oxidizer box shall contain a minimum of 750 g of incendiary mixture NO3 charge I conforming to Drawing B143-13-3.

3.4 Squib assembly. The squib assembly shall be connected in parallel as shown on Drawing D4-11-6.

3.5 Preproduction. Prior to the start of regular production, a preproduction sample of file destroyers shall be produced in accordance with this specification for examination and test (see 4.2).

3.6 Workmanship. The file destroyer shall be free from visible damage and contamination that could affect its intended use.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.

4.1.1 Supplier's responsibility. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

otherwise specified in the contract or order, the supplier may utilize his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.2 Objective evidence. The supplier shall provide evidence acceptable to the contracting officer that the requirements of 3.1 and section 5 for which specific inspection has not been provided in this specification have been satisfied.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) Preproduction inspection (see 4.3).
(b) Quality conformance inspection (see 4.4).

4.3 Preproduction inspection.

4.3.1 Sample. A preproduction sample of 4 file destroyers or 4 igniter boxes, as specified in the contract or purchase order (see 6.2), shall be manufactured using the same methods, materials, equipment and processes as will be used during regular production.

4.3.2 Inspection procedure.

4.3.2.1 For examination. The components of the sample file destroyers (igniter boxes and oxidizer boxes) shall be examined in accordance with the classification of defects and MIL-STD-105.

4.3.2.2 For destructive test. One igniter box from each sample file destroyer shall be tested as specified in 4.4.4.

4.3.3 Acceptance/rejection criteria. The preproduction sample shall comply with the examinations and test specified in 4.3.2 to be acceptable. The supplier shall obtain written approval from the contracting officer prior to proceeding with regular production.

4.4 Quality conformance inspection.

4.4.1 Lotting. A lot shall consist of the file destroyers of one interfix number, produced by one manufacturer, at one plant, from the same materials, under essentially the same manufacturing conditions

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

and offered for acceptance at one time. However, no more than one lot each of squibs, igniter and oxidizer boxes shall be represented in any one lot of file destroyers. A lot of igniter boxes or oxidizer boxes shall consist of the assemblies containing one batch (see 6.5) of the respective mix.

4.4.2 Sampling.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.1 For examination. Sampling shall be conducted in accordance with MIL-STD-105.

4.4.2.2 For destructive test. Five igniter boxes shall be taken at random from each lot of file destroyers or each lot of igniter boxes when procured seperately (see 6.2(c)).

4.4.3 Inspection procedure.

4.4.3.1 For examination. Sample file destroyers and the level A preparation for delivery shall be examined in accordance with the classification of defects and MIL-STD-105.

4.4.3.2 For destructive test. Sample igniter boxes shall be tested in accordance with 4.4.4. The acceptance number is zero.

4.4.3.3 For critical defect. Each item in the lot shall be tested for the critical characteristic listed in the classification of defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

4.4.3.4 Classification of defects.

(a) Box, igniter - assembly (Dwg D4-11-6).

Categories	Defects
Critical:	
1	Squib wire not shunted
Major:	AQL 1.0 percent defective
101	Squib incorrect
102	Filling missing or insufficient
103	Dimensions incorrect
104	Seal incorrect
105	Workmanship (3.6)

(b) Box, oxidizer - assembly (Dwg D4-21-4).

Categories	Defects
Critical:	None defined
Major:	AQL 1.0 percent defective
101	Filling missing or insufficient
102	Dimensions incorrect
103	Adhesive seal missing or loose
104	Workmanship (3.6)

(c) Preparation for delivery (section 5).

Categories	Defects
Critical:	None defined
Major:	AQL 4.0 percent defective
101	Packaging incorrect
102	Loose pack
103	Component missing
104	Container closure incorrect
105	Container damaged (broken or punctured)
106	Strapping loose or missing
107	Instruction card missing
108	Marking missing, illegible or incorrect

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

4.4.4 Igniter box functioning test. The igniter boxes, taken as specified in 4.4.2.2, shall be connected to either dry cells or a storage battery capable of furnishing a minimum current of 1 ampere at a voltage ranging from 2 to 6 volts, depending upon the length of the connecting leads. For lead lengths from 10 to 100 feet, 6 volts are recommended. Connecting leads shall be of ample size to carry a minimum current of 1 ampere. The igniter box shall be placed behind a suitable barrier before igniting.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging.

5.1.1 Level A. Each rack shall be rolled into a cylindrical shape and packaged in a W5c, style RSC, fiberboard box conforming to PPP-B-636. The box shall be closed in accordance with the appendix requirements of the box specification for domestic boxes.

5.1.2 Level C. Each rack shall be rolled into a cylindrical shape and packaged in a type 1, class 1, style RSC fiberboard box conforming to PPP-B-636. The box shall be closed in accordance with the appendix requirements of the box specification for domestic boxes.

5.2 Packing.

5.2.1 Level A. Four racks, packaged as specified in 5.1.1, with 44 oxidizer boxes and 4 igniter boxes shall be packed as shown on Drawing D4-11-103.

5.2.2 Level B. Same as specified in 5.2.1, except that a class 1, nailed wood box and type I, class A flat strapping or finish I, class A round strapping shall be used.

5.2.3 Igniter box, level A (see 6.2). Forty igniter boxes shall be packed in a class 2 overseas style 4 box for a type 1 easy load conforming to PPP-B-621. A case liner conforming to type I or II, grade B of MIL-L-10547 shall be placed inside the box. The igniters shall be separated using fiberboard separators and filler pads conforming to type CF, class - weather resistant, variety SW, grade optional of PPP-F-320. The liner shall then be sealed in accordance with MIL-L-10547, and the box shall be closed and strapped using zinc coated strapping in accordance with the appendix of PPP-B-621.

5.3 Marking. In addition to any special marking required by the contract or order, unit packages and intermediate packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D150-2-1.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

6. NOTES

6.1 Intended use. This item is intended for destroying combustible file material.

6.2 Ordering data. Procurement documents should specify the following:

(a) Title, number and date of this specification.
(b) Additional instruction cards as required.
(c) Quantity of igniter boxes when procured as separate item (see 5.2.3).
(d) Preproduction.

(1) Time allowed for supplier submission of samples for Government test and evaluation after award of contract.
(2) Name and address of test facility and shipping instructions when testing is performed by the Government.
(3) Time required for the Government to notify the supplier whether or not to proceed with production.

6.3 Caution. Precaution should be taken to prevent fires while preparing file destroyer mixtures for assembly.

6.4 International interest. Certain provisions of this specification are the subject of international standardization agreement (see Serial No. 1, Supplement B to Quadripartite Standardization List Sheet Report). When amendment, revision or cancellation of this specification is proposed which will affect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.5 Batch. A batch is defined as that quantity of material which has been subjected to some chemical or physical mixing process intended to yield a substantially uniform product.

Custodians:

Army - MU
Navy - OS
Air Force - 70
International interest (see section 6)

User interest:

Navy - OS, MC

Preparing activity:

Army - MU(EA)

Project No. 1375-1003

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.