MIL-F-13549F
AMENDMENT 5
30 July 1970
SUPERSEDING
INTERIM AMENDMENT 4(MU)
20 February 1970

MILITARY SPECIFICATION

FILE DESTROYER, INCENDIARY, ABC-M4

This amendment forms a part of Military Specification MIL-F-13549F, 22 March 1968.

Page 1

2.1: Add the following:

"TT-W-572 - Wood Preservative, Water Repellant."
"PPP-T-76 - Tape, Pressure-Sensitive Adhesive Paper, Water Resistant (For Carton Sealing)."
"MIL-B-117 - Bags, Sleeves and Tubing, Interior Packaging."
"MIL-B-2427 - Boxes, Ammunition Packing, Wood, Nailed."

Page 3

4.3.2.1: Delete "and MIL-STD-105" and substitute "listed in 4.4.3.4."

4.3.3: Between first and second sentence, add the following: "The acceptance number is zero."

Page 5

4.4.3.4(b): Delete "(Dwg D4-21-4)" and substitute "(Dwg D4-11-4)".

Page 6

5.: Delete all following "PREPARATION FOR DELIVERY", and substitute the following:

"5.1 Packaging, level A and C. Forty-four oxidizer boxes and four igniter boxes shall be packaged together as shown on Drawing D4-11-103. The fiberboard box shall be closed in accordance with the appendix to PPP-B-636 using PPP-T-76 tape. The barrier bag shall be heat sealed in accordance with the manufacturer's suggested procedure and tested in accordance with the requirements of MIL-B-117.

FSC 1375

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.

Page 6 (continued)

"5.2 Packing, level A. The oxidizer and igniter boxes packaged as specified in 5.1, shall be packed together with four racks (Drawing C4-11-23). The racks shall be folded transversely, butted end to end in accordance with Drawing D4-11-103. An instruction card conforming to Drawing C4-11-9 shall be placed face up on top of the packaged oxidizer and igniter boxes. The shipping container and all wood parts thereof shall be immersed in wood preservative conforming to composition A of TT-W-572 for a minimum of three minutes. Prior to packing the contents in the treated shipping container, the preservative shall be dry as evidenced by the dryness test in MIL-B-2427.

"5.3 Igniter box, level A (see 6.2). Forty igniter boxes shall be packed in a class 2 overseas style 4 box for a type I easy load conforming to PPP-B-621. A case liner conforming to type I or II, grade B of MIL-L-10547 shall be placed inside the box. The igniters shall be separated using fiberboard separators and filler pads conforming to type CF, class-weather resistant, variety SQ, grade optional of PPP-F-320. The liner shall then be sealed in accordance with MIL-L-10547 and the box closed and strapped using zinc coated strapping in accordance with the appendix of PPP-B-621.

"5.4 Marking. In addition to any special marking required by the contract or order, unit packages shall be marked in accordance with MIL-STD-129. Shipping containers shall be marked in accordance with Drawing D4-11-105. Sufficient dry time shall be allowed for wood preservative (see 5.2).

"5.5 Palletization. When specified in the contract or order (see 6.2), the shipping containers shall be palletized in accordance with Drawing D4-11-104."

Page 7

6.2: Add the following:

"(e) When palletization is required."

Source: https://assist.dla.mil -- Downloaded: 202610-18T00:50Z
Check the source to verify that this is the current version before use.

Custodians:

Army - MU
Navy - OS
Air Force - 70

Preparing activity:

Army - MU(EA)

International interest (see section 6)

Project No. 1375-0111

Review activity:

Navy - OS

User activity:

Navy - MC

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T00:50Z
Check the source to verify that this is the current version before use.