INCH-POUND

MIL-B-44306B
30 September 1991
SUPERSEDING
MIL-B-44306A
27 April 1988

MILITARY SPECIFICATION

BAG, STUFF, SLEEPING SYSTEM

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers one type of nylon stuff bag used to pack and carry the components of the extreme or intermediate cold weather sleeping systems.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be used in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5019 by using the Standardization Documents Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-50083	-	Bag, Plastic, Folded Garment
DDD-L-20	-	Label: For Clothing, Equipage and Tentage, (General Use)
PPP-B-26	-	Bag, Plastic
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	-	Loads, Unit; Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads
MIL-STD-731	-	Quality of Wood Members for Containers and Pallets

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-2-472	-	Bag, Stuff, Extreme and Intermediate Cold Weather Sleeping Systems

(Copies of drawings are available from the U.S. Army Natick Research, Development, and Engineering Center, ATTN: STRNC-UX, Natick, MA 01760-5017.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

2.2 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

(Non-Government standards and other publications are normally available from organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.2 Guide samples. Samples, when furnished, are solely for guidance and information to the contractor (see 6.4). Variations from this specification may appear in the sample, in which case this specification shall govern.

3.3 Materials. The materials shall be as specified herein and on Drawing 2-2-472 and all subsidiary drawings and parts lists pertaining thereto. It is encouraged that recycled material be used when practical as long as it meets the requirements of this specification.

3.3.1 Labels. Each stuff bag shall have a class 1 identification label conforming to type VI of DDD-L-20, stating "BAG, STUFF, SLEEPING SYSTEM". The label color shall be medium green, C.A. 70130, 70131 or 70034 and shall show fastness to laundering.

3.4 Design and construction. The design and construction of the stuff bag shall be as specified herein and as shown on Drawing 2-2-472 and all subsidiary drawings and parts lists pertaining thereto.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

3.4.1 Stitches, seams, and stitching. All stitches, seams, and stitching shall conform to FED-STD-751. The type of seam, stitching and stitches per inch shall be as shown on Drawing 2-2-472 and all subsidiary drawings. Seam allowances shall be maintained with seams sewn so that no raw edges, run-offs, twists, pleats, puckers, or open seams occur.

3.4.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1/2 inch except where ends are turned under or caught in other seams or stitching. Ends of continuous lines of stitching shall be overlapped not less than 1/2 inch. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be imbedded in the materials sewn.

3.4.1.1.1 Repairs of type 301 stitching.

a. When thread breaks, skipped stitches, run-offs, or bobbin run-outs occur during sewing, the stitching shall be repaired by restarting the stitching a minimum of 1/2 inch back of the end of the stitching. 1/

b. Except for prestitching, thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item shall be repaired by overstitching. The stitching shall start a minimum of 1/2 inch in back of the defective area, continue over the defective area, and continue a minimum of 1/2 inch beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner. 1/

1/ When making the above repairs, the ends of the stitching are not required to be backstitched.

3.4.1.2 Type 515 or 516 stitching. All repairs shall be in accordance with 3.4.1.1.1a and b. Thread tension shall be maintained so that there will be no loose stitching or excessively tight stitching resulting in puckering of the material sewn.

3.4.2 Automatic stitching. Automatic stitching machines may be used to perform any of the required stitch patterns provided the requirements for the stitch pattern, stitches per inch, and size and type of thread are met, and at least three or more tying, overlapping, or back stitches are used to secure the ends of the stitching.

3.5 Finished dimensions. The stuff bag shall conform to the following finished dimensions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

Area to be measured	Dimension inches	Tolerance inch
Length 1/	31-1/2	± 1
Opening width 2/	17-1/2	± 1/2
Base width 3/	9	± 1/2

1/ With the drawstring totally loosened and the top flap tucked inside the bag, lay the bag on a flat surface. Measure the length in a straight line from the top of the bag opening to the base piece seam.

2/ With the bag positioned as indicated in footnote 1/, measure across the opening width along the drawstring tunnel.

3/ With the bag positioned as indicated in footnote 1/, measure the diameter of the base piece from seam to seam along the center of the base piece 2 inch webbing.

3.6 Workmanship. The finished stuff bag shall conform to the quality of product established by this specification. The occurrence of defects shall not exceed the applicable acceptable quality level.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless otherwise disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for ensuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to ensure compliance with all dimensional requirements.

4.1.3 Certificates of compliance. When certificates of compliance are submitted, the Government reserves the right to inspect such items to determine the validity of the certification.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 3.1 and 6.2), it shall be examined for the defects specified in 4.4.2 and 4.4.3. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this specification or applicable purchase document.

4.4.1.1 Component and material certification. A certificate of compliance may be acceptable as evidence that the barrel locks and ladder locks on Drawing 2-2-472 and subsidiary drawings conform to requirements specified.

4.4.2 End item visual examination. The end items shall be examined for the defects listed in table I. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 6.5 for total (major and minor combined) defects.

TABLE I. End item visual defects

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, or tear	101	
	Any abrasion mark, smash, large slub, broken or missing yarn, multiple float, or open place, clearly visible at normal inspection distance	102	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Minor
Fabric (cont'd)	Fine or coarse filling bar		201
	Any mend, darn, patch, or unauthorized splice	103	
	Needle chews	104	
	NOTE: Needle holes visible as the result of broken or skipped stitching or stitching that has been removed shall not be considered as needle chews providing that the holes are spaced as in normal stitching.		
Webbing and tape	Cut or frayed edge	105	
	Not firmly and tightly woven		202
	Needle chews:		
	- up to 1/8 inch in length		203
	- over 1/8 inch in length	106	
Open seam	1/2 inch or less		204
	More than 1/2 inch	107	
	NOTE: A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		
Seam and stitch type	Wrong seam or stitch type	108	
Stitching	Loose tension, resulting in a loose top or bottom thread		205
	Excessively tight tension resulting in puckering of material		206
	NOTE: Defects are to be scored only when the condition exists for 4 inches or more or in several areas with an accumulated distance of 8 inches or more. Applicable to individual seams.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitching (cont'd)	Stitching ends and breaks not backstitched or not overstitched as specified		207
Stitches per inch	One to two stitches less than minimum specified		208
	Three or more stitches less than minimum specified	109	
	One or more stitches in excess of maximum specified		209
Cleanness	Spots or stains, clearly noticeable; thread ends not trimmed as specified		210
Label	Omitted or incorrect	110	
	Not positioned as specified		211
Drawcord	Any drawcord caught in stitching restricting use of drawcord	111	
	Any end not heat sealed		212
	Any drawcord omitted	112	
	Any end not knotted or not having a barrel lock		213
	Any drawcord insufficient in length	113	

4.4.3 End item dimensional examination. The end items shall be examined for conformance to the finished dimensions specified in 3.5. Any dimension not within the specified tolerance shall be scored as a defect. The lot size shall be expressed in units of bags. The sample unit shall be one bag. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

4.4.4 Packaging examination. The fully packaged end items shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers. The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and unit pack)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

Materials	Any component missing, damaged, or not as specified
Workmanship	Inadequate application of components, such as: incomplete closure of container flap, loose strapping, improper taping, or inadequate stapling Bulged or distorted container Open or noncontinuous heat-sealed seams and closures of polyethylene bags Incorrectly fabricated polyethylene bag
Content	Number per container is more or less than required

4.4.5 Palletization examination. The fully packaged and palletized end items shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load, fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements
Palletization	Pallet pattern not as specified Load not bonded as specified
Weight	Exceeds maximum load limits
Marking	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A preservation. Each stuff bag shall be folded to the approximate dimensions of 11 inches in length, 9 inches in width, and 1-1/2 inches in depth. The stuff bag shall then be placed in a clear polyethylene bag conforming to type I or II, style 1 or 2 of PPP-B-26 or a plastic bag conforming to A-A-50083. The style 1 polyetheylene bag shall have a 1/4 inch hole located near a bottom corner to allow air to escape.

5.1.2 Commercial. The stuff bag shall be preserved in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial, as specified (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

5.2.1 Level A packing. Twenty-four stuff bags, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of the box shall be approximately 27 inches in length, 11 inches in width, and 12 inches in depth. Each shipping container shall be closed in accordance with Method III, waterproofed in accordance with Method V, and reinforced in accordance with the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.4. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Twenty-four stuff bags, preserved as specified in 5.1, shall be packed in a shipping container. The shipping container shall be a fiberboard box conforming to style RSC-L, type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The inside of each box shall be fitted with a box liner conforming to type CF, class domestic, variety DW, grade 275 of PPP-B-636. Inside dimensions of the box shall be approximately 27 inches in length, 11 inches in width, and 12 inches in depth. Each box shall be closed in accordance with Method II as specified in the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.4.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with the appendix of PPP-B-636, except the inspection shall be in accordance with 4.4.4.

5.2.3 Commercial packing. Stuff bags, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

5.3 Palletization. When specified (see 6.2), stuff bags, packed as specified in 5.2.2 or 5.2.3, shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV, or type V in accordance with MIL-STD-147. Pallets shall be fabricated from wood groups I, II, III, or IV of MIL-STD-731. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means C and D or film bonding means F or G. Pallet pattern shall be number 35 in accordance with the appendix of MIL-STD-147.

5.4 Marking. In addition to any special marking required by the contract or purchase order, shipping containers and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

6.1 Intended use. The stuff bag is intended for use by personnel of the Department of Defense as a container for either the Intermediate Cold Weather Sleeping Systems or the Extreme Cold Weather Sleeping System.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required (see 3.2, 4.3, and 6.3).
d. Levels of preservation and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should also include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.4 Samples. For access to standard samples, address the contracting activity issuing the invitation for bids or request for proposal.

6.5 Subject term (key word) listing.

Carry
Extreme cold weather
ECWSS
Intermediate cold weather
ICWSS

6.6 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Air Force - 99

Review activities:

Army - MD
Navy - MC
Air Force - 82
DLA - CT

User activity:

Air Force - 45

Preparing activity:

Army - GL

(Project 8465-0076)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-B-44306B	1991 September 30

3. DOCUMENT TITLE
BAG, STUFF, SLEEPING SYSTEM

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code) (1) Commercial	(2) AUTOVON/DSN
U.S. Army Natick RD&E Center	508-651-4532	256-4532
c. ADDRESS (Include Zip Code) Commander, U.S. Army Natick RD&E Center ATTN: STRNC-IRT Natick, MA 01760-5019	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

DD Form 1426, OCT 89 NATICK OP2, JUL 91 *Previous editions are obsolete.*

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:20Z
Check the source to verify that this is the current version before use.