MIL-F-44324A
15 April 1988
SUPERSEDING
MIL-F-44324(GL)
1 February 1988

MILITARY SPECIFICATION

FIELD PACK, LARGE, WITH INTERNAL FRAME: AND, PACK, PATROL, COMBAT

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers one type (item 1) large field pack fabricated from woodland camouflage nylon duck, webbings, tape, coated cloth and supported by an internal frame. This document also covers one type (item 2) combat patrol pack also fabricated from woodland camouflage nylon duck, webbing, tape and coated cloth (see 6.1).

1.2 Classification. The large field pack with internal frame, and combat patrol pack shall be classified as follows (see 6.2):

Item 1 - Large field pack with internal frame
Item 2 - Combat patrol pack

2. APPLICABLE DOCUMENTS

2.1 Government documents.

* 2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of the document or by letter.

AMSC N/A FSC 8465

DISTRIBUTION STATEMENT A. Approved for public release; distribution unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

A-A-1668	-	Bag, Plastic, General Purpose, Flat
DDD-L-20	-	Label: For Clothing, Equipage, and Tentage (General Use)
PPP-B-636	-	Boxes, Shipping, Fiberboard

MILITARY

MIL-L-35078	-	Loads, Unit: Preparation of Semiperishable Subsistance Items; Clothing, Personal Equipment and Equipage; General Specification For

STANDARDS

FEDERAL

FED-STD-751	-	Stitches, Seams, and Stitchings

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129	-	Marking for Shipment and Storage
MIL-STD-147	-	Palletized Unit Loads

* 2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY NATICK RESEARCH, DEVELOPMENT, AND ENGINEERING CENTER

2-6-5	-	Pack, Patrol, Combat Assembly
2-6-20	-	Field Pack Assembly, Large, with Internal Frame
2-6-30	-	Harness Release Assembly

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

* 2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3951 - Standard Practice for Commercial Packaging

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

* 2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Samples.

3.1.1 Guide samples. Guide samples, when furnished, are solely for guidance and information (see 6.3). Variations from the document may appear in the sample, in which case the document shall govern.

3.2 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.3, 6.2, and 6.4).

3.3 Materials and components. Materials and components shall be as specified herein and on applicable drawings. Materials and components not definitely specified shall be of the quality normally used by the manufacturer provided the completed item complies with all the provisions of this document (see 6.5).

3.4 Construction. The construction of items 1 and 2 shall conform in all respects to the drawings listed in 2.1.1 and all subsidiary drawings and parts lists for each item as specified herein.

3.4.1 Stitches, seams and stitching. All seams and stitching, except bartacking, shall conform to FED-STD-751 as follows:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

For all stitching except overedge stitching, binding, and piecing	Stitch type 301 6 to 8 stitches per inch.
For prestitching the binding	Stitch type 301, 6 to 8 stitches per inch.

3.4.1.1 Type 301 stitching. Ends of all stitching shall be backstitched or overstitched not less than 1 inch (1/2 inch for box, box-x, and W-W stitching) except where ends are caught in other seams or stitching. Thread tensions shall be maintained so that there will be no loose stitching resulting in loose bobbin or top thread or excessively tight stitching resulting in puckering of the materials sewn. The lock shall be embedded in the materials sewn.

3.4.1.1.1 Repairs of type 301 stitching. Repairs of type 301 stitching shall be as follows:

a. When thread breaks or bobbin run-outs occur during stitching, except prestitching, the stitching shall be repaired by restarting the stitching a minimum of 1 inch (1/2 inch for box, box-x and W-W stitching) back of the end of the stitching.

b. Except for prestitching, thread breaks or two or more consecutive skipped or run-off stitches noted during inspection of the item (in-process or end item) shall be repaired by overstitching. The stitching shall start a minimum of 1 inch in back of the defective area (1/2 inch on box, box-x, and W-W stitching), continue over the defective area and continue a minimum of 1 inch (1/2 inch on box, box-x, and W-W stitching) beyond the defective area onto the existing stitching. Loose or excessively tight stitching shall be repaired by removing the defective stitching without damaging the materials, and restitching in the required manner.

(When making the above repairs in a. and b. above, the ends of the stitching are not required to be backstitched.)

3.4.1.2 Bartacking. Unless otherwise specified, bartacking shall be as follows:

		Tolerance		
Length	Width	Length	Width	Stitches per bartack
1/2 inch	1/8 inch	± 1/16 inch	± 1/32 inch	28
3/4 inch	1/8 inch	± 1/16 inch	± 1/32 inch	42
1 inch	1/8 inch	± 1/16 inch	± 1/32 inch	42
2 inch	1/8 inch	± 1/16 inch	± 1/32 inch	80 to 84

Bartacking shall be free from thread breaks and loose stitching.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the currentversion before use.

3.4.1.3 Automatic stitching. Automatic stitching machines may be used to perform any of the stitch patterns provided the requirements of stitch pattern, stitches per inch, and size and type of thread are met; and at least three tying, overlapping, or backstitches are used to secure the ends of the stitching.

3.4.1.4 Thread ends. All thread ends shall be trimmed to 1/4 inch maximum length.

3.4.1.5 Lubrication of thread. There shall be no lubrication of the thread by any means, prior to or during sewing (see 4.4.1.1).

3.4.2 Setting of eyelets. Holes shall be prepunched to receive the eyelets. Holes prepunched to receive the eyelets shall be smaller than the outside diameter of the eyelet barrel so that the barrel must be forced through the hole.

3.4.2.1 Eyelets. The eyelets shall be securely clinched in a manner that will prevent detachment from, or cutting of, the surrounding material. The eyelets shall be clinched without splitting. The clinched portion of the eyelet shall be on the inside portion of the assembly.

3.4.3 Setting of grommets. Holes shall be prepunched to receive the grommets. Holes prepunched to receive the grommets shall be smaller than the outside diameter of the grommet barrel so that the barrel must be forced through the hole. The grommet shall be securely clinched without cutting the adjacent material.

3.4.4 Setting of snap fasteners. A hole shall be prepunched to receive the button and eyelet components of the snap fasteners. The hole shall be smaller than the outside diameter of the button and eyelet barrels so that the barrel must be forced through the hole. The hole shall not be punched in the setting operation with the button or eyelet barrel. The fasteners shall be securely clinched without cutting the adjacent materials and no more than three splits shall occur in the button or eyelet barrels.

3.4.5 Fusing of ends of nylon cord and webbing. All ends of nylon webbing and cord shall be fused. The apparatus used to fuse the webbing ends shall be capable of providing sufficient heat to provide a smooth edge and with the cut ends of the webbing yarns all fused together. Fusing of the webbing ends shall be accomplished prior to being assembled for stitching.

3.4.6 Location marks. Location marks shall not be drilled. Printed markings shall not be more than 1/32 inch in width.

3.4.7 Repairs. Repairs such as mends, darns, patches or splices are not permitted on the large field pack or combat patrol pack.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the currentversion before use.

3.4.8 Replacement of defective components. During the spreading, cutting and manufacturing process, components having material defects or damages that are classified as defects in table I (item 1) or table II (item 2) shall be removed from production and replaced with nondefective and properly matched components.

3.5 Markings. Each end item shall be marked separately. The identification marking shall be applied in the location shown on the drawing for each item and shall conform to type IV, class 5 of DDD-L-20. The item description for item 1 shall read FIELD PACK, LARGE, WITH INTERNAL FRAME. The item description for item 2 shall read PACK, PATROL, COMBAT. The letters "US" shall be applied in the location and in the size characters indicated on the drawings for each item and shall conform to type IV, class 9 of DDD-L-20. Fastness of class 9 marking shall be as specified for class 5 marking. The instruction marking for hand washing the field pack and the combat patrol pack shall be applied directly on the polyurethane coated cloth as shown on the drawing and shall conform to type IV, class 3 of DDD-L-20 and shall show colorfastness to laundering. The hand washing instruction shall be printed in letters 1/8 inch high. The contents of the hand washing shall be the same for each item except for the title and shall be as follows:

FIELD PACK, LARGE, WITH INTERNAL FRAME 1/

PACK, PATROL, COMBAT 2/

Hand Washing:

1. Scrape dirt/dust from item using a brush or flat stick which will not cut fabric/webbing.

2. Wash item in a pail of warm water using mild detergent or soap.

3. Rinse "thoroughly" in clean warm water.

4. DO NOT USE CHLORINE BLEACH, YELLOW SOAP, CLEANING FLUIDS OR SOLVENTS - WILL DISCOLOR/DETERIORATE THE ITEM.

5. Dry item in shade or indoors.

6. DO NOT DRY IN DIRECT SUNLIGHT, DIRECT HEAT OR OPEN FLAME.

7. DO NOT LAUNDER OR DRY ITEM IN FIXED/COMMERCIAL/HOME-TYPE LAUNDRY EQUIPMENT.

8. DO NOT ATTEMPT TO DYE ITEM OR REPAIR IT. TURN IN FOR REPAIR/REPLACEMENT.

1/ Applicable to item 1.

2/ Applicable to item 2.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the currentversion before use.

3.6 Patterns. Standard patterns for textile components other than tape or webbing are shown full scale on drawings and provide allowances for all seams and shall be used for making working patterns. The standard patterns shall not be altered in any way.

3.7 Workmanship. The large field pack and combat patrol pack shall conform to the quality of product established by this document and occurrence of defects shall not exceed the applicable acceptable quality levels.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this document where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the document shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.1.2 Responsibility for dimensional requirements. Unless otherwise specified in the contract or purchase order, the contractor is responsible for assuring that all specified dimensions have been met. When dimensions cannot be examined on the end item, inspection shall be made at any point, or at all points in the manufacturing process necessary to assure compliance with all dimensional requirements.

4.2 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection. When a first article is required (see 6.2), it shall be examined for the defects specified in 4.4.3, 4.4.4 and 4.4.5. The presence of any defect shall be cause for rejection of the first article.

4.4 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the currentversion before use.

4.4.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.4.1.1 Certification. The contractor shall furnish a certificate of compliance for the requirement of 3.4.1.5 prohibiting use of thread lubricants prior to or during sewing.

* 4.4.2 In-process inspection. Inspection shall be made at any point or during any phase of the manufacturing process to determine whether cut lengths, cut parts, markings for location of components, location of assembled component parts, fused webbing on the quick release assembly (item 3 on Drawing 2-6-30) are in accordance with specified requirements. Whenever nonconformance is noted, corrections shall be made to the parts affected and lot in-process. Components which cannot be corrected shall be removed from production.

4.4.3 End item inspection.

4.4.3.1 Large field pack visual examination. The large field pack shall be examined for the defects listed in table I. The lot size shall be expressed in units of large field packs. The sample unit shall be one completely fabricated large field pack. The inspection level shall be II and the acceptable quality level (AQL), expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE I. End item visual defects, large field pack

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet).	X	
	Shade bar or abrasion mark.		X
	Defective or partially omitted coating.		X
Webbing or tape	Any hole, cut, tear, or smash.	X	
	Not firmly and tightly woven, edges frayed or scalloped.	X	
	Multiple floats.		X
	Abrasion mark, slub, or broken end or pick.	X	
	Cut ends of webbing not fused as specified.	X	

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the currentversion before use.

TABLE I. End item visual defects, large field pack (cont'd)

Examine	Defect	Classification Major	Minor
Hardware	Broken or malformed, failing to serve intended purpose, corroded area, burr or sharp edge.	X	
	Finish omitted or not as specified: - on brass or aluminum components		X
	- on steel components.	X	
	Area of partial or no finish.		X
	Any required component improperly installed causing failure to serve intended purpose.	X	
	Not assembled as specified.	X	
	Size or type not as specified.	X	
Snap fasteners	Any fastener not functioning properly i.e., fails to snap closed, provide a secure closure or to open freely.	X	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material.	X	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use.		X
	Clinched loosely to the degree that components can be expected to become detached during use.	X	
	NOTE: Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
Drawstrings	Cut, chafed, or abraded.	X	
	Ends not fused.		X
	Not threaded through grommets or knotted as specified.		X
	Omitted.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, large field pack (cont'd)

Examine	Defect	Classification Major	Classification Minor
Clamp cord	Reversed.		X
Side pockets	Not attached as specified.		X
Brass grommets and eyelets	Clinched excessively tight, cutting adjacent material.	X	
	Insecurely clinched to a degree that grommet or eyelet may be detached from material.	X	
	Washer installed on incorrect side of material.		X
	Eyelet barrel split.		X
Eyelets, aluminum	Insecurely clinched; clinched excessively tight, cutting fabric.	X	
	Not set with scored setting.	X	
	Installed with scored side on outside.		X
Slide fastener	Not functioning properly, failing to effect a secure closure or to open freely.	X	
	Not specified type or size.	X	
	Slider jams or fails to interlock.	X	
	Thong omitted.	X	
	Fastener tape cut or torn.	X	
Open seam	1/2 inch or less.		X
	More than 1/2 inch.	X	
NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, large field pack (cont'd)

Examine	Defect	Classification Major	Classification Minor
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching.		X
NOTE:	Raw edge not securely caught in stitching shall be classified as an open seam.		
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type.	X	
Bartacks	Any bartack omitted.	X	
	Any bartack not as specified or not in specified location.		X
	Loose stitching, incomplete or broken.		X
Stitch tension	Loose, resulting in loose bobbin or top thread.		X
	Excessively tight, resulting in puckering of material.		X
Stitches per inch	Up to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
NOTE:	Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corner shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, large field pack (cont'd)

Examine	Defect	Classification Major	Classification Minor
Stitching ends	Not secured as specified.		X
Thread breaks, skipped stitches, or run-offs	Not overstitched as specified.		X
NOTE:	Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams.		
Rows of stitching	Any row missing except on box, box-x, and W-W stitching.	X	
	On box, box-x, and W-W stitching: - one row of stitching omitted.		X
	- two or more rows of stitching omitted.	X	
Component and assembly	Any component part omitted or not as specified or any operation omitted or not as specified (unless otherwise classified herein).	X	
	Needle chews.	X	
	Any mend, darn, patch, splice or other unauthorized repair.	X	
	Any material pleated or caught in stitching where not specified.		X
Torso-trac	Aluminum back plate not knurled as specified.	X	
	Not sewn as specified.	X	
	Does not slide by hand when screws are loose.	X	
Binding	Loosely applied but not exposing raw edge of material.		X
	Loosely applied exposing raw edge of material.	X	
	Ends of binding on pocket flap not caught in seams.		X
Darts (on pouch and large pocket flap)	One or more omitted.		X
	Not formed and sewn separately on pouch flap pocket as specified.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE I. End item visual defects, large field pack (cont'd)

Examine	Defect	Classification Major	Minor
Pocket and flaps	Pocket or flap not formed as specified.		X
	Flaps improperly set or distorted failing to effect a full and smooth closure.	X	
Cleanness	Grease, oil, dirt, or ink stains clearly noticeable.		X
	Thread end not trimmed as specified.		X
Location markings	Drilled.	X	
	Printed marking more than 1/32 inch width or not covered by component part.		X
Markings: US, identification, and instructions	Omitted, incorrect, illegible, misplaced, or size of characters not as specified.		X

4.4.3.2 Combat patrol pack visual examination. The combat patrol pack shall be examined for the defects listed in table II. The lot size shall be expressed in units of combat patrol packs. The sample unit shall be one completely fabricated combat patrol pack. The inspection level shall be II and the AQL, expressed in terms of defects per hundred units, shall be 2.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE II. End item visual defects, combat patrol pack

Examine	Defect	Classification Major	Minor
Fabric	Hole, cut, tear, smash, broken or missing yarn, or open place clearly visible at normal inspection distance (approximately 3 feet).	X	
	Shade bar or abrasion mark.		X
	Defective or partially omitted coating.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, combat patrol pack (cont'd)

Examine	Defect	Classification Major	Minor
Webbing or tape	Any hole, cut, tear, or smash.	X	
	Not firmly and tightly woven, edges frayed or scalloped.	X	
	Multiple floats.		X
	Abrasion mark, slub, or broken end or pick.	X	
	Cut ends of webbing not fused as specified.	X	
Hardware	Broken or malformed, failing to serve intended purpose, corroded area, burr, or sharp edge.	X	
	Finish omitted or not as specified on brass components		X
	Area of partial or no finish.		X
	Any required component improperly installed causing failure to serve intended purpose.	X	
	Not assembled as specified.	X	
	Size or type not as specified.	X	
Snap fasteners	Any fastener not functioning properly i.e., fails to snap closed, to provide a secure closure, or to open freely.	X	
	NOTE: The fasteners shall be snapped and unsnapped twice to determine whether parts of fastener separate freely and also effect a secure closure.		
	Clinched excessively tight, cutting adjacent material.	X	
	Clinched loosely, permitting any component to rotate freely but not to the degree that any component can be expected to become detached during use.		X
	Clinched loosely to the degree that components can be expected to become detached during use.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, combat patrol pack (cont'd)

Examine		Defect	Classification Major	Minor
Snap fasteners (cont'd)	NOTE:	Incomplete roll of end of button or eyelet barrel is evidence of improper and insecure clinching.		
Drawstrings		Cut, chafed, or abraded.	X	
		Ends not fused.		X
		Not threaded through grommets or knotted as specified.		X
		Omitted.	X	
Back pocket		Not attached as specified.		X
Brass grommets		Clinched excessively tight, cutting adjacent material.	X	
		Insecurely clinched to a degree that grommet or eyelet may be detached from material.	X	
Slide fastener		Not functioning properly, failing to effect a secure closure or to open freely.	X	
		Not specified type or size.	X	
		Slider jams or fails to interlock.	X	
		Thong omitted.	X	
		Fastener tape cut or torn.	X	
Open seam		1/2 inch or less.		X
		More than 1/2 inch.	X	
	NOTE:	A seam shall be classified as open when one or more stitches joining a seam are broken or when two or more consecutive skipped or run-off stitches occur. On double stitched seams, a seam shall be considered open when either one or both sides of the seam are open.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, combat patrol pack (cont'd)

Examine	Defect	Classification Major	Classification Minor
Raw edge (on edge required to be finished)	More than 1/2 inch when securely caught in stitching.		X
NOTE:	Raw edge not securely caught in stitching shall be classified as an open seam.		
Run-off (see open seam)			
Seam and stitch type	Wrong seam or stitch type.	X	
Bartacks	Any bartack omitted.	X	
	Any bartack not as specified or not in specified location.		X
	Loose stitching, incomplete or broken.		X
Stitch tension	Loose, resulting in loose bobbin or top thread.		X
	Excessively tight, resulting in puckering of material.		X
Stitches per inch	Up to two stitches less than minimum specified.		X
	Three or more stitches less than minimum specified.	X	
	One or more stitches in excess of maximum specified.		X
NOTE:	Variation in the number of stitches per inch caused by the operator speeding up the machine and pulling the fabric in order to sew over heavy seams, or in turning corner shall be classified as follows: (a) Within the minor defect classification - no defect. (b) Within the major defect classification - minor defect.		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, combat patrol pack (cont'd)

Examine	Defect	Classification Major	Minor
Stitching ends	Not secured as specified.		X
Thread breaks, skipped stitches, or run-offs	Not overstitched as specified.		X
	NOTE: Thread breaks or two or more consecutive skipped or run-off stitches not overstitched shall be classified as open seams.		
Rows of stitching	Any row missing except on box, box-x, and W-W stitching.	X	
	On box, box-x, and W-W stitching:		
	- one row of stitching omitted.		X
	- two or more rows of stitching omitted.	X	
Components and assembly	Any component part omitted or not as specified or any operation omitted or not as specified (unless otherwise classified herein).	X	
	Needle chews.	X	
	Any mend, darn, patch, splice or other unauthorized repair.	X	
	Any material pleated or caught in stitching where not specified.		X
Binding	Loosely applied but not exposing raw edge of material.		X
	Loosely applied exposing raw edge of material.	X	
	Ends of binding on pocket flap not caught in seams.		X
Darts (outside pocket flap)	One or more omitted.		X
	Not formed and sewn separately on pouch flap pocket as specified.	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE II. End item visual defects, combat patrol pack (cont'd)

Examine	Defect	Classification Major	Minor
Pocket and flaps	Pocket or flap not formed as specified.		X
	Flaps improperly set or distorted failing to effect a full and smooth closure.	X	
Cleanness	Grease, oil, dirt, or ink stains clearly noticeable.		X
	Thread end not trimmed as specified.		X
Location markings	Drilled.	X	
	Printed marking more than 1/32 inch width or not covered by component part.		X
Markings: US, identification, and instructions	Omitted, incorrect, illegible, misplaced, or size of characters not as specified.		X

4.4.4 End item dimensional examination. The large field pack or combat patrol pack, as applicable, shall be examined for the defects listed in table III. The lot size shall be expressed in units of large field packs or combat patrol packs. The sample unit shall be one completely fabricated large field pack or combat patrol pack. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 6.5 for major defects and 15.0 for total (major and minor combined) defects.

TABLE III. End item dimensional examination

Examine	Defect	Classification Major	Minor
Dimensions (overall)	Smaller than nominal dimensions less applicable minus tolerance indicated on drawings, but not smaller than nominal dimensions less twice the applicable minus tolerance.		X
	Smaller than nominal dimensions less twice the applicable minus tolerance.	X	
	Larger than nominal dimensions and applicable plus tolerance.		X

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

TABLE III. End item dimensional examination (cont'd)

Examine	Defect	Classification Major	Classification Minor
Component and location dimensions	Not within specified tolerance.		X
Stitch margin or gage	Not within specified tolerance.		X
Box, box-x, and W-W stitching	Dimensions not within specified tolerance.		X
Brass eyelets	Not spaced on equipment hangers within specified dimensions (large field pack only).		X
Grommets	Set off center on hems by more than 1/4 inch.		X

4.4.5 End item fit examination. The large field pack or combat patrol pack, as applicable, shall be examined for the defects listed below. The lot size shall be expressed in units of large field packs or combat patrol packs. The sample unit shall be one completely fabricated large field pack or combat patrol pack. The inspection level shall be S-3 and the AQL, expressed in terms of defects per hundred units, shall be 0.65.

Examine	Defect
Fit of gauge in radio pocket (gauge is to simulate the size of AN/PRC25 or 77 radio	Pocket too small, i.e., gauge fails to fit radio pocket. (combat patrol pack has zippered pocket on the inside)
	The tie down straps on the combat patrol pack shall securely hold radio.
	The gauge shall be fully inserted in the radio pocket without effort other than that required to overcome friction between gauge and pocket.

NOTE: Fit examination shall be performed with an 11 by 11 by 5-1/2 inch wooden gauge.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

4.4.6 Packaging examination. The fully packaged end items (large field pack or combat patrol pack) shall be examined for the defects listed below. The lot size shall be expressed in units of shipping containers (large field pack or combat patrol pack). The sample unit shall be one shipping container fully packaged. The inspection level shall be S-2 and the AQL, expressed in terms of defects per hundred units, shall be 2.5.

Examine	Defect
Marking (exterior and unit pack)	Omitted; incorrect; illegible; of improper size, location, sequence, or method of application.
Materials	Any component missing, damaged, or not as specified for applicable item.
Workmanship	Inadequate application of components, such as: incomplete sealing or closure of container flap, loose strapping, improper taping, or inadequate stapling. Bulged or distorted container.
Content	Number per container is more or less than required for applicable item.

4.4.7 Palletization examination. The fully packaged and palletized end items (large field pack or combat patrol pack) shall be examined for the defects listed below. The lot size shall be expressed in units of palletized unit loads. The sample unit shall be one palletized unit load (large field pack or combat patrol pack), fully packaged. The inspection level shall be S-1 and the AQL, expressed in terms of defects per hundred units, shall be 6.5.

Examine	Defect
Finished dimensions	Length, width, or height exceeds specified maximum requirements.
Palletization	Pallet pattern not as specified for applicable item. Interlocking of loads not as specified. Load not bonded with required straps as specified.
Weight	Exceeds maximum load limits for applicable item.
Marking	Omitted, incorrect, illegible, of improper size, location, sequence, or method of application.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or Commercial as specified (see 6.2).

5.1.1 Level A. Each large field pack or combat patrol pack with all flaps closed, fasteners secured, and straps cinched to form a compact unit, shall be placed individually in a snug-fitting plastic bag conforming to A-A-1668.

5.1.2 Commercial. Large field packs or combat patrol packs shall be preserved individually in accordance with ASTM D 3951.

5.2 Packing. Packing shall be level A, B, or Commercial as specified (see 6.2).

5.2.1 Level A packing. Six large field packs or twelve combat patrol packs, preserved as specified in 5.1, shall be neatly packed in a fiberboard shipping container conforming to style RSC-L, grade V2s of PPP-B-636. The inside of each fiberboard container shall be fitted with a box liner conforming to type CF, class weather-resistant, variety DW, grade V15c of PPP-B-636. Inside dimensions of each shipping container shall approximate 26 inches in length, 18-1/2 inches in width, and 21 inches in depth for the large field packs and 18 inches in length, 12 inches in width, and 18 inches in depth for the combat patrol packs. Approximate dimensions are furnished as a guide only. Each shipping container shall be closed in accordance with method III, waterproofed in accordance with method V, and reinforced in accordance with the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.6. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.2). Strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Six large field packs or twelve combat patrol packs, preserved as specified in 5.1, shall be neatly packed in a fiberboard shipping container as specified in 5.2.1, except that the fiberboard shall be type CF (variety SW) or SF, class domestic, grade 275 of PPP-B-636. The box liner shall conform to class domestic, variety DW, grade 275, and closure shall be in accordance with method II of PPP-B-636 except that the inspection shall be in accordance with 4.4.6.

5.2.2.1 Weather-resistant fiberboard containers. When specified (see 6.2), the fiberboard shipping container shall be a grade V3c, V3s, or V4s fiberboard box fabricated in accordance with the appendix of PPP-B-636 and closed in accordance with method III, as specified in the appendix of PPP-B-636 except that the inspection shall be in accordance with 4.4.6.

5.2.3 Commercial packing. Large field packs or combat patrol packs, preserved as specified in 5.1, shall be packed in accordance with ASTM D 3951.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

5.3 Palletization. When specified (see 6.2), large field packs or combat patrol packs packed as specified in 5.2.2 and 5.2.3 shall be palletized on a 4-way entry pallet in accordance with load type Ia of MIL-STD-147. Pallet type shall be type I (4-way entry), type IV , or type V in accordance with MIL-STD-147. Each prepared load shall be bonded with primary and secondary straps in accordance with bonding means K and L or film bonding means O or P. Pallet pattern shall be number 90 for large field packs and pallet pattern number 8 shall be used for combat patrol packs. Interlocking of loads shall be effected by reversing the pattern of each course.

5.4 Marking. In addition to any special marking required by the contract or purchase order, unit packs, shipping containers, and palletized unit loads shall be marked in accordance with MIL-STD-129 or ASTM D 3951, as applicable.

5.4.1 Plastic bagged unit packs. Plastic bagged unit packs shall have the required identification information legibly printed or stamped in black, directly on the bag across the center face or on a white paper label inserted within the bag, so as to permit ready identification.

6. NOTES

6.1 Intended use. The large field pack with internal frame and detachable combat patrol pack are designed to carry existence loads which may include clothing, personal items, and rations. Hangers are provided for carrying individual equipment. The large field pack and combat patrol pack each have a pocket to accommodate the AN/PRC25 or 77 radios. The field pack is carried on the soldiers back and has an adjustable shoulder strap suspension system. The detachable combat patrol pack is used to carry mission essential items on short duration missions and also to serve as a top cover for the large field pack.

6.2 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. Item required (see 1.2).
c. When a first article sample is required (see 3.2, 4.3, and 6.4).
d. Selection of applicable levels of preservation, and packing (see 5.1 and 5.2).
e. Type and class of unit load required (see 5.2.1).
f. When weather-resistant grade fiberboard shipping containers are required for level B packing (see 5.2.2.1).
g. When palletization is required (see 5.3).

6.3 Samples. For access to standard samples, address the contracting activity issuing the invitation for bids.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:27Z
Check the source to verify that this is the current version before use.

* 6.4 Plastic hardware. A source of supply for the plastic hardware used on this item is ITW NEXUS, Division of Illinois Tool Works Inc., 201 Scott Street, Elk Grove Village, IL 60007.

6.5 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should specify the appropriate type of first article and the number of units to be furnished. The contracting officer should include specific instructions in all acquisition instruments regarding arrangements for selection, inspection, and approval of the first article.

6.6 Recycled material. It is encouraged that recycled material be used when practical as long as it meets the requirements of the document (see 3.3).

6.7 International standardization agreements. Certain provisions of this document are the subject of international standardization agreement number STANAG 2311. When amendment, revision, or cancellation of this agreement is proposed which will effect or violate the international agreement concerned, the preparing activity will take appropriate reconciliation action through international standardization channels including departmental standardization offices, if required.

6.8 Subject term (key word) listing.

Pack, combat
Pack, field
Pack, large
Pack, patrol

* 6.9 Changes from previous issue. The margins of this document have been marked with an asterisk (*) to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Goverment assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document basesd on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

Custodians:

Army - GL
Navy - NU
Air Force - 99

Review activities:

Army - MD
Air Force - 82
DLA - CT
Navy - YD

User activities:

Navy - MC
Air Force - 45

Preparing activity:

Army - GL

Project No. 8465-0004

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

U.S. ARMY NATICK RESEARCH, DEVELOPMENT
and ENGINEERING CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
U.S. Army Natick Research, Development
and Engineering Center
ATTN: STRNC-ES
Natick, MA 01760-5014

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-F-44324A	Field Pack, Large, w/Internal Frame: and, Pack, Patrol, Combat

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK OP-1, Feb 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:27Z
Check the source to verify that this is the current version before use.