MIL-M-44310
23 December 1987
SUPERSEDING
PP-M-002205 (Army GL)
31 December 1984

MILITARY SPECIFICATION

MEATBALLS WITH RICE IN TOMATO SAUCE AND CABBAGE, THERMOSTABILIZED, TRAY PACK

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This document covers meatballs with rice in tomato sauce and cabbage thermostabilized in tray pack cans for use by the Department of Defense as a component of operational rations.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Documents. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

FEDERAL

TT-C-495	-	Coatings, Exterior, for Tinned Food Cans
PPP-B-636	-	Boxes, Shipping, Fiberboard

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: U.S. Army Natick Research, Development, and Engineering Center, Natick, MA 01760-5014 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 8940

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-L-1497 - Labeling of Metal Cans for Subsistence Items
MIL-L-35078 - Loads, Unit: Preparation of Semiperishable Subsistence Items; Clothing, Personal Equipment and Equipage; General Specification for

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-129 - Marking for Shipment and Storage
MIL-STD-900 - Bacterial Standards for Starches, Flours, Cereals, Alimentary Pastes, Dry Milks, and Sugars Used in the Preparation of Thermostabilized Foods for the Armed Forces.

(Copies of documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.1.2 Other Government documents. The following other Government documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

U.S. DEPARTMENT OF HEALTH AND HUMAN SERVICES

Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder (21 CFR Parts 1-199)

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

U.S. DEPARTMENT OF AGRICULTURE (USDA)

U.S. Standards for Milled Rice

(Applications for copies should be addressed to the Federal Grain Inspection Service, Resource Management Division, 14th and Independence Avenue, SW, Washington, DC 20250.)

U.S. Standards for Grades of Tomato Paste

(Application for copies should be addressed to the Chief, Processed Products Branch, Fruit and Vegetable Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

Meat and Poultry Inspection Regulations

(Application for copies should be addressed to the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402.)

Institutional Meat Purchase Specifications for Fresh Beef, Series 100

(Application for copies should be addressed to the Director, Livestock and Seed Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

U.S. Standards for Condition of Food Containers

(Application for copies should be addressed to the Director, Market Research and Development Division, Agricultural Marketing Service, U.S. Department of Agriculture, Washington, DC 20250.)

ENVIRONMENTAL PROTECTION AGENCY (EPA)

National Primary Drinking Water Regulations

(Application for copies should be addressed to the Office of Drinking Water, Environmental Protection Agency, WH550D, 401 M Street, S.W. Washington, DC 20460.)

2.2 Other publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issues of the nongovernment documents which are current on the date of the solicitation.

AMERICAN ASSOCIATION OF CEREAL CHEMISTS (AACC)

Approved Methods of the American Association of Cereal Chemists

(Application for copies should be addressed to the American Association of Cereal Chemists, 3340 Pilot Knob Road, St. Paul, MN 55121.)

AMERICAN DEHYDRATED ONION AND GARLIC ASSOCIATION (ADOGA)

Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

(Application for copies should be addressed to the American Dehydrated Onion and Garlic Association, 650 California Street, Suite 800, San Francisco, CA 94108.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

ASSOCIATION OF OFFICIAL ANALYTICAL CHEMISTS (AOAC)

Official Methods of Analysis of the Association of Official Analytical Chemists

(Application for copies should be addressed to the Association of Official Analytical Chemists, 1111 North 19th Street, Suite 210, Arlington, VA 22209.)

NATIONAL ACADEMY OF SCIENCES

Food Chemicals Codex

(Application for copies should be addressed to the National Academy Press, 2101 Constitution Avenue, N.W., Washington, DC 20418.)

(Technical society and technical association documents are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

2.3 Order of precedence. In the event of conflict between the text of this document and the references cited herein, the text of this document shall take precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order, a sample shall be subjected to first article inspection (see 4.4, 6.1, and 6.3).

3.2 Ingredients. All ingredients shall be clean, sound, wholesome, and free from foreign material, evidence of rodent and insect infestation, extraneous material, off-odors, off-flavors, and off-colors.

3.2.1 Beef. The beef shall be from steers, heifers, or cows and shall be derived from any combination of carcasses, quarters, and any of the following recognizable primal and subprimal cuts: square-cut chucks, shoulder clods, chuck rolls, ribs, ribeyes, trimmed full loins, trimmed short loins, strip loins, sirloins, top sirloin butts, rounds, top rounds, peeled knuckles, and bottom rounds. Recognizable cuts are those which, when compared to Institutional Meat Purchase Specifications (IMPS) cuts, have no more than a minor amount of lean, fat, or bone removed or included from an adjacent cut. All suitable lean meat shall be used, except tenderloins, rib fingers (intercostal meat), and any part of a rough cut may be excluded at the option of the contractor. The beef shall be in the fresh-chilled state and shall be in excellent condition; i.e., exposed lean and fat surfaces shall be of a color and bloom normally associated with the class, grade, and cut of meat, and typical of

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

meat which has been properly stored and handled. Cut surfaces and naturally exposed lean surfaces shall show no more than slight darkening or discoloration due to dehydration, aging, or microbial activity. The fat shall show no more than a very slight discoloration due to oxidation or microbial activity. No odors foreign to fresh meat shall be present. Changes in color and odor characteristically associated with vacuum-packaged meat in excellent condition shall be acceptable. Also, the meat shall show no evidence of freezing, defrosting, or mishandling.

3.2.1.1 Boning and trimming. The beef shall be boned and trimmed to remove objectionable material such as bone, cartilage, heavy connective tissue, etc. The boneless, trimmed beef shall meet the limitations specified in tables I and II.

3.2.1.2 Handling and storage. Handling and storage of the boned and trimmed beef prior to processing into the finished product shall be in accordance with the following requirements:

a. Beef processed on the day of initial certification shall be maintained in the temperature range of 28° to 50°F (inclusive).

b. Holding in the fresh-chilled state for not more than 4 days after initial certification is permitted provided that the beef is maintained in the temperature range of 28° to 40°F (inclusive).

c. Holding in the frozen state for not more than 120 days after initial certification is permitted provided that the beef is:

- frozen to 0°F or lower within 72 hours after initial certification
- stored at 0°F or lower
- protected from freezer deterioration and damage
- stored in containers that are adequate to maintain product excellence
- held after storage at an internal temperature not to exceed 40°F when further processing is resumed.

3.2.2 Cabbage, green, fresh. Cabbage shall be fresh, firm, mature, and of a variety suitable for canning.

3.2.3 Rice, long grain, parboiled. Rice shall be parboiled, long grain, milled rice, U.S. No. 1 in accordance with the U.S. Standards for Milled Rice. The rice shall be of such varieties as Belle patina, Bluebelle, Bluebonnet, Lebonnet or similar varieties. The rice shall contain not more than 2 percent of kernels having white ungelatinized areas and not less than 10 percent or more than 15 percent moisture.

3.2.4 Water. Water used for ice making, formulation, blanching, and washing shall conform to the National Primary Drinking Water Regulations.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

3.2.5 Tomato paste. Tomato paste shall be U.S. Grade A paste conforming to the U.S. Standards for Grades of Tomato Paste.

3.2.6 Sugar. Sugar shall be white, refined, sucrose, liquid or granulated, cane or beet sugar, or a combination thereof. The sugar shall comply with the requirements of MIL-STD-900.

3.2.7 Starch, waxy maize, modified. The starch shall be white, odorless finely pulverized, modified waxy maize starch for use in canned foods and shall comply with MIL-STD-900. The modified starch shall demonstrate initial viscosity development in the temperature range of 140° to 170°F and a typical viscosity (be fully hydrated) at common retort temperatures. The starch shall resist breakdown at low pH, under shear stress, and under conditions of cold storage. The cooked modified starch slurry shall be bland with essentially no cereal or starch taste.

3.2.8 Lecithin. Lecithin shall comply with the Food Chemicals Codex.

3.2.9 Salt. Salt shall be noniodized, white, refined, sodium chloride with or without anticaking agents and shall comply with purity standards for sodium chloride of the Food Chemicals Codex.

3.2.10 Pepper, black, ground. Ground black pepper shall have been ground from the deep brown to black, deep-set, wrinkled immature berries of Piper nigrum L. The ground pepper shall have a characteristic penetrating odor, a hot biting pungent flavor, and a light grey to speckled black-grey color. The ground pepper shall contain not less than 2.0 mL of volatile oil per 100 grams of black pepper and shall be of such size that not less than 95 percent shall pass through a U.S. Standard No. 16 sieve.

3.2.11 Onions, chopped, dehydrated. Chopped dehydrated onions shall be fancy grade of the Official Standards and Methods of the American Dehydrated Onion and Garlic Association for Dehydrated Onion and Garlic Products.

3.2.12 Worcestershire sauce. Worcestershire sauce shall be a brown to dark brown colored liquid and shall possess a pleasant, tart, peppery, fruit-spice flavor with a typical heavy viscosity. The sauce shall have a titratable acidity (as acetic acid) of not less than 2.8 nor more than 3.8 percent.

3.2.13 Basil, ground. Ground basil shall be derived from the dried leaves of Ocimum basilicum L. and shall possess a sweet anise-like odor and aromatic, warm, slightly pungent flavor. A minimum of 95 percent, by weight, shall pass through a U.S. Standard No. 35 sieve. The volatile oil content shall be not less than 0.4 mL per 100 grams of ground basil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

3.2.14 Preblended spice and seasoning mixture. Preblended spices and seasonings may be used. The spices and seasonings in the mixture shall comply with the requirements of this document. The containers used for the spice and seasoning blend shall be labeled with each ingredient and the percentage of each ingredient in the blend. The ingredients shall be in the same proportions as specified in the ingredient formula.

3.3 Preparation and processing. Processing shall be on a continuous basis.

3.3.1 Beef preparation. Boned and trimmed beef meeting the requirements of 3.2.1.1 shall be further trimmed, if necessary, so as to assure compliance with finished product requirements (see 3.6). The beef shall be ground once through a plate having holes 3/16 inch in diameter. The ground beef shall be maintained for not more than 24 hours in the temperature range of 28° to 40°F prior to meatball preparation (see 3.3.5).

3.3.2 Cabbage preparation. The cabbage heads shall be cored, chopped into strips approximately 1-inch wide by 2 inches long and blanched sufficiently to prevent discoloration and to remove excess air. The blanched cabbage strips shall be immediately cooled to the initial temperature of the cooling water and thoroughly drained. The blanched cabbage shall be handled in a manner to prevent discoloration and filled into the tray pack can within 4 hours after blanching.

3.3.3 Rice preparation. The rice shall be soaked in room temperature water (approximately 70°F) until the rice has gained approximately 70 percent of its original weight. After soaking, the rice shall be placed in a cooler to lower the temperature to 40°F prior to mixing with the ground beef.

3.3.4 Sauce preparation. The sauce shall be formulated and prepared as follows:

Ingredients	Percent by weight
Water	74.05
Tomato paste (26 percent solids) 1/	21.88
Sugar	1.90
Starch, waxy maize, modified	1.75
Lecithin	0.25
Salt 2/	0.15
Pepper, black, ground	0.02

1/ If the specified tomato solids are not available, the tomato solids that are used must be calculated to bring the solid level to that specified.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

2/ The total amount of salt in the sauce formula shall be adjusted as necessary to produce a product that complies with the finished product salt requirements (see 3.6).

a. The starch and part of the water shall be mixed to form a slurry.

b. The remaining ingredients shall be mixed together and heated to 190° to 200°F.

c. The starch slurry shall be added and the final mixture heated to 180° to 190°F, and held in this temperature range for approximately 5 minutes.

d. The volume of the final mixture shall be adjusted with water to compensate for evaporation loss during heating and holding.

e. The sauce shall be maintained in the temperature range of 150° to 180°F for not more than 4 hours prior to tray pack filling.

3.3.5 Meatball preparation. The meatballs shall be formulated and prepared as follows:

Ingredients	Percent by weight
Beef, ground	76.25
Rice	18.91
Onions, chopped, dehydrated	1.80
Worcestershire sauce	1.75
Salt	1.25
Pepper, black, ground	0.02
Basil, ground	0.02

The above ingredients shall be mixed together and formed into approximately 2-1/4 ounce meatballs. Once formed, the temperature of the meatballs shall be not greater than 40°F (there shall be no evidence of freezing) and shall be held for not more than 4 hours prior to filling into tray pack cans.

3.4 Tray pack filling and sealing. Each tray pack can (see 5.1.1) shall be filled with 18 ounces of blanched cabbage, and sufficient meatballs and sauce such as to conform to the finished product requirements and to the following requirements.

a. A multi-stage filling operation shall be used.

b. The product shall be filled into the tray pack can in the following order: cabbage strips, meatballs, and then sauce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

c. Each can shall be hermetically sealed under a vacuum established by a processing authority and specified in the scheduled process so as to assure compliance with the finished product requirement (see 3.6s).

d. The filled and sealed tray pack cans shall be in the retort process within two hours after sealing.

3.5 Tray pack thermoprocessing. The filled and sealed tray pack cans shall be thermostabilized by retorting until a sterilization value (F_o) of not less than 6 has been achieved.

3.6 Finished product requirements. The finished product shall comply with the following requirements.

a. There shall be no foreign material such as, but not limited to, dirt, insect parts, hair, wood, glass, or metal.

b. There shall be no foreign odor or flavor such as, but not limited to, burnt, scorched, stale, sour, rancid, or moldy.

c. There shall be no color foreign to the product.

d. Total weight of cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in any individual can shall be not more than 1 ounce.

e. No individual can shall contain a bone piece measuring 0.3 inch or more in any dimension.

f. The average net weight shall be not less than 106 ounces.

g. No individual can shall contain less that 104 ounces of product.

h. There shall be not less than 24 intact meatballs in each can.

i. Drained weight of 24 meatballs in an individual can shall be not less than 48.0 ounces.

j. The average drained weight of meatballs shall be not less than 52.0 ounces.

k. Cabbage strips shall retain their identity and not be mushy or tough.

l. Meatballs shall not be dry, tough, rubbery, or mushy.

m. Meatballs shall be uniform in size and shape.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

n. Sauce consistency shall not be lumpy or excessively thick or thin.

o. The average fat content shall be not greater than 10.0 percent.

p. The fat content of any individual tray pack shall be not greater than 12.0 percent.

q. The salt content of any individual tray pack shall be not less than 0.5 percent nor greater than 1.3 percent.

r. The product shall show no evidence of excessive heating (materially darkened or scorched).

s. Filled, sealed, and retorted cans shall show evidence of proper vacuum as determined by concavity of the can lid (see 4.5.6).

3.6.1 Palatability. The finished product shall be equal to or better than the preproduction sample (see 6.1) in palatability and overall appearance.

3.7 Plant qualification. The beef component and the finished product shall originate and be produced, processed, and stored in plants regularly operating under Meat and Poultry Inspection Regulations of the U.S. Department of Agriculture.

3.8 Federal Food, Drug, and Cosmetic Act. All deliveries shall conform in every respect to the provisions of the Federal Food, Drug, and Cosmetic Act and regulations promulgated thereunder.

4. QUALITY ASSURANCE PROVISIONS

4.1 Contractor's responsibility. Inspection and acceptance by the USDA shall not relieve the contractor of obligation and responsibility to deliver a product complying with all requirements of this document. The contractor shall assure product compliance prior to submitting the product to the USDA for any inspection.

4.2 Inspection and certification. Product acceptability shall be determined by the USDA. The USDA will determine the degree of inspection necessary to assure compliance with the requirements of this document.

4.3 Classification of inspection. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).
b. Quality conformance inspection (see 4.5)

4.4 First article inspection. When a first article is required (see 6.1), it shall be inspected in accordance with the quality assurance provisions of this document and evaluated for overall appearance and palatability. Any failure to conform to the quality assurance provisions of this document or any appearance or palatability failure shall be cause for rejection of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

4.5 Quality conformance inspection. Unless otherwise specified, sampling for inspection shall be performed in accordance with MIL-STD-105.

4.5.1 Component and material inspection. In accordance with 4.1, components and materials shall be inspected in accordance with all the requirements of referenced documents unless otherwise excluded, amended, modified, or qualified in this document or applicable purchase document.

4.5.1.1 Beef examination for condition and cut. All beef shall be examined in either the bone-in or boneless state for conformance to the condition and cut requirements in 3.2.1. Cuts initially examined in the boneless state shall be in the form of whole boneless recognizable cuts. Any nonconforming beef shall be rejected.

4.5.1.2 Boned and trimmed beef examination. After boning and trimming and prior to any further processing or to any freezing, the beef shall be examined for the defects listed in table II. The lot size expressed in terms of pounds shall be declared to the Agricultural Marketing Service (AMS) agent by the contractor. However, the AMS agent reserves the right to declare as a lot a portion of a declared lot, if, in his or her opinion, that portion may be out of compliance with any requirement. The sample unit shall be a minimum of 12 pounds of adjacent boneless beef. The sample size shall be as specified in table I. If all or a portion of the sample unit falls within a larger cut, the entire cut shall be examined. Failure of the beef to meet the acceptance criteria as indicated in table I shall be cause for rejection of the lot. Except for beef rejected because of freezing, defrosting, or not being in excellent condition, the beef may be reworked by the contractor and reoffered for examination. For reexamination, the sampling plan used shall be the one in table I designed for the next larger lot size than the one under which the lot was initially rejected. Beef shall not be reexamined more than one time.

TABLE I. Sampling plan for boned and trimmed beef

Lot size (pounds)	Sample size (No. of sample units)	Defect categories Major AC	Major RE	Minor AC	Minor RE
500 or less	20	2	3	5	6
501 to 1200	32	3	4	7	8
1201 to 3200	50	5	6	10	11
3201 to 10000	80	7	8	14	15
10001 to 38000	125	10	11	21	22
Reinspection lots of 10001 to 38000	200	14	15	21	22

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed beef defects 1/ 2/

Category		Defect
Major	Minor	
101		Presence of popliteal, prescapular, prefemoral or any exposed lymph gland measuring 0.5 inch or more in any dimension.
102		Presence of blood clot measuring 1.0 inch or more in any dimension.
	201	Presence of blood clot measuring 0.5 inch or more but less than 1.0 inch in any dimension.
103		Presence of bruise measuring 1.0 inch or more in any dimension.
	202	Presence of bruise measuring 0.5 inch or more but less than 1.0 inch in any dimension.
104		Presence of bone measuring 0.3 inch or more in any dimension.
105		Presence of cartilage measuring 0.5 inch or more in any dimension.
106		Presence of backstrap measuring 1.0 inch or more in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	203	Presence of backstrap measuring 0.5 inch or more but less than 1.0 inch in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
107		Presence of heavy connective tissue (for example, on the surface of the outside round adjacent to the knuckle, along the skin surface of the strip loin, or the gracilis membrane) measuring 2.0 square inches or more.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed beef defects 1/ 2/ (cont'd)

Category		Defect
Major	Minor	
	204	Presence of heavy connective tissue (for example, on the surface of the outside round adjacent to the knuckle, along the skin surface of the strip loin, or gracilis membrane) measuring 0.5 square inches or more but less than 2.0 square inches.
	205	Presence of heavy connective tissue on lower edge of short plate or flank.
	206	Presence of heavy connective (abdominal tunic) tissue on the flank measuring 1.0 inch or more in any dimension.
	207	Presence of membranous portion of diaphragm or membranous covering from skirt, flank, or abdominal section of short plate measuring 3.0 square inches or more.
108		Presence of knuckle cover.
109		Presence of kidney, pizzle eye, prepubic tendon, thymus gland, or hanging tender measuring 1.0 inch or more in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	208	Presence of kidney, pizzle eye, prepubic tendon, hanging tender, or thymus gland measuring less than 1.0 inch in one dimension and 0.2 inch or more in a second dimension (when measured at right angles to each other).
	209	Presence of calcified (scratchy) periosteum measuring 2.0 square inches or more.
	210	Presence of shank, clod, knuckle, or bottom (outside) round with tendinous end showing less than 75 percent lean tissue on a cross-sectional cut surface.
	211	Presence of dehydrated surface measuring 1.0 square inch or more.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

TABLE II. Boned and trimmed beef defects 1/ 2/ (cont'd)

Category		Defect
Major	Minor	
	212	Presence of discolored meat (including blood discolored neck meat) measuring 1.0 square inch or more.
	213	Present of exposed blood vessel measuring 1.0 inch or more in any dimension.
	214	Presence of cod, udder, kidney, or pelvic fat.

1/ Determination of wholesomeness and acceptability of product with respect to the presence of foreign material (for example: glass, dirt, insect parts, hair, wood, metal) shall be determined by a Meat and Poultry Inspection Operations employee.

2/ Evidence of freezing or defrosting or product not in excellent condition shall cause rejection of the involved lot.

4.5.1.3 Ingredient and component examination. Conformance of ingredients and components to identity, condition, and other requirements specified in 3.2 shall be certified by the ingredient supplier or ingredient manufacturer, or compliance be verified by examination of pertinent labels, markings, U.S. Grade certificates, certificates of analysis, or other such valid documents acceptable to the inspection agency. If necessary, each ingredient shall be examined organoleptically or inspected according to generally recognized test methods, such as the standard methods described in the Official Methods of Analysis of the Association of Official Analytical Chemists and in the Approved Methods of the American Association of Cereal Chemists, to determine conformance to the requirements. Any nonconformance to an identity, condition, or other requirement shall be cause for rejection of the ingredient or component lot or of any involved product.

4.5.2 In-process examination. In-process examination shall be performed to determine conformance to the preparation, processing, can interior coating, filling, sealing, and packing requirements. Any nonconformance revealed by actual examination or by review of records of time, temperature, and formulation or of other valid documents shall be cause for rejection of the involved product.

4.5.3 Tray pack inspection. The inspection lot shall include only tray packs produced in one workshift. The USDA reserves the right to separate the inspection lot into smaller inspection lots.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

4.5.3.1 Net weight inspection. Randomly select 30 filled and sealed tray pack cans from the inspection lot and weigh separately. Subtract the average tare weight (determined by randomly selecting and weighing 30 of the empty tray pack cans and lids used in preparing the product and dividing the total weight by 30) from the weight of each tray pack in the sample. The results shall be reported to the nearest 1 ounce. If the average net weight is less than 106 ounces or if the net weight of any individual can is less than 104 ounces, the lot shall be rejected.

4.5.3.2 Product inspection. The sample size shall be as indicated by the double sampling plan specified in table III. The tray pack cans shall be selected at random from the lot. The tray pack cans shall be heated for 35 minutes in boiling water, opened, and inspected for the defects listed in table IV.

TABLE III. Double sampling plan for product inspection 1/

Lot size (cans)	Sample size (cans)	Cumulative sample	Acceptance number	Rejection number
0 to 3200	8	-	0	2
	8	16	1	2
3201 to 35000	13	-	0	3
	13	26	3	4

1/ a. If no defects are found in the first sample, the lot shall be accepted.

b. If the number of defects found in the first sample equals or exceeds the rejection number, the lot shall be rejected.

c. If the number of defects found in the first sample exceeds the acceptance number but is less than the rejection number, the second sample shall be inspected. Defects found in the first and second samples shall be combined and if the number of defects in the cumulative sample equals or exceeds the rejection number, the lot shall be rejected.

TABLE IV. Product defects 1/ 2/

Category	Defect
Major	
101	Total weight of cartilage, coarse connective tissue, section of tendons or ligaments, and glandular material, collectively, in a can is more than 1 ounce.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:22Z
Check the source to verify that this is the current version before use.

TABLE IV. Product defects 1/ 2/ (cont'd)

Category	Defect
Major	
102	Presence of bone piece measuring 0.3 inch or more in any dimension in an individual can.
103	Less than 24 intact meatballs in a can.
104	Drained weight of 24 meatballs less than 48.0 ounces. 3/ 4/
105	Cabbage strips do not retain their identity or are mushy or tough.
106	Meatball texture dry, tough, rubbery, or mushy.
107	Meatballs not uniform in size and shape.
108	Sauce consistency lumpy or excessively thick or thin.
109	Product shows evidence of excessive heating (materially darkened or scorched).

1/ The presence of foreign material (e.g. glass, dirt, insect parts, hair, wood, metal), foreign odor or flavor (e.g. burnt, scorched, moldy, rancid, sour, stale), or foreign color shall be cause for rejection of the lot.

2/ Product not equal to or better than the approved preproduction sample in palatability and overall appearance shall be cause for rejection of the lot. (This comparison shall be performed only when deemed necessary by an AMS agent.)

3/ To determine drained weight, the entire contents of the can shall be poured into a flat bottom container. A minimum of three times the tray pack can's volume of 190° to 212°F water shall be added to the container so as to cover the contents. The contents and water shall be agitated so as to liquify rendered fat without breaking the meatballs. The contents shall then be poured into a U.S. Standard 1/4 inch sieve in a manner that will distribute the product over the sieve without breaking the meatballs. Sieve area shall be such that the distributed product does not completely cover all the openings of the sieve. The sieve shall be tilted at approximately a 45° angle and allowed to drain for 2 minutes before determining the drained weight of the meatballs. Any cabbage adhering to the meatballs shall be manually removed. The drained weight shall be reported to the nearest 0.1 ounce.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

4/ If the sample average drained weight of meatballs is less than 52.0 ounces, the lot shall be rejected.

4.5.3.3 Fat and salt content testing. Nine tray pack cans shall be selected at random from the lot and distributed as follows:

- Three for laboratory analysis
- Three for submission to the contractor
- Three for retention by an AMS agent as reserve samples.

The three tray packs for laboratory analyses shall individually be tested for fat and salt content in accordance with the Official Methods of Analysis of the Association of Official Analytical Chemists, Chapter: Meat and Meat Products, except that preparation of the samples shall be as follows: The three unopened cans shall be gently warmed in a water bath to melt fat adhering to the inside of the cans. The cans shall be opened and the entire contents of each can shall be separately blended in a Waring blender or equivalent. Results shall be reported to the nearest 0.1 percent. The lot shall be rejected if:

a. The average fat content of the three tray packs is greater than 10.0 percent.

b. The fat content of any individual tray pack is greater than 12.0 percent.

c. The salt content of any individual tray pack is less than 0.5 percent or greater than 1.3 percent.

Analysis of reserve samples at the request of the contractor shall not be permitted unless the original laboratory analysis indicated that the involved lot will be rejected because of noncompliance with the fat and salt content requirement. When the reserve samples are analyzed, the analyses for both fat and salt shall be made and will be considered final. Unused reserve samples shall be returned to the contractor for inclusion in subsequent lots.

4.5.4 Can condition examination. Examination of filled and sealed tray pack cans shall be in accordance with the United States Standards for Condition of Food Containers, except that inspection for labeling shall be in accordance with MIL-L-1497 (see 5.4).

4.5.5 Can closure examination. Can closures shall be examined visually and by teardowns in accordance with the can manufacturer's requirement and 21 CFR, Part 113, Subpart D, or 9 CFR, Part 318, Subpart G, as applicable. Any non-conformance based on observation of can seam teardowns or of record of can seam teardowns shall be cause for rejection of any involved product.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

4.5.6 Vacuum examination. Cans shall be allowed to cool to 75° ± 5°F, held for at least 24 hours after sealing, and then examined for vacuum retention. To examine, lay a straight edge in the center of the lid along the length of the tray pack. Both ends of the straight edge shall touch the lid at the inside edge of the double seam. There shall be a visible gap between the straight edge and the lid for the entire distance of the label panel. Using a shorter straight edge, the same procedure shall be used across the width, in the center of the tray pack can. When examining a ribbed lid, only lay the straight edge between the two center ribs along the length of the can. The inspection lot shall include only tray packs produced in a single shift on a single sealing machine. The sample size shall be 50 cans. Any nonconforming tray pack can shall be cause for rejection of the lot.

4.5.7 Shipping container examination. Shipping containers shall be examined for defects in assembly, closure, and reinforcement (when applicable) in accordance with PPP-B-636. In addition, the following defects shall be classified as follows:

Major: National stock number, item description, contract number or date of pack markings missing, incorrect, or illegible.
Reinforced with other than nonmetallic strapping or tape.
Dimensions of pads not as specified.
Interior packing with fiberboard liner or pads not as specified.

Minor: Other required markings missing, incorrect or illegible.
Arrangement or number of cans not specified.

4.5.8 Unit load inspection. Inspection of unit loads shall be in accordance with the quality assurance provisions of MIL-L-35078.

5. PACKAGING

5.1 Preservation. The product shall be preserved in accordance with level A or C as specified (see 6.1).

5.1.1 Level A. A size 1001 by 1206 by 200 tray pack can shall be filled with 106 ounces of the food product, sealed, and thermoprocessed as specified in 3.4 and 3.5. The base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 90 pounds per base box. The entire inside area of the can shall be coated. Scratches or fractures shall not penetrate through the interior can coating. The interior can coating shall not peel or blister when in contact with the product. The interior can coating shall neither affect nor be affected by the packaged product. A certificate of conformance shall be furnished to certify compliance with the interior can coating requirements. The can shall be coated overall on the outside with a coating conforming to type I of TT-C-495.

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:22Z
Check the source to verify that this is the current version before use.

5.1.1.1 When specified (see 6.1), the base plate of the can shall be electrolytic chromium-coated steel and shall be of sufficient temper to protect the product during shipment and storage. The base plate weight of the body and end of each can shall be 98 pounds per base box. The body design shall be reinforced on the bottom with six longitudinal beads or ribs 0.050 ± 0.010 inches deep. The beads shall be 9 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the bottom. The end design shall be reinforced with eight longitudinal beads 0.018 ± 0.004 inches deep. The beads shall be 11 inches by 3/4 inch in length and width and shall be equidistant in the center panel of the end. The center four beads on the end design shall be interrupted to provide a 5-inch by 5-inch flat center panel for labeling. The apex of all these beads shall be outward. The interior and exterior can coating requirements shall be as specified in 5.1.1.

5.1.2 Level C. The product shall be preserved as specified in 5.1.1, except that cans with commercial exterior coating will be acceptable.

5.2 Packing. The product shall be packed in accordance with level A, B, or C as specified (see 6.1).

5.2.1 Level A packing. Four cans of product, preserved as specified in 5.1, shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L or HSC-L with an HSC full depth cover, grace V2s of PPP-B-636. The cans shall be packed flat, four in depth within the box, with the first two cans placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads fabricated of grade V3c fiberboard. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box. Each fiberboard box shall be reinforced with nonmetallic strapping or pressure-sensitive adhesive filament-reinforced tape in accordance with the appendix of PPP-B-636. Shipping containers shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified (see 6.1) except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.2.2 Level B packing. Four cans of product, preserved as specified in 5.1, shall be packed as specified in 5.2.1, except the box shall be constructed of grade V3c, V3s, or V4s fiberboard.

5.2.3 Level C packing. Four cans of product, preserved as specified in 5.1 shall be packed in a snug-fitting fiberboard box, constructed and closed in accordance with style RSC-L, class domestic, grade 275 of PPP-B-636. The cans shall be packed flat, four in depth within the box with the first two cans

Source: https://assist.dla.mil -- Downloaded: 202640-22T01:22Z
Check the source to verify that this is the currentversion before use.

placed with the lids together and the next two cans with the lids together. The inside of each box shall be provided with a box liner and five fiberboard pads. The height of the box liner shall be equal to the full inside depth of the box (+0 inch, -1/8 inch). The pads shall be placed between the cans and on the top and bottom of the stacked cans. The pad dimensions shall be not less than 1/8 inch of the full length and width dimensions of the box and shall be fabricated of the same material as the box.

5.3 Unit loading. When specified (see 6.1), the product, packed as specified in 5.2.2 and 5.2.3, shall be arranged in unit loads in accordance with MIL-L-35078 for the type and class of load specified except that the unit load shall consist of 48 boxes with 12 boxes per course and four courses per load with all courses having the same pattern so as to create columnar stacking. When unit loads are strapped, the strapping shall be limited to nonmetallic strapping, except for type II, class F loads.

5.4 Labeling. Each tray pack can shall be labeled in accordance with MIL-L-1497 and with the following:

- Official establishment number (e.g., EST 38) or a three letter code identifying the establishment.
- Lot number 1/
- Product shift number 1/
- Retort identification number 1/
- Retort cook number 1/

1/ The lot number shall be expressed as a four digit Julian code. The first digit shall indicate the year of production and the next three digits shall indicate the day of the year. (Example, March 19, 1987 would be coded as 7078). The Julian code shall represent the day the product was packaged and processed. Sub-lotting (when used) shall be represented by an alpha character immediately following the four digit Julian code. Following the four digit Julian code and the alpha character (when used), the other required code information shall be printed in the sequence as listed above.

In addition, the name of the product shall be marked, stamping is permitted, on one 1001 by 200 side of the can. The labeling shall be legible when examined as specified in 4.5.4 after preparation of product in accordance with heating instructions. Paper labels are not permitted. Cans shall show the following statements:

TO HEAT: Submerge unopened can in boiling water. Simmer gently for 40 to 45 minutes. Avoid overheating (can shows evidence of bulging).

CAUTION: Use care when opening as pressure may have been generated within the can.

Source: https://assist.dla.mil -- Downloaded: 202610-22T01:22Z
Check the source to verify that this is the current version before use.

To heat in oven: Either punch several holes in lid of can or open can in usual manner leaving the loose lid in place. Place in a 350°F oven for approximately 35 to 40 minutes.

WARNING: Do not place unopened can in oven. This may cause the can to burst.

YIELD: Serves 12 portions of 2 meatballs and 1/3 cup cabbage and sauce each

5.5 Marking.

5.5.1 Shipping containers. In addition to any special marking required by the contract or purchase order, shipping containers shall be marked in accordance with MIL-STD-129.

5.5.2 Unit loads. Unit loads shall be marked in accordance with MIL-L-35078. In addition, when tray pack cans are fabricated from 90 pounds per base box, the following precautionary markings in capital letters larger than other markings shall be included:

CAUTION: DO NOT STACK PALLETS IN TRANSIT OR MORE THAN TWO HIGH IN STORAGE.

6. NOTES

6.1 Ordering data. Acquisition documents should specify the following:

a. Title, number, and date of this document.
b. When a first article is required (see 3.1, 4.4, and 6.3).
c. Provisions for approved preproduction samples (see 3.6.1 and 6.3).
d. Level of preservation and packing required (see 5.1 and 5.2).
e. When tray pack cans are to be fabricated from 98 pounds per base box (see 5.1.1.1).
f. Type and class of unit load when unit loading is required (see 5.2.1 and 5.3).

6.2 Appropriate level of pack. Based on the conditions known or expected to be encountered during shipment, handling and storage of the specific item being procured, the procuring activity should select the appropriate level of pack in accordance with the criteria established in AR 700-15/NAVSUPINST 4030.28/AFR 71-6/MCO 4030.33A/DLAR 4145.7.

6.3 First article. When a first article is required, it shall be inspected and approved under the appropriate provisions of FAR 52.209. The first article should be a preproduction sample. The contracting officer should include specific instructions in all acquisition documents regarding arrangements for selection, inspection, and approval of the first article.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

6.4 Subject term (key word) listing.

Beef
Canned foods
Meatballs
Rations
Thermostabilized
Tray pack

Custodians:

Army - GL
Navy - SA
Air Force - 50

Review Activities:

Army - MD, TS
Navy - MC
DP - SS

Preparing activity:

Army - GL

Project No. 8940-A545

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

US ARMY NATICK RESEARCH
and DEVELOPMENT CENTER
ATTN: STRNC-ES
Natick, MA 01760-5014

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Natick Research
and Development Center
ATTN: STRNC-ES
Natick, MA 01760-5014

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-44310	Meatballs with Rice, in Tomato Sauce, and Cabbage, Thermostabilized, Tray Pack

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

NATICK, OP 20, Nov 86

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T01:22Z
Check the source to verify that this is the current version before use.